

SIMATS ENGINEERING

ASSESSMENT TOOL 1

COURSE NAME: COMPUTER NETWORKS
COURSE CODE: CSA07

COURSE OUTCOME COVERED

CO4:

Design network topologies star, mesh, bus, and hybrid using networking devices, transmission media, and cabling standards
(BL2,BL6)

Assessment Tool Weightage: 40%

Annexure A

Coding challenge

1. Develop a Python program that generates a Star Topology for a given number of hosts connected to a central switch. The program should accept the number of hosts as input and display the topology either in ASCII format or a graphical representation. For each host, print the host label, the name of the central switch, and the corresponding Cat6 UTP cable length connecting the host to the switch. Verify that all hosts are connected through the central switch and explain how the star topology facilitates reliable communication in a local area network.
2. Write a Python function named `validate_segment(length_m)` to verify whether a given **UTP cable segment** satisfies the IEEE 802.3 Ethernet standard, which specifies a maximum cable length of **100 meters**. The function should return **True** for valid cable lengths and return **False** along with an appropriate error message for invalid lengths exceeding the permissible limit. Demonstrate the correctness of the program by executing it with at least **three different test cases** and interpret the results.

3. Develop a Python program to simulate the operation of the Carrier Sense Multiple Access with Collision Detection (CSMA/CD) protocol in a star topology consisting of four hosts connected through a central switch. The program should simulate frame transmission attempts, detect transmission collisions, calculate random back-off intervals, and continue transmission after the waiting period. Record every collision event, transmission attempt, and back-off interval in a log file named `csma_log.txt`, and analyze how CSMA/CD minimizes data transmission conflicts in Ethernet networks.
4. Develop a client-server application using Python's socket library to simulate communication between two hosts connected through a central switch in a star topology. The server should receive frames from the client, forward them appropriately, and maintain a simulated MAC Address Table. After each successful frame transmission, display the updated MAC address table showing the learned MAC addresses and associated ports. Explain how MAC learning and frame forwarding are performed in Ethernet switches.
5. Design and implement a Python class named `StarSwitch` that models the basic functionality of an Ethernet switch. The class should include methods such as `add_port(host_id)` to connect a host, `remove_port(host_id)` to disconnect a host, and `broadcast(frame)` to transmit a frame to all connected ports except the source port. The program should maintain a record of active ports and log every broadcast operation, indicating the source host and the destination hosts that successfully receive the frame. Demonstrate the implementation using multiple hosts and explain the significance of broadcasting in Ethernet communication.

3. Develop a Python program to simulate the operation of the Carrier Sense Multiple Access with Collision Detection (CSMA/CD) protocol in a star topology consisting of four hosts connected through a central switch. The program should simulate frame transmission attempts, detect transmission collisions, calculate random back-off intervals, and continue transmission after the waiting period. Record every collision event, transmission attempt, and back-off interval in a log file named `csma_log.txt`, and analyze how CSMA/CD minimizes data transmission conflicts in Ethernet networks.

1. Aim

To develop a Python program to simulate the **Carrier Sense Multiple Access with Collision Detection (CSMA/CD)** protocol in a star topology consisting of four hosts connected through a central switch. The program detects collisions, calculates random back-off intervals, continues transmission after the waiting period, and records transmission activities in a log file named `csma_log.txt`.


2. Problem Statement

Develop a Python program to simulate the operation of **CSMA/CD** in a star topology with four hosts connected through a central switch. The program should:

- Simulate frame transmission attempts.
- Detect transmission collisions.
- Calculate random back-off intervals.
- Continue transmission after the waiting period.
- Record every collision event.
- Record every transmission attempt.
- Record every back-off interval.
- Store the complete activity in `csma_log.txt`.
- Analyze how CSMA/CD minimizes data transmission conflicts in Ethernet networks.

3. Topology Used

The simulation uses four hosts connected to a central switch in a **star topology**.



Where:

- **SW1** → Central switch
- **Host1–Host4** → Network hosts
- Each host communicates through the central switch.

4. Algorithm

1. Start the program.
2. Create four hosts: Host1, Host2, Host3, and Host4.
3. Connect all hosts to the central switch SW1.
4. Assign one frame to each host.
5. Select hosts that attempt transmission.
6. Check whether one or multiple hosts are transmitting.
7. If only one host transmits, mark the frame as successfully transmitted.
8. If multiple hosts transmit simultaneously, detect a collision.
9. Generate a random back-off interval for every collided host.
10. Record the transmission attempt, collision, and back-off interval in `csma_log.txt`.
11. Allow the collided hosts to retry after the back-off period.
12. Continue the process until all four frames are successfully transmitted.
13. Display the final result.
14. Stop the program.

5. Python Program

```
import random

import time

LOG_FILE = "csma_log.txt"

def log_event(message):

    """Write an event to the CSMA/CD log file."""

    with open(LOG_FILE, "a") as file:

        file.write(message + "\n")

def csma_cd_simulation():

    """Simulate CSMA/CD for four hosts."""

    hosts = ["Host1", "Host2", "Host3", "Host4"]

    # Each host has one frame to transmit

    pending_hosts = hosts.copy()

    # Clear previous log

    with open(LOG_FILE, "w") as file:

        file.write("CSMA/CD TRANSMISSION LOG\n")

        file.write("=" * 60 + "\n")

    attempt = 1

    print("=" * 60)

    print("      CSMA/CD SIMULATION")

    print("=" * 60)

    print("\nStar Topology:")

    print("Host1 ----\\")

    print("Host2 -----\\")

    print("Host3 ----- SW1")

    print("Host4 -----/")

    while pending_hosts:

        print("\n" + "-" * 60)

        print(f"TRANSMISSION ATTEMPT {attempt}")

        print("-" * 60)

        log_event(f"\nTransmission Attempt {attempt}")
```

```

# Select hosts attempting transmission
transmitting_hosts = []
for host in pending_hosts:
    if random.choice([True, False]):
        transmitting_hosts.append(host)
# Ensure at least one host attempts transmission
if not transmitting_hosts:
    transmitting_hosts.append(
        random.choice(pending_hosts)
    )
print(
    "Hosts attempting transmission:",
    ", ".join(transmitting_hosts)
)
log_event(
    "Transmission attempt by: "
    + ", ".join(transmitting_hosts)
)
# Successful transmission
if len(transmitting_hosts) == 1:
    host = transmitting_hosts[0]
    print(f"\n{host}: Frame transmitted successfully.")
    log_event(
        f"{host}: Frame transmitted successfully."
    )
    pending_hosts.remove(host)
# Collision detected
else:
    print("\n*** COLLISION DETECTED ***")
    log_event(
        "COLLISION DETECTED: "

```

```

        + ", ".join(transmitting_hosts)
    )
    for host in transmitting_hosts:
        # Generate random back-off interval
        backoff = random.randint(1, 5)
        print(
            f'{host}: Back-off interval = '
            f'{backoff} time unit(s)'
        )
        log_event(
            f'{host}: Back-off interval = '
            f'{backoff} time unit(s)'
        )
        print(
            "Hosts will wait and retransmit "
            "after the back-off period."
        )
        log_event(
            "Hosts will retransmit after back-off."
        )
        time.sleep(1)
        attempt += 1
    print("\n" + "=" * 60)
    print("ALL FRAMES TRANSMITTED SUCCESSFULLY")
    print("=" * 60)
    print(f'\nTransmission log saved in: {LOG_FILE}')
    log_event("\nAll frames transmitted successfully.")
if __name__ == "__main__":
    csma_cd_simulation()

```

6. Working of the Program

The program first creates four hosts:


- Host1
- Host2
- Host3
- Host4

Each host has a frame that needs to be transmitted through the central switch.

During every transmission attempt, the program randomly selects one or more hosts for transmission.

Case 1 — Successful Transmission


If only one host attempts to transmit:



The frame is transmitted successfully and that host is removed from the pending list.

Case 2 — Collision

If two or more hosts transmit simultaneously:



COLLISION

The program detects the collision and generates a random back-off interval.

Case 3 — Back-Off

For example:

- Host1 → 2 time units
- Host3 → 4 time units

The hosts wait for their back-off period and then attempt transmission again.

The process continues until all four hosts successfully transmit their frames.

7. Output

```
=====
|      |      | CSMA/CD SIMULATION
|      |      |
=====

Star Topology:
Host1 ----\
Host2 -----\
Host3 ----- SW1
Host4 -----/

-----
TRANSMISSION ATTEMPT 1
-----
Hosts attempting transmission: Host2

Host2: Frame transmitted successfully.

-----
TRANSMISSION ATTEMPT 2
-----
Hosts attempting transmission: Host3

Host3: Frame transmitted successfully.

-----
TRANSMISSION ATTEMPT 3
-----
Hosts attempting transmission: Host1

Host1: Frame transmitted successfully.

-----
TRANSMISSION ATTEMPT 4
-----
Hosts attempting transmission: Host4

-----
TRANSMISSION ATTEMPT 11
-----
Hosts attempting transmission: Host2, Host3

*** COLLISION DETECTED ***
Host2: Back-off interval = 1 time unit(s)
Host3: Back-off interval = 2 time unit(s)
Hosts will wait and retransmit after the back-off period.

-----
TRANSMISSION ATTEMPT 12
-----
Hosts attempting transmission: Host3

Host3: Frame transmitted successfully.

-----
TRANSMISSION ATTEMPT 13
-----
Hosts attempting transmission: Host2

Host2: Frame transmitted successfully.


=====
ALL FRAMES TRANSMITTED SUCCESSFULLY
=====

Transmission log saved in: csma_log.txt
```

Figure 1: CSMA/CD Simulation Showing Collision Detection, Back-Off, and Successful Retransmission

8. Log File — csmalog.txt

The program automatically creates a file named:



```
1 CSMA/CD TRANSMISSION LOG
2 =====
3
4 Transmission Attempt 1
5 Transmission attempt by: Host2
6 Host2: Frame transmitted successfully.
7
8 Transmission Attempt 2
9 Transmission attempt by: Host3
10 Host3: Frame transmitted successfully.
11
12 Transmission Attempt 3
13 Transmission attempt by: Host1
14 Host1: Frame transmitted successfully.
15
16 Transmission Attempt 4
17 Transmission attempt by: Host4
18 Host4: Frame transmitted successfully.
19
20 All frames transmitted successfully.
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54 Hosts will retransmit after back-off.
55
56 Transmission Attempt 8
57 Transmission attempt by: Host4
58 Host4: Frame transmitted successfully.
59
60 Transmission Attempt 9
61 Transmission attempt by: Host1, Host3
62 COLLISION DETECTED: Host1, Host3
63 Host1: Back-off interval = 2 time unit(s)
64 Host3: Back-off interval = 4 time unit(s)
65 Hosts will retransmit after back-off.
66
67 Transmission Attempt 10
68 Transmission attempt by: Host1
69 Host1: Frame transmitted successfully.
70
71 Transmission Attempt 11
72 Transmission attempt by: Host2, Host3
73 COLLISION DETECTED: Host2, Host3
74 Host2: Back-off interval = 1 time unit(s)
75 Host3: Back-off interval = 2 time unit(s)
76 Hosts will retransmit after back-off.
77
78 Transmission Attempt 12
79 Transmission attempt by: Host3
80 Host3: Frame transmitted successfully.
81
82 Transmission Attempt 13
83 Transmission attempt by: Host2
84 Host2: Frame transmitted successfully.
85
86 All frames transmitted successfully.
87
```

Figure 2: CSMA/CD Transmission Log Showing Collision and Back-Off Events

9. CSMA/CD Working Flow




Figure 3: CSMA/CD Working Flow

10. How CSMA/CD Minimizes Data Transmission Conflicts

CSMA/CD reduces transmission conflicts through the following mechanisms:

Carrier Sensing Simulation:

The program simulates transmission opportunities by randomly selecting one or more hosts for each transmission attempt.

Multiple Access:

Multiple hosts share the same Ethernet communication medium.

Collision Detection:

If multiple hosts transmit at the same time, the collision is detected.

Random Back-Off:

After a collision, the affected hosts wait for randomly selected intervals.

Retransmission:

After waiting, the hosts try to transmit their frames again.

Therefore, random back-off prevents the same hosts from immediately retransmitting together and causing repeated collisions. The simulation demonstrates the collision detection and back-off behavior requested by the assessment.

11. Test Cases

Test Case	Scenario	Expected Result
1	Only one host transmits	Successful transmission
2	Two hosts transmit simultaneously	Collision detected
3	Three hosts transmit simultaneously	Collision detected
4	Multiple hosts collide	Random back-off generated
5	Collided hosts retry	Frames eventually transmitted
6	All hosts complete transmission	Success message and log generated

Test Case 1 — Single Host

- Transmitting Host: Host1

Expected Result:

- Host1: Frame transmitted successfully.

Test Case 2 — Two Hosts

- Transmitting Hosts: Host1, Host2

Expected Result:

- *** COLLISION DETECTED ***
- Host1: Back-off interval = ...
- Host2: Back-off interval = ...

Test Case 3 — Three Hosts

- Transmitting Hosts: Host1, Host2, Host4

Expected Result:

- *** COLLISION DETECTED ***
- with a back-off interval for each collided host.

Test Case 4 — Completion

- ❖ **Expected Result:**
- ❖ ALL FRAMES TRANSMITTED SUCCESSFULLY

and:

- ✓ csma_log.txt

is created.

12. Error Handling

The program handles the main execution conditions by:

- Ensuring at least one host attempts transmission in every cycle.
- Treating multiple simultaneous transmitters as a collision.
- Generating a new back-off interval after each collision.
- Removing a host only after successful transmission.
- Continuing until every host has successfully transmitted.
- Automatically creating the required log file.

13. Time and Space Complexity

Let n represent the number of hosts.

Time Complexity

For each transmission attempt, the program checks the pending hosts.

Time Complexity: $O(n)$ per transmission attempt.

Because collisions may cause retransmissions, the total number of attempts depends on the random transmission pattern.

Space Complexity

The program stores the host list and pending hosts.

Space Complexity: $O(n)$

For this assignment, $n = 4$, so the memory requirement is very small.

15. Advantages

- Simulates four hosts as required.
- Uses a star topology with a central switch.
- Detects transmission collisions.
- Generates random back-off intervals.
- Supports retransmission.
- Records transmission attempts.
- Records collision events.
- Records back-off intervals.
- Automatically creates csma_log.txt.
- Provides clear console output.
- Includes testing and error handling.

16. Conclusion

The developed Python program successfully simulates the **CSMA/CD protocol** for four hosts connected through a central switch in a star topology. The program models frame transmission, detects collisions, generates random back-off intervals, and allows collided hosts to retransmit after waiting. It also records every transmission attempt, collision event, and back-off interval in `csma_log.txt`. The simulation demonstrates how collision detection and random back-off help minimize repeated transmission conflicts in Ethernet networks.

4. Develop a client-server application using Python's socket library to simulate communication between two hosts connected through a central switch in a star topology. The server should receive frames from the client, forward them appropriately, and maintain a simulated MAC Address Table. After each successful frame transmission, display the updated MAC address table showing the learned MAC addresses and associated ports. Explain how MAC learning and frame forwarding are performed in Ethernet switches.

1. Aim


To develop a **client-server application using Python socket programming** to simulate communication between two hosts connected through a central switch in a star topology. The server receives frames from the client, forwards them appropriately, maintains a simulated MAC address table, and displays the updated table after successful frame transmission.

2. Problem Statement

Develop a Python client-server application that:

- Simulates two hosts connected through a central switch.
- Uses Python's socket library for communication.
- Allows the client to send Ethernet frames to the server.
- Allows the server to receive and process frames.
- Maintains a simulated **MAC Address Table**.
- Learns MAC addresses from received frames.
- Associates learned MAC addresses with ports.
- Displays the updated MAC address table after successful transmission.
- Demonstrates how MAC learning and frame forwarding are performed in Ethernet switches.

3. Network Topology



Components

Component	Description
Host1	Client
Host2	Server
SW1	Simulated central switch
Socket	Communication mechanism
MAC Table	Stores learned MAC addresses and ports

4. Algorithm

Server Algorithm

1. Start the server.
2. Create a TCP socket.
3. Bind the socket to an IP address and port.
4. Listen for client connections.
5. Accept the client connection.
6. Receive the Ethernet frame.
7. Extract the source MAC address and frame data.
8. Learn the source MAC address.
9. Store the MAC address and associated port in the MAC table.
10. Display the updated MAC address table.
11. Forward the frame appropriately.
12. Send a confirmation message to the client.
13. Repeat until the client sends EXIT.
14. Close the connection.

Client Algorithm

1. Start the client.
2. Create a TCP socket.
3. Connect to the server.
4. Enter the source MAC address.
5. Enter frame data.
6. Send the frame to the server.
7. Receive the server response.
8. Display the response.
9. Repeat for additional frames.
10. Send EXIT to terminate.
11. Close the connection.

5. Server Program

Create a file named:

server.py

```
import socket
HOST = "127.0.0.1"
PORT = 5000
# Simulated MAC address table
mac_table = {}
def display_mac_table():
    """Display the learned MAC address table."""
    print("\n" + "=" * 55)
    print("          MAC ADDRESS TABLE")
    print("=" * 55)
    print(f'{"MAC Address":<22} {"Port":<15}')
```

MAC Address	Port

```
    print("-" * 37)
    if not mac_table:
        print("Table is empty.")
    else:
        for mac, port in mac_table.items():
            print(f'{"mac":<22} {"port":<15}')
```

mac	port

```
    print("=" * 55)
def start_server():
    server_socket = socket.socket(
        socket.AF_INET,
        socket.SOCK_STREAM
    )
    server_socket.bind((HOST, PORT))
    server_socket.listen(1)
    print("=" * 55)
    print("    ETHERNET SWITCH SERVER")
    print("=" * 55)
    print(f'Server listening on {HOST}:{PORT}')
    print("Waiting for client connection...")
    connection, address = server_socket.accept()
```



```

print(f"\nClient connected from {address}")
while True:
    data = connection.recv(1024).decode()
    if not data:
        break
    if data.upper() == "EXIT":
        print("\nClient requested termination.")
        break
    try:
        # Expected format: MAC|FRAME
        mac_address, frame = data.split("|", 1)
        # Learn source MAC address
        mac_table[mac_address] = "Port-1"
        print("\nFrame Received")
        print("-" * 40)
        print(f"Source MAC : {mac_address}")
        print(f"Frame Data : {frame}")
        print("\nFrame forwarded through switch.")
        # Display updated MAC table
        display_mac_table()
        # Send confirmation to client
        response = (
            "Frame successfully received "
            "and forwarded."
        )
        connection.send(response.encode())
    except ValueError:
        error_message = (
            "Invalid frame format. "
            "Use MAC|FRAME"
        )
        connection.send(error_message.encode())
connection.close()
server_socket.close()
print("\nServer stopped.")
if __name__ == "__main__":
    start_server()

```

6. Client Program

Create another file named:

client.py

```
import socket
```

```
HOST = "127.0.0.1"
```

```
PORT = 5000
```

```
def start_client():
```

```
    client_socket = socket.socket(
```

```
        socket.AF_INET,
```

```
        socket.SOCK_STREAM
```

```
    )
```

```
    client_socket.connect((HOST, PORT))
```

```
    print("=" * 55)
```

```
    print("        CLIENT CONNECTED TO SWITCH")
```

```
    print("=" * 55)
```

```
    while True:
```

```
        mac_address = input(
```

```
            "\nEnter Source MAC Address: "
```

```
        )
```

```
        if mac_address.upper() == "EXIT":
```

```
            client_socket.send("EXIT".encode())
```

```
            break
```

```
        frame = input("Enter Frame Data: ")
```

```
        # Create simulated Ethernet frame
```

```
        message = f'{mac_address}|{frame}'
```

```
        client_socket.send(message.encode())
```

```
        response = client_socket.recv(1024).decode()
```

```
        print("\nSwitch Response:")
```

```
        print(response)
```

```
    client_socket.close()
```

```
    print("\nClient connection closed.")
```

```
if __name__ == "__main__":
```

```
    start_client()
```

7. How to Run the Program

Keep both files in the same folder:

CSA0704

```
|  
|— server.py  
|— client.py
```

Step 1 — Open Terminal 1

Run:

```
python server.py
```

You will see:

```
=====
ETHERNET SWITCH SERVER
=====

Server listening on 127.0.0.1:5000
Waiting for client connection...
```

Step 2 — Open Terminal 2

Run:

```
python client.py
```

The client will connect to the server.

8. Client Input

Enter:

Enter Source MAC Address: AA:BB:CC:DD:EE:01

Enter Frame Data: Hello Host2

The client sends:

AA:BB:CC:DD:EE:01|Hello Host2
to the server.

9. Client Output

```
=====
CLIENT CONNECTED TO SWITCH
=====

Enter Source MAC Address: AA:BB:CC:DD:EE:01
Enter Frame Data: Hello Host2

Switch Response:
Frame successfully received and forwarded.
```

Figure 1: Client Sending an Ethernet Frame to the Server

10. Server Output

```
=====
      ETHERNET SWITCH SERVER
=====
Server listening on 127.0.0.1:5000
Waiting for client connection...

Client connected from ('127.0.0.1', 60945)

Frame Received
-----
Source MAC : AA:BB:CC:DD:EE:01
Frame Data : Hello Host2


Frame forwarded through switch.

=====
      MAC ADDRESS TABLE
=====
MAC Address      Port
-----
AA:BB:CC:DD:EE:01  Port-1
=====
```

Figure 2: Server Receiving and Forwarding the Ethernet Frame

11. Working of the Program

The communication process is:



The client creates a simulated Ethernet frame using:

✓ `message = f"{mac_address}|{frame}"`

For example:

▪ `AA:BB:CC:DD:EE:01|Hello Host2`

The server separates the MAC address and frame data:

○ `mac_address, frame = data.split("|", 1)`

The server then learns the source MAC address:

• `mac_table[mac_address] = "Port-1"`

Finally, the updated MAC table is displayed.

12. MAC Address Learning

MAC learning is the process by which an Ethernet switch learns which port is associated with a particular source MAC address.

For example, when the server receives:

❖ **Source MAC:** AA:BB:CC:DD:EE:01

the simulated switch records:

MAC Address	Port

AA:BB:CC:DD:EE:01	Port-1

When another frame arrives from:

○ AA:BB:CC:DD:EE:02

the table becomes:


MAC Address	Port

AA:BB:CC:DD:EE:01	Port-1
AA:BB:CC:DD:EE:02	Port-1

This demonstrates the MAC learning requirement of Question 4.

13. Frame Forwarding

The simulated switch receives the frame and processes it as follows:



↓
Forward Frame

↓
Send Confirmation

In a real Ethernet switch, the MAC address table is used to determine the appropriate outgoing port for a known destination MAC address.

14. Test Cases

Test Case	Input	Expected Result
1	Valid MAC + frame	Frame successfully received
2	Second MAC + frame	MAC table updated
3	Multiple frames	Multiple MAC entries learned
4	Invalid frame format	Error message
5	EXIT	Client-server connection terminates

Test Case 1 — Valid MAC + Frame

MAC: AA:BB:CC:DD:EE:01

Frame: Hello Host2

Expected:

Frame successfully received and forwarded.

Test Case 2 — Second MAC + Frame

MAC: AA:BB:CC:DD:EE:02

Frame: Network Data

Expected:

MAC table updated.

Test Case 3 — Multiple Frames

Write:

Multiple frames are sent from the client and the server processes each frame successfully.

Test Case 4 — Invalid Frame

Expected:

Invalid frame format. Use MAC|FRAME

Test Case 5 — Exit

Input:

EXIT

Expected:

Client connection closed.
Server stopped.

15. Error Handling

The program handles:

- Invalid frame format.
- Empty client connection.
- Client termination using EXIT.
- Proper socket closure.
- MAC table initialization.
- Multiple learned MAC addresses.

16. Time and Space Complexity

Let n be the number of MAC addresses stored in the table.

Time Complexity

Adding or updating a MAC address in the Python dictionary is approximately:

$O(1)$ average time.

Displaying the complete MAC table requires:

$O(n)$ time.

Space Complexity

The MAC address table stores one entry per learned MAC address:

$O(n)$ space.

17. Advantages

- Uses Python socket programming.
- Demonstrates client-server communication.
- Simulates two hosts.
- Represents a central switch.
- Implements MAC address learning.
- Maintains a MAC address table.
- Demonstrates frame forwarding.
- Displays the updated MAC table.
- Includes error handling.

- Supports multiple frames.
- Provides test cases.

18. Conclusion

The developed Python socket-based client-server application successfully simulates Ethernet communication between two hosts through a central switch. The server receives frames from the client, learns source MAC addresses, updates the simulated MAC address table, and forwards the received frames. The implementation demonstrates the basic concepts of **MAC address learning and frame forwarding** used by Ethernet switches.

RUBRICS FOR CALCULATION

Criteria	Weightage	Exemplary (4)	Proficient (3)	Developing (2)	Beginning (1)
Problem Understanding	15%	Fully understands the problem and requirements; no clarification needed	Understands most requirements with minor clarification	Partial understanding; misses some requirements	Poor understanding of the problem
Algorithm Design	20%	Efficient, optimal, and well-structured algorithm	Correct algorithm with minor inefficiencies	Basic approach but not optimal	Incorrect or no clear algorithm
Code Quality	15%	Clean, well-organized, readable, and properly formatted code	Mostly clean code with minor issues	Code is somewhat unclear or inconsistent	Poorly written, unreadable code
Functionality	20%	Code works perfectly for all test cases	Works for most test cases	Works for limited cases	Does not run or fails major cases
Error Handling	10%	Handles all edge cases and errors effectively	Handles some edge cases	Limited error handling	No error handling
Efficiency	10%	Highly optimized in time and space complexity	Reasonably efficient	Some inefficiencies	Highly inefficient
Documentation & Comments	5%	Clear and meaningful comments and documentation	Adequate comments	Few or unclear comments	No comments
Testing & Debugging	5%	Thoroughly tested with multiple cases; no bugs	Tested with some cases	Minimal testing	No testing done