

## NLP LAB 9

In [4]:

```
import nltk
from nltk.tokenize import word_tokenize
text=word_tokenize('And now for something completely different')
nltk.pos_tag(text)
```

Out[4]:

```
[('And', 'CC'),
 ('now', 'RB'),
 ('for', 'IN'),
 ('something', 'NN'),
 ('completely', 'RB'),
 ('different', 'JJ')]
```

In [5]:

```
nltk.download('brown')
```

```
[nltk_data] Downloading package brown to
[nltk_data] C:\Users\1mscdsa40\AppData\Roaming\nltk_data...
[nltk_data] Unzipping corpora\brown.zip.
```

Out[5]:

```
True
```

In [8]:

```
tagsen = brown.tagged_sents()
tagsen
```

Out[8]:

```
[[(('The', 'AT'), ('Fulton', 'NP-TL'), ('County', 'NN-TL'), ('Grand', 'JJ-TL'),
 ('Jury', 'NN-TL'), ('said', 'VBD'), ('Friday', 'NR'), ('an', 'AT'), ('investiga
tion', 'NN'), ('of', 'IN'), ('Atlanta's', 'NP$'), ('recent', 'JJ'), ('primary',
'NN'), ('election', 'NN'), ('produced', 'VBD'), ('``', ''), ('no', 'AT'), ('e
vidence', 'NN'), ('"', ''), ('that', 'CS'), ('any', 'DTI'), ('irregularitie
s', 'NNS'), ('took', 'VBD'), ('place', 'NN'), ('.', '.')], [(('The', 'AT'), ('ju
ry', 'NN'), ('further', 'RBR'), ('said', 'VBD'), ('in', 'IN'), ('term-end', 'N
N'), ('presentments', 'NNS'), ('that', 'CS'), ('the', 'AT'), ('City', 'NN-TL'),
 ('Executive', 'JJ-TL'), ('Committee', 'NN-TL'), (',', ','), ('which', 'WDT'),
 ('had', 'HVD'), ('over-all', 'JJ'), ('charge', 'NN'), ('of', 'IN'), ('the', 'A
T'), ('election', 'NN'), (',', ','), ('``', ''), ('deserves', 'VBZ'), ('the',
'AT'), ('praise', 'NN'), ('and', 'CC'), ('thanks', 'NNS'), ('of', 'IN'), ('th
e', 'AT'), ('City', 'NN-TL'), ('of', 'IN-TL'), ('Atlanta', 'NP-TL'), ('"',
'''), ('for', 'IN'), ('the', 'AT'), ('manner', 'NN'), ('in', 'IN'), ('which',
'WDT'), ('the', 'AT'), ('election', 'NN'), ('was', 'BEDZ'), ('conducted', 'VB
N'), ('.', '.')], ...]
```

In [9]:

```
len(tagsen)
```

Out[9]:

```
57340
```

```
In [11]: br_train = tagsen[0:50000]
br_test = tagsen[50000:]
br_test[0]
```

```
Out[11]: [('I', 'PPSS'),
('was', 'BEDZ'),
('loaded', 'VBN'),
('with', 'IN'),
('suds', 'NNS'),
('when', 'WRB'),
('I', 'PPSS'),
('ran', 'VBD'),
('away', 'RB'),
(',', ','),
('and', 'CC'),
('I', 'PPSS'),
("haven't", 'HV*'),
('had', 'HVN'),
('a', 'AT'),
('chance', 'NN'),
('to', 'TO'),
('wash', 'VB'),
('it', 'PPO'),
('off', 'RP'),
('.', '.')]

```

```
In [12]: t0 = nltk.DefaultTagger('NN')
t1 = nltk.UnigramTagger(br_train, backoff=t0)
t2 = nltk.BigramTagger(br_train, backoff=t1)
```

```
In [13]: t2.evaluate(br_test)
```

```
Out[13]: 0.9111006662708622
```

```
In [14]: total_train = [len(l) for l in br_train]
sum(total_train)
```

```
Out[14]: 1039920
```

```
In [15]: total_test = [len(l) for l in br_test]
sum(total_test)
```

```
Out[15]: 121272
```

```
In [16]: t1.evaluate(br_test)
```

```
Out[16]: 0.8897849462365591
```

```
In [17]: t2.evaluate(br_test)
```

```
Out[17]: 0.9111006662708622
```

```
In [19]: br_train[0]
```

```
Out[19]: [('The', 'AT'),  
          ('Fulton', 'NP-TL'),  
          ('County', 'NN-TL'),  
          ('Grand', 'JJ-TL'),  
          ('Jury', 'NN-TL'),  
          ('said', 'VBD'),  
          ('Friday', 'NR'),  
          ('an', 'AT'),  
          ('investigation', 'NN'),  
          ('of', 'IN'),  
          ("Atlanta's", 'NP$'),  
          ('recent', 'JJ'),  
          ('primary', 'NN'),  
          ('election', 'NN'),  
          ('produced', 'VBD'),  
          ('', ''),  
          ('no', 'AT'),  
          ('evidence', 'NN'),  
          ('', ''),  
          ('that', 'CS'),  
          ('any', 'DTI'),  
          ('irregularities', 'NNS'),  
          ('took', 'VBD'),  
          ('place', 'NN'),  
          ('.', '.')] 
```

```
In [20]: br_train  
[1277  
]
```

```
Out[20]: [1277]
```

```
In [21]: br_train[1277] [11]
```

```
Out[21]: ('cold', 'JJ')
```

```
In [22]: br_train_flat = [(word, tag) for sent in br_train for (word, tag) in sent]
```

```
In [23]: br_train_flat[:40]
```

```
Out[23]: [('The', 'AT'),
          ('Fulton', 'NP-TL'),
          ('County', 'NN-TL'),
          ('Grand', 'JJ-TL'),
          ('Jury', 'NN-TL'),
          ('said', 'VBD'),
          ('Friday', 'NR'),
          ('an', 'AT'),
          ('investigation', 'NN'),
          ('of', 'IN'),
          ("Atlanta's", 'NP$'),
          ('recent', 'JJ'),
          ('primary', 'NN'),
          ('election', 'NN'),
          ('produced', 'VBD'),
          ('', ''),
          ('no', 'AT'),
          ('evidence', 'NN'),
          ('', ''),
          ('that', 'CS'),
          ('any', 'DTI'),
          ('irregularities', 'NNS'),
          ('took', 'VBD'),
          ('place', 'NN'),
          ('.', '.'),
          ('The', 'AT'),
          ('jury', 'NN'),
          ('further', 'RBR'),
          ('said', 'VBD'),
          ('in', 'IN'),
          ('term-end', 'NN'),
          ('presentments', 'NNS'),
          ('that', 'CS'),
          ('the', 'AT'),
          ('City', 'NN-TL'),
          ('Executive', 'JJ-TL'),
          ('Committee', 'NN-TL'),
          ('', ''),
          ('which', 'WDT'),
          ('had', 'HVD')]
```

```
In [24]: br_train_flat[13]
```

```
Out[24]: ('election', 'NN')
```

```
In [25]: fd = nltk.FreqDist(br_train_flat)
         cfd = nltk.ConditionalFreqDist(br_train_flat)
```

```
In [26]: cfd['cold'].most_common()
```

```
Out[26]: [('JJ', 110), ('NN', 8), ('RB', 2)]
```

```
In [27]: br_train_2grams = list(nltk.ngrams(br_train_flat, 2))
br_train_cold = [a[1] for (a,b) in br_train_2grams if b[0] == 'cold']
fdist = nltk.FreqDist(br_train_cold)
[tag for (tag, _) in fdist.most_common()]
```

```
Out[27]: ['AT',
'IN',
'CC',
'QL',
'BEDZ',
'JJ',
',',
',',
'DT',
'PP$',
'RP',
'``',
'NN',
'VBN',
'VBD',
'CS',
'BEZ',
'DOZ',
'RB',
'PPSS',
'BE',
'VB',
'VBZ',
'NP$',
'BEDZ*',
'--',
'DTI',
'WRB',
'BED']
```

```
In [28]: br_pre = [(w2+"/"+t2, t1) for ((w1,t1),(w2,t2)) in br_train_2grams]
br_pre_cfd = nltk.ConditionalFreqDist(br_pre)
br_pre
('investigation/NN', 'AT'),
('of/IN', 'NN'),
('Atlanta's/NP$', 'IN'),
('recent/JJ', 'NP$'),
('primary/NN', 'JJ'),
('election/NN', 'NN'),
('produced/VBD', 'NN'),
('`/``', 'VBD'),
('no/AT', ``),
('evidence/NN', 'AT'),
(''''/'', 'NN'),
('that/CS', '''),
('any/DTI', 'CS'),
('irregularities/NNS', 'DTI'),
('took/VBD', 'NNS'),
('place/NN', 'VBD'),
('./.', 'NN'),
('The/AT', '.'),
('jury/NN', 'AT'),
('further/RBR', 'NN'),
...

```

```
In [29]: br_pre_cfd['cold/NN'].most_common()
```

```
Out[29]: [('AT', 4), ('JJ', 2), ('', 1), ('DT', 1)]
```

```
In [30]: br_pre_cfd['cold/JJ'].most_common()
```

```
Out[30]: [('AT', 38),
          ('IN', 14),
          ('CC', 8),
          ('QL', 7),
          ('BEDZ', 7),
          ('JJ', 4),
          ('DT', 3),
          ('', 3),
          ('PP$', 3),
          ('``', 2),
          ('NN', 2),
          ('VBN', 2),
          ('VBD', 2),
          ('CS', 1),
          ('BEZ', 1),
          ('DOZ', 1),
          ('RB', 1),
          ('PPSS', 1),
          ('BE', 1),
          ('VB', 1),
          ('VBZ', 1),
          ('NP$', 1),
          ('BEDZ*', 1),
          ('--', 1),
          ('RP', 1),
          ('DTI', 1),
          ('WRB', 1),
          ('BED', 1)]
```

```
In [31]: bigram_tagger = nltk.BigramTagger(br_train)
```

```
In [32]: text1 = word_tokenize('I was very cold.')
bigram_tagger.tag(text1)
```

```
Out[32]: [('I', 'PPSS'), ('was', 'BEDZ'), ('very', 'QL'), ('cold', 'JJ'), ('.', '.')] 
```

```
In [33]: text2 = word_tokenize('I had a cold.')
bigram_tagger.tag(text2)
```

```
Out[33]: [('I', 'PPSS'), ('had', 'HVD'), ('a', 'AT'), ('cold', 'JJ'), ('.', '.')] 
```

```
In [34]: text3 = word_tokenize('I had a severe cold.')
bigram_tagger.tag(text3)
```

```
Out[34]: [('I', 'PPSS'),
          ('had', 'HVD'),
          ('a', 'AT'),
          ('severe', 'JJ'),
          ('cold', 'JJ'),
          ('.', '.')] 
```

```
In [35]: text4 = word_tokenize('January was a cold month.')
bigram_tagger.tag(text4)
```

```
Out[35]: [('January', None),
          ('was', None),
          ('a', None),
          ('cold', None),
          ('month', None),
          ('.', None)]
```

```
In [36]: text5 = word_tokenize('I failed to do so.')
bigram_tagger.tag(text5)
```

```
Out[36]: [('I', 'PPSS'),
          ('failed', 'VBD'),
          ('to', 'TO'),
          ('do', 'DO'),
          ('so', 'RB'),
          ('.', '.')] 
```

```
In [37]: text6 = word_tokenize('I was happy, but so was my enemy.')
bigram_tagger.tag(text6)
```

```
Out[37]: [('I', 'PPSS'),
          ('was', 'BEDZ'),
          ('happy', 'JJ'),
          (',', ','),
          ('but', 'CC'),
          ('so', 'RB'),
          ('was', 'BEDZ'),
          ('my', 'PP$'),
          ('enemy', 'NN'),
          ('.', '.')] 
```

```
In [38]: text7 = word_tokenize('So, how was the exam?')
bigram_tagger.tag(text7)
```

```
Out[38]: [('So', 'RB'),
          (',', ','),
          ('how', 'WRB'),
          ('was', 'BEDZ'),
          ('the', 'AT'),
          ('exam', None),
          ('?', None)]
```



```
In [39]: text8 = word_tokenize('The students came in early so they can get good seats.')
bigram_tagger.tag(text8)
```

```
Out[39]: [('The', 'AT'),
('students', 'NNS'),
('came', 'VBD'),
('in', 'IN'),
('early', 'JJ'),
('so', 'CS'),
('they', 'PPSS'),
('can', 'MD'),
('get', 'VB'),
('good', 'JJ'),
('seats', 'NNS'),
('.', '.')]

```

```
In [40]: text9 = word_tokenize('She failed the exam, so she must take it again.')
bigram_tagger.tag(text9)
```

```
Out[40]: [('She', 'PPS'),
('failed', 'VBD'),
('the', 'AT'),
('exam', None),
(',', None),
('so', None),
('she', None),
('must', None),
('take', None),
('it', None),
('again', None),
('.', None)]

```

```
In [41]: text9 = word_tokenize('She failed the exam, so she must take it again.')
bigram_tagger.tag(text9)
```

```
Out[41]: [('She', 'PPS'),
('failed', 'VBD'),
('the', 'AT'),
('exam', None),
(',', None),
('so', None),
('she', None),
('must', None),
('take', None),
('it', None),
('again', None),
('.', None)]

```

```
In [42]: text9 = word_tokenize('She failed the exam, so she must take it again.')
bigram_tagger.tag(text9)
```

```
Out[42]: [('She', 'PPS'),
          ('failed', 'VBD'),
          ('the', 'AT'),
          ('exam', None),
          (',', None),
          ('so', None),
          ('she', None),
          ('must', None),
          ('take', None),
          ('it', None),
          ('again', None),
          ('.', None)]
```

```
In [ ]:
```

```
In [44]: text11 = word_tokenize('Wow, so incredible.')
bigram_tagger.tag(text11)
```

```
Out[44]: [('Wow', None), (',', None), ('so', None), ('incredible', None), ('.', None)]
```

```
In [ ]:
```