



Secure Exit

SIMATS Online Programming Lab

C++ PROGRAMMING

J Raksakanth
1911260099D

CO1_AT2_MCQ

View Only

← Back

QUESTIONS

Q1
3
1 mark

Q2
15
1 mark

Q3
19
1 mark

Q4
32
1 mark

Q5
20
1 mark

Q6
39
1 mark

Q7
43
1 mark

Q49 24

1 mark

Implicit conversion is performed by:

A. User

B. Compiler ✓

C. OS

D. Linker

✓ Correct — 1.00 / 1 marks



Secure Exit

SIMATS Online Programming Lab

C++ PROGRAMMING

J Raksakanth
1911260099D

CO1_AT2_MCQ

View Only

← Back

QUESTIONS

Q1
3
1 mark

Q2
15
1 mark

Q3
19
1 mark

Q4
32
1 mark

Q5
20
1 mark

Q6
39
1 mark

Q7
43
1 mark

Q47 9

1 mark

Which language supports both procedural and OOP paradigms?

A. Smalltalk

B. Java

C. C++ ✓

D. Ruby

✓ Correct — 1.00 / 1 marks

CO1_AT2_MCQ

View Only

← Back

QUESTIONS
Q1 ✓

3
1 mark

Q2 ✓

15
1 mark

Q3 ✓

19
1 mark

Q4 ✓

32
1 mark

Q5 ✓

20
1 mark

Q6 ✓

39
1 mark

Q7 ✓

32
1 mark

Q47 9

1 mark

Which language supports both procedural and OOP paradigms?

A. Smalltalk

B. Java

C. C++ ✓

D. Ruby

✓ Correct — 1.00 / 1 marks

CO1_AT2_MCQ

View Only

← Back

QUESTIONS
Q1 ✓

3
1 mark

Q2 ✓

15
1 mark

Q3 ✓

19
1 mark

Q4 ✓

32
1 mark

Q5 ✓

20
1 mark

Q6 ✓

39
1 mark

Q7 ✓

32
1 mark

Q46 17

1 mark

Size of bool is typically:

A. 1 byte ✓

B. 2 bytes

C. 4 bytes

D. 8 bytes

✓ Correct — 1.00 / 1 marks



Secure Exit

SIMATS Online Programming Lab

C++ PROGRAMMING

J Raksakanth

1911260099D

CO1_AT2_MCQ

View Only

← Back

QUESTIONS

Q1

3

1 mark

✓

Q2

15

1 mark

✓

Q3

19

1 mark

✓

Q4

32

1 mark

✓

Q5

20

1 mark

✓

Q6

39

1 mark

✓

Q7

40

1 mark

✓

Q45 40

1 mark

What is the output?

#include <iostream> using namespace std;

int main()

{

for(int i=1;i<=5;i++)

{

if(i==3)

break;

cout<<i;

}

}

A. 12345

B. 12 ✓

C. 345

CO1_AT2_MCQ

View Only

← Back

QUESTIONS

Q1

3

1 mark

✓

Q2

15

1 mark

✓

Q3

19

1 mark

✓

Q4

32

1 mark

✓

Q5

20

1 mark

✓

Q6

39

1 mark

✓

Q7

40

1 mark

✓

Q44 16

1 mark

Which data type stores decimal values?

A. int

B. char

C. float ✓

D. bool

✓ Correct — 1.00 / 1 marks

CO1_AT2_MCQ

View Only

← Back

QUESTIONS

Q1

3

1 mark



Q2

15

1 mark



Q3

19

1 mark



Q4

32

1 mark



Q5

20

1 mark



Q6

39

1 mark



Q43 35

1 mark

What is the output?

```
#include <iostream> using namespace std;
int main()
{
    int x = 10;
    cout << x++;
    return 0;
}
```

A. 10 ✓

B. 11

C. Error

D. Garbage Value

CO1_AT2_MCQ

View Only

← Back

QUESTIONS

Q1

3

1 mark



Q2

15

1 mark



Q3

19

1 mark



Q4

32

1 mark



Q5

20

1 mark



Q6

39

1 mark



Q42 46

1 mark

What is the output?

```
#include <iostream> using namespace std;
int main()
{
    int x = 1;
    switch(x)
    {
        case 1:
            cout << "A";
        case 2:
            cout << "B";
        default:
            cout << "C";
    }
}
```

A. A

CO1_AT2_MCQ

View Only

← Back

QUESTIONS

- Q1**
3
1 mark
- Q2**
15
1 mark
- Q3**
19
1 mark
- Q4**
32
1 mark
- Q5**
20
1 mark
- Q6**
39
1 mark

Q41 11

1 mark

Smallest individual unit in a program is:

- A. Token** ✓
- B. Statement**
- C. Expression**
- D. Block**

✓ Correct — 1.00 / 1 marks

CO1_AT2_MCQ

View Only

← Back

QUESTIONS

- Q1**
3
1 mark
- Q2**
15
1 mark
- Q3**
19
1 mark
- Q4**
32
1 mark
- Q5**
20
1 mark
- Q6**
39
1 mark

Q40 2

1 mark

Which OOP concept binds data and methods together?

- A. Inheritance**
- B. Encapsulation** ✓
- C. Polymorphism**
- D. Overloading**

✓ Correct — 1.00 / 1 marks



Secure Exit

SIMATS Online Programming Lab

C++ PROGRAMMING

J Raksakanth
1911260099D

CO1_AT2_MCQ

View Only

← Back

QUESTIONS

Q1
3
1 mark

Q2
15
1 mark

Q3
19
1 mark

Q4
32
1 mark

Q5
20
1 mark

Q6
39
1 mark

Q7
45
1 mark

Q39 8

1 mark

Which access specifier makes members accessible only within the class?

A. Public

B. Protected

C. Private ✓

D. Friend

✓ Correct — 1.00 / 1 marks



Secure Exit

SIMATS Online Programming Lab

C++ PROGRAMMING

J Raksakanth
1911260099D

CO1_AT2_MCQ

View Only

← Back

QUESTIONS

Q1
3
1 mark

Q2
15
1 mark

Q3
19
1 mark

Q4
32
1 mark

Q5
20
1 mark

Q6
39
1 mark

Q7
45
1 mark

Q38 29

1 mark

Which loop guarantees at least one execution?

A. for

B. while

C. do-while ✓

D. none

✓ Correct — 1.00 / 1 marks

CO1_AT2_MCQ

View Only

← Back

QUESTIONS

- Q1**
3
1 mark
- Q2**
15
1 mark
- Q3**
19
1 mark
- Q4**
32
1 mark
- Q5**
20
1 mark
- Q6**
39
1 mark

Q37 22

1 mark

User-defined data type example:

A. int

B. float

C. class ✓

D. char

✓ Correct — 1.00 / 1 marks

CO1_AT2_MCQ

View Only

← Back

QUESTIONS

- Q1**
3
1 mark
- Q2**
15
1 mark
- Q3**
19
1 mark
- Q4**
32
1 mark
- Q5**
20
1 mark
- Q6**
39
1 mark

Q36 42

1 mark

What is the output?

```
#include <iostream> using namespace std;
int main()
{
    int a = 10;
    int b = a++;
    cout << a << " " << b; }
```

A. 10 10

B. 11 10 ✓

C. 11 11

D. 10 11

✓ Correct — 1.00 / 1 marks

CO1_AT2_MCQ

View Only

← Back

QUESTIONS

- Q1**
3
1 mark
- Q2**
15
1 mark
- Q3**
19
1 mark
- Q4**
32
1 mark
- Q5**
20
1 mark
- Q6**
39
1 mark

Q36 42

1 mark

What is the output?

```
#include <iostream> using namespace std;
int main()
{
    int a = 10;
    int b = a++;
    cout << a << " " << b; }
```

A. 10 10

B. 11 10 ✓

C. 11 11

D. 10 11

✓ Correct — 1.00 / 1 marks

CO1_AT2_MCQ

View Only

← Back

QUESTIONS

- Q1**
3
1 mark
- Q2**
15
1 mark
- Q3**
19
1 mark
- Q4**
32
1 mark
- Q5**
20
1 mark
- Q6**
39
1 mark

Q35 28

1 mark

Which statement is a selection control structure?

A. for

B. while

C. if ✓

D. do-while

✓ Correct — 1.00 / 1 marks

CO1_AT2_MCQ

View Only

← Back

QUESTIONS

- Q1**
3
1 mark
- Q2**
15
1 mark
- Q3**
19
1 mark
- Q4**
32
1 mark
- Q5**
20
1 mark
- Q6**
39
1 mark

Q34 48

1 mark

What is the output? #include <iostream> using namespace std;

```
int main() {
    int i = 5;
    do {
        cout << i << " "; i--;
    } while(i > 5);
}
```

- A.** No Output
- B.** 5 ✓
- C.** Infinite Loop D) Error

✓ Correct — 1.00 / 1 marks

CO1_AT2_MCQ

View Only

← Back

QUESTIONS

- Q1**
3
1 mark
- Q2**
15
1 mark
- Q3**
19
1 mark
- Q4**
32
1 mark
- Q5**
20
1 mark
- Q6**
39
1 mark

Q33 13

1 mark

Which is an integer constant?

- A.** 45 ✓
- B.** 4.5
- C.** 'A'
- D.** "45"

✓ Correct — 1.00 / 1 marks

CO1_AT2_MCQ

View Only

← Back

QUESTIONS
Q1 ✓

3
1 mark

Q2 ✓

15
1 mark

Q3 ✓

19
1 mark

Q4 ✓

32
1 mark

Q5 ✓

20
1 mark

Q6 ✓

39
1 mark

Q7 ✓

32
1 mark

Q32 18

1 mark

Which data type stores a single character?

A. string

B. char ✓

C. text

D. symbol

✓ Correct — 1.00 / 1 marks

CO1_AT2_MCQ

View Only

← Back

QUESTIONS
Q1 ✓

3
1 mark

Q2 ✓

15
1 mark

Q3 ✓

19
1 mark

Q4 ✓

32
1 mark

Q5 ✓

20
1 mark

Q6 ✓

39
1 mark

Q7 ✓

32
1 mark

Q31 4

1 mark

Which OOP principle promotes code reusability?

A. Abstraction

B. Inheritance ✓

C. Encapsulation

D. Binding

✓ Correct — 1.00 / 1 marks

CO1_AT2_MCQ

View Only

← Back

QUESTIONS

- Q1**
3
1 mark
- Q2**
15
1 mark
- Q3**
19
1 mark
- Q4**
32
1 mark
- Q5**
20
1 mark
- Q6**
39
1 mark
- Q7**
40
1 mark

Q30 31

1 mark

Which loop is entry controlled?

A. while

B. for

C. Both A and B ✓

D. do-while

✓ Correct — 1.00 / 1 marks

CO1_AT2_MCQ

View Only

← Back

QUESTIONS

- Q1**
3
1 mark
- Q2**
15
1 mark
- Q3**
19
1 mark
- Q4**
32
1 mark
- Q5**
20
1 mark
- Q6**
39
1 mark
- Q7**
40
1 mark

Q29 14

1 mark

Which is a character constant?

A. A

B. 'A' ✓

C. "A"

D. char

✓ Correct — 1.00 / 1 marks

CO1_AT2_MCQ

View Only

← Back

QUESTIONS

- Q1**
3
1 mark
- Q2**
15
1 mark
- Q3**
19
1 mark
- Q4**
32
1 mark
- Q5**
20
1 mark
- Q6**
39
1 mark
- Q7**
43
1 mark

Q28 5

1 mark

Runtime polymorphism is achieved through:

- A. Function Overloading
- B. Operator Overloading
- C. Virtual Functions ✓
- D. Templates

✓ Correct — 1.00 / 1 marks

CO1_AT2_MCQ

View Only

← Back

QUESTIONS

- Q1**
3
1 mark
- Q2**
15
1 mark
- Q3**
19
1 mark
- Q4**
32
1 mark
- Q5**
20
1 mark
- Q6**
39
1 mark
- Q7**
43
1 mark

Q27 43

1 mark

What is the output?

```
#include <iostream> using namespace std;
int main()
{
    int x = 5;
    cout << (x > 3 ? x+2 : x-2); }
```

- A. 3
- B. 5
- C. 7 ✓
- D. 2

✓ Correct — 1.00 / 1 marks

CO1_AT2_MCQ

View Only

← Back

QUESTIONS
Q1 ✓

3
1 mark

Q2 ✓

15
1 mark

Q3 ✓

19
1 mark

Q4 ✓

32
1 mark

Q5 ✓

20
1 mark

Q6 ✓

39
1 mark

Q7 ✓

1
1 mark

Q26 6

1 mark

An object is:

A. Blueprint of a class

B. Instance of a class ✓

C. Function inside class

D. Variable

✓ Correct — 1.00 / 1 marks

CO1_AT2_MCQ

View Only

← Back

QUESTIONS
Q1 ✓

3
1 mark

Q2 ✓

15
1 mark

Q3 ✓

19
1 mark

Q4 ✓

32
1 mark

Q5 ✓

20
1 mark

Q6 ✓

39
1 mark

Q7 ✓

1
1 mark

Q25 23

1 mark

Assigning int to double causes:

A. Error

B. Narrowing

C. Widening ✓

D. Overflow

✓ Correct — 1.00 / 1 marks

CO1_AT2_MCQ

View Only

← Back

QUESTIONS

- Q1**
3
1 mark
- Q2**
15
1 mark
- Q3**
19
1 mark
- Q4**
32
1 mark
- Q5**
20
1 mark
- Q6**
39
1 mark

Q24 49

1 mark

How many times will the loop execute? for(int i=0; i<10; i+=2)
cout << i;

A. 4

B. 5 ✓

C. 6

D. 10

✓ Correct — 1.00 / 1 marks

CO1_AT2_MCQ

View Only

← Back

QUESTIONS

- Q1**
3
1 mark
- Q2**
15
1 mark
- Q3**
19
1 mark
- Q4**
32
1 mark
- Q5**
20
1 mark
- Q6**
39
1 mark

Q23 38

1 mark

What is the output?
#include <iostream> using namespace std;
int main()
{
int x=5;
cout<<x--<<" "<<x;
}

A. 5 4 ✓

B. 4 4 ✗

C. 5 5

D. 4 5

✗ Incorrect — 0.00 / 1 marks

CO1_AT2_MCQ

View Only

← Back

QUESTIONS

- Q1**
3
1 mark
- Q2**
15
1 mark
- Q3**
19
1 mark
- Q4**
32
1 mark
- Q5**
20
1 mark
- Q6**
39
1 mark
- Q7**
40
1 mark

Q22 21

1 mark

Which type provides highest precision?

A. float

B. int

C. double ✓

D. char

✓ Correct — 1.00 / 1 marks

CO1_AT2_MCQ

View Only

← Back

QUESTIONS

- Q1**
3
1 mark
- Q2**
15
1 mark
- Q3**
19
1 mark
- Q4**
32
1 mark
- Q5**
20
1 mark
- Q6**
39
1 mark
- Q7**
40
1 mark

Q21 26

1 mark

Explicit conversion is also known as:

A. Promotion

B. Casting ✓

C. Binding

D. Parsing

✓ Correct — 1.00 / 1 marks

CO1_AT2_MCQ

View Only

← Back

QUESTIONS

- Q1**
3
1 mark
- Q2**
15
1 mark
- Q3**
19
1 mark
- Q4**
32
1 mark
- Q5**
20
1 mark
- Q6**
39
1 mark

Q20 7

1 mark

A class is:

A. Data Type

B. User-defined blueprint ✓

C. Object instance

D. Keyword

✓ Correct — 1.00 / 1 marks

CO1_AT2_MCQ

View Only

← Back

QUESTIONS

- Q1**
3
1 mark
- Q2**
15
1 mark
- Q3**
19
1 mark
- Q4**
32
1 mark
- Q5**
20
1 mark
- Q6**
39
1 mark

Q19 37

1 mark

What is the output?

```
#include <iostream> using namespace std;
int main()
{
    cout << (5>3);
}
```

A. True

B. False

C. 1 ✓

✓ Correct — 1.00 / 1 marks

CO1_AT2_MCQ

View Only

← Back

QUESTIONS

- Q1**
3
1 mark
- Q2**
15
1 mark
- Q3**
19
1 mark
- Q4**
32
1 mark
- Q5**
20
1 mark
- Q6**
39
1 mark

Q18 44

1 mark

What is the output?

```
#include <iostream> using namespace std;
int main()
{
    char ch = 'A';
    cout << int(ch);
}
```

A. A

B. 64

C. 65 ✓

D. 66

✓ Correct — 1.00 / 1 marks

CO1_AT2_MCQ

View Only

← Back

QUESTIONS

- Q1**
3
1 mark
- Q2**
15
1 mark
- Q3**
19
1 mark
- Q4**
32
1 mark
- Q5**
20
1 mark
- Q6**
39
1 mark

Q17 45

1 mark

What is the output?

```
#include <iostream> using namespace std;
int main()
{
    int x = 0;
    cout << !x;
}
```

B. 1 ✓

C. True

D. Error ✗

✗ Incorrect — 0.00 / 1 marks

CO1_AT2_MCQ

View Only

← Back

QUESTIONS
Q1

3
1 mark

Q2

15
1 mark

Q3

19
1 mark

Q4

32
1 mark

Q5

20
1 mark

Q6

39
1 mark

Q16 33

1 mark

Infinite loop example:

A. while(0)

B. while(1) ✓

C. for(i=0;j<0;i++)

D. if(1)

✓ Correct — 1.00 / 1 marks

CO1_AT2_MCQ

View Only

← Back

QUESTIONS
Q1

3
1 mark

Q2

15
1 mark

Q3

19
1 mark

Q4

32
1 mark

Q5

20
1 mark

Q6

39
1 mark

Q15 25

1 mark

Which conversion may lose data?

A. int → double B) float → double C) double → int D) short → int ✗

✗ Incorrect — 0.00 / 1 marks

CO1_AT2_MCQ

View Only

← Back

QUESTIONS

- Q1**
3
1 mark
- Q2**
15
1 mark
- Q3**
19
1 mark
- Q4**
32
1 mark
- Q5**
20
1 mark
- Q6**
39
1 mark

Q14 47

1 mark

What is the output?

```
#include <iostream> using namespace std;
int main() {
    int i;
    for(i=1; i<=5; i++);
    cout << i;
    return 0;
}
```

A. 5

B. 6 ✓

C. 1

D. Error

CO1_AT2_MCQ

View Only

← Back

QUESTIONS

- Q1**
3
1 mark
- Q2**
15
1 mark
- Q3**
19
1 mark
- Q4**
32
1 mark
- Q5**
20
1 mark
- Q6**
39
1 mark

Q13 34

1 mark

Default case in switch is:

A. Mandatory

B. Optional ✓

C. Illegal

D. First case only

✓ Correct — 1.00 / 1 marks

CO1_AT2_MCQ

View Only

← Back

QUESTIONS

- Q1**
3
1 mark
- Q2**
15
1 mark
- Q3**
19
1 mark
- Q4**
32
1 mark
- Q5**
20
1 mark
- Q6**
39
1 mark

Q12 30

1 mark

Which statement is used for multi-way selection?

- A. if
- B. switch ✓
- C. for
- D. while

✓ Correct — 1.00 / 1 marks

CO1_AT2_MCQ

View Only

← Back

QUESTIONS

- Q1**
3
1 mark
- Q2**
15
1 mark
- Q3**
19
1 mark
- Q4**
32
1 mark
- Q5**
20
1 mark
- Q6**
39
1 mark

Q11 41

1 mark

What is the output?

```
#include <iostream> using namespace std;
int main()
{
    for(int i=1;i<=5;i++)
    {
        if(i==3)
            continue;
        cout<< i;
    }
}
```

- A. 12345
- B. 1245 ✓
- C. 345



Secure Exit

SIMATS Online Programming Lab

C++ PROGRAMMING

J Raksakanth
1911260099D

CO1_AT2_MCQ

View Only

← Back

QUESTIONS

Q1
3
1 mark

Q2
15
1 mark

Q3
19
1 mark

Q4
32
1 mark

Q5
20
1 mark

Q6
39
1 mark

Q7
45
1 mark

Q10 27

1 mark

Bitwise AND operator:

A. &&

B. & ✓

C. ||

D. |

✓ Correct — 1.00 / 1 marks



Secure Exit

SIMATS Online Programming Lab

C++ PROGRAMMING

J Raksakanth
1911260099D

CO1_AT2_MCQ

View Only

← Back

QUESTIONS

Q1
3
1 mark

Q2
15
1 mark

Q3
19
1 mark

Q4
32
1 mark

Q5
20
1 mark

Q6
39
1 mark

Q7
45
1 mark

Q9 36

1 mark

What is the output?
#include <iostream> using namespace std;
int main()
{
int i=1;
while(i<=3)
{
cout<<i;
i++;
}
}

A. 321

B. 123 ✓

C. 12



Secure Exit

SIMATS Online Programming Lab

C++ PROGRAMMING

J Raksakanth
1911260099D

CO1_AT2_MCQ

View Only

← Back

QUESTIONS

Q1
3
1 mark

Q2
15
1 mark

Q3
19
1 mark

Q4
32
1 mark

Q5
20
1 mark

Q6
39
1 mark

Q7
50
1 mark

Q8 12

1 mark

Which is a valid identifier?

A. 2value

B. total_marks ✓

C. float

D. @sum

✓ Correct — 1.00 / 1 marks



Secure Exit

SIMATS Online Programming Lab

C++ PROGRAMMING

J Raksakanth
1911260099D

CO1_AT2_MCQ

View Only

← Back

QUESTIONS

Q1
3
1 mark

Q2
15
1 mark

Q3
19
1 mark

Q4
32
1 mark

Q5
20
1 mark

Q6
39
1 mark

Q7
50
1 mark

Q7 50

1 mark

What is the output?
for(int i=0;j=10; i<j; i++j--)
cout << i << j;

A. 9182736 ✓

B. 1019283746

C. 01019283746 55

D. Error ✗

✗ Incorrect — 0.00 / 1 marks

CO1_AT2_MCQ

View Only

← Back

QUESTIONS

- Q1**
3
1 mark
- Q2**
15
1 mark
- Q3**
19
1 mark
- Q4**
32
1 mark
- Q5**
20
1 mark
- Q6**
39
1 mark

Q6 39

1 mark

What is the output?

```
#include <iostream> using namespace std;
int main()
{
    cout<<(10/3);
}
```

A. 3.33

B. 3 ✓

C. 4

D. Error

✓ Correct — 1.00 / 1 marks

CO1_AT2_MCQ

View Only

← Back

QUESTIONS

- Q1**
3
1 mark
- Q2**
15
1 mark
- Q3**
19
1 mark
- Q4**
32
1 mark
- Q5**
20
1 mark
- Q6**
39
1 mark

Q5 20

1 mark

Which type occupies the least memory?

A. char ✓

B. int

C. float

D. double

✓ Correct — 1.00 / 1 marks

CO1_AT2_MCQ

View Only

← Back

QUESTIONS
Q1

3

1 mark


Q2

15

1 mark


Q3

19

1 mark


Q4

32

1 mark


Q5

20

1 mark


Q6

39

1 mark


Q4 32

1 mark

Which is exit-controlled?

A. while

B. for

C. do-while ✓

D. switch

✓ Correct — 1.00 / 1 marks

CO1_AT2_MCQ

View Only

← Back

QUESTIONS
Q1

3

1 mark


Q2

15

1 mark


Q3

19

1 mark


Q4

32

1 mark


Q5

20

1 mark


Q6

39

1 mark


Q3 19

1 mark

Which has the largest range?

A. int

B. short

C. long long ✓

D. char

✓ Correct — 1.00 / 1 marks

CO1_AT2_MCQ

View Only

← Back

QUESTIONS
Q1 ✓

3
1 mark

Q2 ✓

15
1 mark

Q3 ✓

19
1 mark

Q4 ✓

32
1 mark

Q5 ✓

20
1 mark

Q6 ✓

39
1 mark

Q7 ✓

1
1 mark

Q2 15

1 mark

Which is a string literal?

A. 'ABC'

B. "ABC" ✓

C. ABC

D. string

✓ Correct — 1.00 / 1 marks

CO1_AT2_MCQ

View Only

← Back

QUESTIONS
Q1 ✓

3
1 mark

Q2 ✓

15
1 mark

Q3 ✓

19
1 mark

Q4 ✓

32
1 mark

Q5 ✓

20
1 mark

Q6 ✓

39
1 mark

Q7 ✓

1
1 mark

Q1 3

1 mark

Hiding implementation details from users is called:

A. Inheritance

B. Encapsulation

C. Abstraction ✓

D. Polymorphism

✓ Correct — 1.00 / 1 marks

CO1_AT2_MCQ

View Only

[← Back](#)

QUESTIONS

Q1 ✓
3
1 mark**Q2** ✓
15
1 mark**Q3** ✓
19
1 mark**Q4** ✓
32
1 mark**Q5** ✓
20
1 mark**Q6** ✓
39
1 mark**Q7** ✓
48
1 mark**Q50 10**

1 mark

GUI applications are commonly developed using:

A. OOP ✓**B. Assembly****C. Machine Language****D. Macro Processing**

✓ Correct — 1.00 / 1 marks