Accenture Australia Pty Ltd

Spatial WA – Next Generation Spatial Cadastre (NGSC)

3D CSDM Solution Architecture Contribution

Prepared by: Surround Australia Pty Ltd (SURROUND)

Date: 2026-11-02

Table of Contents

1 Purpose, scope, and responsibilities 1

1.1 Purpose 1

1.2 Contractual context and scope 1

1.3 Responsibilities and architectural boundaries 1

1.4 Relationship to supporting documentation 2

2 Architectural overview 2

2.1 Architecture context and scope 2

2.2 Modular implementation and external standards 3

2.3 NGSC information exchange boundary 4

3 Architectural viewpoints 4

3.1 Enterprise viewpoint 5

3.2 Information viewpoint 5

3.3 Computational viewpoint 6

3.4 Engineering viewpoint 6

3.5 Technology viewpoint 6

4 Requirement-specific architecture contributions 6

4.1 Cadastral information exchange and transformation 7

4.2 Survey observations and control 7

4.3 3D cadastral representation and visualisation 8

4.4 Metadata, naming, and standards compliance 8

4.5 Plan lodgement and validation interfaces 9

4.6 Architectural dependencies and traceability 9

5 Specifications and verification 9

5.1 Machine-readable specifications 9

5.2 Verification approach 11

5.3 Supporting implementations and evidence 11

6 Integration considerations and dependencies 11

6.1 NGSC integration boundaries 11

6.2 Source transformation and information preservation 13

6.3 Validation and authoritative acceptance 13

6.4 External specification dependencies 13

6.5 Outstanding architectural decisions 13

7 Summary 13

8 References 15

Revision History

Version	Status	Date	Author	Description
0.1	Draft	2026-10-26	Andrew Hunter	Report created
0.2	Draft	2026-10-28	Rob Atkinson	Reviewd for release to Accenture as DRAFT

Table of Figures

Figure 1: WA 3D CSDM Profile Architecture 3
Figure 2: Modular composition and external dependencies 4
Figure 3: WA 3D CSDM controlled vocabularies and semantic bindings 6
Figure 4: Schema, profile and validation architecture 10
Figure 5: 3D CSDM information exchange and NGSC integration boundaries 12

Table of Tables

Table 1: Supporting documentation 2
Table 2: Cadastral information exchange and transformation architecture contributions 7
Table 3: Survey observations and control architecture contributions 7
Table 4: 3D cadastral representation and visualisation architecture contributions 8
Table 5: Metadata, naming, and standards compliance architecture contributions 8
Table 6: Plan lodgement and validation interfaces architecture contributions 9

Acronyms and Terms

Acronym	Description
2D	Two-dimensional: Having or representing extent in two spatial dimensions, such as easting and northing.
3D	Three-dimensional: Having or representing extent in three spatial dimensions, usually width, depth and height, or easting, northing and elevation.
3D CSDM	3D Cadastral Survey Data Model: A proposed standard for the exchange of digital cadastral survey information between the survey industry and government land administration agencies / land registries for Australian and New Zealand jurisdictions.
API	Application Programming Interface: A defined set of operations and data formats through which software components or systems exchange requests and data.
APX-05	WA Digital Data Format specification: The Western Australian User Guide produced for surveyors when creating Cadastral Survey Data (CSD) files for lodgement with Landgate to meet the requirements of Transfer of Land (Surveys) Regulations 1995 - Regulation 3.
CSD	Cadastral Survey Data: The digital record of a cadastral survey (its parcels, boundaries, marks, observations and metadata), lodged with or exchanged between land administration authorities.
ICSM	Intergovernmental Committee on Surveying and Mapping: The committee of Australian and New Zealand government agencies that coordinates national surveying, mapping, cadastral and geodetic standards.
JSON	JavaScript Object Notation: A lightweight, text-based format for structured data, built from name–value pairs and ordered lists.
NGSC	Next Generation Spatial Cadastre: Landgate's programme to replace Western Australia's cadastral systems with a spatially accurate, three-dimensional-capable digital cadastre.
OGC	Open Geospatial Consortium: An international not-for-profit consortium that develops open standards for geospatial content and services.
PROV	Provenance: A W3C family of specifications for describing the provenance of data: the entities, activities and agents involved in producing it.
RDF	Resource Description Framework: A W3C data model that represents information as subject–predicate–object statements (triples), forming graphs that can be linked across sources.
SHACL	Shapes Constraint Language: A W3C language for describing constraints on RDF data and for validating RDF graphs against them.
SKOS	Simple Knowledge Organization System: A W3C data model for representing thesauri, classification schemes, taxonomies and other controlled vocabularies, so that their concepts, labels and relationships can be published and linked on the web.
SOSA	Sensor, Observation, Sample, and Actuator: A lightweight W3C and OGC ontology for describing sensors, observations, sampling and actuation, and the procedures behind them.
W3C	World Wide Web Consortium: An international standards organisation that develops open standards for the World Wide Web.
WA	Western Australia: The Australian state covering the western third of the continent.

Purpose, scope, and responsibilities

Purpose

This document consolidates SURROUND Australia Pty Ltd's (SURROUND) Cadastral Survey Data (CSD), 3D Cadastral Survey Data Model (3D CSDM), and metadata architecture contributions to the Western Australian Next Generation Spatial Cadastre (NGSC) project.

It identifies the information structures, specifications, technical artefacts, and integration dependencies relevant to SURROUND's allocated requirements. It supports Accenture's NGSC Solution Architecture and draws on the five requirements analysis deliverables prepared by SURROUND Pty Ltd [1]–[5], the WA Implementation Profile, and associated technical developments.

Contractual context and scope

Accenture engaged SURROUND to provide specialist cadastral information modelling, standards development, requirements analysis, and technical support.

Schedule 1 of the subcontract [6] identifies 34 allocated requirements, comprising 15 classified as SURROUND Responsible and 19 as SURROUND Supporting. The 34 requirements represent the original contractual allocation. Requirement NN01.02.026 was subsequently moved out of scope but remains included in the Engagement Outcomes and Recommendations Report [7] for traceability. This architecture contribution addresses the 15 requirements classified as SURROUND Responsible. For applicable Responsible requirements, Schedule 1 requires documentation of CSD, 3D CSDM, or metadata components in a Solution Architecture document, together with other specified technical deliverables.

This document addresses the architectural documentation requirement through the following areas:

- **Information architecture:** 3D CSDM structures, WA profile extensions, identifiers, metadata, provenance, and controlled vocabularies.
- **Geometry and topology:** Cadastral geometry, topological relationships, legal boundary definitions, and geometric constraints.
- **Data exchange:** Survey information exchange, legacy CSD transformation, and preservation of source observations.
- **Validation:** Structural, semantic, geometric, topological, and cadastral validation approaches.
- **Processing capabilities:** Relevant transformation, validation, visualisation, and reporting patterns.
- **Requirement traceability:** Relationships between requirements, specifications, technical artefacts, and dependencies.

Supporting requirements are included where relevant to architectural decisions or shared information components.

Responsibilities and architectural boundaries

Accenture is responsible for the overall NGSC solution architecture, system development, and integration. Landgate retains responsibility for jurisdictional policy, business requirements, and authoritative cadastral decisions.

SURROUND's contribution concerns cadastral information structures, standards, technical specifications, validation approaches, and implementation guidance. The 3D CSDM defines an exchange model; it does not prescribe NGSC applications, Esri Parcel Fabric configuration, databases, security, transactions, or workflows.

Where requirements span both information modelling and system functions, this report identifies the information contribution and outstanding integration dependencies. Referenced technical artefacts are at varying stages of development and do not, by their inclusion, establish formal acceptance or operational readiness.

Relationship to supporting documentation

This document is intended to complement Accenture's NGSC Solution Architecture.

The principal supporting materials are listed in Table 1.

Table 1: Supporting documentation

Reference	Purpose
Subcontract Schedule 1	Contractual requirements and deliverable obligations.
Deliverables 1–5 [1]–[5]	Requirements analyses, 3D CSDM perspectives, proposed acceptance criteria, and dependencies.
Engagement Outcomes and Recommendations Report [7]	Consolidated technical findings, architectural decisions, and recommendations, including requirements traceability matrix and technical artefact register.
Technical repositories	Machine-readable specifications, datasets, validation resources, and supporting implementations.

Requirement-specific details and outstanding decisions are cross-referenced to these sources rather than repeated here.

Architectural overview

Architecture context and scope

The 3D Cadastral Survey Data Model (3D CSDM) provides a standards-based exchange model for cadastral survey information, including 2D and 3D parcels, observations, spatial relationships, metadata, and provenance. It separates the representation of cadastral information from the systems used to manage it.

Three specification levels establish progressively specialised constraints:

- **3D CSDM common model:** Reusable cadastral information structures and JSON exchange encoding.
- **ICSM common profile:** Shared implementation constraints and conventions.
- **WA implementation profile:** Jurisdiction-specific rules, constraints, and controlled vocabulary bindings.

OGC Building Blocks support component reuse, schema assembly, automated testing, and documentation. Figure 1 places these specification levels within the broader architecture of model components, standards, and build services.




Figure 1: WA 3D CSDM Profile Architecture

Figure 1 distinguishes standards foundations, independently governed components, the common exchange model, shared ICSM constraints, and WA-specific profiles. These are architectural roles rather than a literal dependency or inheritance sequence. Specialised WA profiles may introduce additional constraints for particular cadastral products.

The detailed schemas, semantic definitions, examples, and versioned dependencies are maintained in the 3D CSDM Common Model, ICSM Common Profile, and WA Implementation Profile.

Modular implementation and external standards

The 3D CSDM reuses external Building Blocks rather than redefining common feature, topology, observation, naming, and provenance structures. Figure 2 groups these dependencies by function, rather than depicting individual schema references.

The principal external dependencies are:

- **Land Parcels:** Cadastral parcel concepts and relationships.
- **Topo Feature:** Explicit geometry and topology, including 3D structures.
- **OGC API Features** and **feature collections:** Common feature representations.
- **SOSA:** Survey observations and associated measurement semantics.
- **PROV:** Provenance and derivation.
- **Compound Name** and **Dublin Core Terms:** Structured names and metadata.




Figure 2: Modular composition and external dependencies

Solid arrows show conceptual composition; dashed arrows show reuse of external specifications. The relationships are explanatory, not a literal schema dependency graph.

The published Building Block specifications record the actual dependency relationships and applicable versions. Figure 2 is a functional summary, not a normative dependency graph.

NGSC information exchange boundary

Within NGSC, the 3D CSDM provides an exchange and interpretation model, not an operational storage schema. Legacy information, including WA APX-05 [8], may require mapping and derivation; conforming 3D CSDM datasets may be ingested directly. Both pathways require source identification, appropriate validation, and provenance preservation.

The exchanged information can support plan lodgement, cadastral maintenance, visualisation, metadata management, and downstream services. Mapping into authoritative cadastral records, workflows, and Esri Parcel Fabric is an NGSC implementation responsibility. Exchange conformance does not establish legal authority or acceptance for lodgement.

Architectural viewpoints

The architecture is described through five complementary viewpoints: Enterprise, Information, Computational, Engineering, and Technology. These viewpoints distinguish the information architecture contribution from the broader NGSC system design.

Enterprise viewpoint

The 3D CSDM provides a common exchange structure for survey data producers, lodgement processes, cadastral maintenance, and downstream consumers. Landgate determines jurisdictional policy and authoritative cadastral outcomes; Accenture integrates the information capabilities into NGSC; SURROUND supplies the relevant modelling, specification, and verification contributions.

Information viewpoint

The common model organises cadastral features, survey observations, spatial representations, identifiers, metadata, and provenance. It supports 2D and 3D parcels and explicit geometric and topological relationships through reuse of Topo Feature.

Specialised products, including WA built strata, may require legal boundary definitions tied to building elements or other reference features, multi-component parcels, and defined vertical extents. The model also distinguishes source observations from derived geometry and interpretation, with provenance supporting traceability.

Controlled vocabularies and semantic bindings

The 3D CSDM uses controlled vocabularies to provide consistent definitions and permitted values for cadastral information. These vocabularies are expressed using the W3C Simple Knowledge Organization System (SKOS), supporting shared terminology, semantic interoperability, and machine-readable validation.

The WA Core profile defines vocabulary bindings that associate information properties and their expected value types with managed vocabularies. As illustrated in Figure 3, these bindings are maintained separately from the vocabulary definitions. The WA profile specifies where vocabularies apply, while the ICSM vocabulary repository maintains their content and supports publication as SKOS resources.

This separation enables vocabulary terms to be governed and maintained independently of the schemas that use them. It also supports reuse across jurisdictional profiles, consistent interpretation of cadastral information, and validation against the applicable vocabulary constraints.

Vocabulary governance should distinguish jurisdiction-specific terminology from concepts suitable for national reuse. Proposed changes to shared vocabularies should be coordinated with the relevant standards custodians, while profile-specific bindings and constraints remain subject to the applicable profile governance arrangements.

The detailed bindings, vocabulary definitions, and published SKOS resources are maintained in the WA Implementation Profile and ICSM Vocabularies repository.

The 3D CSDM Common Model, ICSM Common Profile, and WA Implementation Profile specify the detailed properties, relationships, and vocabulary bindings.




Figure 3: WA 3D CSDM controlled vocabularies and semantic bindings

Computational viewpoint

Principal processing capabilities include source transformation, structural and semantic validation, geometric and topological checks, spatial derivation, visualisation, and reporting. These functions can be implemented as reusable components. For example, JSON Schema checks structure, while specialised tools such as `topo-functions` assess spatial relationships beyond schema validation. Requirement-specific applications are described in the following section.

Engineering viewpoint

The exchange specification provides a potential contract between independently implemented ingestion, transformation, validation, and cadastral services. The allocation of these capabilities to NGSC APIs, applications, transactions, and authoritative data management remains subject to Accenture's solution architecture.

Technology viewpoint

OGC Building Blocks assemble JSON-based exchange schemas and related semantic resources. JSON Schema supports structural checks; JSON-LD and SHACL support semantic interpretation and constraints. Topo Feature and Python-based tools support specialised spatial processing. These technologies do not prescribe NGSC's application framework or storage platform; implementation details reside in the technical repositories.

Requirement-specific architecture contributions

This section maps the 15 SURROUND Responsible requirements (Tables 2–6) to their principal CSD/3D CSDM or metadata components, supporting artefacts, and NGSC integration dependencies. Requirements are grouped by shared architecture

concerns; detailed analyses and proposed acceptance criteria remain in Deliverables 1–5 [1]–[5] and the Engagement Outcomes and Recommendations Report [7].

Cadastral information exchange and transformation

The recommended information architecture uses the 3D CSDM and its Western Australian profile as the common representation for cadastral survey information exchange. Existing CSD formats may be transformed into this representation, subject to defined mapping rules and preservation of source information.

Table 2: Cadastral information exchange and transformation architecture contributions

Requirement	Architectural contribution	Supporting artefacts	Integration considerations and dependencies
NF02.03.047: Manually import lodged surveys	CSD/3D CSDM exchange structures, parcel identifiers, survey observations, spatial representations and provenance.	WA 3D CSDM profile; common components; Deliverable 3 [3].	Source matching, manual exception handling, validation, and authoritative dataset updates.
NF02.03.067: Import 3D CSDM files to Mining Cadastre dataset	Common cadastral information structures with profile-specific constraints for mining cadastral information.	3D CSDM common components; WA profile; Deliverable 3 [3].	Mining Cadastre product requirements, mapping, validation and record maintenance.
NN01.02.016: Support 3D CSDM exchange specification	Machine-readable information structures, schemas, semantic definitions, controlled vocabularies and validation resources.	WA profile; common components; ICSM vocabularies; OGC Building Blocks.	Profile versions, supported product types, conformance requirements and application integration.
NN01.02.017: Support CSD format specification	Legacy CSD information mappings, survey observation structures, identifiers and transformation provenance.	APX-05 [8] analysis; 3D CSDM specifications; Deliverable 3 [3].	Transformation rules, incomplete records, information loss and conversion validation.

Survey observations and control

The 3D CSDM provides structured representations of survey observations, points, survey marks, and associated reference information. Processing requirements must distinguish original observations from derived information and preserve the basis for any calculations.

Table 3: Survey observations and control architecture contributions

Requirement	Architectural contribution	Supporting artefacts	Integration considerations and dependencies
NF02.03.059: eField Records	Survey observation structures, points, lines, angles, connections, and provenance information.	3D CSDM common components; WA profile; Deliverable 3 [3].	eField Records import, geographic placement, control-point creation and survey adjustment interfaces.

Requirement	Architectural contribution	Supporting artefacts	Integration considerations and dependencies
NF02.03.071: Accept angles and bearings when a plan is imported	Representation of observed angles and azimuths, derived bearings, calculation provenance and quality information.	*Angles and Directions*; APX-05 [8] technical advice; `angles-to-bearings` proof of concept.	Bearing derivation, incomplete networks, conflicting observations, uncertainty and quality thresholds.
NF02.03.076: Import non-geodetic control	Survey points, marks, observations, cadastral connections and associated identifiers.	3D CSDM survey information structures; Deliverable 4 [4].	Candidate identification, duplicate detection, Editor selection and authoritative record creation.
NF04.01.010: API eField Records	Information exchange structures for survey records, observations and associated reference information.	3D CSDM survey information structures; Deliverable 3 [3].	API specification, authentication, data mapping, processing states and error handling.

3D cadastral representation and visualisation

The WA 3D CSDM profile supports representation of multi-component 3D parcels, including built-strata schemes where legal boundaries may be defined relative to building elements or other reference features.

Table 4: 3D cadastral representation and visualisation architecture contributions

Requirement	Architectural contribution	Supporting artefacts	Integration considerations and dependencies
NF02.02.027: 2D view of level in a building	3D parcel solids, parcel components, vertical extents and derived horizontal sections.	WA built-strata profile; SP83687 example dataset; horizontal section viewer proof of concept; Topo Feature viewer.	Selection of levels and section elevations, graphical presentation, accuracy and application integration.

The supporting technical developments demonstrate the derivation and visualisation of two-dimensional sections from structured 3D cadastral information. They do not prescribe the NGSC user interface or rendering implementation.

Metadata, naming, and standards compliance

The 3D CSDM provides source-level information concerning survey datasets, identifiers, coordinate reference information, purpose, and provenance. Additional operational metadata, catalogue management, quality assessments, and feedback workflows are NGSC responsibilities.

Table 5: Metadata, naming, and standards compliance architecture contributions

Requirement	Architectural contribution	Supporting artefacts	Integration considerations and dependencies
NF02.02.036: Metadata for my NGSC dataset	Dataset identifiers, provenance and references supporting traceability between cadastral datasets and metadata records.	3D CSDM metadata structures; Deliverable 5 [5].	Metadata feedback interface, catalogue linkage, issue-management workflow, ownership and audit.

Requirement	Architectural contribution	Supporting artefacts	Integration considerations and dependencies
NF03.02.006: Metadata for NGSC dataset	Source metadata structures and proposed mappings to NGSC catalogue information.	3D CSDM metadata structures; Deliverable 4 [4].	Authoritative NGSC Metadata Profile, catalogue ownership and metadata maintenance.
NF03.02.007: Metadata adheres to specified standard	Metadata schema constraints, controlled vocabularies and validation mechanisms.	WA profile; OGC Building Blocks; Deliverable 3 [3].	Applicable metadata standards, profile versions, compliance validation and reporting.
NN01.02.015: Align to Policies and Standards for Geographical Naming in Western Australia	Structured appellations using the `compoundName` pattern, with typed name components and jurisdictional vocabularies.	WA profile appellation datatypes; ICSM vocabularies; Deliverable 2 [2].	Authoritative naming policies, name sources, language attribution and NGSC record mapping.

Plan lodgement and validation interfaces

The 3D CSDM defines the cadastral information exchanged through plan lodgement and validation interfaces. The NGSC platform is responsible for implementing the associated APIs, workflows, transactions, and authoritative data management.

Table 6: Plan lodgement and validation interfaces architecture contributions

Requirement	Architectural contribution	Supporting artefacts	Integration considerations and dependencies
NF04.01.002: API to lodge plan	CSD/3D CSDM survey-package structures, identifiers, cadastral content and provenance.	WA profile; exchange specifications; Deliverable 4 [4].	API contract, lodgement workflows, source matching, record creation and transaction handling.
NF04.01.004: API to validate plan	Structural, semantic, geometric, topological and jurisdiction-specific cadastral validation rules.	WA profile; OGC Building Blocks validation resources; `topo-functions`; Deliverable 4 [4].	Validation stages, API responses, error reporting, applicable rules and acceptance decisions.

Architectural dependencies and traceability

Tables 2–6 identify common information and validation components used by multiple requirements. Supporting specifications should be maintained independently of individual application functions where practical. Outstanding decisions, including supported products, metadata profiles, transformation rules, and service responsibilities, are consolidated in the Engagement Outcomes and Recommendations Report [7] and require reconciliation with Accenture's NGSC architecture.

Specifications and verification

Machine-readable specifications

OGC Building Blocks assemble common model components, ICSM and WA profile constraints, and vocabulary bindings into published schemas and semantic resources. Compiled implementation artefacts provide the practical basis for applying exchange requirements; their source definitions remain in the respective repositories.

Figure 4 distinguishes generated schema and semantic validation resources from supplementary spatial and jurisdiction-specific rules, which may require separate implementations.




Figure 4: Schema, profile and validation architecture

The dashed connections to geometry, topology, and WA cadastral rules are intentional. They indicate that these rules are associated with the applicable specifications but are not necessarily generated automatically by the OGC Building Blocks toolchain.

The validation resources shown in Figure 4 are complementary: passing structural checks does not establish geometric validity, jurisdictional compliance, or authoritative acceptance. Validation results should identify affected components and the specification or rule versions applied.

Verification approach

Verification uses four complementary checks:

- **Syntactic and structural:** JSON encoding, required properties, types, and JSON Schema constraints.
- **Semantic and profile:** Controlled vocabularies and logical constraints, including those assessed using SHACL.
- **Geometric and topological:** Connectivity, closure, orientation, containment, and spatial relationships where applicable.
- **WA cadastral:** Jurisdiction-specific rules that may depend on external cadastral information, survey evidence, or policy.

The applicable checks depend on the dataset and encoding. Reports should distinguish failures from warnings and identify the affected data, applicable rule, and relevant version.

Supporting implementations and evidence

The repositories provide schemas, sample datasets, tests, and validation implementations. In particular, `topo-functions` supplies topology-related processing and validation capabilities. Proofs of concept also demonstrate processing of observations, 3D parcels, derived geometry, and horizontal sections.

These artefacts support architectural evaluation but do not establish operational readiness or formal NGSC acceptance. Integration testing, confirmed jurisdictional rules, and requirement-specific acceptance criteria remain necessary; see Deliverables 1–5 [1]–[5].

A consolidated validation and conformance test suite is recommended to support NGSC implementation and ongoing profile maintenance. This should combine versioned specifications, representative cadastral datasets, applicable validation rules, expected outcomes, and automated reporting. The scope and acceptance baseline require agreement with Accenture and Landgate, consistent with decision AD-08 in the Engagement Outcomes and Recommendations Report [7].

Principal references: WA Implementation Profile, 3D CSDM Common Model, and Topo Functions.

Integration considerations and dependencies

NGSC integration boundaries

Integration requires explicit mapping between the 3D CSDM exchange representation and NGSC's authoritative information structures, including Esri Parcel Fabric. Figure 5 shows the conceptual interface between source processing, profile-based exchange, and NGSC services; it does not prescribe their sequence or deployment.

Mappings must address identifiers, parcels and boundaries, survey observations, geometry, metadata, and provenance. Where operational structures cannot directly represent exchanged information, the solution must determine how it is retained, referenced, or made accessible.




Figure 5: 3D CSDM information exchange and NGSC integration boundaries

> *Figure 5 represents logical responsibilities, not a mandatory processing pipeline.*

Source transformation and information preservation

Legacy sources may require mapping or derivation into the 3D CSDM. Transformation rules must distinguish supplied observations from inferred or calculated results, particularly for bearings, parcel geometry, and 3D representations derived from incomplete evidence.

Integration processes must preserve source identity, derivation methods, limitations, and sufficient provenance for audit. Source matching, exceptions, information loss, and conversion testing require defined handling.

Validation and authoritative acceptance

Exchange conformance and authoritative cadastral acceptance are separate decisions. NGSC must identify required validation stages, responsibility for review and acceptance, handling of errors and warnings, and the rule versions used to support reproducibility and audit.

External specification dependencies

Shared Building Blocks, vocabularies, and model components evolve across repositories. Profile and component versions should therefore be managed together, with regression testing and change-impact assessment across affected profiles and consumers. The functional dependencies are summarised in Figure 2; authoritative details reside in the published specifications.

Outstanding architectural decisions

The NGSC architecture must confirm supported exchange formats and cadastral products; source transformation and preservation rules; mappings to operational records; validation responsibilities and acceptance criteria; metadata and workflow integration; and support for specialised 3D legal boundary representations.

Requirement-level dependencies and decisions are recorded in Deliverables 1–5 [1]–[5] and the Engagement Outcomes and Recommendations Report [7]. Their resolution will determine how the 3D CSDM capabilities are incorporated into NGSC without changing the exchange model's technology-independent role.

The principal outstanding decisions are consolidated as AD-01 to AD-08 in the Engagement Outcomes and Recommendations Report [7]. These address the 3D CSDM exchange architecture, profile and vocabulary governance, legacy transformation, geometry and cadastral validation, authoritative 3D boundaries, metadata governance, workflow integration, and technical acceptance.

The decision register identifies recommended directions and responsible organisations. It provides the basis for resolving the dependencies described in this document through Accenture's NGSC Solution Architecture and Landgate's jurisdictional decision-making processes.

Summary

The 3D CSDM and its Western Australian implementation profile provide a standards-based information architecture for the representation, validation, and exchange of cadastral survey information within NGSC. The modular approach builds on reusable OGC Building Blocks, common information structures, and jurisdiction-specific constraints, supporting interoperability and reducing duplication across cadastral applications.

This report identifies the CSD, 3D CSDM, and metadata components relevant to SURROUND's 15 Responsible requirements, together with supporting technical artefacts and integration dependencies. The associated specifications, example datasets, and proof-of-concept developments demonstrate approaches to information exchange, transformation, geometric and topological validation, and three-dimensional cadastral representation.

The 3D CSDM establishes a common exchange model but does not prescribe NGSC's operational architecture or authoritative cadastral processes. Integration therefore requires further decisions concerning source transformation, mapping to Esri Parcel Fabric, validation responsibilities, metadata management, and the treatment of specialised cadastral representations.

The architecture contributions documented here provide a technical foundation for incorporation into Accenture's NGSC Solution Architecture. Outstanding implementation decisions and acceptance requirements remain subject to confirmation by Accenture and Landgate, with supporting detail provided in the requirements deliverables [1]–[5], technical repositories, and Engagement Outcomes and Recommendations Report [7].

References

[1] A. J. S. Hunter and R. Atkinson, "Deliverable 1: Requirements Analysis," Canberra, ACT, Australia: SURROUND Australia Pty Ltd, 2025.

[2] A. J. S. Hunter and R. Atkinson, "Deliverable 2: Requirements Analysis," Canberra, ACT, Australia: SURROUND Australia Pty Ltd, 2026.

[3] A. J. S. Hunter and R. Atkinson, "Deliverable 3: Requirements Analysis," Canberra, ACT, Australia: SURROUND Australia Pty Ltd, 2026.

[4] A. J. S. Hunter and R. Atkinson, "Deliverable 4: Requirements Analysis," Canberra, ACT, Australia: SURROUND Australia Pty Ltd, 2026.

[5] A. J. S. Hunter and R. Atkinson, "Deliverable 5: Requirements Analysis," Canberra, ACT, Australia: SURROUND Australia Pty Ltd, 2026.

[6] Accenture Australia Pty Ltd and SURROUND Australia Pty Ltd, "Short Form Subcontract Agreement: Spatial WA -- Next Generation Spatial Cadastre (NGSC)," 2025.

[7] A. J. S. Hunter and R. Atkinson, "Engagement Outcomes and Recommendations," Canberra, ACT, Australia: SURROUND Australia Pty Ltd, 2026.

[8] Landgate, *APX-05 Digital Data Format Specification Version 2.0*, Midland, WA, Australia: Landgate, 2022. [Online]. Available: https://www.landgate.wa.gov.au/land-and-property/land-transactions-hub/land-transaction-policy-and-procedure-guides/survey-and-plan/appendices/apx-05-digital-data-format-specification-version-2.0