

Qt Essentials - Graphics View 2 Module

Qt Essentials - Training Course

Produced by Nokia, Qt Development Frameworks

Material based on Qt 4.7, created on December 15, 2010



<http://qt.nokia.com>



Module: Graphics View 2

- Widgets in a Scene
- Drag and Drop
- Effects
- Performance Tuning



Module: Graphics View 2

- Widgets in a Scene
- Drag and Drop
- Effects
- Performance Tuning



Widgets in a Scene



Demo \$QTDIR/examples/graphicsview/padnavigator


Items are not widgets

- QGraphicsItem:
 - Lightweight compared to QWidget
 - No signals/slots/properties
 - Scenes can easily contain thousands of Items
 - Uses different QEvent sub-hierarchy (derived from QGraphicsSceneEvent)
 - Supports transformations directly
- QWidget:
 - Derived from QObject (less light-weight)
 - supports signals, slots, properties, etc
 - can be embedded in a QGraphicsScene with a QGraphicsProxyWidget



QGraphicsWidget

- Advanced functionality graphics item
- Provides signals/slots, layouts, geometry, palette, etc.
- *Not* a QWidget!
- Base class for QGraphicsProxyWidget



QGraphicsProxyWidget

- QGraphicsItem that can embed a QWidget in a QGraphicsScene
- Handles complex widgets like QDialog
- Takes *ownership* of related widget
 - Synchronizes states/properties:
 - visible, enabled, geometry, style, palette, font, cursor, sizeHint, windowTitle, etc
 - Proxies events between Widget and GraphicsView
 - If either (widget or proxy) is deleted, the other is also!
- Widget must not already have a parent
 - Only top-level widgets can be added to a scene



Embedded Widget Example

```
#include <QtGui>
int main(int argc, char **argv) {
    QApplication app(argc, argv);

    QCalendarWidget *calendar = new QCalendarWidget;

    QGraphicsScene scene;
    QGraphicsProxyWidget *proxy = scene.addWidget(calendar);

    QGraphicsView view(&scene);
    view.show();

    return app.exec();
}
```



QGraphicsLayout

- For layout of QGraphicsLayoutItem (+derived) classes in QGraphicsView
- Concrete classes:
 - QGraphicsLinearLayout: equivalent to QVBoxLayout, arranges items horizontally or vertically
 - QGraphicsGridLayout: equivalent to QGridLayout, arranges items in a grid
- QGraphicsWidget::setLayout() - set layout for child items of this QGraphicsWidget



Lab: Widgets in a Scene

- Starting with the graphicsview/lab-mapviewer handout, add zooming controls.
- Suggested widgets:
 - QPushButton for +/-
 - QSlider for selecting zoom level directly.
- Use QGraphicsLayout to lay out the widgets
- Make the mouse work like a "hand-grab" tool on drag, so we can see different zoomed areas.



Module: Graphics View 2

- Widgets in a Scene
- **Drag and Drop**
- Effects
- Performance Tuning



Drag and Drop

- Items can be:
 - Dragged
 - Dropped onto other items
 - Dropped onto scenes
 - for handling empty drop areas



Start Drag

Starting an item drag is similar to dragging from a QWidget.

- Override event handlers:
 - `mousePressEvent()`
 - `mouseMoveEvent()`
- In `mouseMoveEvent()`, decide if drag started? if so:
 - Create a `QDrag` instance
 - Attach a `QMimeData` to it
 - See section on Drag and Drop for `QMimeData` info
 - Call `QDrag::exec()`
 - Function returns when user drops
 - Does not block event loop



Drop on a scene

- Override `QGraphicsScene::dropEvent()`
 - To accept drop:
 - `acceptProposedAction()`
 - `setDropAction(Qt::DropAction); accept();`
- Override `QGraphicsScene::dragMoveEvent()`
- Optional overrides:
 - `dragEnterEvent()`, `dragLeaveEvent()`



startDrag example

```
void startDrag( Qt::DropActions supportedActions ) {
    QList<QListWidgetItem *> items = selectedItems();
    if ( items.size()>0 ) {
        QDrag* drag = new QDrag( this );
        QMimeData *mimeData = new QMimeData; [...]
        QGraphicsItem* gitem =
            DiagramItem::createItem( item->toolType() );
        mimeData->setData( "application/x-qgraphicsitem-ptr",
                           QByteArray::number( ( qulonglong )gitem ) );
        drag->setMimeData( mimeData );
        QPixmap pix = item->icon().pixmap( 111,111 );
        drag->setPixmap( pix );
        drag->setHotSpot( pix.rect().center() );
        if ( drag->exec(supportedActions) == Qt::IgnoreAction ) {
            delete gitem; // drag cancelled, must delete item
        }
    }
}
```

Demo graphicsview/ex-dragdrop



dropEvent() on a scene

```
void DiagramScene::dropEvent( QGraphicsSceneDragDropEvent* event ) {  
    if (event->mimeType()->hasFormat("application/x-qgraphicsitem-ptr")  
        QGraphicsItem* item = reinterpret_cast<QGraphicsItem*>(  
            event->mimeType()->data (   
                "application/x-qgraphicsitem-ptr").toULongLong() );  
        if ( item ) {  
            addItem( item );  
            item->setFlag( QGraphicsItem::ItemIsMovable );  
            item->setFlag( QGraphicsItem::ItemIsSelectable );  
            item->setFlag( QGraphicsItem::ItemIsFocusable );  
            item->setPos( event->scenePos() );  
            event->acceptProposedAction();  
        }  
    } else  
        /* Call baseclass to allow per-item dropEvent */  
  
    QGraphicsScene::dropEvent( event );  
}
```


Drop on an item

- To drop into an item:
 - Override `dragEnterEvent()`
 - Optional override: `dragMoveEvent()` (if the item can only accept drops in some parts of its area)

```
void DiagramItem::dragEnterEvent(QGraphicsSceneDragDropEvent* e){  
    if ( e->mimeTypeData()->hasColor() )  
        e->acceptProposedAction();  
}  
  
void DiagramScene::dragMoveEvent(QGraphicsSceneDragDropEvent* e){  
    if (e->mimeTypeData()->hasFormat(  
        "application/x-qgraphicsitem-ptr"))  
        e->acceptProposedAction();  
    else  
        QGraphicsScene::dragMoveEvent(e);  
}
```

Demo graphicsview/ex-dragdrop



Module: Graphics View 2

- Widgets in a Scene
- Drag and Drop
- **Effects**
- Performance Tuning



Graphics Effects

Effects can be applied to graphics items:

- Base class for effects is `QGraphicsEffect`.
- Standard effects include blur, colorize, opacity and drop shadow.
- Effects are set on items.
 - `QGraphicsItem::setGraphicsEffect()`
- Effects cannot be shared or layered.
- Custom effects can be written.



Using a Graphics Effect



- Applying a blur effect to a pixmap.

```
QPixmap pixmap(":/images/qt-banner.png");
```

```
QGraphicsItem *blurItem = scene->addPixmap(pixmap);
```

```
QGraphicsBlurEffect *blurEffect = new QGraphicsBlurEffect();  
blurItem->setGraphicsEffect(blurEffect);  
blurEffect->setBlurRadius(5);
```

- An effect is owned by the item that uses it.
- Updating an effect causes the item to be updated.



Module: Graphics View 2

- Widgets in a Scene
- Drag and Drop
- Effects
- **Performance Tuning**




Level of Detail

- Don't draw what you can't see!
- `QStyleOptionGraphicsItem` passed to `paint()`
 - Contains `palette`, `state`, `matrix` members
 - `qreal levelOfDetailFromTransform(QTransform T)` method
- "levelOfDetail" is max width/height of the unity rectangle needed to draw this shape onto a `QPainter` with a `QTransform` of `T`.
- use `worldTransform()` of painter for current transform.
 - Zoomed out: `levelOfDetail < 1.0`
 - Zoomed in: `levelOfDetail > 1.0`



Level of detail: Chip demo



Demo \$QTDIR/demos/chip

Level of detail: Chip demo 2

```
void Chip::paint(QPainter *painter,
    const QStyleOptionGraphicsItem *option, QWidget *)
{
    const qreal lod = option->levelOfDetailFromTransform(
        painter->worldTransform());
    [ ... ]
    if (lod >= 2) {
        QFont font("Times", 10);
        font.setStyleStrategy(QFont::ForceOutline);
        painter->save();
        painter->setFont(font);
        painter->scale(0.1, 0.1);
        painter->drawText(170, 180, QString("Model: VSC-2000 ..."))
        painter->drawText(170, 220, QString("Manufacturer: ..."))
        painter->restore();
    }
}
```

Demo \$QTDIR/demos/chip



Caching tips

- Cache item painting into a pixmap
 - So `paint()` runs faster
- Cache `boundingRect()` and `shape()`
 - Avoid recomputing expensive operations that stay the same
 - Be sure to invalidate manually cached items after zooming and other transforms

```
QRectF MyItem::boundingRect() const {  
    if (m_rect.isNull()) calculateBoundingRect();  
    return m_rect;  
}
```

```
QPainterPath MyItem::shape() const {  
    if (m_shape.isEmpty()) calculateShape();  
    return m_shape;  
}
```



setCacheMode()

- Property of QGraphicsView and QGraphicsItem
- Allows caching of pre-rendered content in a QPixmap
 - Drawn on the viewport
 - Especially useful for gradient shape backgrounds
 - Invalidated whenever view is transformed.

```
QGraphicsView view;  
view.setBackgroundBrush(QImage(":/images/backgroundtile.png"));  
view.setCacheMode(QGraphicsView::CacheBackground);
```



Tweaking

The following methods allow you to tweak performance of view/scene/items:

- `QGraphicsView::setViewportUpdateMode()`
- `QGraphicsView::setOptimizationFlags()`
- `QGraphicsScene::setItemIndexMethod()`
- `QGraphicsScene::setBspTreeDepth()`
- `QGraphicsItem::setFlags()`
 - `ItemDoesntPropagateOpacityToChildren` and `ItemIgnoresParentOpacity` especially recommended if your items are opaque!

See API documentation for details.



Tips for better performance

- `boundingRect()` and `shape()` are called frequently so they should run fast!
 - `boundingRect()` should be as small as possible
 - `shape()` should return simplest reasonable path
- Try to avoid drawing gradients on the painter. Consider using pre-rendered backgrounds from images instead.
- It is costly to dynamically insert/remove items from the scene. Consider hiding and reusing items instead.
- Embedded widgets in a scene is costly.
- Try using a different paint engine (OpenGL, Direct3D, etc)
 - `setViewport (new QGLWidget);`
- Avoid curved and dashed lines
- Alpha blending and antialiasing are expensive



© 2010 Nokia Corporation and its Subsidiary(-ies).

The enclosed Qt Training Materials are provided under the Creative Commons Attribution ShareAlike 2.5 License Agreement.



The full license text is available here:

<http://creativecommons.org/licenses/by-sa/2.5/legalcode>

Nokia, Qt and the Nokia and Qt logos are the registered trademarks of Nokia Corporation in Finland and other countries worldwide.

