

Instantly share code, notes, and snippets.



jbwhit / **example-ruff-formatting.ipynb**

Last active 2 months ago

<> **Code** Revisions 4 Stars 25 Forks 1

Embed <script src: Download ZIP

Steps to use `ruff` in JupyterLab with the `jupyterlab\_code\_formatter` plugin.

example-ruff-formatting.ipynb



dlimpid commented on Jan 25, 2024

Thank you very much for the great guide! A problem for me was that cells containing non-ascii unicode characters were not formatted. I could fix this by adding `encoding="utf-8"` in the `subprocess.run()` call.



jbwhit commented on Jan 25, 2024

Author

Thank you for the comment! I'm thinking of revisiting this and seeing if I can make a PR to the extension itself. I'll add your change.



Gr1nse commented on Mar 26, 2024

Hi!
Nice Guide!
in this Guide you just use the formater right?
Do you know how to get the ruff linter to work in jupyterlab?



nicornk commented on Apr 19, 2024

I had to add the import "from typing import List" to the config file snippet. [@jbwhit](#)



jbwhit commented on Apr 19, 2024

Author

Thanksk [@nicornk](#) -- I've added that to my snippet!



aliavni commented on Apr 23, 2024



amano-takahisa commented on May 3, 2024

I am very happy with your config that can also reflect ruff configs written in `pyproject.toml` such as:

```
[tool.ruff.format]
quote-style = "single"
```



brurucy commented on Jul 17, 2024 • edited ▼

If you guys **also** want it to run `check` before `format`, then use this:

```
@handle_line_ending_and_magic
def format_code(
    self, code: str, notebook: bool, args: List[str] = [], **options
) -> str:
    # Lint
    linting = subprocess.run(
        [self.ruff_bin, "check", "--fix", "--exit-zero", "-"],
        input=code,
        stdout=subprocess.PIPE,
        stderr=subprocess.PIPE,
        universal_newlines=True,
        encoding="utf-8",
    )

    # Format
    linted_code = linting.stdout
    process = subprocess.run(
        [self.ruff_bin, "format", "-"],
        input=linted_code,
        stdout=subprocess.PIPE,
        stderr=subprocess.PIPE,
        universal_newlines=True,
        encoding="utf-8",
    )

    if process.stderr:
        logger.info(process.stderr)
        return code
    else:
        return process.stdout
```

JordanTheDodger commented on Apr 22



I followed steps from YT vid, still could not get `Formatter_icon` work w/ `ruff_format` in active Jupyter notebook . I have installed python 3.10<= using `venv` . I liked `keyboard shortcut` which also doesn't work ss attached below. Any help appreciated. Discord: JordanTheDodger  [image](#)

Update: I finally figured out the error. I am elated to capture my first error with new kid on the block
RUFFFFF :100 Kudos [@jbwhit](#)



jbwhit commented on Apr 23

Author

I followed steps from YT vid, still could not get `Formatter_icon` work w/ `ruff_format` in active Jupyter notebook . I have installed python 3.10<= using `venv` . I liked `keyboard shortcut` which also doesn't work ss attached below. Any help appreciated. Discord: JordanTheDodger  [image](#)

Update: I finally figured out the error. I am elated to capture my first error with new kid on the block
RUFFFFF :100 Kudos [@jbwhit](#)

Was the error on from this document or something on your side?



JordanTheDodger commented on May 4

I configured `virtual env` using `conda`. For some reason, `ruff` configuration didn't register. I had to shutdown Jupyter and virtual env. Technically not a "true" error just operational hiccup. 👍