

SQLite C Interface

SQL Trace Hook

```
int sqlite3_trace_v2(  
    sqlite3*,  
    unsigned uMask,  
    int(*xCallback)(unsigned,void*,void*,void*),  
    void *pCtx  
);
```

The `sqlite3_trace_v2(D,M,X,P)` interface registers a trace callback function `X` against [database connection](#) `D`, using property mask `M` and context pointer `P`. If the `X` callback is `NULL` or if the `M` mask is zero, then tracing is disabled. The `M` argument should be the bitwise OR-ed combination of zero or more [SQLITE_TRACE](#) constants.

Each call to either `sqlite3_trace(D,X,P)` or `sqlite3_trace_v2(D,M,X,P)` overrides (cancels) all prior calls to `sqlite3_trace(D,X,P)` or `sqlite3_trace_v2(D,M,X,P)` for the [database connection](#) `D`. Each database connection may have at most one trace callback.

The `X` callback is invoked whenever any of the events identified by mask `M` occur. The integer return value from the callback is currently ignored, though this may change in future releases. Callback implementations should return zero to ensure future compatibility.

A trace callback is invoked with four arguments: `callback(T,C,P,X)`. The `T` argument is one of the [SQLITE_TRACE](#) constants to indicate why the callback was invoked. The `C` argument is a copy of the context pointer. The `P` and `X` arguments are pointers whose meanings depend on `T`.

The `sqlite3_trace_v2()` interface is intended to replace the legacy interfaces [sqlite3_trace\(\)](#) and [sqlite3_profile\(\)](#), both of which are deprecated.

See also lists of [Objects](#), [Constants](#), and [Functions](#).