

# COMP6771

## Advanced C++ Programming

### Week 8

### Part One: Custom Iterators

2017


[www.cse.unsw.edu.au/~cs6771](http://www.cse.unsw.edu.au/~cs6771)

# Iterators

- Iterators that are classes (or types) support an abstract model of data as a **sequence** of objects
- An iterator is an abstract notion of **pointers**
- **Glue** between containers and generic algorithms:
  - The designer of algorithms do not have to be concerned with details about various data structures
  - The designer of containers do not have to provide extensive access operations

## An Iterator for a Container

- $a$  is a container with all its  $n$  objects ordered



- `a.begin()`: a “pointer” to the first element
- `a.end()`: a “pointer” to one past the last element
- if  $p$  “points” to the  $k$ -th element, then
  - $*p$  is the object pointed to
  - $++p$  “points” to  $(k + 1)$ -st element
- The loop:

```
1 for (first = a.begin(); first != a.end(); ++first)
2     do something on *first
```

## Container::iterator

- `vector<int> ivec;`

```
1 for (auto first = ivec.begin(); first != ivec.end(); ++first) {  
2  
3     std::cout << *first << std::endl;  
4  
5 }
```

- `list<int> ilist;`

```
1 for (auto first = ilist.begin(); first != ilist.end(); ++first) {  
2  
3     std::cout << *first << std::endl;  
4  
5 }
```

The for loops look "identical".

## Five Categories of Iterators

Operation	ITERATORS				
	OUTPUT	INPUT	FORWARD	BI-DIR	RANDOM
Read		<code>=*p</code>	<code>=*p</code>	<code>=*p</code>	<code>=*p</code>
Access		<code>-&gt;</code>	<code>-&gt;</code>	<code>-&gt;</code>	<code>-&gt; []</code>
Write	<code>*p=</code>		<code>*p=</code>	<code>*p=</code>	<code>*p=</code>
Iteration	<code>++</code>	<code>++</code>	<code>++</code>	<code>++ --</code>	<code>++ -- + - += -=</code>
Compare		<code>== !=</code>	<code>== !=</code>	<code>== !=</code>	<code>== != &lt; &gt; &gt;= &lt;=</code>

Different algorithms require different kinds of iterators for their operations:

- **input:** `find()`, `equal()`, ...
- **output:** `copy()`
- **forward:** `replace()`, ...
- **bi-directional:** `next_permutation()`, `reverse()`, ...
- **random:** `sort`, `binary_search()`, `nth_element()`, ...

## Prefer ++first to first++

```
self& operator++() {    // prefix
    node = (link_type)((*node).next);
    return *this;
}
self operator++(int) { // postfix
    self tmp = *this;
    ++*this;
    return tmp;
}
```

- ++first is more efficient than first++
- --first is more efficient than first--

# Iterator Traits

- Traits define/describe the class properties for an iterator.
- Defined as nested **typedefs** in **#include <iterator>**:

```
template <typename Iterator>
struct iterator_traits {
    typedef typename Iterator::iterator_category iterator_category;
    typedef typename Iterator::value_type        value_type;
    typedef typename Iterator::difference_type    difference_type;
    typedef typename Iterator::pointer            pointer;
    typedef typename Iterator::reference          reference;
};

template <typename T> // specialised for the pointer iterator
struct iterator_traits<T*> {
    typedef random_access_iterator_tag iterator_category;
    typedef T                          value_type;
    typedef ptrdiff_t                  difference_type;
    typedef T*                         pointer;
    typedef T&                         reference;
};
```

- <http://www.sgi.com/tech/stl/Iterators.html>
- When we write a custom iterator we have to define these 5 type defs for our types.

## Writing a Forward Iterator

<code>list.hpp:</code>	a singly linked list
<code>list_iterator.hpp:</code>	a non-const forward iterator (as a class template) (the const version is similar)
<code>list-user.cpp:</code>	client code

- List is a class template
- List\_Iterator is also class template



# list.hpp I

```

1  #ifndef LIST_HPP
2  #define LIST_HPP
3
4  #include "list_iterator.hpp"
5
6  template <typename T> class List {
7  public:
8      friend class List_Iterator<T>;
9      typedef List_Iterator<T> iterator;
10
11     List() : head_(nullptr), tail_(nullptr) {}
12     ~List() { delete head_; }
13
14     bool isEmpty() const { return head_ == nullptr; }
15     void push_back(const T&);
16     iterator begin() { return iterator(head_); }
17     iterator end() { return iterator(nullptr); }
18
19 private:
20     struct Node {
21         Node(const T& t, Node *next) : elem_(t), next_(next) {}

```

## list.hpp II

```

22     ~Node() {
23         delete next_;
24     };
25     T elem_;
26     Node *next_;
27 };
28 Node *head_, *tail_;
29 };
30
31 template <typename T>
32 void List<T>::push_back(const T& elem) {
33     Node *newNode = new Node(elem, nullptr);
34     if (!head_)
35         head_ = newNode;
36     else
37         tail_->next_ = newNode;
38     tail_ = newNode;
39 }
40 // add more member functions here
41
42 #endif

```

# list\_iterator.hpp I

```

1  #ifndef LIST_ITERATOR_HPP
2  #define LIST_ITERATOR_HPP
3
4  #include <iterator>
5  #include <cassert>
6
7  template <typename T> class List;
8
9  template <typename T> class List_Iterator {
10 public:
11     typedef std::ptrdiff_t                difference_type;
12     typedef std::forward_iterator_tag     iterator_category;
13     typedef T                            value_type;
14     typedef T*                           pointer;
15     typedef T&                           reference;
16
17     reference operator*() const;
18     pointer operator->() const { return &(operator*()); }
19     List_Iterator& operator++();
20     bool operator==(const List_Iterator& other) const;
21     bool operator!=(const List_Iterator& other) const { return !operator==(other); }
22
23     List_Iterator(typename List<T>::Node *pointee = nullptr) : pointee_(pointee) {}
24 private:
25     typename List<T>::Node *pointee_;
26 };
27
28
29

```

## list\_iterator.hpp II

```

30 template <typename T> typename List_Iterator<T>::reference
31 List_Iterator<T>::operator*() const {
32     return pointee_->elem_;
33 }
34
35 template <typename T> List_Iterator<T>&
36 List_Iterator<T>::operator++() {
37     assert(pointee_ != nullptr);
38     pointee_ = pointee_->next_;
39     return *this;
40 }
41
42 template <typename T>
43 bool List_Iterator<T>::operator==(const List_Iterator<T>& other) const {
44     return this->pointee_ == other.pointee_;
45 }
46
47 #endif

```

## Dissecting the Custom Iterator

Key points in the Iterator Class:

- The typedefs
- The overloaded operators ( $*$ ,  $->$ )
- The equality operators
- The constructor (default to nullptr)
- **The private data** - a pointer to a private inner class (friend)
- The  $++$  operator knows how the inner class works to move onto the next item in the sequence.

Key points in the List Class:

- `begin()` – returns an Iterator object
- `end()` – returns an Iterator object (with nullptr as private data)

Note: The Iterator Class does not modify the List/Node data except through returning references.

## A Custom InputIterator

- Custom InputIterator required for Assignment Three!
- To be valid it needs to adhere correctly to the requirements for the InputIterator defined in the links below:
- See:  
<http://en.cppreference.com/w/cpp/concept/InputIterator>
- See:  
<http://www.sgi.com/tech/stl/InputIterator.html>
- Will be checked/tested with test case(s) that use type traits.
- Note: an InputIterator does not allow the data to be modified (hint: use const!).
- Tip: Use smart pointers! Maybe store a collection of pointers in your Iterator to get the sort order right?
- Tip: Define ++ in terms of remove the head of the collection? Define \* as return the const head?

## list-user.cpp

```

1  #include<iostream>
2  #include<algorithm>
3
4  #include "list.hpp"
5
6  template <typename T> void display(T &c) {
7      std::cout << "Iterating over List: ";
8      for (typename T::iterator i = c.begin(); i != c.end(); ++i)
9          // or for (auto i = c.begin(); i != c.end(); ++i)
10         std::cout << *i << " ";
11     std::cout << std::endl;
12 }
13
14 int main() {
15     List<int> l;
16
17     l.push_back(4);
18     l.push_back(3);
19     l.push_back(2);
20     l.push_back(1);
21
22     display(l);
23
24     // use our iterator with a stl algorithm.
25     List<int>::iterator i = std::find(l.begin(), l.end(), 3);
26     if (i != l.end())
27         std::cout << "3 found" << std::endl;
28     else
29         std::cout << "3 not found" << std::endl;
30 }

```

# Combining Traits and Custom Iterators

- The input:

```
1  #include <iostream>
2  #include <algorithm>
3
4  #include "list.hpp"
5
6  template <typename InputIterator>
7  typename std::iterator_traits<InputIterator>::value_type
8  last_value(InputIterator first, InputIterator last) {
9      typename std::iterator_traits<InputIterator>::value_type result = *first;
10     for (; first != last; ++first)
11         result = *first;
12     return result;
13 }
14
15 int main() {
16     List<int> l;
17
18     l.push_back(4);
19     l.push_back(3);
20
21     std::cout << last_value(l.begin(), l.end()) << std::endl;
22 }
```



# Combining Traits and Custom Iterators

- The instantiations from the compiler:


```
1  #include <iostream>
2  #include <algorithm>
3
4  #include "list.hpp"
5
6  int last_value(std::List_Iterator<int> first, std::List_Iterator<int> last) {
7      int result = *first;
8      for (; first != last; ++first)
9          result = *first;
10     return result;
11 }
12
13 int main() {
14     List<int> l;
15
16     l.push_back(4);
17     l.push_back(3);
18
19     std::cout << last_value(l.begin(), l.end()) << std::endl;
20 }
```

# What about Generalising to a Bidirectional Iterator?

- Must define `operator--()`
- Must be able to move from `c.end()` to the last element of the list!  
⇒ the list should be doubly linked

## Add Reverse Iterators

- Modify List so that it is doubly linked



- Create reverse iterators by using the reverse iterator adaptor:
  - The original iterator must be bidirectional or random\_access
  - BEWARE:** `end()` must bring us to the last element in the list!
  - Add the following to the list class:
 

```
typedef reverse_iterator<const_iterator> const_reverse_iterator;
typedef reverse_iterator<iterator>      reverse_iterator;
reverse_iterator rbegin()
{ return reverse_iterator(end()); }
const_reverse_iterator rbegin() const
{ return const_reverse_iterator(end()); }
reverse_iterator rend()
{ return reverse_iterator(begin()); }
const_reverse_iterator rend() const
{ return const_reverse_iterator(begin()); }
```
  - IMPORTANT:** `&*reverse_iterator(i) == &*(i-1)`
  - How does the reverse adaptor work (see `stl_iterator.h`)?

# Add C++11-Style `const` Iterators

Implement

`cbegin()`

`cend()`

`crbegin()`

`crend()`

in terms of `begin()`, `end()`, `rbegin()` and `rend()` (in a few minutes)

# Summary

- Iterators are classes
- You can define your iterators as class templates (as demonstrated here)
- You can also define your iterators as template or ordinary classes nested inside other classes
- Do it in stages
  - 1 Develop a forward iterator first
  - 2 Add `operator--()` to obtain a bidirectional iterator first
  - 3 Use `reverse_iterator` to adapt your iterators to obtain reverse iterators (const and non-const)
  - 4 Add `cbegin()`, `cend()`, `crbegin()` and `crend()`

# Reading

- Section 15.2, text
- Chapter 10, Thinking in C++, Vol. 2
- Chapter 15, Stroustrup's C++ Book, 3rd Ed.