




1. IN CASE OF CONFLICT BETWEEN REQUIREMENTS OF 2D-DRAWING AND ANY RECEIVED REFERENCE 3D FILE OR DXF FILE, THEN THE REQUIREMENTS ON THE 2D-DRAWING SHALL PREVAIL.

2. FOR UNSPECIFIED MEASUREMENTS THE TOLERANCE CLASSES LISTED BELOW APPLY:
THE TOLERANCE FOR LINEAR DIMENSIONS : ISO 2768-c.
THE TOLERANCE FOR ANGULAR DIMENSIONS : ISO 2768-c.

E	Alt.		Amendments					Name		Sign	Date	Alt.		Amendments					Name		Sign	Date	F		
	Sur.Sym.		N1	N2	N3	N4	N5	N6	N7	N8	N9	N10	N11	N12	Mat. SS 304 GRADE S2 IS:6911/EN10088-2:14										
	Ra Value (µm)		0.025	0.05	0.1	0.2	0.4	0.8	1.6	3.2	6.3	12.5	25	50	Sur. Treat.- N.A.										
	IS:3073		REF. NO.:-												Size -		Wt.	1.58	kg. Appx.						
Gen. Tol. : IS-2102																									
		Fine	Med.	Coar.	Very Coar.	Name		Sign.		Date				Scale		 SONA COMSTAR SONA BLW Precision Forgings Limited Railway Business Plot No. 114-115, Sector-24, Faridabad-121005									
						Drawn		PRIYANSHU S		PS				16/01/25							1:5				
>3-6		±0.05	±0.1	±0.3	±0.5	Checked		SAURABA G		SG		16/01/25													
>6-30		±0.10	±0.2	±0.5	±1.0	Approved		HARENDER KEENA		HK		16/01/25		Dimensions in mm											
>30-120		±0.15	±0.3	±0.8	±1.5	Title FRONT PLATE FOR CONTROL CUBICLE BOX										Drawing No. 1S101050064									
>120-400		±0.2	±0.5	±1.2	±2.5																				
>400-1000		±0.3	±0.8	±2.0	±4.0																				
>1000-2000		±0.5	±1.2	±3.0	±6.0																				
>2000-4000		-	±2.0	±4.0	±8.0																				
Project :-		CAB AC E LOCO										Status:													
1		2					3					4													



1. IN CASE OF CONFLICT BETWEEN REQUIREMENTS OF 2D-DRAWING AND ANY RECEIVED REFERENCE 3D FILE OR DXF FILE, THEN THE REQUIREMENTS ON THE 2D-DRAWING SHALL PREVAIL.

2. FOR UNSPECIFIED MEASUREMENTS THE TOLERANCE CLASSES LISTED BELOW APPLY:
THE TOLERANCE FOR LINEAR DIMENSIONS : ISO 2768-c.
THE TOLERANCE FOR ANGULAR DIMENSIONS : ISO 2768-c.

Gen. Tol. : IS-2102				
	Fine	Med.	Coar.	Very Coar.
0.5-3	±0.05	±0.1	±0.2	--
>3-6	±0.05	±0.1	±0.3	±0.5
>6-30	±0.10	±0.2	±0.5	±1.0
>30-120	±0.15	±0.3	±0.8	±1.5
>120-400	±0.2	±0.5	±1.2	±2.5
>400-1000	±0.3	±0.8	±2.0	±4.0
>1000-2000	±0.5	±1.2	±3.0	±6.0
>2000-4000	-	±2.0	±4.0	±8.0

Project :-
CAB AC E LOCO