

SAFETY / REGULATION --
FIT / FUNCTION --

SECTION Z-Z

MATERIAL:-
EN-19 HARDENED & TEMPERED / EQUIVALENT
INDUCTION HARDENED: 50-55 HRC, CASE DEPTH 1-1.5mm
CORE HARDNESS : 32-39 HRC.
GRADE 10.9, IS-1367 (Part-3) MECHANICAL PROPERTIES TO BE ACHIEVED.

NOTES: -
1. BREAK ALL SHARP EDGES AND CORNERS.
2. UNSPECIFIED TOLERANCES AS PER IS:2102-m.
3. HARDENED SURFACE SHALL BE VERIFIED FOR SURFACE CRACK THROUGH MPI & UT FOR INTERNAL DEFECTS AFTER COMPLETION OF GRINDING.
4. SURFACE TREATMENT: BLACKENED AS PER IS: 13212 & OILED.
5. POSITION FOR SONA MARKING & SUPPLIER TRACEABILITY MAY VARY BUT LOCATING FACE MUST REMAIN AS SPECIFIED.
6. ALL TRACEABILITY LETTERS MUST BE VISIBLE AND TO BE FORMED THROUGH EITHER PUNCHING, ENGRAVING OR PRINTING.

Supplier Traceability
XX: Supplier Code
YY: Month Code
ZZ: Year Code

Gen. Tol. : IS-2102

	Fine	Med.	Coar.	Very Coar.
0.5-3	±0.05	±0.1	±0.2	--
>3-6	±0.05	±0.1	±0.3	±0.5
>6-30	±0.10	±0.2	±0.5	±1.0
>30-120	±0.15	±0.3	±0.8	±1.5
>120-400	±0.2	±0.5	±1.2	±2.5
>400-1000	±0.3	±0.8	±2.0	±4.0
>1000-2000	±0.5	±1.2	±3.0	±6.0
>2000-4000	-	±2.0	±4.0	±8.0

Project :-
AAR-H COUPLER

Title
MAIN PIN FOR KNUCKLE
(Rev. 03)

Drawing No.
1C101060068

Sheet 1 of 1 **Alt No.** 02
Status: DRAFT DRAWING

SONA CONSTAR
SONA BLW Precision Forgings Limited
Railway Business
Plot No. 114-115, Sector-24, Faridabad-121005

The present drawing is the intellectual property of SONA BLW Precision Forgings Limited. It must not be photocopied, scanned, photographed or copied either wholly or in part or made accessible, disclosed or handed over to any third party or unauthorised party without the prior express written agreement of SONA BLW Precision Forgings Limited. Any breach of this condition will be prosecuted under legal laws and subjected to actions for claim of damages and injunctions.