

# Surveillance Rover: The Future of Defense

Praphulla M P, Sushma M, "Gayathri" M A

B.E, Dept. of Electronics and Communication Engineering"  
GSSS Institute of Engineering and Technology for Women  
Mysore, India

Padma R

Dept. of Electronics and Communication Engineering  
GSSS Institute of Engineering and Technology for Women  
Mysore, India

**Abstract** - Surveillance robots prove to be advantageous in defensive environment. This project provides real-time surveillance at hazardous terrain and borderline by means of versatile robot based on Lab VIEW software, for safeguarding the frontier. It works in real-world environment and no conditioned scenario is required by it. Various peripherals like vision camera for live system tracking, inductive proximity for metal detection and radar for obstacle detection are implemented.

**Keywords** - LabVIEW; NI-myRIO; Inductive proximity sensor; Doppler RADAR;

## I. INTRODUCTION

Surveillance is the monitoring of behavior, activities, or information for the purpose of influencing, managing or directing. This can be done by observing conditions prevailing on ground from a distance via CCTV, by intercepting the information that was transmitted electronically or through post. It can also be done manually by humans who gather the intelligence information. Surveillance is used by governments for intelligence gathering, prevention of crime, the protection of a process, person, group or object, or the investigation of crime.

MyRIO is a real time embedded evaluation board developed by National Instruments. It provides real time response needed to control the actions of surveillance vehicle. Its processing speed is almost ten times more than that of general micro-controllers and microprocessor, which decreases the response time. Program can be circuited with LabVIEW, fused with MyRIO, and can be operated in wireless mode.

Radar (Radio Detection and Ranging) is a detection system that uses radio waves to determine the range, angle, or velocity of objects. It can be used to detect aircraft, ships, spacecraft, guided missiles, motor vehicles, weather formations, and terrain. A radar system consists of transmitter section which produces radio waves or microwaves that are capable of travelling without getting damped or affected by atmospheric conditions to very long distances. Microwaves or radio waves are transmitted via transmitting antenna and they revert back after getting bounced off by object/target. The altered signal is received by receiving antenna (usually same antenna is used for implementing both the actions) and is processed in receiver section of radar system. The change in frequency and phase

of received signal reveals the object's location, its speed and its relative movement from radar.

This project proposes to develop an autonomous navigation vehicle by using machine vision techniques available in LabVIEW platform. Computer vision techniques are used for sensing the environment through a web camera. Live video & audio can be procured through webcam and can be processed in computer by taking advantage of image processing toolkit offered by LabVIEW i.e. IMAQ (Image Acquisition). ARM Cortex-A9 dual core processor present in NI-myRIO enables programmer to incorporate embedded logic control techniques required for vehicle navigation. This vehicle also acts as obstacle detector due to the presence of radar hence it automatically alerts the user if any object/target is present in its range of operation and proceeds to next step.

Our approach in building this surveillance vehicle and its controlling differs from existing ones in a number of ways. This project operates in real-time environment and not just as any prototype. Using LabVIEW platform to implement this project, alone has its advantages. LabVIEW enhances the efficiency of the system to the next level due to its excellent computational performance and analysis capability. Thus, making this approach much more reliable than others. Also, this vehicle can be wi-fi controlled and monitored using data dashboard (android application of National Instruments).

## II. LITERATURE REVIEW

Previous works in this domain were explored and reviewed thoroughly to understand the pros and cons of existing systems.

Karthikeyan et al [1] proposed a system that could control surveillance vehicle wirelessly using GPS navigation and wireless LAN. Anto Clinton et al [2] developed a robot to perform the act of surveillance in domestic areas by means of Arduino and ESP8266. Ravikumar et al [3] devised a methodology for tracking the surveillance rover in real-time and monitor potential threats using LabVIEW software and tracking camera. Thirumurugan et al [4] proposed a low-cost, light weight, small size unmanned ground vehicle (UGV), controlled by NI-myRIO. Along with this gas sensor was used to detect the presence of harmful gases. Kanagavel et al [5] designed a surveillance robot that could detect obstacles via IR sensors mounted upon it.







