

## S.113139 Multi-Function Jump Starter Powerbank 12V

- 12V Jump Start, Boost Start
- Output:
- 5V/2A & 5V/1A suitable for mobile phone, tablet and various digital devices
- 12V/10A suitable for 12V vehicle electronic products
- 19V/3.5A suitable for laptop
- Input: 15V/1A
- Battery capacity: 18,000mAh
- Start Current: 300A
- Peak Current: 600A
- Operation Temperature: -20°~60° (-4°~140°)
- Charging time: 6 hours full charge (230V AC charger)
- Jump Start Cycle (after full charge): Approximate 40 \*subject to battery condition
- Vehicle type: 8.0L Petrol, 5.0L Diesel
- Battery type: LiCoO2 (Lithium cobalt oxides)
- Material: ABS VO (Fireproofing)
- Battery lifetime: Approximate 1,000 Cycles
- Battery (on standby): 6 months in dry storage condition
- LED lighting: Flash, SOS, Constant
- Built-in Safety Feature: Reverse Polarity Protection, Reverse Charge Protection, Short-Circuit Protection, Overload-Protection, Starting override
- Always follow the OEM's recommendation and procedure prior for any emergency jump start or boost start your vehicle



**£81.99**

## S.118478 HD Dashboard Camera 2.5" Screen Size

- Records video in case of accident and provides vital evidence for insurance claims. Auto stop/start feature with loop recording means easy use and no missing video. Micro SD card not included.
- Resolution 1080p
- Frame Rate 30fps (frames per second)
- Audio Yes
- G Sensor No
- Motion Sensor No
- File Locking Function No
- Photo Mode Yes
- SD Card Size 32GB
- SD Card Supplied No
- Night Vision Yes
- Contains Dashboard camera, mounting bracket, mini USB to USB cable, mini USB to 12V cigarette lighter plug cable, manual



**£18.95**

## S.118479 HD Dashboard Camera 2.2" Screen Size

- Records video in case of accident and provides vital evidence for insurance claims. Auto stop/start feature with loop recording means easy use and no missing video. Micro SD card not included.
- Resolution 1080p
- Frame Rate 30fps (frames per second)
- Audio Yes
- G Sensor Yes
- Motion Sensor Yes
- File Locking Function Yes
- Photo Mode Yes
- SD Card Size 32GB TF Micro Card
- SD Card Supplied No
- Night Vision Yes
- Contains Dashboard camera, mounting bracket, mini USB to USB cable, mini USB to 12V cigarette lighter plug cable, manual



**£35.99**

### S.115176 Waterproof Wired Reversing Camera System with 7" LCD Monitor

- Waterproof screen allows installation on cabless machine
- Ideal for vineyard & fruit tractors
- Wired system adapted for the farming environment- robust & practical
- Easy to install - easy to use
- Wide angle view and 450cd brightness
- High definition : 800x3(RGB)x480
- IP69K Waterproof 1/3 SHARP CCD Camera
- 18 infrared LED's for night vision
- Working Temperature: -20 to 60°C
- 20m cable included
- English software
- Up to 2 cameras can be used
- Additional Camera: S.115188



**£195.95**

**NEW**

### S.115175 Wired Reversing Camera System with 7" LCD Monitor & Camera

- Very good value for money
- Wired system adapted for the farming environment- robust & practical
- Easy to install - easy to use
- Wide angle view and 450cd brightness
- High definition : 800x3(RGB)x480
- IP69K Waterproof 1/3 SHARP CCD Camera
- 18 infrared LED's for night vision
- Working Temperature: -20 to 60°C
- 20m cable included
- English software
- Additional Camera: S.115188



**£110.00**

**NEW**

### Camera Adaptor Cable



**NEW**

	Description	Cable Length M:	
<b>S.118453</b>	Fendt Camera Adaptor Cable	1.2	<b>£19.95</b>
<b>S.118454</b>	Trimble System Camera Adaptor Cable	6	<b>£26.50</b>

### S.118152 LED Rechargeable Flood Light

- Lumens:1000,
- Light Source: 5 x 3W LEDs,
- Volts: 12-240,
- Charging Time: 8 Hours,
- Run time: up to 3 hours (100% Brightness),
- Overall Width: 115mm,
- Overall Height: 180mm,
- Depth: 100mm, 3 modes: Full brightness, half brightness, SOS



**£28.50**

**NEW**

### Grease Gun Relief Valve



**NEW**

	Thread Size	Max. Pressure psi	
<b>S.118406</b>	M10	10000	<b>£18.45</b>
<b>S.118407</b>	1/8 BSP	10000	<b>£18.45</b>

### S.118408 Release Hook for Quick Release Grease Coupler

Allows to unhinge the coupler easily



**£5.90**

**NEW**

# 2017 Special Offer

# Sparex

Your 1<sup>st</sup> choice

## S.1573 Complete PTO Shaft, (Lz) Length 1080mm, 1 3/8 x 6 Spline Q.R. to 1 3/8 x 6 Spline Q.R.

HP Rating @ 540RPM: 52HP, German Series: AW35/W2400.



**£79.00**

## S.13157 Complete PTO Shaft, (Lz) Length 1150mm, 1 3/8 x 6 Spline Q.R. to 1 3/8 x 6 Spline Shearbolt Limiter

HP Rating @ 540RPM: 55HP, Italian Series: AB6/A6.



**£99.00**

## S.59610 PTO Guard - Easylock, (Lz) Length: 1360mm, Size: Large.



**£39.00**

## Hydraulic Quick Release Coupling



	Thread Size	Male   Female	
<b>S.2960</b>	1/2 BSP	Male	<b>£1.58</b>
<b>S.2961</b>	1/2 BSP	Female	<b>£4.75</b>

## Flat Faced Hydraulic Couplings



	Body Size	Thread Size	Thread Type	Male   Female	Coupler Type	
<b>S.8032</b>	1/2"	1/2	BSP	Male	Flat Face Probe	<b>£8.50</b>
<b>S.8033</b>	1/2"	1/2	BSP	Female	Flat Face Push Release	<b>£13.95</b>

## S.13108 Ball Hitch Pin-1 1/4"

- Pin Ø 1 1/4/32mm.
- Maximum recommended trailer weight 3000kgs.
- (Must be used with locknuts fully tightened and lynch pin fitted).



**£12.95**

EN

These parts are Sparex parts and are not manufactured by the Original Equipment Manufacturer. Original Manufacturer's name, part numbers and descriptions are quoted for reference purposes only and are not intended to indicate or suggest that our replacement parts are made by the OEM.

**Dealer Nett**  
Excl VAT  
Valid Until 31/03/2017

### S.3204 Pistol Grease Gun (Standard Duty)

- 5000 PSI / 345 BAR
- Bulk fill or 400 gm cartridge
- Aluminium head
- One hand operation for use in confined spaces or where access is restricted
- 1/8" BSPT threads
- 100mm straight extension, 300mm high pressure flexible extension & 4 jaw coupler
- Thread 1/8" BSPT



**£14.95**

### S.22770 Point

Replacement for Simba



**£8.50**

### S.23039 Loader Bracket comes with Spacer Arm

Replacement For Euro-Norm



**£26.90**

### S.105901 Antifreeze Universal (20L)

- Universal Antifreeze will protect all engines to -45°C.
- Ethylene Glycol based, blended with inhibitors to give high degree of corrosion & rust protection to all parts of engine cooling systems.
- Recommended for all year round use.



**£29.50**

### S.28345 Radio FM / AM Receiver / MP3 Player / USB / SD MMc / AUX point

- This radio is suitable for shallow dashboards
- Front AUX jack plug connection
- USB SD input connection
- 4 x 25w power output
- Chassis dimensions: W 178 x H 50 x D 130mm



**£49.75**

### S.23051 Wired Reversing Camera System with 7" LCD Monitor & 1 Camera

Wired system adapted for for the farming environment- robust, waterproof & practical  
Easy to install - easy to use  
This system is only suitable for use with a single camera  
12V / 24V  
Audio: Yes



**£149.00**



### S.101802 PTO Driven Vacuum Pump 540 r.p.m

- Fits MEC8000M
- Capacity ltr. min 8100
- Max. Working Pressure 2.5 bar
- Oil Tank Capacity ltr 3.8
- Power Absorption Max Pressure kw 27
- Power Absorption Max Vacuum kw 16



**£760.00**


### S.29642 Hydraulic Hose 3/8"



**£2.25 per Meter**

### S.112562 Hydraulic Hose Swaging Machine - BS20 Mini

- 1 Phase electric machine
- Micrometer auto cut off adjustment
- Push button operation
- Easy to set and use
- Die Sets: 16, 19, 23, 26, 29, 39, 45, 51mm
- Hose Sizes: 1/4" - 1 1/4" 2 Wire & 1/4" - 1" 4 Wire



**£3282.62**

Dealer Nett - Prices Exclude VAT

Valid Until 31/03/2017

These parts are Sparex parts and are not manufactured by the Original Equipment Manufacturer. Original Manufacturer's name, part numbers and descriptions are quoted for reference purposes only and are not intended to indicate or suggest that our replacement parts are made by the OEM.

**Sparex**  
Your 1<sup>st</sup> choice

### S.113181 Halogen Beacon 12V (DC), 24V (DC) Fitting: Flexible Pin

- Profile Low
- Overall Height: 215
- Ø 127
- Bulb Type: H1 12V/55W, H1 24V/70W
- Volts: 12V (DC), 24V (DC)
- Power Consumption @ 12V: 4.5A
- Power Consumption @ 24V: 2.7A
- Temperature Range: -30/+50°C
- Speed: 140+/-20 rpm
- Dome Material: Polycarbonate
- Homologated ECE Reg 65
- Electromagnetic Compatibility: Conforms ECM
- IP Rating: IP55



**£14.95**

**NEW**

### S.113180 Halogen Beacon 12V (DC), 24V (DC) Flexible Pin (ECE Reg 65 / IP55)

- Profile Standard
- Overall Height: 240
- Ø 128
- Bulb Type: H1 12V/55W, H1 24V/70W
- Replacement Bulb: H1 12V: S.110042, H1 24V: S.110045
- Power Consumption @ 12V: 4.5A
- Power Consumption @ 24V: 2.7A
- Temperature Range: -30/+50°C
- Speed: 140+/-20 rpm
- Dome Material: Polycarbonate
- Homologated ECE Reg 65
- Electromagnetic Compatibility: Conforms ECM
- IP Rating: IP55




**£14.95**

**NEW**

### S.113199 LED Beacon 12V (DC), 24V (DC) Flexible Pin (ECE Reg 10 / IP55)

- Profile Standard
- Overall Height: 240
- Ø 128
- No. of LED's: 40 / 8W
- Power Consumption @ 12V: 1.2A
- Power Consumption @ 24V: 1.2A
- Temperature Range: -30/+50°C
- Dome Material: Polycarbonate
- Homologated ECE Reg 10
- Electromagnetic Compatibility: Conforms ECM
- IP Rating: IP55



**£19.50**

**NEW**

### S.113214 LED Beacon 12V (DC), 24V (DC) Flexible Pin (ECE Reg 10 / IP55)

- Profile Low
- Overall Height: 240
- Ø 128
- No. of LED's: 40 / 8W
- Power Consumption @ 12V: 1.2A
- Power Consumption @ 24V: 1.2A
- Temperature Range: -30/+50°C
- Dome Material: Polycarbonate
- IP Rating: IP55



**£19.50**

### S.118305 Beacon Lens, Green

- Compatible with S.118306, S.113199 & S.113214



**£1.66**

