

Generative Adversarial Networks with Joint Distribution Moment Matching (GAN with JDMM)

Chaomin Shen¹

Joint work with Yiyin Zhang¹, Hao Feng¹, Yaxin Peng², Guixu Zhang¹

¹Dept of Computer Science, East China Normal University, Shanghai, China

²Dept of Mathematics, Shanghai University, Shanghai, China

Apr. 14, 2018, Nanjing

Generative Adversarial Networks (GAN)



Real MNIST



Generated MNIST

airplane
automobile
bird
cat
deer
dog
frog
horse
ship
truck




Real CIFAR-10




Generated CIFAR-10

Generative Adversarial Networks (GAN)



Real Brain MRI



Generated Brain MRI

Basic formula of GAN

G : Generator

D : Discriminator

$$\min_G \max_D \mathbb{E}_{\mathbf{x} \sim \mathbb{P}_r} [\log(D(\mathbf{x}))] + \mathbb{E}_{\mathbf{z} \sim \mathbb{P}_g(\mathbf{z})} [\log(1 - D(G(\mathbf{z})))]$$

Basic formula of GAN

G : Generator

D : Discriminator

$$\min_G \max_D \mathbb{E}_{\mathbf{x} \sim \mathbb{P}_r} [\log(D(\mathbf{x}))] + \mathbb{E}_{\mathbf{z} \sim \mathbb{P}_g(\mathbf{z})} [\log(1 - D(G(\mathbf{z})))]$$

■ \mathbf{x} : 真实图像 \mathbf{z} : 输入网络的噪声

Basic formula of GAN

G : Generator

D : Discriminator

$$\min_G \max_D \mathbb{E}_{\mathbf{x} \sim \mathbb{P}_r} [\log(D(\mathbf{x}))] + \mathbb{E}_{\mathbf{z} \sim \mathbb{P}_g(\mathbf{z})} [\log(1 - D(G(\mathbf{z})))]$$

- \mathbf{x} : 真实图像 \mathbf{z} : 输入网络的噪声
- $D(\mathbf{x})$: D 判断真实图像 \mathbf{x} 是否是真实的概率.

Basic formula of GAN

G : Generator

D : Discriminator

$$\min_G \max_D \mathbb{E}_{\mathbf{x} \sim \mathbb{P}_r} [\log(D(\mathbf{x}))] + \mathbb{E}_{\mathbf{z} \sim \mathbb{P}_g(\mathbf{z})} [\log(1 - D(G(\mathbf{z})))]$$

- \mathbf{x} : 真实图像 \mathbf{z} : 输入网络的噪声
- $D(\mathbf{x})$: D 判断真实图像 \mathbf{x} 是否是真实的概率. $D(\mathbf{x})$ 越大越好

Basic formula of GAN

G : Generator

D : Discriminator

$$\min_G \max_D \mathbb{E}_{\mathbf{x} \sim \mathbb{P}_r} [\log(D(\mathbf{x}))] + \mathbb{E}_{\mathbf{z} \sim \mathbb{P}_g(\mathbf{z})} [\log(1 - D(G(\mathbf{z})))]$$

- \mathbf{x} : 真实图像 \mathbf{z} : 输入网络的噪声
- $D(\mathbf{x})$: D 判断真实图像 \mathbf{x} 是否是真实的概率. $D(\mathbf{x})$ 越大越好
- $G(\mathbf{z})$: G 生成的假图像

Basic formula of GAN

G : Generator

D : Discriminator

$$\min_G \max_D \mathbb{E}_{\mathbf{x} \sim \mathbb{P}_r} [\log(D(\mathbf{x}))] + \mathbb{E}_{\mathbf{z} \sim \mathbb{P}_g(\mathbf{z})} [\log(1 - D(G(\mathbf{z})))]$$

- \mathbf{x} : 真实图像 \mathbf{z} : 输入网络的噪声
- $D(\mathbf{x})$: D 判断真实图像 \mathbf{x} 是否是真实的概率. $D(\mathbf{x})$ 越大越好
- $G(\mathbf{z})$: G 生成的假图像 希望能以假乱真, 理想的 G 应该 $D(G(\mathbf{z}))$ 越大越好, i.e., $1 - D(G(\mathbf{z}))$ 越小越好,

Basic formula of GAN

G : Generator

D : Discriminator

$$\min_G \max_D \mathbb{E}_{\mathbf{x} \sim \mathbb{P}_r} [\log(D(\mathbf{x}))] + \mathbb{E}_{\mathbf{z} \sim \mathbb{P}_g(\mathbf{z})} [\log(1 - D(G(\mathbf{z})))]$$

- \mathbf{x} : 真实图像 \mathbf{z} : 输入网络的噪声
- $D(\mathbf{x})$: D 判断真实图像 \mathbf{x} 是否是真实的概率. $D(\mathbf{x})$ 越大越好
- $G(\mathbf{z})$: G 生成的假图像 希望能以假乱真, 理想的 G 应该 $D(G(\mathbf{z}))$ 越大越好, i.e., $1 - D(G(\mathbf{z}))$ 越小越好, 所以 **min G** .

Basic formula of GAN

G : Generator

D : Discriminator

$$\min_G \max_D \mathbb{E}_{\mathbf{x} \sim \mathbb{P}_r} [\log(D(\mathbf{x}))] + \mathbb{E}_{\mathbf{z} \sim \mathbb{P}_g(\mathbf{z})} [\log(1 - D(G(\mathbf{z})))]$$

- \mathbf{x} : 真实图像 \mathbf{z} : 输入网络的噪声
- $D(\mathbf{x})$: D 判断真实图像 \mathbf{x} 是否是真实的概率. $D(\mathbf{x})$ 越大越好
- $G(\mathbf{z})$: G 生成的假图像 希望能以假乱真, 理想的 G 应该 $D(G(\mathbf{z}))$ 越大越好, i.e., $1 - D(G(\mathbf{z}))$ 越小越好, 所以 **min G** .
- $D(\mathbf{x})$: 理想的 D 应该使得 $D(\mathbf{x})$ 大; $D(G(\mathbf{z}))$ 小, 即第2项大,

Basic formula of GAN

G : Generator

D : Discriminator

$$\min_G \max_D \mathbb{E}_{\mathbf{x} \sim \mathbb{P}_r} [\log(D(\mathbf{x}))] + \mathbb{E}_{\mathbf{z} \sim \mathbb{P}_g(\mathbf{z})} [\log(1 - D(G(\mathbf{z})))]$$

- \mathbf{x} : 真实图像 \mathbf{z} : 输入网络的噪声
- $D(\mathbf{x})$: D 判断真实图像 \mathbf{x} 是否是真实的概率. $D(\mathbf{x})$ 越大越好
- $G(\mathbf{z})$: G 生成的假图像 希望能以假乱真, 理想的 G 应该 $D(G(\mathbf{z}))$ 越大越好, i.e., $1 - D(G(\mathbf{z}))$ 越小越好, 所以 $\min G$.
- $D(\mathbf{x})$: 理想的 D 应该使得 $D(\mathbf{x})$ 大; $D(G(\mathbf{z}))$ 小, 即第2项大, 所以 $\max D$.

Outline

1 Introduction

- Generative Adversarial Networks (GAN)
- Main Idea

2 Proposed Method

- Marginal Distribution Moment Matching
- Conditional Distribution Moment Matching
- Joint Distribution Moment Matching
- Proposed Model: GAN with JDMM

3 Experimental Results

- Datasets / Benchmarks
- Experimental Results

4 Conclusion

Generative Adversarial Networks

- A generative network G tries to capture the data distribution.
Input: random noise z from prior distribution $p(z)$ (e.g. normal)
Output: synthetic data $G(z)$.
- An adversarial network D for distinguishing training and generated data.
Input: $G(z)$
Output: feature indicating whether fake or not
- The objective function of GAN:

$$\min_G \max_D \mathbb{E}_{\mathbf{x} \sim \mathbb{P}_r} [\log(D(\mathbf{x}))] + \mathbb{E}_{z \sim \mathbb{P}_g(z)} [\log(1 - D(G(z)))],$$

where \mathbb{P}_r is the distribution of the training data

\mathbb{P}_g is the distribution of the generated data

- Conditional GAN:

$$\min_G \max_D \mathbb{E}_{\mathbf{x} \sim \mathbb{P}_r} [\log(D(\mathbf{x}|y))] + \mathbb{E}_{z \sim \mathbb{P}_g(z)} [\log(1 - D(G(z|y)))],$$

where y is the label.

Variants of GANs

- Traditional GANs are **unsupervised** (and also marginal since no label)
- **Conditional** GANs: generate data with labels in **semi-supervised** learning
 - **Advantages:** Achieve better performance than traditional GANs



(a)



(b)

- **Disadvantages:** Generally only minimize the difference between **marginal** distributions of real data and generated data, **neglecting** the difference with respect to **each class**, e.g. [1]

[1] Y. Ren, J. Li, Y. Luo, J. Zhu, "Conditional generative moment-matching networks," NIPS 2016.

Main idea / Novelties

- Minimize the differences of both the **marginal** and **conditional** distributions. Therefore, termed as **J**oint **D**istribution **M**oment **M**atching.
- Use JDMM as a general framework for both **unsupervised** and **semi-supervised** generative tasks.

GAN with JDMM

Frequently used notations

Notation	Description
\mathbf{x}, y_r	training data and its corresponding label
$\tilde{\mathbf{x}}, y_g$	generated data and its corresponding label
$\mathbb{P}_r, \mathbb{P}_g$	marginal distribution of $\mathbf{x}/\tilde{\mathbf{x}}$
$\mathbb{C}_r, \mathbb{C}_g$	conditional distribution of $\mathbf{x}/\tilde{\mathbf{x}}$ e.g., $\mathbb{C}(\mathbf{x} y)$ or $\mathbb{C}(y \mathbf{x})$
$\mathbb{J}_r, \mathbb{J}_g$	joint distribution of $\mathbf{x}/\tilde{\mathbf{x}}$
N, M	number of real/generated data
C	number of classes

Maximum Mean Discrepancy (MMD)

- Given two sets of samples $X = \{\mathbf{x}_i\}_{i=1}^N$ and $X' = \{\mathbf{x}'_j\}_{j=1}^M$ from distributions \mathbb{P}_X and $\mathbb{P}_{X'}$, MMD¹ is an estimator to answer whether $\mathbb{P}_X = \mathbb{P}_{X'}$.

$$\text{MMD}[\mathcal{K}, \mathbb{P}_X, \mathbb{P}_{X'}] := \sup_{f \in \mathcal{K}} (\mathbb{E}_X[f(X)] - \mathbb{E}_{X'}[f(X')]),$$

where \mathcal{K} is a class of functions in a Reproducing Kernel Hilbert Space (RKHS) \mathcal{H} , with an associated continuous kernel $k(\cdot, \cdot)$.

- In practice, MMD can also be calculated as the squared difference between the empirical kernel mean embeddings:

$$\mathcal{L}_{\text{MMD}}^2 = \left\| \frac{1}{N} \sum_{i=1}^N \phi(\mathbf{x}_i) - \frac{1}{M} \sum_{j=1}^M \phi(\tilde{\mathbf{x}}_j) \right\|^2,$$

where ϕ is a feature mapping: $X \rightarrow \mathcal{H}$.

¹A. Gretton, K. Borgwardt, M. Rasch, et al., “A kernel two-sample test,”
Journal of Machine Learning Research, 13(3):723–773, 2012.

Marginal Distribution Moment Matching

- Computationally **expensive** to apply MMD directly on the **data space**.
- MMD can be computed on the **features** extracted by the discriminator, since the discriminator is a CNN whose output contains features extracted from input images.

Marginal Distribution Moment Matching

$$L_{\text{MMD}}(\mathbb{P}_r, \mathbb{P}_g) = \left\| \frac{1}{N} \sum_{i=1}^N \phi(D(\mathbf{x}_i)) - \frac{1}{M} \sum_{j=1}^M \phi(D(\tilde{\mathbf{x}}_j)) \right\|^2$$

where $\phi(\cdot)$ is a feature mapping: $X \rightarrow \mathcal{H}$,

$D(\cdot)$ represents the outputs of the discriminator,

$\{\mathbf{x}_i\}_{i=1}^N$ are samples from the training data distribution,

$\{\tilde{\mathbf{x}}_j\}_{j=1}^M$ are samples from the generated data distribution.

Conditional Distribution Moment Matching

$$\mathbb{C}_r(y_r = c|\mathbf{x}), \mathbb{C}_g(y_g = c|\tilde{\mathbf{x}}), \quad \mathbb{C}_r(\mathbf{x}|y_r = c), \mathbb{C}_g(\tilde{\mathbf{x}}|y_g = c)$$

Given labels in the real data, $\mathbb{C}_r(y_r|\mathbf{x})$ is known.

We also want to get the labels for the generated data, i.e., $\mathbb{C}_g(y_g|\tilde{\mathbf{x}})$

- The conditional distributions $\mathbb{C}_r(y_r|\mathbf{x})$ and $\mathbb{C}_g(y_g|\tilde{\mathbf{x}})$ should be close as well.
- Matching $\mathbb{C}_r(y_r|\mathbf{x})$ and $\mathbb{C}_g(y_g|\tilde{\mathbf{x}})$ is **nontrivial**.
 - The probability density of $\tilde{\mathbf{x}}$ is changing through the whole training procedure. Therefore it is impossible to compute $\mathbb{C}_g(y_g|\tilde{\mathbf{x}})$.

Conditional Distribution Moment Matching

We employ the nonparametric statistic $\mathbb{C}_r(\mathbf{x}|y_r)$ and $\mathbb{C}_g(\tilde{\mathbf{x}}|y_g)$ instead

Conditional Distribution Moment Matching *for each class*

$$L_{\text{MMD}}^{(c)}(\mathbb{C}_r^{(c)}, \mathbb{C}_g^{(c)}) = \left\| \frac{1}{N^c} \sum_{i=1}^{N^c} \phi(D(\mathbf{x}_i)) - \frac{1}{M^c} \sum_{j=1}^{M^c} \phi(D(\tilde{\mathbf{x}}_j)) \right\|^2,$$

where $\mathbb{C}_r^{(c)}$ and $\mathbb{C}_g^{(c)}$: conditional distributions,

$\{\mathbf{x}_i : \mathbf{x}_i \sim \mathbb{C}_r^{(c)}, y(\mathbf{x}_i) = c\}$: set of real samples for class c ,

$y(\mathbf{x}_i)$: real label,

$\{\tilde{\mathbf{x}}_j : \tilde{\mathbf{x}}_j \sim \mathbb{C}_g^{(c)}, y(\tilde{\mathbf{x}}_j) = c\}$: set of generated samples for class c ,

$y(\tilde{\mathbf{x}}_j)$: generated label,

N^c and M^c : numbers of real and generated samples for class c .

Joint Distribution Moment Matching

Joint Distribution Moment Matching

$$L(\mathbb{J}_r, \mathbb{J}_g) = L_{\text{MMD}}(\mathbb{P}_r, \mathbb{P}_g) + \lambda \sum_{c=1}^C L_{\text{MMD}}^{(c)}(\mathbb{C}_r^{(c)}, \mathbb{C}_g^{(c)}),$$

where \mathbb{J}_r represents joint distribution of real data

\mathbb{J}_g represents joint distribution of generated data

$\lambda = 0$ indicates the GAN is unsupervised

Framework of GAN with JDMM

A minimax game between the discriminator and generator:

Framework of GAN with JDMM

$$\begin{aligned} \max_D L(\mathbb{J}_r, \mathbb{J}_g) - \gamma L_C, \\ \min_G L(\mathbb{J}_r, \mathbb{J}_g) + \gamma L_C \end{aligned}$$

where L_C is the cross entropy $L_C = -\mathbf{y}_r \cdot \log(\hat{\mathbf{y}}_r) - \mathbf{y}_g \cdot \log(\hat{\mathbf{y}}_g)$.
 $\gamma = 0$ for unsupervised GAN

A. Odena, C. Olah, and J. Shlens, “Conditional image synthesis with auxiliary classifier GANs,” in ICML, pp. 2642-2651, 2017

Framework of GAN with JDMM

We improve the **robustness** of our model:

Gradient penalty in WGAN¹


$$GP = \mathbb{E}_{\hat{\mathbf{x}} \sim \mathbb{P}_{\hat{\mathbf{x}}}} [(\|\nabla_{\hat{\mathbf{x}}} D(\hat{\mathbf{x}})\|_2 - 1)^2]$$

Final framework of GAN with JDMM


$$\begin{aligned} \max_D L(\mathbb{J}_r, \mathbb{J}_g) - \gamma L_C - \xi GP, \\ \min_G L(\mathbb{J}_r, \mathbb{J}_g) + \gamma L_C \end{aligned}$$

[1] M. Arjovsky, S. Chintala, and L. Bottou, "Wasserstein GAN," arXiv preprint arXiv:1701.07875, 2017.

Network structure



Network G



Network D

Implementation

Algorithm 1 GAN with JDMM

Input : n_c : number of iterations for discriminator per generator update
 α : learning rate
 β_1, β_2 : Adam hyperparameters
 θ_G and θ_D : Initial generator/discriminator parameters

1. **for** number of training iterations **do**
2. **for** $t = 1$ to n_c **do**
3. Sample a minibatch x from \mathbb{P}_r and z from $\mathbb{P}(z)$
4. Generate fake data $G(z)$
5. Compute gradient $g_D = \nabla_D L(\mathbb{J}_r, \mathbb{J}_g) - \gamma \nabla_D L_C - \xi \nabla_D GP$
6. $\theta_D = \text{Adam}(g_D, \alpha, \beta_1, \beta_2)$
7. **end for**
8. Compute gradient $g_G = \nabla_G L(\mathbb{J}_r, \mathbb{J}_g) + \gamma \nabla_G L_C$
9. $\theta_G = \text{Adam}(g_G, \alpha, \beta_1, \beta_2)$
10. **end for**

Experimental results (Databases)

MNIST (unsupervised and semi-supervised)

- 50,000 gray-scale images, 10 classes
- Image size: 28×28

CIFAR-10 (semi-supervised)

- 50,000 color images, 10 classes
- Image size: 32×32

Extended Yale Face (semi-supervised)

- 38 classes of gray-scale human faces under different light conditions and poses
- Resize to 32×32

Data provided by 上海市磁共振重点实验室 (unsupervised)

- 3000 images
- Resize to 32×32

手写汉字 (Semi-supervised)

- 300×3750 images
- Image size: 32×32


Experimental results (Benchmarks)

WGAN and its variants: One of the best GANs

MMD based GANs: Similar methods

Experimental results (Evaluation rule for CIFAR)

Inception score: a **benchmark** of measuring sample quality



Method	Score
SteinGAN [Wang and Liu, 2016]	6.35
DCGAN (with labels, in [Radford <i>et al.</i> , 2015])	6.58
Improved GAN [Salimans <i>et al.</i> , 2016]	8.09±.07
AC-GAN [Odena <i>et al.</i> , 2017]	8.25±.07
WGAN-GP ResNet [Gulrajani <i>et al.</i> , 2017]	8.42±.10
GAN with JDMM (ours)	8.59±.10

Examples of inception scores

Experimental results (MNIST: unsupervised and semi-supervised)



Groundtruth



(a)



(b)

(a) Unsupervised (labels not used); (b) Semi-supervised (labels used)

Experimental results (Comparison with other unsupervised GANs)



(a) GMMN-C

(b) WGAN

(c) MMD GAN

(d) Ours

Images generated from MNIST in the **unsupervised** setup


Experimental results (Comparison with other semi-supervised GANs)




Results of WGAN-GP and GAN with JDMM on CIFAR-10 (labels used).

Inception score: (a) 8.42 ± 0.1 (b) **8.59 ± 0.1**

Experimental results (Inception score and MMD value)



(a) Inception score



(b) MMD


Inception score and MMD during the training of GAN with JDMM on CIFAR-10.

Experimental results (Extended Yale Face: semi-supervised)




Images generated from Extended Yale Face.
Each column represents one particular individual.

Experimental results (MRI: unsupervised)



Real Brain MRI



Generated Brain MRI

Experimental results (Chinese characters: supervised)

Real 形丽伍做典到医卧固姻

Generated 形丽伍做典到医卧固姻

Real 凯功墙文曲杞椰由粗聘

Generated 凯功墙文曲杞椰由粗聘

Real 肝膳贾问同陆题弛琦骑

Generated 肝膳贾问同陆题弛琦骑

Conclusion

- Minimize the difference not only of **marginal** distributions but also of **conditional** distributions.
- For **unsupervised** and **semi-supervised** cases
- Desirable and competitive performance on several databases.

Conclusion

- Minimize the difference not only of **marginal** distributions but also of **conditional** distributions.
- For **unsupervised** and **semi-supervised** cases
- Desirable and competitive performance on several databases.

Future Works

- Medical images
 - 512×512
 - Images other than brain images, e.g., CT images of bones

Thanks

`cmshen@cs.ecnu.edu.cn`

International Conference of Union of Mathematical Imaging 2018 (UMI 2018)

2018.5.11-13 上海 华东师范大学

首页

会议组织

会议日程

参会专家

演讲视频

会议总结

会场与酒店

论文投稿

English



电子科技
大学



北京大学



浙江大学



国防科技
大学



哈尔滨工
业大学



河南大学



华北电力
大学



华东师范
大学



南京大学



上海大学




上海交通
大学



中山大学




香港浸会
大学




1 pixel error

我覺得不行




1 pixel error

我覺得不行



6 pixel errors

我覺得
其實 OK



6 pixel errors

我覺得
其實 OK

Created with EverCam