



RM II

Resin Capsule



- RM II is the first bonded anchor with threaded rod RG M for cracked and non-cracked concrete that does not require drill hole cleaning. This allows for a rapid working progress and an economic installation.
- Moreover, there is a reduced exposition to drill dust on the building site. This increases the safety for the user.
- The pre-portioned capsule is easy to install & especially suitable for individual applications and overhead installations.
- The 2-component resin capsule RM II contains styrene-free vinyl ester resin and hardener.
- Ideal for overhead installations and water-filled drill holes.
- The threaded rod RG M is set using a hammer drill and the accompanying setting tool in rotating and hitting motions.
- During setting, the oblique edge of the RG M destroys the capsule, and mixes and activates the mortar.
- The mortar bonds the entire surface of the threaded rod with the drill hole wall and seals the drill hole.

Description/Size	Hole Depth/mm	Packed	Drill Ø
8 mm	80	10	10
10 mm	90	10	12
12 mm	110	10	14
16 mm	125	10	18
20 mm	170	10	25
24 mm	210	5	28

RG

Chemical Anchor Stud



- The wide range of the RG M from M8 to M30 opens up a wide range of applications and therefore offers great flexibility.
- The wide range of approved steel types for RG M allows for use in all corrosion resistance classes and offers the best possible application safety.
- Due to its oblique edge, the threaded rod RG M is particularly suitable for use in conjunction with resin capsules.
- The threaded rod RG M is set using a hammer drill and the accompanying setting tool in rotating and hitting motions.
- During setting, the oblique edge of the RG M destroys the capsule, and mixes and activates the mortar.
- Use with injection mortar is also possible. Here, the stud is manually inserted into the drill hole with a light rotating movement until it reaches the base of the hole.

Description/Size	Length/mm	Drill Ø
8 mm E/G	110	10
10 mm E/G	130	12
10 mm E/G	165	12
10 mm E/G	190	12
12 mm E/G	160	14
12 mm E/G	220	14
12 mm E/G	250	14
12 mm E/G	300	14
16 mm E/G	165	18
16 mm E/G	190	18
16 mm E/G	250	18
16 mm E/G	300	18
20 mm E/G	220	25
20 mm E/G	260	25
20 mm E/G	300	25
24 mm E/G	300	28
30 mm E/G	380	35
8 mm A2	110	10
10 mm A2	130	12
10 mm A2	165	12
10 mm A2	190	12
12 mm A2	160	14
12 mm A2	220	14
16 mm A2	165	18
16 mm A2	190	18
16 mm A2	250	18
20 mm A2	220	25
20 mm A2	260	25
20 mm A2	300	25
24 mm A2	300	28
30 mm A2	380	35
10 mm A4	130	12
12 mm A4	165	14
16 mm A4	180	18
20 mm A4	220	25
24 mm A4	280	28
30 mm A4	350	35

FHB II

Highbond System



- › The Highbond system FHB II achieves the highest load values in cracked concrete. Thus fewer fixing points and smaller anchor plates are required.
- › The injection mortar FIS HB and the capsules FHB II-P/PF offer the same performance and can be used with the FHB II-A S (short version) or L (long version) anchor rods. Thus, you can select the most economical solution based on requirements.
- › The large cartridge size of the injection mortar FIS HB is ideally suited for serial installation.
- › The pre-portioned resin capsule FHB II-P / PF HIGH SPEED is the economical solution for single applications or under water. A cleaning of the borehole during processing with capsule is not required.

Description/Size	Length/mm	Packed	Drill Ø
12 mm	120	10	14
16 mm	125	10	18
16 mm	160	10	18
20 mm	210	4	25
Related Injection Mortar			
FIS HB 345 S			

ANCHOR RODS



- › The anchor rod can be set either with injection mortar or with the capsule and is fully bonded in the drill hole.
- › When tightening the hexagon nut, the anchor rod cones are pulled into the mortar shell, which expands against the drill hole wall.
- › The styrene-free vinyl ester mortar fully seals the drill hole.
- › When using the resin capsule, set the anchor rod through rotating and hitting motions with a hammer drill.

Description/Size	Embed/mm	Hold/mm
12 mm S 8.8 E/G	75	25
12 mm S 8.8 E/G	75	100
16 mm S 8.8 E/G	95	30
16 mm S 8.8 E/G	95	60
20 mm S 8.8 E/G	170	50
24 mm S 8.8 E/G	170	50
12 mm L 8.8 E/G	100	60
12 mm L 8.8 E/G	120	25
12 mm L 8.8 E/G	120	60
12 mm L 8.8 E/G	120	100
16 mm L 8.8 E/G	125	30
16 mm L 8.8 E/G	125	60
16 mm L 8.8 E/G	160	60
16 mm L 8.8 E/G	160	100
20 mm L 8.8 E/G	210	50
24 mm L 8.8 E/G	220	50
10 mm S A4	60	20
12 mm S A4	75	10
12 mm S A4	75	25
16 mm S A4	95	30
8 mm L A4	60	30
12 mm L A4	120	25
12 mm L A4	100	40
16 mm L A4	125	30
16 mm L A4	160	30
16 mm L A4	160	100
20 mm L A4	210	50

RSB

Superbond System



- › The Superbond system is a combined capsule and injection system for cracked and non-cracked concrete. The injection mortar FIS SB and resin capsule RSB perform the same as each other at the same anchorage depth.
- › Superbond is a bonded anchor system based on a vinyl ester hybrid with silane technology.
- › Resin and hardener are stored in two separate chambers and are not mixed and activated until extrusion through the injection cartridge in the static mixer or destruction of the capsule during the setting procedure.
- › The mortar bonds the entire surface of the threaded rod with the drill hole wall and seals the drill hole.
- › The approval-compliant use for seismic applications (performance category C1, C2) as well as in waterfilled and diamond drill holes ensures safety even in extreme conditions.

Description/Size	Hole Depth/mm	Packed	Drill Ø
10 mm	90	10	12
12 mm	110	10	14/18
16 mm	125	10	18
20 mm	170	10	25
30 mm	260	5	35
Related Injection Mortar			
FIS SB 360 S			

RG

Chemical Anchor Stud



- > The wide range of the RG M from M8 to M30 opens up a wide range of applications and therefore offers great flexibility.
- > The wide range of approved steel types for RG M allows for use in all corrosion resistance classes and offers the best possible application safety.
- > Due to its oblique edge, the threaded rod RG M is particularly suitable for use in conjunction with resin capsules.
- > The threaded rod RG M is set using a hammer drill and the accompanying setting tool in rotating and hitting motions.
- > During setting, the oblique edge of the RG M destroys the capsule, and mixes and activates the mortar.
- > Use with injection mortar is also possible: Here, the stud is manually inserted into the drill hole with a light rotating movement until it reaches the base of the hole.

Description/Size	Length/mm	Packed	Drill Ø
10 mm HDG	130	50	10
10 mm HDG	165	50	12
12 mm HDG	160	25	14
12 mm HDG	220	50	14
16 mm HDG	165	25	18
16 mm HDG	190	20	18
16 mm HDG	250	20	18
20 mm HDG	220	25	25
20 mm HDG	260	25	25
20 mm HDG	300	20	25
24 mm HDG	300	10	28

CTR

Chemical Anchor Stud



- > Steel grade C1035, which is equal to Grade 5.8 steel.
- > Due to its oblique edge, the threaded rod CTR M is particularly suitable for use in conjunction with resin capsules.
- > The stud is set using a hammer drill and setting tool in rotating and hitting motions.
- > During setting, the oblique edge of the stud destroys the capsule, and mixes and activates the mortar.
- > Use with injection mortar is also possible: Here, the stud is manually inserted into the drill hole with a light rotating movement until it reaches the base of the hole.

Description/Size	Length/mm	Packed	Drill Ø
8 mm	110	50	10
10 mm	130	50	12
12 mm	160	25	14
16 mm	190	20	18
20 mm	260	25	25
24 mm	300	10	28

FIS A

Chemical Mortar Anchor Stud



- > The system of anchor rod FIS A and injection mortar for cracked concrete (M10 to M30) and non-cracked concrete (M6 to M30) can be individually selected based on requirements, thus allowing for a wide range of applications.
- > Variable anchorage depths allow for ideal adaptation to the load to be applied, and ensure an optimised installation time and use of materials.
- > Push-through installation is possible without any special parts through filling the annular gap with injection mortar.
- > Wide range of approved steel types allow for use in all corrosion resistance classes and offers maximum safety.
- > The mortar bonds the entire surface of the threaded rod with the drill hole wall and seals the drill hole.
- > The stud is set manually, by lightly rotating it until it reaches the drill hole base.

Description/Size	Length/mm	Packed	Drill Ø
8 mm E/G	90	50	10
8 mm E/G	110	50	10
8 mm E/G	130	50	10
10 mm E/G	95	50	12
10 mm E/G	110	50	12
10 mm E/G	130	50	12
10 mm E/G	150	50	12
12 mm E/G	105	25	14
12 mm E/G	115	25	14
12 mm E/G	140	25	14
12 mm E/G	160	25	14
16 mm E/G	160	25	18
16 mm E/G	200	25	18
16 mm E/G	300	25	18
20 mm E/G	220	25	25
20 mm E/G	240	25	25
24 mm E/G	290	10	28
30 mm E/G	340	-	35

FIS H L

Metal Anchor Sleeves



- All metal anchor sleeves are 1 meter long. It can be cut to the required length and thus allows for a range of usable lengths, providing flexibility and cost-effectiveness.
- The grating structure of the sleeve allows for uniform distribution of mortar in the drill hole and thus for secure hold.
- Turning in the anchor causes the mortar to be pushed through the anchor sleeve's grating structure, so that it fits the base material perfectly.
- The load is borne by the interlock.

Description/Size	Stud Ø	Packed
12 x 1000L	6 & 8	10
16 x 1000L	10 & 12	10
22 x 1000L	12 & 16	6
30 x 1000L	16 & 22	4

VBS 8

Remedial Wall Tie



- The expansion-force-free fixing prevents splitting and cracks. This means that VBS 8 can be used even in old and sensitive masonry.
- The drill bit diameter of just 8 mm means that a minimal amount of mortar is required for each fixing point. Thus VBS 8 is particularly economical.
- The installation is approved anywhere along the entire bed joint, thus ensuring a high level of installation safety.
- The grey colour of the injection mortar is similar to the colour of the bed joint. This means that the fixing is almost invisible to the eye.
- Comprises a perforated plastic sleeve and a profiled A4 stainless steel tie Ø 4 mm.
- Used together with the injection mortar FIS V.

Description/Size	Length/mm	Max Cav	Packed	Drill Ø
8 mm A4	218	20 - 50	100	8
8 mm A4	318	80 - 120	100	8

Cleaning Brush - Stainless Steel



- The expert and approval-compliant installation of chemical fixings requires the use of stainless steel brushes for cleaning drill holes in concrete and masonry.
- The Fischer steel brushes BS with stainless steel bristles are approved for automatic or manual drill hole cleaning.
- The colour coding makes it easy to select the right brush for the relevant drill hole diameter.
- High cleaning performance and simple to use.
- Removable handle for space-saving storage.

Description/Size	Stud Ø	Packed
8 mm	8 mm	-
10 mm	10 mm	-
12 mm	12 mm	-
14 mm	14 mm	-
16/18 mm	16/18 mm	-
20/22 mm	20-22 mm	-
24 mm	24 mm	-
25 mm	25 mm	-
28 mm	28 mm	-
30/32/35 mm	30/32/35 mm	-

Cleaning Brush - Nylon



- Nylon brushes are for general hole cleaning.
- It is not recommended for chemical anchor hole cleaning.

Description/Size	Stud Ø	Packed
Brush Set Ø 14/20 mm	8 & 16 mm	-
Brush Set Ø 20/30 mm	16 & 30 mm	-

Blow-out Pumps



Description/Size	Packed
AB G Red (Medium)	-
WT Blow Out Bulb	-



FIS A

Chemical Mortar Anchor Stud



- ▶ The system of anchor rod FIS A and injection mortar for cracked and non-cracked concrete (M10 to M30) can be individually selected based on requirements, thus allowing for a wide range of applications.
- ▶ Variable anchorage depths allow for ideal adaptation to the load to be applied, and ensure an optimised installation time and use of materials.
- ▶ Push-through installation is possible without any special parts through filling the annular gap with injection mortar.
- ▶ Wide range of approved steel types allow for use in all corrosion resistance classes and offers maximum safety.
- ▶ The mortar bonds the entire surface of the threaded rod with the drill hole wall and seals the drill hole.
- ▶ The stud is set manually, by lightly rotating it until it reaches the drill hole base.

Description/Size	Length/mm	Packed	Drill Ø
8 mm A2	90	50	10
8 mm A2	110	50	10
10 mm A2	95	50	12
10 mm A2	110	50	12
10 mm A2	130	50	12
12 mm A2	105	25	14
12 mm A2	115	25	14
12 mm A2	140	25	14
12 mm A2	200	25	14
16 mm A2	160	25	18
20 mm A2	200	25	25
24 mm A2	290	10	28
12 mm HDG	160	25	-
16 mm HDG	200	25	-
20 mm HDG	245	25	-
12 mm Gr8.8	160	25	-
16 mm Gr8.8	200	25	-
20 mm Gr8.8	245	10	-

RG M I

Internal-threaded Chemical Anchor Stud



- ▶ The system internal threaded anchor RG M I and an injection mortar for concrete can be individually selected based on requirements, thus allowing for a wide range of applications.
- ▶ The internal threaded anchor allows for surface flush removal and reuse of the fixing point, offering the best flexibility.
- ▶ Allows for the use of standard metric screws or threaded rods for the ideal adaptation to suit the intended use.
- ▶ The mortar bonds the entire surface of the anchor with the drill hole wall and seals the drill hole.
- ▶ The anchor is set manually by lightly rotating it until it reaches the drill hole base.

Description/Size	Length/mm	Packed
12 mm M8I	90	10
16 mm M10I	90	10
18 mm M12I	125	10
22 mm M16I	160	5

FIS E

Internal-threaded Socket Stud



- ▶ The fixing system threaded stud FIS A and an injection mortar for concrete can be individually selected based on requirements, thus allowing for a wide range of applications.
- ▶ FIS E is suitable for pre-positioned installation, whilst FIS A is suitable for pre-positioned and push-through installation.
- ▶ Allows for the use of standard metric screws or threaded rods for the ideal adaptation to suit the intended use.
- ▶ The mortar bonds the entire surface of the anchor with the drill hole wall and seals the drill hole.
- ▶ The anchor is set manually by lightly rotating it until it reaches the drill hole base.

Description/Size	Length/mm	Packed
11 mm M8	85	10
15 mm M10	85	10
15 mm M12	85	10

Small quantities of internally threaded studs are available from stock. Supply on bigger quantities dependent on air freight best practice. Deliveries on confirmed orders only. No credits accepted.

FIS H K

Nylon Anchor Sleeves



- ▶ The grating structure of the anchor sleeve is adapted for the injection mortars FIS V, FIS GREEN and FIS P Plus, and ensures sparring mortar use with the best interlock.
- ▶ Centring blades perfectly align the anchor in the anchor sleeve and allow for use with various threaded rod diameters.
- ▶ Barbed hooks secure the anchor sleeve in the drill hole and allow for a trouble-free overhead installation.
- ▶ The geometry of the sleeves allows for the bridging of non-bearing layers for a simple and convenient installation.

Description/Size	Stud Ø	Packed
12 x 50 K	6 & 8	50
12 x 85 K	6 & 8	50
16 x 85 K	8 & 10	50
16 x 130 K	8 & 10	20
20 x 85 K	12 & 16	20
20 x 130 K	12 & 16	20
20 x 200 K	12 & 16	20



FIS A

Chemical Mortar Anchor Stud



- ▶ The system of anchor rod FIS A and injection mortar for cracked and non-cracked concrete (M10 to M30) can be individually selected based on requirements, thus allowing for a wide range of applications.
- ▶ Variable anchorage depths allow for ideal adaptation to the load to be applied, and ensure an optimised installation time and use of materials.
- ▶ Push-through installation is possible without any special parts through filling the annular gap with injection mortar.
- ▶ Wide range of approved steel types allow for use in all corrosion resistance classes and offers maximum safety.
- ▶ The mortar bonds the entire surface of the threaded rod with the drill hole wall and seals the drill hole.
- ▶ The stud is set manually, by lightly rotating it until it reaches the drill hole base.

Description/Size	Length/mm	Packed	Drill Ø
8 mm A2	90	50	10
8 mm A2	110	50	10
10 mm A2	95	50	12
10 mm A2	110	50	12
10 mm A2	130	50	12
12 mm A2	105	25	14
12 mm A2	115	25	14
12 mm A2	140	25	14
12 mm A2	200	25	14
16 mm A2	160	25	18
20 mm A2	200	25	25
24 mm A2	290	10	28
12 mm HDG	160	25	-
16 mm HDG	200	25	-
20 mm HDG	245	25	-
12 mm Gr8.8	160	25	-
16 mm Gr8.8	200	25	-
20 mm Gr8.8	245	10	-

RG M I

Internal-threaded Chemical Anchor Stud



- ▶ The system internal threaded anchor RG M I and an injection mortar for concrete can be individually selected based on requirements, thus allowing for a wide range of applications.
- ▶ The internal threaded anchor allows for surface flush removal and reuse of the fixing point, offering the best flexibility.
- ▶ Allows for the use of standard metric screws or threaded rods for the ideal adaptation to suit the intended use.
- ▶ The mortar bonds the entire surface of the anchor with the drill hole wall and seals the drill hole.
- ▶ The anchor is set manually by lightly rotating it until it reaches the drill hole base.

Description/Size	Length/mm	Packed
12 mm M8I	90	10
16 mm M10I	90	10
18 mm M12I	125	10
22 mm M16I	160	5

FIS E

Internal-threaded Socket Stud



- ▶ The fixing system threaded stud FIS A and an injection mortar for concrete can be individually selected based on requirements, thus allowing for a wide range of applications.
- ▶ FIS E is suitable for pre-positioned installation, whilst FIS A is suitable for pre-positioned and push-through installation.
- ▶ Allows for the use of standard metric screws or threaded rods for the ideal adaptation to suit the intended use.
- ▶ The mortar bonds the entire surface of the anchor with the drill hole wall and seals the drill hole.
- ▶ The anchor is set manually by lightly rotating it until it reaches the drill hole base.

Description/Size	Length/mm	Packed
11 mm M8	85	10
15 mm M10	85	10
15 mm M12	85	10

Small quantities of internally threaded studs are available from stock. Supply on bigger quantities dependent on air freight best practice. Deliveries on confirmed orders only. No credits accepted.

FIS H K

Nylon Anchor Sleeves



- ▶ The grating structure of the anchor sleeve is adapted for the injection mortars FIS V, FIS GREEN and FIS P Plus, and ensures sparring mortar use with the best interlock.
- ▶ Centring blades perfectly align the anchor in the anchor sleeve and allow for use with various threaded rod diameters.
- ▶ Barbed hooks secure the anchor sleeve in the drill hole and allow for a trouble-free overhead installation.
- ▶ The geometry of the sleeves allows for the bridging of non-bearing layers for a simple and convenient installation.

Description/Size	Stud Ø	Packed
12 x 50 K	6 & 8	50
12 x 85 K	6 & 8	50
16 x 85 K	8 & 10	50
16 x 130 K	8 & 10	20
20 x 85 K	12 & 16	20
20 x 130 K	12 & 16	20
20 x 200 K	12 & 16	20



FH II

High Performance Anchor



- ▶ The international approvals guarantee maximum safety and the best performance. These approvals even cover use in earthquake zones (seismic C1 and C2).
- ▶ The anchor is designed with different head styles for fixing points with aesthetic design.
- ▶ Design between bolt and sleeve ensures high shear load-bearing capacity. Thus, fewer fixing points are required.
- ▶ The optimised geometry minimises the energy required for installation and thus allows for fast installation.
- ▶ The use of hollow drills is included in the approval.
- ▶ The black plastic ring prevents rotation when tightening the anchor and acts as a crumple zone to take the torque slippage, so that the fixture of pulled onto the substrate.
- ▶ All anchors are electro plated with clear passivation.

Description/Size	Stud Ø	Packed
10/10 B Stud/Nut	M6	50
10/50 B Stud/Nut	M6	50
12/10 B Stud/Nut	M8	50
12/25 B Stud/Nut	M8	50
12/50 B Stud/Nut	M8	25
15/10 B Stud/Nut	M10	25
15/25 B Stud/Nut	M10	25
15/50 B Stud/Nut	M10	25
18/25 B Stud/Nut	M12	20
18/50 B Stud/Nut	M12	20
24/25 B Stud/Nut	M16	10
24/100 B Stud/Nut	M16	5
28/30 B Stud/Nut	M20	4
32/30 B Stud/Nut	M24	4
10/10 S Bolt	M6	50
10/25 S Bolt	M6	50
12/10 S Bolt	M8	50
12/25 S Bolt	M8	50
15/10 S Bolt	M10	25
15/25 S Bolt	M10	25
18/25 S Bolt	M12	20
24/25 S Bolt	M16	10
24/50 S Bolt	M16	10
12/15 SK Countersunk	M8	25
12/25 SK Countersunk	M8	25
12/50 SK Countersunk	M8	25
15/15 SK Countersunk	M10	25
15/25 SK Countersunk	M10	25
18/15 SK Countersunk	M12	20
18/25 SK Countersunk	M12	20
18/50 SK Countersunk	M12	20

*Not all sizes are immediately available from stock – They can be imported within 8 - 10 weeks on seafreight.
If customer wants non-price list items imported via airfreight, the additional charges will be for the customer's account.*

FAZ

High Performance Anchor



- ▶ According to a new ETA assessment, the tensile load capacities are decisively increased. This requires less anchors.
- ▶ Variable anchorage depths for sizes M8 to M16 allow for the first time a millimeter-accurate adjustment to the loads.
- ▶ The international approvals guarantee maximum safety and the best performance.
- ▶ Approved for diamond-drilled holes.
- ▶ Suitable for pre-positioned & push-through installation. Also ideal for stand-off installation thanks to the long thread.

Description/Size	Length/mm	Hold/mm	Packed
8 mm E/G	75	10	50
10 mm E/G	95	10	50
12 mm E/G	110	10	20
12 mm E/G	120	20	20
12 mm E/G	130	30	20
12 mm E/G	200	100	20
12 mm E/G	260	160	10
16 mm E/G	148	25	10
20 mm E/G	172	30	5
20 mm E/G	202	60	5
8 mm A4	75	10	50
10 mm A4	95	10	50
12 mm A4	110	10	20
12 mm A4	150	50	20
16 mm A4	148	25	20
16 mm A4	173	50	20
20 mm A4	202	60	4
24 mm A4	205	30	4

FIS EM Plus

Epoxy Mortar



- ▶ The optimised formulation of the epoxy resin mortar FIS EM Plus leads to improved load values in cracked and non-cracked concrete.
- ▶ The mortar can be used for rebar connections from diameter 8 to 40 mm.
- ▶ With the threaded rod FIS A, the loads to be applied can be designed variably by selecting the anchorage depth.
- ▶ Temporary and detachable fixing points are possible with the internal threaded anchor RG M.I.
- ▶ For practical use on the building site, FIS EM Plus can be processed at low temperatures down to -5 °C.
- ▶ The mortar is approved for diamond drilled and water-filled drill holes as well as seismic applications of performance categories C1, C2 and thus offers safety under extreme conditions.

Description/Size

FIS EM 390 Plus S

FIS EM 585 Plus S

Product

FIS EB II

Epoxy Mortar



- ▶ The fischer injection mortar FIS EB II is an economical epoxy resin mortar for standard applications in cracked and non-cracked concrete and for post-installed rebar connections.
- ▶ It is suitable for fixing heavy loads both indoor and outdoor.
- ▶ Can be installed with the approved system components fischer threaded rods FIS A / RG or with reinforcement bars.
- ▶ Can be used in dry or wet concrete, as well as in water-filled drill holes.
- ▶ This makes the epoxy resin mortar a secure and reliable system under all work site conditions.
- ▶ The long processing time of FIS EB II is particularly suitable for applications in large and deep drillholes.
- ▶ The mortar has ETA assessments for anchorings in cracked concrete and for post-installed rebar connections.

Description/Size

FIS EB II 390 S

FIS EB II 585 S

Product

FIS V

Injection Mortar



- ▶ The FIS V injection mortar has numerous system approvals, such as in cracked and non-cracked concrete, masonry and for special applications.
- ▶ The FIS V is a 2-component injection mortar based on vinyl ester hybrid.
- ▶ Resin and hardener are stored in two separate chambers and are not mixed and activated until extrusion through the static mixer.
- ▶ The injection cartridges are quick and easy to use with the fischer dispensers.
- ▶ Partially used cartridges can be reused, simply by changing the static mixer.
- ▶ FIS VS LOW SPEED with extended gelling time prevents premature curing of the mortar at higher temperatures and is ideally suited to large drill hole depths.

Description/Size

FIS V Plus 360 S

FIS VS Plus 300 T

Product

FIS VL

Injection Mortar



- ▶ The FIS VL is approved for use in cracked concrete and masonry, and achieves a high load-bearing capacity in these conditions.
- ▶ Allows for anchorings in water-filled drill holes (410 ml cartridges only), thus allowing for rapid progress.
- ▶ The temperature resistance of the FIS VL injection mortar of -40 °C to +120 °C allows for a solid load level even when subjected to high temperature demands, thus providing great flexibility.
- ▶ The FIS VL is a 2-component injection mortar based on vinyl ester.
- ▶ Resin and hardener are stored in two separate chambers and are not mixed and activated until extrusion through the static mixer.
- ▶ Partially used cartridges can be reused, simply by changing the static mixer.

Description/Size

FIS VL 410 C

Product

FIS P Plus

Injection Mortar



- ▶ With FIS P Plus, anchorings in masonry and non-cracked concrete for which approval is relevant can be realised in a particularly economical manner.
- ▶ Can be used with stable, standard silicone injection dispensers. No special equipment is required. As a result, procurement costs can be reduced on the basis of polyester resin.
- ▶ The FIS P Plus is a 2-component injection mortar based on vinyl ester.
- ▶ Resin and hardener are stored in two separate chambers and are not mixed and activated until extrusion through the static mixer.
- ▶ Partially used cartridges can be reused, simply by changing the static mixer.

Description/Size

FIS P Plus 300 T

Product



Static Mixer



- ▶ Ensures safe mixing of hardening agent and resin components during application.
- ▶ With suitable screw connection for the cartridge.

Description/Size	Product
FIS Mixer Red	

FIS Case Set



FIS Rebar Case Set consists of:

- ▶ 8 x Cleaning Brushes
- ▶ 5 x Brush Extensions
- ▶ 24 x Injection Adapters
- ▶ 8 x Cleaning Nozzles
- ▶ Cleaning Hose, SDS Chuck
- ▶ Brush Control Template
- ▶ Marker Tape, Digital Thermometer
- ▶ Protect Goggles, Installation Report
- ▶ 2 x SW7 Flat Spanner
- ▶ Instructions

Description/Size	Product
FIS Rebar Case Set	

Dispensers

Shuttle Dispensers



- ▶ The robust design can withstand the high requirements of the job site and thus offers a long life.
- ▶ The infinitely variable feed allows the exact dosing and thus ensures easy handling.
- ▶ For use on shuttle cartridges with 345, 360 and 390 ml content, multibond cartridges with 300 ml content and standard silicone cartridges.
- ▶ *AM E specs may vary from AM*

Description/Size	Product
FIS AM	
FIS AM E	

Manual Dispenser



- ▶ The ergonomic design enables fast and effortless installation.
- ▶ The optimized geometry of the manual dispenser ensures the quick inserting and removing of the cartridges.
- ▶ The fiberglass-reinforced plastic housing gives the manual dispenser maximum stability and increases its service life.
- ▶ The manual dispenser FIS DM S Pro can be used with the cartridge sizes 150 ml, 300 ml, 360 ml and 390 ml.

Description/Size	Product
DMS S Pro	


FBN II
Bolt Anchor


- ▶ The standard anchorage depth achieves the maximum load-bearing capacities.
- ▶ The reduced anchorage depth reduces the drill hole depth. This minimises the amount of time needed for installation whilst increasing flexibility.
- ▶ Additional short version „K“ with short anchoring depth.
- ▶ The long thread balances component tolerances and allows for stand-off installations, thus increasing flexibility.
- ▶ Few hammer blows and the minimal torque slippage allow for a noticeably simpler installation.
- ▶ Drive-in pin protects thread from damage, ensuring a faster installation and dismantling of the attachment.

Description/Size	Length/mm	Hold/mm	Packed
6 mm E/G	55	10	100
6 mm E/G	75	30	100
8 mm K E/G	56	5	50
8 mm E/G	71	10	50
8 mm E/G	91	30	50
10 mm K E/G	71	5	50
10 mm E/G	86	10	50
10 mm E/G	96	20	50
10 mm E/G	106	30	50
10 mm E/G	126	50	20
10 mm E/G	216	140	20
12 mm K E/G	86	5	20
12 mm E/G	106	10	20
12 mm E/G	126	30	20
12 mm E/G	146	50	20
12 mm E/G	196	100	20
16 mm K E/G	120	15	10
16 mm E/G	145	25	10
16 mm E/G	170	50	10
16 mm E/G	320	200	10
20 mm K E/G	141	10	10
20 mm E/G	184	30	10
20 mm E/G	277	120	10
6 mm A4	55	10	100
6 mm A4	75	30	100
8 mm A4	71	10	50
8 mm A4	91	30	50
10 mm A4	86	10	50
10 mm A4	96	20	50
10 mm A4	126	50	20
12 mm A4	106	10	20
12 mm A4	126	30	20
16 mm K A4	120	10	10
16 mm A4	145	25	10
16 mm A4	170	50	10
20 mm A4	187	30	10


ULTRACUT FBS II
Concrete Screw


- ▶ Unique saw-tooth geometry cuts quickly into the concrete - also in multiple use and reinforced concrete.
- ▶ The performance categories seismic C1 and C2 ensure that the strictest of safety standards and earthquake specifications can be fulfilled.
- ▶ For the zinc-plated steel version the checking gauge allows for reuse covered by the approval.
- ▶ Recommended for push-through installation.
- ▶ Drill holes do not need to be cleaned during vertical installation (ceiling and floor). For floor fixings the hole must be drilled 3x drill hole diameter deeper.
- ▶ The approved adjustment allows the screw to be unscrewed twice for a total length of 20 mm, to place maximum 10 mm packing below the base plates or to align the attached part, and then to tighten the screw again.

Description/Size	Drive	Packed
8 x 70 20/5 US TX	TX40/13Hex	50
8 x 80 30/15 US TX	TX40/13Hex	50
8 x 90 40/25 US TX	TX40/13Hex	50
8 x 110 60/45 US TX	TX40/13Hex	50
10 x 70 15/5/- US	16 Hex	50
10 x 90 35/25/5 US	16 Hex	50
10 x 100 45/35/15 US	16 Hex	50
10 x 120 65/55/35 US	16 Hex	50
12 x 85 25/10/- US	17 Hex	20
12 x 110 50/35/10 US	17 Hex	20
12 x 130 70/55/30 US	17 Hex	20
12 x 150 90/75/50 US	17 Hex	20
14 x 100 35/15/- US	21 Hex	20

FBS
Concrete Screw


- ▶ The concrete screw has been approved for the multiple fixing of non-load-bearing systems, and as such is ideal for fixing pipelines, cable conduits etc.
- ▶ The FBS can be set and installed in one go, thereby saving on installation time.
- ▶ Head shapes allows for the fixing of wide-ranging attachments and for the ideal adaptation to suit the intended use.

Description/Size	Drive	Packed
5 x 60/5 P	TX30	100
6 x 80/25 P	TX30	100
6 x 55 M8/19	Male Thread	100



FFS

Window Frame Screw



- ▶ Screw installation without plug for economical processing.
- ▶ The small drill bit diameter of 6 mm allows for efficient series installation.
- ▶ The continuous thread ensures a stress-free fixing of the frame in the substrate.
- ▶ The high-low-thread at the screw tip as well as several cutting notches reduce the amount of force required for screwing in the screws. The installation process can be completed without excessive effort.
- ▶ With two head types applicable for all common frame materials.
- ▶ According to the ift Rosenheim suitable for the fixation of a plastic window in brick masonry.

Description/Size	Packed
FFS 7,5 x 62 T30	100
FFS 7,5 x 72 T30	100
FFS 7,5 x 82 T30	100
FFS 7,5 x 92 T30	100
FFS 7,5 x 102 T30	100
FFS 7,5 x 112 T30	100
FFS 7,5 x 122 T30	100
FFS 7,5 x 132 T30	100
FFS 7,5 x 152 T30	100

FFSZ

Window Frame Screw



- ▶ Screw installation without plug for economical processing.
- ▶ The small drill bit diameter of 6 mm allows for efficient series installation.
- ▶ The continuous thread ensures a stress-free fixing of the frame in the substrate.
- ▶ The high-low-thread at the screw tip as well as several cutting notches reduce the amount of force required for screwing in the screws. The installation process can be completed without excessive effort.
- ▶ With two head types applicable for all common frame materials.
- ▶ According to the ift Rosenheim suitable for the fixation of a plastic window in brick masonry.

Description/Size	Packed
FFSZ 7,5 x 82 T30	100
FFSZ 7,5 x 92 T30	100
FFSZ 7,5 x 102 T30	100
FFSZ 7,5 x 122 T30	100



N

Hammerfix



- ▶ The rapid hammer-set installation reduces the amount of time required and allows for an economic series installation.
- ▶ The integrated hammer-in stop prevents the plug from expanding prematurely (jamming), thus enabling a problem-free installation.
- ▶ Together with the cross-slot recess, the thread of the nail screw allows the screw to be removed, thus allowing for subsequent dismantling.
- ▶ The wide range of diameters, usage lengths and head shapes provides the correct plug for every fixing.

F = Cylindrical head and 'washer'

P = Mushroom head

M6 = Connecting thread

S = Countersunk

S D = A2 + Isolating washer.

Description/Size	Length/mm	Hold/mm	Packed
5 mm F	25	1	100
5 mm F	30	5	100
5 mm F	40	15	100
6 mm F	40	10	100
6 mm F	60	30	100
6 mm F	80	50	100
8 mm F	60	20	100
8 mm F	80	40	100
8 mm F	100	60	100
8 mm F	120	80	100
5 mm F Bulk	40	15	2000
6 mm F Bulk	40	10	1600
6 mm F Bulk	60	30	1000
Description/Size	Length/mm	Hold/mm	Packed
5 mm S	40	15	100
5 mm S	50	25	100
6 mm S	40	10	50
6 mm S	60	30	50
6 mm S	80	50	50
8 mm S	60	20	50
8 mm S	80	40	50
8 mm S	100	60	50
8 mm S	120	80	50
10 mm S	100	50	50
10 mm S	135	85	50
10 mm S	160	110	50
6 mm S Bulk	60	30	1200
Description/Size	Length/mm	Hold/mm	Packed
5 mm S A2	36	5	100
6 mm S A2	42	10	50
6 mm S A2	55	30	50
8 mm S A2	57	20	50
8 mm S A2	75	40	50
8 mm S A2	100	60	50
Description/Size	Length/mm	Hold/mm	Packed
5 mm P	30	5	100
6 mm P	40	7	50
Description/Size	Length/mm	Hold/mm	Packed
6 mm S D A2	60	10	50
Description/Size	Length/mm	Hold/mm	Packed
8 mm M6	40	10	50

UZN

Zinc Nail Plug



- ▶ High temperature resistant all metal version made of zinc grade Z410.

Description/Size	Length/mm	Packed
5 mm	22	100
6 mm	30	100
6 mm	50	100



SXR

Nylon Frame Fixing



- ▶ The special functioning allows for use in solid and hollow building materials with an anchorage depth of just 50 mm, ensuring an economical fixing.
- ▶ The ETA approval covers use in a range of solid and hollow building materials, and guarantees a secure fixing.
- ▶ The specially developed combination of plugs and screws ensures the very best handling. The plug has a noticeable hold, making installation more convenient.

Description/Size	Length/mm	Drive	Packed
8 mm T	60	TX30	50
8 mm T	80	TX30	50
8 mm T	100	TX30	50
8 mm T	120	TX30	50
10 mm T	80	TX40	50
10 mm T	100	TX40	50
10 mm T	120	TX40	50
10 mm T	140	TX40	50
10 mm T	160	TX40	50
10 mm F US	60	X40/13Hex	50
10 mm F US	80	X40/13Hex	50
10 mm F US	100	X40/13Hex	50
10 mm F US	120	X40/13Hex	50
8 x 60	(Plug only)	-	100

SXRL

Nylon Frame Fixing



- ▶ Long expansion with multiple anchorage depths of 50, 70 or 90 mm makes the SXRL a versatile applicable product.
- ▶ Through the special geometry of the plug, the loads are evenly distributed in the drill hole.
- ▶ The approval for single-point fixing in cracked concrete makes the SXRL the designated specialist in concrete, particularly for tasks such as the installation of awning roofs and outdoor railings compared to steel anchors.
- ▶ SXRL-T with countersunk head screw is recommended for the installation of timber constructions.
- ▶ Use SXRL-FUS with wide sleeve rim and moulded washer on the screw in the case of metal constructions.

Description/Size	Length/mm	Drive	Packed
10 mm T	80	TX40	50
10 mm T	100	TX40	50
10 mm T	120	TX40	50
10 mm T	140	TX40	50
10 mm T	160	TX40	50
10 mm F US	80	X40/13Hex	50
10 mm F US	100	X40/13Hex	50
10 mm F US	120	X40/13Hex	50
10 mm F US	140	X40/13Hex	50

FUR

Nylon Frame Fixing



- ▶ The universal operating principle with an anchorage depth of 70 mm and unique asymmetrical teeth, makes it an assembly-friendly anchor even in an unknown base material. As such, the FUR is the right choice for projects with an unknown base material, ensuring a secure fixing at all times.
- ▶ Slim geometry guarantees a simple installation, even in cases involving thick wooden fixtures and narrow drill holes.

Description/Size	Length/mm	Drive	Packed
8 mm T	100	T30	50
10 mm T	80	T40	50
10 mm T	115	T40	50

F-M

Metal Frame Fixing



- ▶ The F-M metal frame plug achieves fire resistance F 120. This allows for use in areas where fire resistance is relevant.
- ▶ The operating principle prevents the window frame from being pulled against the substrate, and ensures a stress-free and long-lasting fixing of the frame.
- ▶ The special plug geometry anchors the metal and plastic profiles against compressive and tensile loads, and allows for a secure hold of the window frame.

Description/Size	Length/mm	Drive	Packed
8 mm	92	PZ2	100
8 mm	112	PZ2	100
10 mm	72	PZ3	100
10 mm	92	PZ3	100
10 mm	112	PZ3	100
10 mm	132	PZ3	100
10 mm	152	PZ3	100
10 mm	182	PZ3	50



HM

Metal Cavity Fixing



- ▶ Due to the extensive range, the HM is suitable for board building materials with a thickness of 3-50 mm and thus suitable for a number of different applications.
- ▶ Metric internal thread allows attachment to be removed and refitted several times, offering the best possible flexibility.
- ▶ The HM's expanding arms ensure a large supporting surface, thus allowing a high load-bearing capacity.
- ▶ The claws around the edge of the fixing penetrate the board building material, preventing the fixing from rotating, thus ensuring a secure installation.

Description/Size	Panel Thickness (mm)	Drill Ø (mm)	Packed
4 x 32 S	3 - 13	8	50
4 x 45 S	16 - 23	8	50
4 x 60 S	31 - 40	8	50
5 x 37 S	6 - 15	10	50
5 x 52 S	7 - 21	10	50
5 x 65 S	20 - 34	10	50
6 x 37 S	6 - 15	12	50
6 x 52 S	7 - 21	12	50
6 x 65 S	17 - 34	12	50
6 x 80 S	32 - 50	12	50
8 x 54 SS (Hex)	7 - 21	12	50
4 x 32 H (Hook)	3 - 13	8	50
5 x 65 H (Hook)	20 - 34	10	50



HM

Metal Cavity Fixing



- ▶ Due to the extensive range, the HM is suitable for board building materials with a thickness of 3-50 mm and thus suitable for a number of different applications.
- ▶ Metric internal thread allows attachment to be removed and refitted several times, offering the best possible flexibility.
- ▶ The HM's expanding arms ensure a large supporting surface, thus allowing a high load-bearing capacity.
- ▶ The claws around the edge of the fixing penetrate the board building material, preventing the fixing from rotating, thus ensuring a secure installation.

Description/Size	Panel Thickness (mm)	Drill Ø (mm)	Packed
4 x 32 S	3 - 13	8	50
4 x 45 S	16 - 23	8	50
4 x 60 S	31 - 40	8	50
5 x 37 S	6 - 15	10	50
5 x 52 S	7 - 21	10	50
5 x 65 S	20 - 34	10	50
6 x 37 S	6 - 15	12	50
6 x 52 S	7 - 21	12	50
6 x 65 S	17 - 34	12	50
6 x 80 S	32 - 50	12	50
8 x 54 SS (Hex)	7 - 21	12	50
4 x 32 H (Hook)	3 - 13	8	50
5 x 65 H (Hook)	20 - 34	10	50


PD
Nylon Board Fixing


- ▶ Operating principle allows for use in various board thicknesses, incl. in low cavity depths, providing great flexibility.
- ▶ Special fixing geometry with a nylon cone ensures a high tightening torque that can be identified immediately, offering a high level of installation safety.
- ▶ Longitudinal ribs prevent the fixing from rotating in the drill hole, thus allowing for a reliable installation.
- ▶ Can be used with the most wide-ranging screws, hooks and eye screws, allowing for a broad range of applications.

Description/Size	Packed with:	Packed
PD 8	-	100
PD 8 S	Chipboard Screw	50
PD 10	-	100
PD 10 S	Chipboard Screw	50
PD 12	-	50
PD 12 S	Chipboard Screw	25

HDF
Nylon Board Fixing


- ▶ The drywall specialist. Produced from high-quality polyamide, making it very elastic and age-resistant.

Description/Size	Length (mm)	Drill Ø (mm)	Packed
HDF	38	10	100

GPF
Nylon Board Fixing


Description/Size	Length (mm)	Drill Ø (mm)	Packed
GPF	35	6	100

FU
Nylon Universal Plug


- ▶ Firm hold in almost all building materials.
- ▶ Expansion of breaks with boards and hollow building materials.
- ▶ Collar prevents falling from occurring.
- ▶ Anti-rotation lock against rotation.
- ▶ Use of wood and chipboard screws.

Description/Size	Packed with:	Packed
6 x 35 mm	-	50
8 x 50 mm	-	50
6 x 35 mm S/10	Screws	25
8 x 50 mm S/10	Screws	25
10 x 60 mm S/20	Screws	10

DUOTEC
Nylon Toggle


- ▶ Flexible screw mount allows for the use of screws and hooks with different thread shapes.
- ▶ Glass fibre-reinforced plastics and a metal skeleton insert (fischer DUOTEC 12) allow the toggle to handle heavy tensile and transverse loads in all panel building materials.
- ▶ Soft grey nylon contact surface distributes the load over the panel surface, thereby minimising weakening of the supporting building material.
- ▶ White flush sleeve with snap function allows the plug to be pre-installed quickly and securely in the drill hole.
- ▶ With scale on the grip strap (fischer DUOTEC 12) for determining the required screw length (scale value + 20 mm).

Description/Size	Packed with:	Packed
10 mm	-	25
12 mm	Chipboard Screw	10
10 mm	-	25
12 mm	Chipboard Screw	10

K 54
Nylon Toggle


- ▶ High load capacity due to good load distribution on the transition beams.
- ▶ Drill hole diameter only 10 mm.
- ▶ Use of standard wood and chipboard screws.
- ▶ Suitable for pre-positioned installation.

Description/Size	Drill Ø (mm)	Packed
K 54 Nylon	10	25



UX

Nylon Plug



- ▶ The universal operating principle (knotting or expanding) allows for use in all solid, hollow and board building materials. Thus the UX is the correct choice for unknown base materials.
- ▶ The UX's angled connection ridges allow for optimum screw guidance. Serrated anti-rotation locks prevent rotation in the drill hole. This guarantees the greatest possible installation safety.
- ▶ Fixing sets with screws, eye screws and hooks provide the right solution for all applications.
- ▶ UX R - With Collar, UX - Without Collar.

Description/Size	Length/mm	Packed
5 mm R	30	100
6 mm R	35	100
8 mm R	50	100
10 mm R	60	50
10 mm	60	50
12 mm	70	25
14 mm	70	20



- ▶ Produced with at least 50% renewable raw materials and therefore particularly environmentally friendly.
- ▶ Just as effective, secure and durable as regular UX plugs.

Description/Size	Length/mm	Packed
6 mm	35	40
8 mm	50	40
10 mm	60	20

S

Nylon Plug



- ▶ The rimless plug sleeve allows for the plug to be set as deep as required below the plaster to the bearing substrate to achieve the maximum load-bearing capacity.
- ▶ As the plug only expands in two directions, it is possible to direct the expansion forces so that they run parallel to the edge of the building material by turning the plug. This allows for smaller edge distances.
- ▶ The slimline plug geometry makes it easy to push the plug into the drill hole for a fast and simple installation.
- ▶ The anti-rotation lock prevents the plug rotating in the drill hole, thus guaranteeing a high level of installation safety.
- ▶ **BULK sold in full box quantities only - boxes can't be broken.**

Description/Size	Length/mm	Packed
4 mm	20	200
5 mm	25	100
6 mm	30	100
7 mm	30	100
8 mm	40	100
10 mm	50	50
12 mm	60	25
14 mm	75	20
16 mm	80	10
20 mm	90	5
5 mm Bulk	25	10000
6 mm Bulk	30	10000
8 mm Bulk	40	5000
10 mm Bulk	50	2500
12 mm Bulk	60	1500
14 mm Bulk	75	750

M-S

Nylon Plug



- ▶ The internal geometry of the M-S allows for the use of standard metric screws or threaded rods for the ideal adaptation to suit the intended use.
- ▶ The rimless plug sleeve allows for the plug to be set as deep as required below the plaster to the bearing substrate to achieve the maximum load-bearing capacity.
- ▶ As the plug only expands in two directions, it is possible to direct the expansion forces so that they run parallel to the edge of the building material by turning the plug. This allows for smaller edge distances.
- ▶ The slimline plug geometry makes it easy to push the plug into the drill hole, for a fast and simple installation.

Description/Size	Length/mm	Packed
6 mm	40	100
8 mm	50	50
10 mm	70	20



DUOPOWER

Nylon Plug



- ▶ Two component materials for top load values and intelligent functioning (expansion, folding, knotting), depending on building material - solid, perforated or panel material.
- ▶ Great feedback (feel-good-factor) of the plug. You can feel exactly when the plug is installed perfectly.
- ▶ The narrow plug rim prevents slipping into the drill hole.
- ▶ Serrated anti-rotation feature interlock in the building material and prevents rotation in the drill hole during installation.
- ▶ The greater anchorage depth of the 6 x 50, 8 x 65 and 10 x 80 means that the plug is especially suited to fixings in hollow building materials, aerated concrete and to bridge plaster.
- ▶ **BULK sold in full box quantities only - boxes can't be broken.**

Description/Size	Length/mm	Packed
5 mm	25	100
6 mm	30	100
8 mm	40	100
10 mm	50	50
12 mm	60	25
14 mm	70	20
5 mm Bulk	25	10000
6 mm Bulk	30	10000
8 mm Bulk	40	5000
10 mm Bulk	50	2000
12 mm Bulk	60	16000
14 mm Bulk	70	9000



Description/Size	Packed with screw:	Packed
5 mm	CBS (PZ2) 3,5 x 35 mm	50
6 mm	CBS (PZ2) 4,5 x 40 mm	50
8 mm	CBS (PZ2) 5 x 60 mm	50
10 mm	HEX13 & TX40 7 x 69 mm	25
12 mm	HEX13 drive 8 x 80 mm	10
6 mm	CBS (PZ2) 4,5 x 60 mm	50
8 mm	CBS (PZ2) 5 x 80 mm	25
10 mm	HEX13 drive 7 x 107 mm	10

SX Plus

Nylon Plug



- ▶ 4-way expansion for high load values.
- ▶ Fixing blades for screw fixation and flexible mounting.
- ▶ Installation of the plug possible with little effort.
- ▶ Plug edge prevents slipping deeper into the drill hole.
- ▶ Noticeable tightening torque prevents overtightening of the screw.
- ▶ **BULK sold in full box quantities only - boxes can't be broken.**

Description/Size	Length/mm	Packed
4 mm	20	200
5 mm	25	100
6 mm	30	100
8 mm	40	100
10 mm	50	50
12 mm	60	25
14 mm	70	20
5 mm Bulk	25	10000
6 mm Bulk	30	10000
8 mm Bulk	40	4000
10 mm Bulk	50	2000
12 mm Bulk	60	12000
6 mm	50	100
8 mm	65	50
10 mm	80	25



Description/Size	Packed with screw:	Packed
6 mm	CBS 4,5 x 40	50
8 mm	CBS 5 x 55	50



KD

Spring Toggle



- ▶ High load capacity due to good load distribution on the transition beams.
- ▶ Simple assembly due to self-opening tension spring.
- ▶ High flexibility due to a long threaded rod. Use with various panel thicknesses and attachment thicknesses.
- ▶ Suitable for pre-positioned installation.
- ▶ H with hook.

Description/Size	Packed	Drill Ø (mm)
KD 3	50	12
KD 3 B	10	12
KDH 3	25	12
KD 4	25	14
KD 4 B	10	14
KDH 4	25	14

KD

Gravity Toggle



- ▶ High load capacity due to good load distribution on the transition beams.
- ▶ High flexibility due to a long threaded rod. Use with various panel thicknesses and attachment thicknesses.
- ▶ No installation tool necessary.
- ▶ H with hook.

Description/Size	Packed	Drill Ø (mm)
KD 5	25	16
KD 6	25	16
KDH 6	20	16
KD 8	20	20



BO

Boiler Fixing Set



- ▶ Complete fixing set with plug, flanged nut and screw.
- ▶ UX plug for use in all solid and hollow building materials. Pre-positioned and push-through installation possible.
- ▶ High-strength nylon that is resistant to ageing.

Description/Size	Drill Ø (mm)	Packed
BO 120	14	1

HK

Insulation Disc



- ▶ The fischer plastic insulation disc HK 36 is used in combination with a 5-mm screw.
- ▶ Lightweight insulation boards and films can be fixed with this in wood and wooden materials.
- ▶ The plastic disc can be used very flexibly.

Description/Size	Disc Ø (mm)	Packed
Polydisc White	36	100

ISO

Insulation Disc



- ▶ The fischer insulation disc ISO disc is used in combination with the fischer Hammerfix N or a fischer frame fixing.
- ▶ Pressure-resistant insulation boards can be fixed with this in all building materials.
- ▶ The optional selection of the appropriate fixing element offers the maximum flexibility for different applications.

Description/Size	Disc Ø (mm)	Packed
ISO 8/60 KS	60	100

DT

Insulation Disc



- ▶ Use in combination with the wall tie VB, Hammerfix N or frame fixings with 8 and 10 mm diameter.
- ▶ Soft and pressure-resistant insulation boards can be fixed with this in all building materials.
- ▶ Ideal addition for fixing insulation boards and insulation with low compressive strength.

Description/Size	Disc Ø (mm)	Packed
DT 90/8	90	250

DHK

Insulation Support



- ▶ Reduced drilling. Optimised geometry lowers anchorage depth.
- ▶ Simple Hammerset installation saves time and costs.
- ▶ When hammered, the ribs expand in the drill hole and the optimal pressure is applied to the DHK.
- ▶ Flexible pins in the plate area adapt to the insulating material, and ensure a sustained contact pressure.

Description/Size	Length (mm)	Drill Ø (mm)	Packed
DHK 45/40	65	8	250
DHK 45/60	85	8	250
DHK 45/80	105	8	250
DHK 45/100	125	8	250

DHK

Insulation Support



- ▶ Reduced drilling. Optimised geometry lowers anchorage depth.
- ▶ Permanent pressure due to flexible pins in the disc area.
- ▶ Simple Hammerset installation saves time and costs.
- ▶ The colouring means that it does not stand out on black clad insulating material.

Description/Size	Length (mm)	Drill Ø (mm)	Packed
DHK 40	65	8	250
DHK 60	85	8	250
DHK 100	125	8	250

DHT S

Retaining Disc



- ▶ Time-saving installation, no pre-drilling.
- ▶ No marks on the plug surface. The plug reduces heat transmission.
- ▶ The thin disc construction makes it possible for thin layers of plaster and reinforcements to be used.
- ▶ Made of high-quality nylon.

Description/Size	Length (mm)	Packed
S 70 W	65	500
S 100 W	100	500



WB 5N

WC Fixing Set



- ▶ Complete fixing set with plug, screw and cover cap.
- ▶ The mounting bracket WB5 N with pre-drilled rows of holes enables flexible fixing in both directions and compensates for height differences in ceramics.
- ▶ Corrosion resistance thanks to stainless steel screw.
- ▶ Pronounced rim of the fixing ring prevents direct contact between ceramics and screw, protecting the ceramics.
- ▶ Plugs, mounting brackets, flush sleeves and cover caps are made from high-strength, ageing-resistant nylon material.

Description/Size	Drill Ø (mm)	Packed
WB 5N	10	1

WB 9N

Wall-mount WC Fixing Set



- ▶ Small number of components.
- ▶ Possible pre-installation in sanitary areas.
- ▶ Flexible towards different sanitary models.
- ▶ Only one plastic part in contact with ceramic.
- ▶ Hidden fixation, design of ceramic shape is not influenced.

Description/Size	Drill Ø (mm)	Packed
WB 9N	-	1

WL

Wash Basin & Urinal Fixing Set



- ▶ The fischer fixing set WL contains all elements for the safe and fast fixing of sanitary system cantilevers to the wall.
- ▶ 2 plugs made from high-quality nylon, 2 zinc-plated wood screws with hexagonal head and 2 zinc-plated washers.
- ▶ The rimless plug allows for the plug to be set as deep as required below the plaster to the bearing substrate to achieve the maximum load-bearing capacity.

Description/Size	Length (mm)	Drill Ø (mm)	Packed
WL 7	60	10	1
WL 8	70	10	1
WL 10	80	12	1

WD

Wash Basin & Urinal Fixing Set



- ▶ Complete fixing set with plug, stud screw and flanged nut.
- ▶ Flanged nut with collar prevents direct contact between ceramics and screw, protecting the ceramics from damage.
- ▶ UX plug for fixings in all solid and hollow building materials. Pre-positioned and push-through installation possible.
- ▶ High-strength nylon that is resistant to ageing.

Description/Size	Length (mm)	Drill Ø (mm)	Packed
WD 8	110	10	1
WD 10	120	14	1

WST

Wash Basin Fixing Set



- ▶ Complete fixing set with plug, stud screw, flush sleeve and nut.
- ▶ Flush sleeve with collar prevents direct contact between ceramics and screw, protecting the ceramics from damage.
- ▶ DuoPower plug for fixings in all solid and hollow building materials.
- ▶ High-strength nylon that is resistant to ageing.
- ▶ Adjustable flush sleeve for precise height adjustment of ceramics.

Description/Size	Length (mm)	Drill Ø (mm)	Packed
WST 10	140	12	1

S-RD

Ceramic Fixing Set



- ▶ Complete fixing set with plug, screw and cover cap.
- ▶ Long plug with shaft prevents contact between ceramics and screw, which protects the ceramics from damage.
- ▶ Corrosion resistance thanks to stainless steel screw.
- ▶ Contains white and chrome cover caps.
- ▶ Set for push-through installation.

Description/Size	Drill Ø (mm)	Packed
S 8 RD 80 WCR	-	1


SF plus LS
ClipFix Power Strap


- ▶ Saves on installation time: Combined anchor, screw, and clamp.
- ▶ One-handed installation makes overhead installations easier.
- ▶ High retention forces due to a locking catch.
- ▶ Space-saving installation due to slimline geometry.

Description/Size	Drill Ø (mm)	Packed
LS 3/13	6	100
LS 8/28	6	100
LS 20/40	6	100

SF plus ZS
ClipFix Twin Clamp


- ▶ Saves on installation time: Combined anchor, screw, and clamp.
- ▶ One-handed installation makes overhead installations easier.
- ▶ High retention forces due to a locking catch.
- ▶ Space-saving installation due to slimline geometry.

Description/Size	Drill Ø (mm)	Packed
ZS 10	6	100

FGRS+
Hinged Pipe Clamp


- ▶ The screw's combination cross-drive thread allows flexibility during the installation process.
- ▶ The compact construction of the pipe clamp enables a simple post-installation insulation.

Description/Size	Packed
45-50 mm	50
50-55 mm	50

FGRS
Universal Hinged Pipe Clamp


- ▶ Full, seamless diameter clamping range for fastening any size of pipe.
- ▶ Quick closure with full edge for secure, convenient assembly.
- ▶ Pipe clamp with embossed beads on the edge for a firm hold and simple pipe adjustment.
- ▶ Combination Torx-slotted thread for added assembly flexibility.
- ▶ With sound protection test report for objectively tested functional safety.

Description/Size	Packed
FGRS 16-19	25
FGRS 20-24	25
FGRS 25-30	25
FGRS 31-37	25
FGRS 53-59	25
FGRS 60-66	10

FRS-L
Universal Pipe Clamp


- ▶ Profiled clamp band for outstanding rigidity and stability.
- ▶ Optimised hold between sound insulation insert and clamp band.
- ▶ Combination thread M8/M10 for flexible connection options.
- ▶ Loss-secured screws.
- ▶ Fire protection test R120.
- ▶ MLAR R30 sample cable system test.

Description/Size	Packed
FRS-L 60-66	10
FRS-L 67-75	10
FRS-L 76-84	10
FRS-L 85-93	10
FRS-L 101-110	10
FRS-L 110-119	10



AM

Spacing Clamp



- ▶ High flexibility: Assembly with fischer nail anchor FNA II or Hammerfix N 6.
- ▶ Fast installation due to fast-locking latch.
- ▶ Pre-assembled combination screw with slot or cross-slot recess.

Description/Size	Packed
AM 8	50
AM 10	50
AM 12	50
AM 16	50
AM 20	50
AM 22	50
AM 26	50
AM 28	50
AM 32	25
AM 40	15
AM 50	10
AM 63	10

TKL

Clamp Hanger



- ▶ The TKL design with its clamping screw allows for fixing to steel girders without the need for welding and drilling.
- ▶ The design of the clamping screw prevents it from slipping from the steel girder.
- ▶ VdS/FM/UL certificates guaranty independently tested safety.
- ▶ The solid design guarantees a high load-bearing capacity.
- ▶ Locking screw guarantees quick and easy installation.

Description/Size	Packed
M8	50
M10	50
Ø11	50
M12	50



Hexagon Nuts



- ▶ Hexagon nut for use with bolts and threaded rods.
- ▶ Available in different grades and materials.
- ▶ Suitable for general engineering and construction applications.

Description/Size	Grade	Packed
M5 E/G	EN8	100
M6 E/G	EN8	100
M8 E/G	EN8	100
M10 E/G	EN8	100
M12 E/G	EN8	100
M16 E/G	EN8	100
M20 E/G	EN8	100
M6 A2	304	100
M8 A2	304	100
M10 A2	304	100
M12 A2	304	100
M16 A2	304	100
M20 A2	304	100
M8 A4	316	100
M10 A4	316	100
M12 A4	316	100
M16 A4	316	100
M20 A4	316	100

Flat Washers



- ▶ Used to distribute the load of a fastener.
- ▶ Suitable for general purpose applications.
- ▶ Available in mild steel, stainless steel (A2) and (A4).

Description/Size	Grade	Packed
M5 E/G	Mild Steel	100
M6 E/G	Mild Steel	100
M8 E/G	Mild Steel	100
M10 E/G	Mild Steel	100
M12 E/G	Mild Steel	100
M16 E/G	Mild Steel	100
M20 E/G	Mild Steel	100
M6 A2	304	100
M8 A2	304	100
M10 A2	304	100
M12 A2	304	100
M16 A2	304	100
M20 A2	304	100
M8 A4	316	100
M10 A4	316	100
M12 A4	316	100
M16 A4	316	100
M20 A4	316	100

Blind Rivets



- ▶ Mainly used in applications where there is no access to the rear (blind side) of the joint.
- ▶ Two-piece construction; aluminium rivet body and steel mandrel.
- ▶ Suitable for a wide range of materials.

Description/Size	Length/mm	Packed
3.2 mm	6	500
3.2 mm	8	500
3.2 mm	10	500
3.2 mm	12	500
3.2 mm	15	500
3.2 mm	18	500
4.0 mm	6	500
4.0 mm	8	500
4.0 mm	10	500
4.0 mm	12	500
4.0 mm	15	500
4.0 mm	18	500
4.8 mm	6	500
4.8 mm	8	500
4.8 mm	10	500
4.8 mm	12	500
4.8 mm	15	500
4.8 mm	18	500



Coach Screw



- ▶ Heavy-duty screw with a hexagonal head and an externally threaded cylindrical shaft that tapers to a point at the tip
- ▶ For use with nylon plugs or for holding together heavy timber and fixing metal to timber.
- ▶ Hexagonal head for installation with a wrench, spanner or socket.
- ▶ Electroplated with a clear passivation.

Description/Size	Length/mm	Packed
6 mm	50	100
6 mm	60	100
6 mm	75	100
6 mm	100	100
8 mm	50	100
8 mm	60	100
8 mm	75	100
8 mm	90	100
8 mm	100	100
10 mm	60	100
10 mm	75	100
10 mm	90	100
12 mm	90	50

Threaded Rod



- ▶ Various material options.
- ▶ Available in 1 and 3 m lengths.
- ▶ EN8 and 304 suitable for use with chemical mortar.

Description/Size	Grade	Length
6 mm x 1 m	E/G	1 m
8 mm x 1 m	E/G	1 m
10 mm x 1 m	E/G	1 m
12 mm x 1 m	E/G	1 m
16 mm x 1 m	E/G	1 m
20 mm x 1 m	E/G	1 m
8 mm x 1 m	EN8	1 m
10 mm x 1 m	EN8	1 m
12 mm x 1 m	EN8	1 m
16 mm x 1 m	EN8	1 m
20 mm x 1 m	EN8	1 m
8 mm x 1 m	304	1 m
10 mm x 1 m	304	1 m
12 mm x 1 m	304	1 m
16 mm x 1 m	304	1 m
20 mm x 1 m	304	1 m
6 mm x 3 m	E/G	3 m
8 mm x 3 m	E/G	3 m
10 mm x 3 m	E/G	3 m
12 mm x 3 m	E/G	3 m
16 mm x 3 m	E/G	3 m
20 mm x 3 m	E/G	3 m
8 mm x 3 m	304	3 m
10 mm x 3 m	304	3 m
12 mm x 3 m	304	3 m
16 mm x 3 m	304	3 m
20 mm x 3 m	304	3 m

Thread Connector



- ▶ Hexagon connector allows threaded rods to be extended in a simple manner.
- ▶ Corrosion protection suitable for application in wet areas due to galvanisation.
- ▶ For use in dry interior areas.

Description/Size	Packed
M6 Connectors	100
M8 Connectors	100
M10 Connectors	50
M12 Connectors	50
M16 Connectors	25



FPF II

PowerFast Chipboard Screw



- ▶ Blue passivated zinc plating screw with a countersunk head.
- ▶ Torx drive guarantees top force transmission & max bit stability for flush screwing operations.
- ▶ Ideal for fixing general wood connections, plankings, corning, as well as door and metal fittings.
- ▶ The integrated thread ensures optimum force transmission.
- ▶ Priced per 100, but sold in full boxed quantities only.

Description/Size	Thread	Drive	Packed
4,0 x 30 mm	Full	TX20	200
4,0 x 40 mm	Partial	TX20	200
4,0 x 50 mm	Partial	TX20	200
5,0 x 50 mm	Partial	TX20	200
5,0 x 70 mm	Partial	TX20	200

FPF

PowerFast Chipboard Screw



- ▶ Blue zinc plated.
- ▶ Countersunk head with torx drive.
- ▶ High performance wax.
- ▶ Priced per 100, but sold in full boxed quantities only.

Description/Size	Thread	Drive	Packed
3,5 x 25 mm	Full	TX10	200
3,5 x 30 mm	Full	TX10	200
3,5 x 45 mm	Partial	TX10	200
4,0 x 16 mm	Full	TX20	200
6,0 x 180 mm	Partial	TX30	100
8,0 x 160 mm	Partial	TX40	75

FPF

A2 PowerFast Chipboard Screw



- ▶ Stainless steel A2.
- ▶ Countersunk head with torx drive.
- ▶ High performance wax.
- ▶ Priced per 100, but sold in full boxed quantities only.

Description/Size	Thread	Drive	Packed
3,5 x 25 mm	Full	TX10	100
3,5 x 30 mm	Full	TX10	100
4,0 x 30 mm	Full	TX20	200
4,0 x 40 mm	Partial	TX20	200
4,0 x 50 mm	Partial	TX20	200
5,0 x 50 mm	Partial	TX20	200
5,0 x 60 mm	Partial	TX20	100
5,0 x 70 mm	Partial	TX20	100

FSP II

Classic Fast Chipboard Screw



- ▶ The countersunk head ensures an attractive surface appearance.
- ▶ The partial thread creates a contraction effect on the wooden parts to be joined due to the longer thread.
- ▶ The full thread offers an increased pull-out resistance.
- ▶ Smooth gliding coating reduces the screwing effort.
- ▶ Priced per 100, but sold in full boxed quantities only.

Description/Size	Thread	Drive	Packed
3,0 x 16 mm	Full	PZ1	1000
3,0 x 30 mm	Full	PZ1	1000
3,5 x 16 mm	Full	PZ2	1000
3,5 x 30 mm	Full	PZ2	1000
3,5 x 40 mm	Partial	PZ2	1000
4,0 x 16 mm	Full	PZ2	1000
4,0 x 25 mm	Full	PZ2	1000
4,0 x 30 mm	Full	PZ2	1000
4,0 x 40 mm	Partial	PZ2	500
4,0 x 50 mm	Partial	PZ2	200
4,0 x 70 mm	Partial	PZ2	200
4,5 x 50 mm	Partial	PZ2	500
5,0 x 50 mm	Partial	PZ2	200
5,0 x 70 mm	Partial	PZ2	200
5,0 x 100 mm	Partial	PZ2	100



FSP

Classic Fast Chipboard Screw



- ▶ Blue zinc plated.
- ▶ Countersunk head with Pozi drive.
- ▶ Waxed.
- ▶ Priced per 100, but sold in full boxed quantities only.

Description/Size	Thread	Drive	Packed
3,0 x 20 mm	Full	PZ1	1000
3,5 x 16 mm	Full	PZ2	1000
3,5 x 20 mm	Full	PZ2	1000
3,5 x 25 mm	Full	PZ2	1000
4,0 x 20 mm	Full	PZ2	1000

FTS-ST

Stainless Steel Chipboard Screw



- ▶ Stainless steel A2.
- ▶ Slim countersunk head.
- ▶ TX-Star recess.
- ▶ High performance wax.
- ▶ Priced per 100, but sold in full boxed quantities only.

Description/Size	Thread	Drive	Packed
5,0 x 50 mm	Partial	TX20	200
5,0 x 60 mm	Partial	TX20	150
5,0 x 70 mm	Partial	TX20	100
5,0 x 80 mm	Partial	TX20	100

FSN-TPD

Drywall Screw



- ▶ Phosphated.
- ▶ Bugle head, Phillips recess.
- ▶ Fine thread
- ▶ Priced per 100, but sold in full boxed quantities only.

Description/Size	Drive	Packed
3,5 x 25 mm	PH2	1000
3,5 x 41 mm	PH2	1000

Wafer Tek Screws



- ▶ Blue zinc plated.
- ▶ Flange head, PH recess.
- ▶ Full thread.
- ▶ For up to 2,0 mm thick metal profiles no pre-drilling.
- ▶ Priced per 100, but sold in full boxed quantities only.

Description/Size	Thread	Drive	Packed
8 x 13 mm American Wafer	-	PH2	1000
10 x 16 mm Wafer	Coarse	PH2	1000
10 x 16 mm Wafer	Fine	PH2	1000
10 x 22 mm Wafer	Coarse	PH2	1000
10 x 22 mm Wafer	Fine	PH2	1000

Tek Screws



- ▶ Features a pointed drill bit at the screw's tip.
- ▶ Screws drill their own pilot holes as you insert them.
- ▶ As you drill in the screw, it easily carves into a solid material surface and spins into place.
- ▶ 5/16 (1/4") hex drive.
- ▶ Priced per 100, but sold in full boxed quantities only.

Description/Size	Packed
12 x 20 mm	1000
12 x 25 mm	1000
12 x 40 mm	500
12 x 50 mm	500
12 x 60 mm	250
12 x 65 mm	250
12 x 75 mm	250
14 x 25 mm	500



Bonded Washers



- ▶ For use with roofing and cladding screws.
- ▶ Weatherproof seal helps prevent water ingress.
- ▶ Suitable for metal and timber applications.
- ▶ Creates a secure, long-lasting seal.

Description/Size	Packed
6 x 19 mm	500
6 x 26 mm	250
8 x 26 mm	250

Installation Sockets



- ▶ Magnetic socket for fast and secure installation.
- ▶ Suitable for use with compatible screws and fixings.
- ▶ Durable and reliable for professional use.
- ▶ Designed for a strong grip and easy bit changes.

Description/Size	Packed
5/16 Magnetic Socket (1/4")	-
10mm (3/8")	-

JOBBER

HSS-Rolled Drill Bit DIN 338



- › High concentricity.
- › 118° tip angle for better heat removal.
- › Type N spiral for optimum chip removal.

Description/Size	Length/mm
2,4mm	57
2,5mm	57
3,0mm	61
3,2mm	65
3,4mm	70
3,5mm	70
3,8mm	75
4,0mm	75
4,2mm	75
4,5mm	80
4,8mm	86
4,9mm	86
5,0mm	86
5,5mm	93
6,0mm	93
6,5mm	101
7,0mm	109
8,0mm	117
8,5mm	117
9,0mm	125
10,0mm	133
10,5mm	133
11,0mm	142
12,0mm	151
12,5mm	151
13,0mm	151
14,0mm Reduced	160
16,0mm Reduced	178
18,0mm Reduced	191
20,0mm Reduced	205

JOBBER

HSS-Ground Drill Bit DIN 338



- › Precision ground solid material for long service.
- › 135° split point for quick drilling progress.
- › Type N spiral for optimum chip removal.

Description/Size	Length/mm
3,0mm	61
3,2mm	65
3,5mm	70
4,0mm	75
4,5mm	80
5,0mm	86
6,0mm	93
8,0mm	117
10,0mm	133
12,0mm	151
13,0mm	151

SDS+ QUATTRIC II

Rotary Hammer Drill Bits



- 4 carbide cutting teeth in innovative Power Shoulder™ design, which causes micro-cracks in the material for faster removal of the debris
- Stable, self-centering tip, wear marks, rebar chamfers
- Up to 150 % higher lifetime in reinforcement than other rotary hammer drill bits
- Excellent resistance to high temperature
- Rapid drilling progress and longer lifetime due to new Multi-Value-Flute™ flute design
- Ø 5 – 10 mm Solid carbide head
- Ø 11 – 16 mm Single-piece carbide element
- Ø 18 – 32 mm Three-piece carbide element

Description/Size	Length/mm	Effective
5mm	115	50
5mm	165	100
6mm	115	50
6mm	165	100
6mm	215	150
8mm	115	50
8mm	165	100
8mm	215	150
10mm	115	50
10mm	165	100
10mm	215	150
10mm	455	400
12mm	160	100
12mm	210	150
12mm	260	200
12mm	450	400
12mm	1000	950
14mm	160	100
14mm	210	150
14mm	260	200
14mm	450	400
14mm	1000	950
16mm	160	100
16mm	210	150
16mm	320	250
16mm	450	400
16mm	1000	950
18mm	250	200
18mm	450	400
20mm	250	200
20mm	450	400
25mm	250	200
25mm	250	400
28mm	250	200
28mm	450	400
30mm	450	400
32mm	450	400

SDS+ POINTER II

Rotary Hammer Drill Bits



- Highest drilling speed, improved impact transfer
- Enlarged rebar chamfers reduce the likelihood of catching in case of reinforcement collisions
- Ideal for use with lightweight (battery-powered) rotary hammer drills
- Maximum fracture resistance
- Head: Speed 2-cutting, Power Breaker™ design, centering tip, patented rebar chamfers, PGM-tested carbide tips
- Varlo-KVS-flute, 2-fluted

Description/Size	Length/mm	Effective
4mm	110	50
5mm	110	50
5mm	160	100
5mm	210	150
5.5mm	110	50
5.5mm	160	100
6mm	110	50
6mm	160	100
6mm	210	150
6mm	260	200
6.5mm	160	100
7mm	110	50
7mm	160	100



SDS+ POINTER II

Rotary Hammer Drill Bits



- Highest drilling speed, improved impact transfer
- Enlarged rebar chamfers reduce the likelihood of catching in case of reinforcement collisions
- Ideal for use with lightweight (battery-powered) rotary hammer drills
- Maximum fracture resistance
- Head: Speed 2-cutter, Power Breaker™ design, centering tip, patented rebar chamfers, PGM-tested carbide tips
- Vario-KVS-flute, 2-fluted

Description/Size	Length/mm	Effective
8mm	110	50
8mm	160	100
8mm	210	150
8mm	260	200
8mm	400	350
8mm	600	550
9mm	210	150
10mm	110	50
10mm	160	100
10mm	210	150
10mm	260	200
10mm	310	250
10mm	450	400
10mm	600	550
10mm	1000	950
11mm	160	100
11mm	260	200
12mm	160	100
12mm	210	150
12mm	260	200
12mm	310	250
12mm	450	400
12mm	600	550
12mm	1000	950
13mm	160	100
13mm	260	200
13mm	310	250
14mm	160	100
14mm	210	150
14mm	260	200
14mm	310	250
14mm	450	400
14mm	600	550
15mm	160	100
16mm	160	100
16mm	210	150
16mm	260	210
16mm	310	260
16mm	450	400
16mm	600	550
16mm	800	750
16mm	1000	950
17mm	210	150
18mm	200	150
18mm	300	250
18mm	450	400
18mm	600	550
20mm	200	150
20mm	250	250
20mm	450	400
20mm	600	550
20mm	1000	950
22mm	250	200
22mm	450	400
24mm	250	200
24mm	450	400
25mm	250	200
25mm	450	400
25mm	600	550
25mm	1000	950
26mm	250	200
26mm	450	400

SDS MAX DRILLER

Rotary Hammer Drill Bits



- › Speed 2-cutter with Power Shoulder™ design
- › Rapid drilling progress and a longer lifetime thanks to new Multi-Value-Flute™ flute design
- › Centering tip
- › Patented rebar chamfers
- › PGM-tested carbide tips

Description/Size	Length/mm	Effective
12mm	340	200
12mm	540	400
14mm	340	200
14mm	540	400



- › Powerful 4-cutter with Power Shoulder™ design
- › Rapid drilling progress and a longer lifetime thanks to new Multi-Value-Flute™ flute design
- › Head turned 90° for optimization of drilling dust removal
- › Stable, self-centering tip
- › Wear marks
- › Patented rebar chamfers
- › PGM-tested carbide tips

Description/Size	Length/mm	Effective
16mm	340	200
16mm	540	400
18mm	340	200
18mm	540	400
18mm	740	600
18mm	1320	1200
20mm	320	200
20mm	520	400
20mm	920	800
22mm	320	200
22mm	520	400
24mm	320	200
24mm	520	400
25mm	320	200
25mm	520	400
25mm	920	800
25mm	1320	1200
28mm	370	250
28mm	570	450
28mm	1320	1200
30mm	370	250
30mm	570	450
32mm	370	250
32mm	570	450
32mm	920	800
32mm	1320	1200
35mm	370	250
35mm	570	450
35mm	920	800
38mm	370	250
38mm	570	450
40mm	370	250
40mm	570	450
45mm	570	450
52mm	570	450

SDS MAX ROCK BLASTER

Rotary Hammer Drill Bits



- › Especially in rock and stone the Rock Blaster shows high resistance.
- › Extremely robust carbide tip geometry makes it work efficiently even under the toughest conditions in natural stone.
- › The carbide tip can be reground and therefore lasts longer.
- › The expanded flutes guarantee fast removal of debris from the drill head making it especially effective in natural stone.
- › Due to the reinforced flute geometry the bit can support more bending stress which is a common challenge when drilling under extreme conditions in hard rock.

Description/Size	Length/mm	Effective
28mm	670	550
30mm	720	600
30mm	920	800
32mm	570	450
32mm	920	800



ALLRO

Straight Shank Percussion Drill Bits



› High quality, ideal for tiles

Description/Size	Length/mm	Width
5mm	85	50
6mm	100	60
8mm	120	80
10mm	120	80
12mm	150	90

GLASS

Straight Shank Percussion Drill Bits



- › Specially ground carbide tip for long service life and heat resistance
- › Cone point for precision pilot drilling
- › 120° carbide tip for processing hard materials such as glass and tiles.

Description/Size
3mm
4mm
5mm
6mm
8mm
10mm
12mm

HM

Straight Shank Percussion Drill Bits



- › Special spiral geometry for optimum drill dust removal.
- › Suitable for rotary and impact drilling.
- › 130° carbide cutting edge ensures long service life.

Description/Size	Length/mm
4mm	75
5mm	85
6mm	100
7mm	100
8mm	100
10mm	120
12mm	150
14mm	150
15mm	150
16mm	150
18mm	160
20mm	160
6mm	200
8mm	200
10mm	200
12mm	200

EXTRA PROFI

Straight Shank Percussion Drill Bits



- › High service life due to special carbide plates on the drill tip.
- › Accurate drilling due to exact soldering of the carbide plates.
- › Ideal for masonry and natural stone.

Description/Size	Length/mm
5mm	75
6mm	100
8mm	120
10mm	120
12mm	150
14mm	150
16mm	150
6mm	200
8mm	200
10mm	200

Termofix B

Screw Fixing



- ▶ Direct mounting without pre-drilling in thin sheets up to 1,5 mm.
- ▶ Time-saving due to pre-assembled screw.
- ▶ Corrosion-resistant screw with Delta-Seal coating.
- ▶ Closing head directly integrated in the plate element.

Description/Size	Length (mm)	Packed
B 90	70	100
B 130	110	100

FGC 100

Gas-actuated Fastening Tool



- ▶ The setting tool is operated with the fischer gas cartridge FC 165 and achieves over 1,100 fastenings per gas cartridge (under standard conditions).
- ▶ The FGC 100 tool can be used with various fischer standard nails DFN and high performance nails DFNH.
- ▶ The 100 joules power of the fischer gas actuated fastening tool FGC 100 ensures correct penetration into the working surface without any drilling or dust.
- ▶ The easy nail depth adjustment switch allows to choose how to set the nails - flush or fully embedded.
- ▶ The FGC 100 has a long lifetime and durability with service intervals after every 20,000 fixings under standard conditions and operates within the temperature range of -7°C to +50°C.

Description/Size	Packed
FGC 100	1



- ▶ Suitable for hard concrete C30/37 and steel.

Description/Size	Packed
DFNH 15	1008
DFNH 17	1008
DFNH 22	1008
DFNH 27	1008
DFNH 32 NP	1008

Fixpin



- ▶ Hand impact protection.
- ▶ Retaining ring.

Description/Size	Packed
Fixpin Hand Tool - SZE	1



- ▶ Quick and easy impact installation without pre-drilling in concrete.
- ▶ Safe hammering due to impact protection on the setting tool SZE.

Description/Size	Packed
ED 18	200
ED 22	200



FTC-CP

Corrosion Spray



- ▶ Prevents the penetration of moisture into the anchor shaft and securely protects the connection from corrosion.
- ▶ Optimised formulation provides long-lasting, elastic protective coating with secure hold and high abrasion resistance.
- ▶ Thixotropic, bitumen-based anti-corrosion agent.
- ▶ Shake canister for at least 2 minutes from the time the mixing balls can be heard.
- ▶ Spray as evenly as possible from a distance of 15 to 20 cm.
- ▶ Ideal processing temperature +16 °C to +25 °C. Quick-drying (dried through after 3-4 hours at 600 µm and 20 °C).
- ▶ Temperature-resistant from -25 °C to 80 °C. Salt and water-resistant, and resistant to abrasion.
- ▶ With one can about 300 screw heads can be coated.

Description/Size

500 ml

FTC-ZS

Zinc Spray



- ▶ In the salt spray test in line with DIN 50021, coated metal parts displayed no corrosion, even after 500 hours.
- ▶ High proportion of zinc in the dry film provides secure protection to all metal surfaces exposed to the elements.
- ▶ Thanks to the adhesive layer of corrosion protection - that can be painted over - it is ideal as a high-quality base layer.
- ▶ The high resistance to cracking and flaking of a metal base material was confirmed by the mandrel flex test in line with DIN EN ISO 1519 (without damage).
- ▶ Dark-grey colour (similar to RAL 7042).
- ▶ Shake can well for approx. 3 minutes. Apply at a distance of 20-30 cm in a cross coat.
- ▶ Surface dust-dry after just approx. 8 minutes. Fully hardened within 24 hours.
- ▶ Ideal processing temperature of 16 °C to 25 °C. Heat-resistant up to approx. 500 °C.
- ▶ Excellent corrosion protection with long-term effect. Electroconductive and suitable for spot welding.

Description/Size

400 ml

FTC-ZA

Zinc-Alu Spray



- ▶ Zinc-alu spray represents a subtle repair to damaged hot-dip galvanised areas thanks to its colour matching with the hot-dip galvanisation.
- ▶ Thanks to the excellent holding properties on blank metal, it guarantees a lasting connection to the base material.
- ▶ Fast-drying spray guarantees good, weatherproof corrosion protection and is suitable for use both indoors and out.
- ▶ Silver-grey colour (similar to RAL 9006) with high gloss level.
- ▶ Shake can well for approx. 2 minutes. Apply at a distance of 25-30 cm in a cross coat.
- ▶ Surface dust-dry after just approx. 8 minutes. Touch-dry after 20-25 minutes. Fully hardened within 24 hours.
- ▶ Ideal processing temp of 16 °C to 25 °C. Long-term heat resistance up to approx. 200 °C (briefly up to 300 °C).
- ▶ Smooth, non-porous film. High abrasion resistance.

Description/Size

400 ml



FiP

Intumescent Pillows



- ▶ FiP are an intumescent graphite and mineral fibre blend covered in a glass fibre PVC coated cloth bag.
- ▶ Suitable for applications where temporary and permanent fire barriers are required.
- ▶ Up to 2 hours fire protection.
- ▶ Dry, quick and easy installation.
- ▶ Approved as permanent fire barrier.
- ▶ No shelf life.
- ▶ Moisture resistant.

Description/Size	Packed
S 330 x 50 x 20 mm	-
M 330 x 200 x 25 mm	-
L 330 x 200 x 45 mm	-

FFB-FM

Fire | Barr Fleximescent



- ▶ Truly versatile - One product covers several applications.
- ▶ Free of halogens, asbestos, fibres and silica.
- ▶ Tested to BS476 Part 20, Fleximescent has been shown to provide up to 2 hours fire resistance.
- ▶ Suitable for use in irregular applications.
- ▶ Brackets included in pack.
- ▶ Structural stone wool for long life, unlike some competitor products.

Description/Size	Packed
25 x 50 mm	-

FFB-ES

Fire | Barr ElastoSeal



- ▶ FFB-ES ElastoSeal is a one part water based acrylic coating which has been designed to provide smoke and fire protection on construction joints in both vertical and horizontal applications.
- ▶ Tested to BS EN1386-4 and BS476-20 the FFB-ES is also ETA approved and CE marked.
- ▶ Developed for use on 80kg/m³ stone wool base the FFB-ES is also halogen and solvent free and exhibits excellent slump and movement characteristics.
- ▶ Working temperature between -10 °C and 95 °C. Can be spray or brush applied.
- ▶ Air permeability. Acoustic performance. Movement capabilities of 25%.

Description/Size	Packed
FFB-ES White 20l	-

FireStop Hand Foam B1



- ▶ Firestop foam is a single component, self expanding polyurethane foam which has been designed to be self curing via the absorption of moisture from the atmosphere.
- ▶ The foam has excellent adhesion properties and can adhere to most building materials, when the foam sets it cures to a semi-rigid structure which accommodates low movement and vibration.
- ▶ High foam yield. No post shrinkage or expansion. High bond strength. Good adhesion to most building materials.
- ▶ CFC free propellant. Effective seal against smoke.
- ▶ Rendered, cut, painted or sanded. Excellent acoustic and thermal properties.

Description/Size	Packed
Firestop Foam B1	-

FCID

Cast in Device



- ▶ FCID Cast-In Device is a pass through system which is constructed from a highly resilient polypropylene material and contains a powerful Intumescent graphite band which has been designed for non-metallic pipe applications in reinforced cast concrete slabs and some prefabricated slab systems. (Subject to design)
- ▶ Quick installation. Watertight seal.
- ▶ Wider base for further connections.
- ▶ No further collars or wraps required.
- ▶ Eco-friendly extension tube. Free of asbestos, solvents and any hazardous ingredients.

Description/Size	Packed
100 mm	-

FCC

Cable Coating



- ▶ High performance cable coating designed to provide fire protection for cables and cable support systems.

Description/Size	Packed
FCC 12.5l	-

FIAM

Intumescent Acoustic Mastic



- ▶ FiAM is a one part water based acrylic emulsion that can provide up to 5 hours fire resistance when used in construction joints and services in both vertical and horizontal applications.
- ▶ When exposed to fire, it reacts to form a highly insulative char that slows down heat transfer, and provides a barrier to fire seal.
- ▶ Tested to BS EN1366-3 & 4, UL 2079 and BS476-20 the FiAM is also ETA approved and CE Marked.
- ▶ Formulated to be halogen and solvent free the FiAM exhibits excellent slump characteristics and has been designed to maintain the sound reduction index of a structure.

Description/Size	Colour	Packed
310 ml	White	-
310 ml	Grey	-
600 ml Foil Pack	-	-

FIGM

Intumescent Graphite Mastic



- ▶ FIGM is a one part water based flexible acrylic emulsion containing a high pressure intumescent graphite which is used to seal service penetrations in both vertical and horizontal applications.
- ▶ It can expand up to 20 times its own volume and cures to form a resilient, flexible fire seal.
- ▶ Tested to both BS 476 & BS EN1366-3/4 the fischer FIGM is also ETA approved and CE Marked for a wide range of applications such as, non metallic pipes, metallic and insulated pipes, MLC pipes, cables and cable bunches and can also be used in combination with the fischer FCPS Coated Panel System.
- ▶ FIGM can provide up to 5 hours fire resistance.

Description/Size	Packed
310 ml	-

Dispensers



Description/Size	Packed
KP M 2	-
310 ml Dispenser	-
600 ml Dispenser	-

FCPS

Coated Panel System



- ▶ FCPS is a rock fibre core coated with ablative sealant FPC - fischer Panel Coating.
- ▶ Designed to provide effective and efficient firestopping seals in both vertical and horizontal applications.
- ▶ Also helps to maintain the sound reduction index of a structure.
- ▶ Tested to BS 476 part 20 and 22, EN 1366-3 and is ETA approved and CE Marked.
- ▶ Design to provide up to 4 hours integrity and 2 hours insulation on a wide range of applications the FCPS will allow additional services to be added or removed & will accommodate thermal & mechanical movement of services.

Description/Size	Packed
FPC 5t	-
FCPS 1200x600x50mm 160kg/m³	-

FFSC

FireStop Compound



- ▶ FFSC is a specially formulated gypsum based compound, which when mixed with water can be trowelled or poured around service penetrations in either vertical or horizontal applications.
- ▶ Tested to EN1366-3 and UL1479, the FFSC can provide up to 4 hours integrity and insulation.
- ▶ It has been designed to set within 30-45 min depending on ambient temperature, and is capable of accommodating foot traffic within 72 hours.
- ▶ Excellent acoustic properties, halogen and asbestos free.

Description/Size	Packed
20 kg	-

FBS

Foam Barrier System



- ▶ Firestop Foam Barrier System PLUS is a system of an innovative two component polyurethane expanding foam and highly elastic mouldable blocks.
- ▶ Both components can be used in conjunction as a system or individually.
- ▶ The quick and easy installation of fischer Firestop Foam Barrier System PLUS means it can be retro fitted as necessary and used with the for more difficult to reach applications.
- ▶ Easy access for difficult to reach openings.
- ▶ Various applications with two products only.
- ▶ Age-resistant. Smoke resistant. Resistant to damp.
- ▶ Re-enterable and repairable. Excellent adhesion. No backing material required.
- ▶ F-rating / E-Integrity rating up to 2 hours. T-rating / EI-Insulation rating up to 2 hours.

Description/Size	Packed
Foam Barrier System PLUS	-
FireStop Block	-

FFC 2

Fire Collar



- ▶ FFC 2 is a powder coated cylindrical steel sleeve which contains a heat reactive graphite based intumescent material that expands during fire.
- ▶ Can be used on its own or in mixed penetration applications with the FCPS Fischer Coated Panel System.
- ▶ Annular gaps up to 10 mm can easily be backfilled with fischer FIAM Intumescent Acoustic Mastic.
- ▶ Designed to be securely fitted around the pipe and held in position with a retaining bolt.
- ▶ Pre-fixed attachment lugs.
- ▶ Fold back tag for secure fixture around pipe.

Description/Size	Packed
30 mm	-
40 mm	-
55 mm	-
63 mm	-
75 mm	-
90 mm	-
110 mm	-
125 mm	-
160 mm	-

FiPP

Intumescent Putty Pad



- ▶ FiPP are manufactured from a red, non-setting, silicone based intumescent polymer.
- ▶ Tested in accordance with BS EN 1366-3 for up to 2 hour fire rating and 2 hour insulation.
- ▶ Excellent acoustic properties.
- ▶ Primerless adhesion to most substrates.
- ▶ No electrical conductivity.
- ▶ Air permeability.
- ▶ Quick and simple installation.

Description/Size	Packed
I-S 170 x 170 mm	-
I-D 230 x 170 mm	-
E-S 155 x 155 mm	-
E-D 210 x 180 mm	-

FiPW

Intumescent Pipe Wraps



- ▶ FiPW is a flexible composite strip, composed of thermoplastic component containing intumescent graphite in a synthetic compound.
- ▶ Efficient and effective for sealing of pipe openings in floors and walls.
- ▶ Manufactured to be wrapped around non metallic pipes and trunking, FiPW is designed to expand and provide up to 4 hours fire resistance in a pipe cavity created under fire.
- ▶ Tested to BS476 pt.20 and BS EN1366-3, FiPW is an asbestos and halogen-free environment friendly product and is unaffected by oil, fungus, vermin or rodents.
- ▶ Available on a roll for more flexibility in pipe diameters.

Description/Size	Packed
55 mm	-
110 mm	-
FiPW 25 m	-

FiWS

Intumescent Wrap Strip



- ▶ FIAM is a one part water based acrylic emulsion that can provide up to 5 hours fire resistance when used in construction joints and services in both vertical and horizontal applications.
- ▶ When exposed to fire, it reacts to form a highly insulative char that slows down heat transfer & provides a fire seal.
- ▶ Tested to BS EN1366-3 and 4, UL 2079 and BS476-20 the FIAM is also ETA approved and CE Marked.
- ▶ Up to 4 hours fire resistance.
- ▶ Formulated to be halogen and solvent free the FIAM exhibits excellent slump characteristics and has been designed to maintain the sound reduction index of a structure.
- ▶ For large openings, the FiWS can be used in conjunction with the FFSC.

Description/Size	Packed
50 mm x 6 mm x 3.66 m	-
50 mm/3.66 m Collar	-



Multi MS

Construction Adhesive



- ▶ The extremely high initial adhesion of 110 kg/m² makes it possible to attach lots of components without the need for additional fixing, and thus reduces the amount of time required.
- ▶ The MS polymer® allows for an elastic adhesion for vibration-dampening and stress-compensating connections for connections demanding applications.
- ▶ MS is almost odour-free and therefore particularly suitable for closed rooms.
- ▶ Non-corrosive, thus can be used on copper and zinc plated surfaces for maximum flexibility in application.
- ▶ Chemical base: One-component hybrid polymer
- ▶ Processing temperature: +5 °C to +35 °C
- ▶ Setting time approx. 5 minutes. Curing: approx. 3 mm per day.
- ▶ Suitable for bonding non-absorbent components (see TDS). Can be painted (see TDS)

Description/Size	Length/mm
White	290 ml

PU

Rapid Installation Foam



- ▶ Reclosable nozzle allows for immediate use and for reuse of opened cans, guaranteeing long-lasting functionality.
- ▶ The used solid valve prevents adhesion when being stored horizontally and premature gas loss.
- ▶ The rapid installation foam has been approved as watertight by an external inspection and is thus suitable for use in wet conditions. It fulfils the requirements of a well foam.
- ▶ The ergonomic handle sits perfectly in the hand and allows for easy use.
- ▶ 1-component PU foam. Building material class B3
- ▶ Processing temperature: +5 °C to +35 °C (can temp: +5 °C to +25 °C). Temp resistant from -40 °C to +90 °C
- ▶ Non-tacky within approx. 20 minutes. Can be cut within approx. 40 minutes. Cures within 5 to 8 hours.

Description/Size	Yield
500 ml	30 l
750 ml	41 l

PUR

PU-cleaner



- ▶ Active components ensure a high cleaning effect, making the cleaner ideal for the safe removal of fresh PU foam.
- ▶ Gun adapter is suitable for all standard systems and enables universal application.
- ▶ Separate spray head allows for the cleaning of external surfaces, making the product extremely versatile.
- ▶ The highly active cleaner can etch sensitive surfaces (paint, dye, textiles, plastics). Thus you should always conduct preliminary tests.

Description/Size	
150 ml	
500 ml	

Foam Guns



- ▶ Robust plastic casing with all product contacted parts made of metal for heavy-duty use
- ▶ The universal basket integrated into the casing is designed for all common valve systems
- ▶ Trigger made of black powder-coated metal withstands highest stress
- ▶ Extended secured adjusting screw allows controlled filling and insulating and enables application-oriented working
- ▶ Screwed-on, replaceable conical metal nozzle allows extension tubes (Ø 6 mm) to be slid on for narrow joints

Description/Size	
PUPK 2	



- ▶ The PUP M3 meets the tough requirements of a construction site and thus offers a long lifespan.
- ▶ The ergonomic handle allows for an ideal position of centre of gravity, and therefore precise handling.
- ▶ The infinitely variable control of the foam expulsion allows for a controlled filling and insulating, and enables application-oriented work.
- ▶ Opened cans can remain screwed onto the gun during interruptions of work without curing.

Description/Size	
PUPM 3	



DEC

Express Cement



- ▶ Ready-to-use, sprayable joint mortar means there is no need to add water or carry out time-consuming pre-mixing work.
- ▶ It enables clean, purposeful work. This means that you avoid dirtying surrounding areas and wasting material.
- ▶ Good adhesion even on slightly damp substrates allows for all-weather work and prevents forced interruptions.
- ▶ The structure of the high-quality water-based polymer has been perfectly designed with the visual appearance of the mortar in mind. This ensures a discreet joint and perfect appearance.
- ▶ Chemical base: 1C polymer dispersion. Free of silicone, MDI and solvents.
- ▶ Skin formation time: Approx. 10 minutes. Weather-proof after approx. 24 hours.
- ▶ Processing temperature: +5 °C to +40 °C. Temperature resistance up to -30 °C (fully cured).
- ▶ Very good resistance to UV, weather and ageing. Paintable.

Description/Size

Grey

Volume

310 ml

DDK

All-weather Sealant



- ▶ Thanks to the high elasticity of 25%, DDK is ideally suited to high-stress joints. This guarantees long-lasting jointing.
- ▶ Holds without a base coat, including on moist and bituminous substrates, and is therefore suitable for all applications in the roofing area. For a high degree of economy.
- ▶ Immediate rain resistance allows for external application in all weather conditions, thus avoiding interruption of work.
- ▶ Non-corrosive, and thus can be used on aluminium, copper and zinc-plated surfaces. This offers maximum flexibility.
- ▶ Chemical base: 1-component synthetic rubber. Permanently elastic.
- ▶ Skin formation time: 15 - 20 minutes.
- ▶ Processing temperature: +5 °C to +40 °C. Temperature resistance: -25 °C to +100 °C.
- ▶ Very good resistance to weather, ageing and UV. Paintable.

Description/Size

Transparent

Volume

310 ml

DD

Roof Sealing Compound



- ▶ The special bitumen-based formulation seals roofing membranes and roofing felt securely.
- ▶ Holds to moist substrates without a base layer. This makes application largely independent of the weather and thus helps to avoid interruption of work.
- ▶ Non-corrosive, thus can be used on aluminium, copper, zinc-plated surfaces and polystyrene, offering max flexibility.
- ▶ Chemical base: 1-component bitumen.
- ▶ Skin formation time: approx. 30 minutes.
- ▶ Processing temperature: +5 °C to +40 °C. Temperature resistance: -20 °C to +80 °C.

Description/Size

Black

Volume

310 ml

High Tack AC

Building Adhesive



- ▶ Very high initial adhesion as well as final strength ensures the secure fixing of add-on parts without additional aids.
- ▶ Mounting without drilling or nailing allows attachments to be securely fastened even in hard-to-reach places.
- ▶ The high-quality raw materials also allow use on sensitive substrates such as natural stone.
- ▶ The components can still be readjusted within a few minutes for flexible assembly.
- ▶ The water-based acrylic adhesive is odourless and therefore particularly suitable for indoor processing.
- ▶ The special formulation ensures good compatibility with foamed polystyrene, such as Styropor®.
- ▶ Chemical base: 1K acrylic dispersion (water-based). Solvent-, silicone- and MDI-free.
- ▶ Processing temperature: +10 °C to +30 °C. Temperature resistance: -20 °C to +60 °C.
- ▶ Very high initial adhesive strength of up to 345 kg/m². High final strength.
- ▶ Minimum one substrate must be non-absorbent.

Description/Size

Creamwhite

Volume

310 ml

Express PU

Adhesive



- ▶ Extremely high final strength of up to 100 kg/cm² ensures the secure fastening of heavy attachments.
- ▶ Fast curing allows the adhesive joint to be loaded after only approx. 10 minutes.
- ▶ Heat resistant up to 110 °C and therefore suitable for applications with extreme temperature exposure.
- ▶ Water resistance according to DIN EN 204 D4 allows indoor and outdoor applications.
- ▶ High-quality raw materials allow the use on sensitive substrates, such as natural stone, without discoloration.
- ▶ Special formulation ensures good compatibility with foamed polystyrene, such as Styropor®.
- ▶ Chemical base: 1K PUR adhesive. Solvent and silicone free.
- ▶ Processing temperature: 0 °C to +35 °C. Temperature resistance: -40 °C to +110 °C.
- ▶ Processing time: approx. 3 minutes. Functionally stable after approx. 10 minutes (with zero joint).
- ▶ Does not drip for overhead applications. Easily foaming and gap bridging.
- ▶ Press parts until functional strength is achieved. Very high final strength.

Description/Size

Beige

Volume

310 ml

Dispensers

Shuttle Dispensers



- ▶ The fast venting minimises cartridge after-run, which facilitates clean work at the site.
- ▶ Reducing valve in the handle enables the optimum adjustment of the volume flow in line with processing conditions.
- ▶ Due to the ergonomically formed handle, the dispensers fit nicely in your hand and make work less tiring.
- ▶ For use on shuttle cartridges with 345, 360 and 390 ml content, multibond cartridges with 300 ml content and standard silicone cartridges.

Description/Size

FIS AP



- ▶ For use with cartridge sizes with 150ml, 300ml, 360ml, and 390ml content.
- ▶ Dosing function for the efficient adjustment of the mortar quantity to the drill hole size.
- ▶ Device design with optimum weight distribution for ergonomic working.
- ▶ Integrated controller for dispensing speed adjustment.
- ▶ Compatible with all Cordless Alliance System (CAS) tools and batteries.

Description/Size

DB S Pro



- ▶ The patented parallel lever of the FIS DM S-L allows a large and even force transmission and ensures fatigue-free working.
- ▶ The drop protection on the cartridge holder provides a secure hold of the cartridge in the dispenser.
- ▶ For use on cartridges with 585 ml content.
- ▶ S-E specs vary from S-L

Description/Size

FIS DM S-L

FIS DM S-E

Coaxial Dispensers



- ▶ The robust design can withstand the high requirements of the job site and thus offers a long life.
- ▶ The infinitely variable feed allows the exact dosing and thus ensures easy handling.
- ▶ For use on coaxial cartridges with 380 and 410 ml content.

Description/Size

FIS AC

Single Plunger 50 mm



- ▶ The 18:1 transmission ratio enables the fast, low-energy application of even highly viscous materials, thus ensuring stress-free work.
- ▶ The robust design with the special, hardened drive block meets the tough requirements of a construction site and thus offers a long lifespan.
- ▶ The freely accessible cartridge makes it possible to perfectly align the extrusion nozzle, guaranteeing safe and precise application oriented work.
- ▶ For use on multibond cartridges with 300 ml content and standard silicone cartridges.

Description/Size

KP M 2



- ▶ The handy, robust solid metal construction for standard cartridges up to 310 ml bears up against requirements on the construction site and, as such, is also suitable for professional use.
- ▶ The continuous in-feed allows for a precise dosage, making it easy to use.
- ▶ The slim shape of the device allows for an exact application, even in difficult to reach spots, thus offering a high level of flexibility.
- ▶ For use on multibond cartridges with 300 ml content and standard silicone cartridges.

Description/Size

KP M 1



- ▶ Max force: 400 kgf
- ▶ 7.4V 1.3Ah Li-Ion Battery
- ▶ No load speed: 4,8mm/second
- ▶ Built-in LED spotlight
- ▶ Dripless function
- ▶ For use on multibond cartridges with 300 ml content and standard silicone cartridges.

Description/Size

BOC-1 (7.4V 1.3Ah Li-Ion)

7.4V 1.3Ah Li-Ion



Dispensers

Shuttle Dispensers



- ▶ The fast venting minimises cartridge after-run, which facilitates clean work at the site.
- ▶ Reducing valve in the handle enables the optimum adjustment of the volume flow in line with processing conditions.
- ▶ Due to the ergonomically formed handle, the dispensers fit nicely in your hand and make work less tiring.
- ▶ For use on shuttle cartridges with 345, 360 and 390 ml content, multibond cartridges with 300 ml content and standard silicone cartridges.

Stock Ref
171-908

Description/Size
FIS AP

Product



- ▶ For use with cartridge sizes with 150ml, 300ml, 360ml, and 390ml content.
- ▶ Dosing function for the efficient adjustment of the mortar quantity to the drill hole size.
- ▶ Device design with optimum weight distribution for ergonomic working.
- ▶ Integrated controller for dispensing speed adjustment.
- ▶ Compatible with all Cordless Alliance System (CAS) tools and batteries.

Stock Ref
171-900

Description/Size
DB S Pro

Product



- ▶ The patented parallel lever of the FIS DM S-L allows a large and even force transmission and ensures fatigue-free working.
- ▶ The drop protection on the cartridge holder provides a secure hold of the cartridge in the dispenser.
- ▶ For use on cartridges with 585 ml content.
- ▶ S-E specs vary from S-L

Stock Ref
171-904
171-903

Description/Size
FIS DM S-L
FIS DM S-E

Product

Coaxial Dispensers



- ▶ The robust design can withstand the high requirements of the job site and thus offers a long life.
- ▶ The infinitely variable feed allows the exact dosing and thus ensures easy handling.
- ▶ For use on coaxial cartridges with 360 and 410 ml content.

Stock Ref
171-905

Description/Size
FIS AC

Product

Single Plunger 50 mm



- ▶ The 18:1 transmission ratio enables the fast, low-energy application of even highly viscous materials, thus ensuring stress-free work.
- ▶ The robust design with the special, hardened drive block meets the tough requirements of a construction site and thus offers a long lifespan.
- ▶ The freely accessible cartridge makes it possible to perfectly align the extrusion nozzle, guaranteeing safe and precise application oriented work.
- ▶ For use on multibond cartridges with 300 ml content and standard silicone cartridges.

Stock Ref
171-902

Description/Size
KP M 2

Product



- ▶ The handy, robust solid metal construction for standard cartridges up to 310 ml bears up against requirements on the construction site and, as such, is also suitable for professional use.
- ▶ The continuous in-feed allows for a precise dosage, making it easy to use.
- ▶ The slim shape of the device allows for an exact application, even in difficult to reach spots, thus offering a high level of flexibility.
- ▶ For use on multibond cartridges with 300 ml content and standard silicone cartridges.

Stock Ref
171-901

Description/Size
KP M 1

Product



- ▶ Max force: 400 kgf
- ▶ 7.4V 1.3Ah Li-Ion Battery
- ▶ No load speed: 4,8mm/second
- ▶ Built-in LED spotlight
- ▶ Dripless function
- ▶ For use on multibond cartridges with 300 ml content and standard silicone cartridges.

Stock Ref
171-898
171-895

Description/Size
BOC-1 (7.4V 1.3Ah Li-Ion)
7.4V 1.3Ah Li-Ion

Product



HM Z

Installation Pliers



- ▶ Ergonomic handle for fatigue-free work.
- ▶ Stable, heavy duty design.
- ▶ Transport security due to attachments.
- ▶ Z 1 for professional use, Z 2 for DIY use.

Description/Size	Packed
HM Z 1	1
HM Z 2	1

GK

Nylon Plasterboard Fixing



- ▶ The sharp, self-tapping thread of the GK enables a secure, positive fit fixing for a high load-bearing capacity.
- ▶ The short fixing length means that only a small amount of space is required behind the board. As a result, the GK can also be used in the case of unknown board thickness and cavity depth.
- ▶ Cross-drive recess in the head means that the GK can also be screwed out like a screw without a setting tool.

Description/Size	Packed with:	Packed
GK	Setting Tool	100
GKS	Setting Tool & C/B Screws	50

Description/Size	Packed
GK Setting Tool	1

GK M

Metal Plasterboard Fixing



- ▶ Due to its material properties, the GKM can be used in gypsum plasterboard and gypsum fibreboard, and can be used with the most wide-ranging screws, hooks and eye screws, allowing for a broad range of applications.
- ▶ The sharp, self-tapping thread enables a secure, positive fit fixing. This achieves a high load-bearing capacity.
- ▶ The cross-drive recess means that a standard screwdriver or bit can be used.
- ▶ No special setting tool is required.

Description/Size	Packed with:	Packed
GKM	-	100
GKMS 12	Panhead screws	100
GKMS 27	Countersunk screws	100