

Description

NewBerry Library

Objective:

To work with HTML5 Semantic Tags.

Concept Explanation:

HTML5 Semantic Tags are specific elements in HTML that carry meaning about the content they enclose,

beyond just presentation.

Unlike traditional HTML elements, semantic tags provide clarity and context to the structure of a web page.

Concept Implementation:

The structure given below can be implemented using HTML5 semantic tags:

1. Use header and footer tags to create the header and footer portions of your web page, respectively.
2. Use nav tag to create the navigation bar in the header, and main tag between header and footer to wrap the main content of your web page.
3. Use tags like section, h1, h2, h3, p, mark and article to build the main content.

Problem Description:

One of the well-known libraries is the NewBerry Library. They have made the decision to build a website where they would advertise the notable books they have in their library. Aid them in developing a site.

IMPORTANT NOTE: For better layout understanding, please, refer to the snapshot given.

You **NEED NOT** have the **ACTUAL** content specified **within the page**

Create elements **AS PER THE ORDER** specified in the table given below:

Element Id	Description
head	Create a HEADER element for the page using the header tag with the given id. The header should contain the navigation tag inside it.
navigation	Create a navigation bar with the given id. Inside this should have 4 anchor tags such as Home, Books, Contact, about Us
heading1	Inside the Main, Create an H1 tag with id heading1 and inside it type "Welcome to the NewBerry Library"
address	Inside the Main, Create aside using the given id and type "ADDRESS: 60 W Walton St, Chicago, IL 60610, USA"

about	Create a section with the given id. Inside that create offer,heading2,about_us.
offer	Set " Now New Candidates can Register for free " as mark using the given id.
heading2	Set " About Us " in the h2 tag using the given tag.
about_us	Create a paragraph tag using the given id and type the content as shown in the screenshot. Close the section tag
books	Create a section for the given id inside that set " Popular Books " inside an h2 tag. Create book1,book2,book3 inside this books.
book1	Create an article with the given id. Set " American History and Culture " in h3 tag with id bookName1 . Set by F. Scott Fitzgerald in paragraph tag. In the next paragraph, tag set A classic novel depicting the roaring 1920s in America.
book2	Create an article with the given id. Set " Genealogy and Local History " in h3 tag with id bookName2 .Set by Harper Lee in a paragraph tag. In the next paragraph, tag set A powerful story of racial injustice and moral courage.
book3	Create an article with the given id. Set " Pride and Prejudice " in h3 tag with id bookName3 .Set by Jane Austen in a paragraph tag. In the next paragraph, tag set A beloved novel exploring love, class, and societal expectations.
foot	Within the footer tag, create the short footer-text : 2023 Library Website. All rights reserved. - within the paragraph tag with id copyright

Screenshot:



<!-- do not make any changes in the template -->

<!-- fill your code in the areas indicated -->

<!DOCTYPE html>

<html lang="en">

<head>

<meta charset="UTF-8" />

<meta name="viewport" content="width=device-width, initial-scale=1.0" />

<title>NewBerry Library</title>

<style>

body{

font-family: Arial, sans-serif;

margin: 0;

padding: 0;

}

h1{

text-align: center;

}

h2{

padding-bottom: 15px;

padding-top: 10px;

}

header{

background-color: #ec8f00;

padding: 20px;

}

nav{

margin-bottom: 20px;

}

```
main {
  padding: 20px;
}

footer {
  background-color: #ec8f00;
  padding: 20px;
  text-align: center;
}

aside {
  width: 30%;
  padding: 30px;
  margin-left: 15px;

  float: right;
  font-style: italic;
  background-color: lightgray;
}

a {
  padding-right: 10px;
}

mark {
  padding: 20px;
}

</style>
</head>
<body>

<!--Create header with nav bar-->
<header id="head">
  <nav id="navigation">
```

```
<a>Home</a>

<a>Books</a>

<a>Contacts</a>

<a>about Us</a>

</nav>

</header>

<main>

<!--Fill the code here-->

<h1 id="heading1">Welcome to the NewBerry library</h1>

<aside id="address">ADDRESS:60 W Walton St,Chicago,IL 60610,USA</aside>

<section id="about">

  <mark id="offer">Now New Candidates can Register for free</mark>

  <h2 id="heading2">About Us</h2>

  <p id="about_us">Our collections, programs, and exhibitions are a portal to more than six
centuries of human history, from the 15th century to the present. The Newberry welcomes
anyone who is eager to learn about who we are, where we came from, and where we are
going.</p>

</section>

<section id="books">

  <h2>Popular Books</h2>

  <article id="book1">

    <h3 id="bookName1">American History and culture</h3>

    <p>By F.Scott Fitzgerald</p>

    <p>A classic novel depicting the roaring 1920s in America</p>

  </article>

  <article id="book2">

    <h3 id="bookName2">Genealogy and local History</h3>

    <p>By Harper Lee</p>

    <p>A powerful story of racial injustice and moral courage</p>

  </article>

  <article id="book3">

    <h3 id="bookName3">Pride and Prejudice</h3>
```

<p>By Jane Austen</p>

<p>A beloved novel exploring love, class, and societal expectations</p>

</article>

</section>

</main>

<!--create a footer here-->

<footer id="foot">

<p id="copyright">2023 Library Website.All rights reserved.</p>

</footer>

</body>

</html>

Description

Jasper Sports Academy

Objective:

To work with HTML5 Forms.

Concept Explanation:

HTML5 forms use the <form> tag to collect user input, with elements like <input>, <textarea>, <select>, and <button> for various input types. New input types (e.g., email, date, range) and attributes (e.g., placeholder, required) enhance functionality and validation.

Concept Implementation:

The Jasper Sports Academy Player Registration form uses various HTML tags to structure the form. It includes <h2> for the title, <table>, <tr>, and <td> for the layout, <input> for text fields, dates, numbers, and file uploads, <textarea> for addresses, <select> for dropdowns, <label> for labeling inputs. The form concludes with a submit button.

Problem Description:

Jasper Sports Academy is a recently started sports academy in the city. They would like to design the web page for their academy to register online for the new enrollments and the offers provided to attract the people. Help them in designing a web page towards the same, referring to the screenshot given below.

Use the Label Name and the element Id as given. All the necessary attributes for the element should be given. The element Id should be specified for each HTML element. All Tags, Elements and Attributes should conform to HTML5 standards.

Design the web page "JASPER SPORTS ACADEMY" with specified fields and the **constraints specified in the table below:**

Label Name	element Id(Specify it for the "id" attribute)	Description
Player Registration Details		
Date of Registration	registrationDate	To enter the registration date. Design Constraints: Provide the correct input type to make this element accept a date. The element should be mandatory.
Name	playerName	To enter the name of the student. Design Constraints: Use "text" type input with the pattern attribute that accepts only alphabets and spaces.The element should be mandatory.
Age	playerAge	To enter the age. Design Constraints: Use "number" type input. Set the "min" age required as 3. The element is mandatory.

Sports Type	Use "indoorSport" and "outdoorSport" as the element ids for the radio button options.	To select the sports type Design Constraints: The option values pertaining to the sports type are ' Indoor ' and ' Outdoor '. The name of radio button pertaining to all the options is ' spo '
Phone Number	phoneNumber	To enter the phone number: Design Constraints: Use " tel " type input. Use the " pattern " attribute to accept the mobile number to start with either of the following numbers 9. The element is mandatory.
Email	emailAddress	To enter the email id; Design Constraints: Use the " email " type input. The element is mandatory.
Address	homeAddress	To enter the address: Design Constraints: The text " Enter your address " should appear by default. Provide the correct tag and attributes to create a text area with " 4 " rows and " 50 " columns. It should be mandatory.
Number of Players	numberOfPlayers	To select the Number of players: Design Constraints: The option values pertaining to educational qualification are ' Select-- ', ' Single ', ' Double ', ' Multiple '
Location	locationField	To specify the location: Design Constraints: Mandatory element with " text " type input.
Sports (with duration) & Sports Fee		
	Use "athletics", "cricket", "basketball" and "tableTennis" as the ids for the check box elements.	To select the courses. Design Constraints: The names of checkboxes pertaining to all the options is ' spo ' their values (in the order of checkboxes) are as follows : "Athletics (6 months)" "Cricket (3 months)" "BasketBall (9 months)" "Table Tennis (6 months)"
Birth Certificate (Jpeg/Pdf)	birthCertificate	To upload birth certificate: Design Constraints: Provide the correct input type to make this element accept a of type jpeg or pdf file format only. It should be mandatory.

Schedule	scheduleLink	Create a anchor tag with given id and give a hypertext referer "timing.html".While clicking this it should redirect to the timing page.
Deposit	depositAmount	To specify the deposit: Design Constraints: Provide the correct input type to make this element a range with min value 10000 and max value 20000 . It should be mandatory.
	discountInfo	*A discount of 15% will be applied on total amount on registration for more than 6 months must be the table data, holding title value : "Only on registration for more than 6 months"
	enroll	Submit button to submit the page Design Constraints: The input type should be " submit " and the value should be " ENROLL ". It is clickable but has no action associated with it.
Timing.html		Create a table in timing.html page which the following table data given in screen shot.

NOTE: The text highlighted in bold in the Description needs to be implemented in the code to complete the web page design.

IMPORTANT constraints on elements:

1. Every table row has 2 table data except "Player Registration Details" & "the last table data" containing a statement on discount - whose tds span across 2 columns.
2. Apply class : '**title**'(given) to table data (**td**) containing : Player Registration Details, Sports (with duration) & Sports Fee.
3. Partially filled table row pertaining to Sports (with duration) & Sports Fee is given in the template.

```
<!DOCTYPE html>
```

```
<html>
```

```
<head>
```

```
<!-- Write necessary code wherever needed to complete this code challenge -->
```

```
<!-- Do specify all the element-ids correctly for your code to get evaluated successfully -->
```

```
<title>JASPER SPORTS ACADEMY</title>
```

```
<style>
```

```
*{
```

```
        font-weight: bold;
    }
body{
    background-image: url("Jasper.jpeg");
}

    h2{
        text-align: center;
        color: #a2eb1b;
}

        .title{
            text-align: center;
            background-color:#173b6bd2;
            color:#ffffff;
        }
        td{
            background-color:#ffffff;
            width: 50%;
            padding:7px;
            border-radius: 5px;
            border:2px solid #34495E;
            color: #34495E;
        }
        table{
            width: 60%;
            margin-left: auto;
            margin-right: auto;
        }
        #enroll{
            margin-left: 45%;
            margin-right: auto;
            background-color:#34495E;
```

```

        color:#ffffff;
        padding:7px;
    }
    input[type="email"],input[type="text"],
input[type="number"],input[type="tel"]{
        width:97%;
    }
    select{
        width:99%;
    }
</style>
</head>
<body>
    <h2>JASPER SPORTS ACADEMY</h2>

    <table>
        <tr>
            <th colspan="1"><label name="Player Registration Details">Player Registration
Details</label></th>
        </tr>
        <tr>
            <td><label name="Date of Registration" >Date of Registration</label></td>
            <td><input id="registrationDate" required type="date"></td>
        </tr>
        <tr>
            <td><label name="Name">Name</label></td>
            <td><input id="playerName" required type="text" pattern="[A-Za-z ]+$"></td>
        </tr>
        <tr>
            <td><label name="Age">Age</label></td>
            <td><input id="playerAge" type="number" min="3" required></td>
        </tr>
    </table>

```

```

<tr>

  <td><label name="Sports Type">Sports Type</label></td>

  <td>

    <input type="radio" name="sports" id="indoorSport" value="Indoor">

    <!--<label for="indoorSport">Indoor</label>-->

    <input type="radio" name="sports" id="outdoorSport" value="Outdoor">

    <!--<label for="outdoorSport">Outdoor</label>-->

  </td>

</tr>

<tr>

  <td><label name="Phone Number">Phone Number</label></td>

  <td><input id="phoneNumber" required type="tel" pattern="^[6-9][0-9]{9}$"></td>

</tr>

<tr>

  <td><label name="Email">Email</label></td>

  <td><input id="emailAddress" type="email" required></td>

</tr>

<tr>

  <td><label name="Address" >Address</label></td>

  <td><textarea id="homeAddress" rows="4" cols="50" required placeholder="Enter your
address"></textarea></td>

</tr>

<tr>

  <td name="Number of Players">Number of Players</td>

  <td><select id="numberOfPlayers">

    <optgroup>

      <option>--select--</option>

      <option>Single</option>

      <option>Double</option>

      <option>Multiple</option>

    </optgroup>

  </td>

</tr>

```

```

        </select></td>

</tr>

<tr>

    <td><label name="Location">Location</label></td>

    <td><input id="locationField" type="text" required></td>

</tr>

<!-- Fill code for Player Registration Details as per the specified constraints -->

<tr>

    <th>

        <label>Sports (with duration) </label>

    </th>

    <th>

        <label>Sports Fee</label>

    </th>

</tr>

----

<!DOCTYPE html>

<html>

    <head>

        <!-- Write necessary code wherever needed to complete this code challenge -->

        <!-- Do specify all the element-ids correctly for your code to get evaluated successfully -->

        <title>JASPER SPORTS ACADEMY</title>

        <style>

            *{

                font-weight: bold;

            }

            body{

                background-image: url("Jasper.jpeg");

            }

            h2{

```

```

        text-align: center;
        color: #a2eb1b;
    }

    .title{
        text-align: center;
        background-color:#173b6bd2;
        color:#ffffff;
    }

    td{
        background-color:#ffffff;
        width: 50%;
        padding:7px;
        border-radius: 5px;
        border:2px solid #34495E;
        color: #34495E;
    }

    table{
        width: 60%;
        margin-left: auto;
        margin-right: auto;
    }

    #enroll{
        margin-left: 45%;
        margin-right: auto;
        background-color:#34495E;
        color:#ffffff;
        padding:7px;
    }

    input[type="email"],input[type="text"],
input[type="number"],input[type="tel"]{
        width:97%;

```

```

        }

        select{

        width:99%;

        }

    </style>

</head>

<body>

    <h2>JASPER SPORTS ACADEMY</h2>

    <table>

        <tr>

            <th colspan="1"><label name="Player Registration Details">Player Registration
Details</label></th>

            </tr>

            <tr>

                <td><label name="Date of Registration" >Date of Registration</label></td>

                <td><input id="registrationDate" required type="date"></td>

            </tr>

            <tr>

                <td><label name="Name">Name</label></td>

                <td><input id="playerName" required type="text" pattern="[A-Za-z ]+$"></td>

            </tr>

            <tr>

                <td><label name="Age">Age</label></td>

                <td><input id="playerAge" type="number" min="3" required></td>

            </tr>

            <tr>

                <td><label name="Sports Type">Sports Type</label></td>

                <td>

                    <input type="radio" name="sports" id="indoorSport" value="Indoor">

                    <!--<label for="indoorSport">Indoor</label-->

```

```

        <input type="radio" name="sports" id="outdoorSport" value="Outdoor">
        <!--<label for="outdoorSport">Outdoor</label-->
    </td>
</tr>
<tr>
    <td><label name="Phone Number">Phone Number</label></td>
    <td><input id="phoneNumber" required type="tel" pattern="^[6-9][0-9]{9}$"></td>
</tr>
<tr>
    <td><label name="Email">Email</label></td>
    <td><input id="emailAddress" type="email" required></td>
</tr>
<tr>
    <td><label name="Address" >Address</label></td>
    <td><textarea id="homeAddress" rows="4" cols="50" required placeholder="Enter your
address"></textarea></td>
</tr>
<tr>
    <td name="Number of Players">Number of Players</td>
    <td><select id="numberOfPlayers">
        <optgroup>
            <option>--select--</option>
            <option>Single</option>
            <option>Double</option>
            <option>Multiple</option>
        </optgroup>
    </select></td>
</tr>
<tr>
    <td><label name="Location">Location</label></td>
    <td><input id="locationField" type="text" required></td>

```


</tr>

<!-- Fill code for Player Registration Details as per the specified constraints -->

<tr>

<th>

<label>Sports (with duration) </label>

</th>

<th>

<label>Sports Fee</label>

</th>

</tr>

[Skip to main content](#)

Whatsapp Chat

Description

Objective:

To work with CSS Selectors, Combinators, Responsive Web Design(RWD), and Flexbox.

Concept Explanation:

CSS Selectors: Define patterns to select the elements you want to style on a webpage.

Combinators: Symbols that specify the relationship between selectors, like descendant, child, or adjacent sibling.

Responsive Web Design (RWD): Approach to design and development where content adjusts dynamically to fit various screen sizes and devices.

Flexbox: CSS layout model providing an efficient way to arrange, align, and distribute space among elements in a container.

Concept Implementation:

The styles for the WhatsApp Chat Window can be implemented using CSS properties by employing class selectors to style various elements, child selectors to target direct children within the chat body, adjacent sibling selectors to style timestamp elements next to message text, and Flexbox properties to create a flexible and responsive layout for the chat container and its items.

Problem Description:

You are tasked with styling a WhatsApp Chat Window to enhance its visual appeal and ensure it is responsive across different devices. The HTML structure of the chat window has already been created for you. Your goal is to apply various CSS techniques, to achieve a modern and functional design.

Selectors and Combinators	Constraints
class selector .message_incoming .message_outgoing	To the elements with the message_incoming class, set the alignment of flex items to the start of the vertical axis. For the elements with the message_outgoing class, set the alignment of flex items to the end of the vertical axis.
child selector .chat_body > .message_incoming all elements with the class message_incoming that are direct children of the element with the class chat_body. .chat_body > .message_outgoing all elements with the class	Set the display property of the elements with these 2 classes to flex, to enable flexbox layout. Set the direction of the flex containers' main axis to column. Set their margin-bottom property to 8px, so that the bottom of each message container will have some spacing between messages.

message_outgoingthat are direct children of the element with the class chat_body.	
space selector .message_incoming .message_text .message_outgoing .message_text	Elements with message_text class within elements with message_incoming class must be set with the background color: #dbfac0. Elements with message_text class within elements with message_outgoing class must be set with the background color: #d9f5c4.
adjacent sibling selector .message_text + .message_timestamp	The adjacent sibling selector (+) must target the timestamp element that immediately follows the message text element. Set the font size to 10 pixels, color to #010d0f, and top margin to 2 pixels.
class selector .chat_footer .message_input	Set the display property of the element with class chat_footer to flex, to enable flexbox layout, and align the items in it to the center. Set the flex-grow property of the element with class message_input to 1.This will flex item to grow and fill available space along the main axis of the flex container.
For screens with maximum width of 600px: .chat_footer .send_button	To the element with class chat_footer, set the direction of the flex containers' main axis to column. Align the element with class send_button to the center of its container element, which is typically the chat footer.

<!DOCTYPE html>

<html>

<head>

<link rel="stylesheet" href="style.css">

<meta name="viewport" content="width=device-width, initial-scale=1.0">

</head>

<body>

<div class="chat_container">

<div class="chat_header">

WhatsApp

</div>

```
<div class="chat_body">

  <div class="message_incoming">

    <div class="message_text">Hello, how are you?</div>

    <div class="message_timestamp">10:00 AM</div>

  </div>

  <div class="message_outgoing">

    <div class="message_text">I'm good, thanks!</div>

    <div class="message_timestamp">10:02 AM</div>

  </div>

  <div class="message_incoming">

    <div class="message_text">Did you watch the latest movie?</div>

    <div class="message_timestamp">10:05 AM</div>

  </div>

  <div class="message_outgoing">

    <div class="message_text">Yes, it was amazing!</div>

    <div class="message_timestamp">10:09 AM</div>

  </div>

  <div class="message_incoming">

    <div class="message_text">What did you like the most about it?</div>

    <div class="message_timestamp">10:10 AM</div>

  </div>

  <div class="message_outgoing">

    <div class="message_text">I loved the plot twists and the cinematography!</div>

    <div class="message_timestamp">10:11 AM</div>

  </div>

  <div class="message_incoming">

    <div class="message_text">Agreed! The cinematography was exceptional.</div>

    <div class="message_timestamp">10:12 AM</div>

  </div>

</div>

<div class="chat_footer">
```

```
<input type="text" class="message_input" placeholder="Type a message...">
<button class="send_button">Send</button>
</div>
</div>
</body>
</html>
```

[Skip to main content](#)

Calculator

Description

Objective:

To work with CSS Selectors, Flexbox, and Grid Layouts.

Concept Explanation:

CSS Selectors: Define patterns to select the elements you want to style on a webpage.

Combinators: Symbols that specify the relationship between selectors, like descendant, child, or adjacent sibling.

Flexbox: CSS layout model providing an efficient way to arrange, align, and distribute space among elements in a container.

Concept Implementation:

The styles given below can be implemented using CSS properties:

Use class selector to style flexbox layout, class selector and row selector to style grid layout, pseudo-classes selector to click, focus, hover.

Problem Description:

Apply styles to the web page with a simple Calculator that has already been created for you, adhering to the requirements specified.

Styling using Class Selector :

Styles applied to element with class - container :

Set the container element with a flexbox layout.

Center align the items within the flex container along the horizontal axis and vertical axis.

Styles applied to element with class - buttons :

Set the container element to use a grid layout.

The layout should have 4 columns, each with a width of 54 pixels.

Specify the gap between the grid columns to be 19 pixels.

Styles applied to element with class - row :

Set the container element to use a grid layout.

Specify the gap between the grid rows to be 9 pixels.

Styles applied to the button element with various pseudo-classes :

When the mouse pointer hovers (:hover) over the button, the background color of the button must be set to #575555.

When the button is clicked (:active), the background color of the button must be set to #2ecc71.

When the button receives focus (:focus), then the outline that appears around the button must be set to "2px solid orange"

On hovering, On focus, When active/clicked :

- [index.html](#)
- [style.css](#)

client

- [TerminalX](#)
- [FeedbackX](#)

[Next activity](#) **4*4 Sudoku**

Kudos! You have earned some XP points.

```
<!DOCTYPE html>
```

```
<html>
```

```
<head>
```

```
<link rel="stylesheet" href="style.css">

</head>

<body>

  <div class="container">

    <div class="calculator">

      <input type="text" class="display" readonly>

      <div class="buttons">

        <div class="row">

          <button>7</button>

          <button>8</button>

          <button>9</button>

          <button class="operator">+</button>

        </div>

        <div class="row">

          <button>4</button>

          <button>5</button>

          <button>6</button>

          <button class="operator">-</button>

        </div>

        <div class="row">

          <button>1</button>

          <button>2</button>

          <button>3</button>

          <button class="operator">*</button>

        </div>

        <div class="row">

          <button class="zero">0</button>

          <button>.</button>

          <button class="equal">=</button>

          <button class="operator">/</button>

        </div>

      </div>

    </div>

  </div>

</body>
```



```
        </div>

    </div>

</div>

</div>
</body>
</html>

/* Base styles */
.container {

    /* Fill code here */

    display: flex;

    align-items: center;

    justify-content: center;

    height: 100vh;

}

.calculator {

    width: 320px;

    height: auto;

    background-color: #222222;

    color: #ffffff;

    border-radius: 10px;

    padding: 20px;

    box-sizing: border-box;

}

.display {

    width: 100%;

    height: 60px;

    margin-bottom: 20px;

    font-size: 36px;

    text-align: right;
```

```
background-color: #111111;
color: #ffffff;
border: none;
border-radius: 5px;
}
```

```
.buttons{
  /* Fill code here */
  display: grid;
  /*columns: 4 54px;*/
  grid-template-columns:repeat(4,54px);
  grid-column-gap : 19px;
}
```

```
.row{
  /* Fill code here */
  display: grid;
  grid-row-gap: 9px;
}
```

```
button {
  width: 100%;
  height: 60px;
  background-color: #333333;
  border: none;
  border-radius: 5px;
  font-size: 24px;
  color: #ffffff;
  cursor: pointer;
}
```

```
.operator {  
    background-color: #f0932b;  
}
```

```
.equal {  
    background-color: #2ecc71;  
}
```

```
button:hover {  
    background-color: #575555;  
}
```

```
button:active{  
    background-color:#2ecc71;  
}
```

```
button:focus{  
    outline: 2px solid orange;  
}
```

```
/* Pseudo-classes */
```

```
/* Fill code here */
```

[Skip to main content](#)

4*4 Sudoku

Description

Objective:

To work with CSS Selectors, Flexbox, and Grid Layouts.

Concept Explanation:

CSS Selectors: CSS selectors are patterns used to select the elements you want to style in a webpage, enabling precise targeting based on element type, class, ID, attributes, or relationship to other elements.

Flexbox: Flexbox is a layout model in CSS that provides a more efficient way to design, align, and distribute space among items in a container, allowing for dynamic resizing and alignment of elements in one dimensional either horizontally or vertically.

Grid Layouts: Grid Layouts are a two-dimensional layout system in CSS that enables designers to create complex web layouts with rows and columns, offering precise control over the placement and alignment of elements within a grid structure.

Concept Implementation:

The styles given below can be implemented using CSS properties:

Use Element Selector to style the image, Class Selector to style the heading, container, row, relative, and absolute, Use Pseudo-classes to hover over the image.

Problem Description:

Apply styles to the web page with information on 4*4 Sudoku, that has already been created for you, adhering to the requirements specified.

Styling using Element Selector :

Styles applied to img :

The border radius must be set to 50%, and the left margin must be set to 250px.

Styling using Class Selector :

Styles applied to the element with class heading:

The heading must float to left and the border radius must be set to 6px .
Set its padding and margin to 10px and 25px, respectively.

Styles applied to the element with class desc:

The description must float to the left, in the next line of the heading, and its border radius too must be set to 6px .
Set its padding and margin to 10px and 25px, respectively.

Styles applied to the element with class container:

Set the container to use flexbox layout, and wrap the same.

Styles applied to the element with class row:

Set the width and height of this element to 400px and 100px, respectively.

Set the display property of the element to flex, to enable flexbox layout.

Styles applied to the element with class box:

Set the width and height of this element to 400px and 100px, respectively.

Set the display property of the element to flex, to enable flexbox layout.

Justify the box content and align the items in it to the center.

Styles applied to the element with class relative:

Position the element in relative manner.

Set the width and height of this element to 1000px and 810px, respectively.

Styles applied to the element with class absolute:

Position the element in absolute manner.

Set the top and right attributes of this element to 400px and 0px, respectively.

Style applied to the img element with pseudo-classes - :hover

When the mouse pointer hovers over the image, the image must show itself in 100% greyscale.

Web page after applying all the styles & on hovering over the image, will look like below :

Notes:

- HTML template, CSS and image files are given as part of the code.
- Do not make any changes in the template. Write the code wherever indicated in the given template.
- Fill in the style tag to have the given styles applied to the elements. **(Do not use Inline CSS or shorthand styling, unless mentioned)**
- When there's id or class specified for an element, use the **id selector** or **class selector** to style.
- Else, use **element selector**. (Don't use both the id/class selectors and element selectors at the same time).

- [index.html](#)
- [style.css](#)
- [think.jpg](#)

client

- [TerminalX](#)
- [FeedbackX](#)

[Next activity](#) **JavaScript - The Complete Guide (Beginner + Advanced)**

Kudos! You have earned some XP points.

```
<!DOCTYPE html>
```

```
<html>
```

```
  <head>
```

```
    <link rel="stylesheet" href="style.css">
```

```
  </head>
```

```
  <body>
```

```
    <div class="relative">
```

```
      <div class="heading">Sudoku</div>
```

```
      <div class="desc">
```

```
        <ul>
```

```
          <li>The 4x4 Sudoku for Kids are set to a general difficulty level suitable for kids ages 4 to 8</li>
```

```
          <li>They are easy and perfect for beginners to get acquainted with the dynamics and rules of the game</li>
```

```
          <li>Even adults can use them to learn how to play Sudoku puzzles before graduating to the 9x9 grids!</li>
```

```
          <li>The rules are simple: the kids must fill the blanks using only logic while paying attention not to repeat a digit in the same row or column</li>
```

Each Sudoku puzzle has only one possible solution
it
The numbers allocated at the beginning of each puzzle are the clues to unveil

No guessing is allowed! Sudoku is a game of logic!!

</div>

<div class="container">

<div class="absolute">

<div class="row">

<div class="box"></div>

<div class="box dark">1</div>

<div class="box dark">4</div>

<div class="box"></div>

</div>

<div class="row">

<div class="box dark">3</div>

<div class="box"></div>

<div class="box"></div>

<div class="box"></div>

</div>

<div class="row">

<div class="box"></div>

<div class="box"></div>

<div class="box"></div>

<div class="box dark">4</div>

</div>

<div class="row">

<div class="box"></div>

<div class="box dark">3</div>


```
        <div class="box dark">2</div>

        <div class="box"></div>

    </div>

</div>

</div>

</div>

</body>

</html>
```

```
img{
    height:40%;
    width:30%;
    /*Fill code here*/
    border-radius: 50%;
    margin-left : 250px;
}

.heading{
    background-color: #9f5919;
    color: white;
    font-size: 40px;
    /*Fill code here*/
    float: left;
    border-radius: 6px;
    padding: 10px;
    margin: 25px;
}

.desc {
    background-color: #b5651d;
    color: white;
    font-size: 20px;
    /*Fill code here*/
    float: left;
```

```
border-radius: 6px;

padding: 10px;

margin: 25px;

}

.container {

    /*Fill code here*/

    display: flex;

    flex-wrap: wrap;

    width: 400px;

    height: 400px;

}

.row {

    /*Fill code here*/

    width: 400px;

    height: 100px;

    display: flex;

}

.box {

    /*Fill code here*/

    width: 400px;

    height: 100px;

    display: flex;

    justify-content: center;

    align-items: center;

    background-color: #b5651d;

    border: 4px solid white;

}

.relative {
```

```
background-color: #BD9A7A;

/*Fill code here*/

position: relative;

width: 1000px;

height: 810px;
}

.absolute {

/*Fill code here*/

position: absolute;

top: 400px;

right: 0px;

}

.dark{p

background-color: #9f5919;

color:white;

font-size: 30px;

}

img:hover{

/*Fill code here*/

/*scale: 1;*/

filter: grayscale(100%);

}
```