Enhanced Gastric Cancer Classification Using Optimized CNN Architecture

Dr. N. Krishnammal
Department of Artificial Intelligence and Data Science
Vel Tech Rangarajan Dr. Sagunthala
R&D Institute of Science and Technology
Avadi, Chennai, India
drkrishnammaln@veltech.edu.in

Yarradoddy Sushanth Reddy
Department of Artificial Intelligence and Data Science
Vel Tech Rangarajan Dr. Sagunthala
R&D Institute of Science and Technology
Avadi, Chennai, India
vtu22734@veltech.edu.in

Maddineni Revanth
Department of Artificial Intelligence and Data Science
Vel Tech Rangarajan Dr. Sagunthala
R&D Institute of Science and Technology
Avadi, Chennai, India
vtu23162@veltech.edu.in

***Abstract*—Gastric cancer remains one of the leading causes of cancer-related mortality worldwide, which underscores the need for accurate and rapid diagnosis that can support timely treatment. Recent advances in medical image analysis using deep learning have created promising opportunities for reliable and scalable computer-aided diagnostic systems. In this work, we develop an optimized gastric cancer contouring and classification model that leverages both histopathological and endoscopic images. The proposed approach integrates hyperparameter optimization, depth-wise separable convolutions, and transfer learning to improve accuracy and computational efficiency. The model is evaluated on multiple benchmark datasets and consistently achieves superior performance in terms of classification accuracy, sensitivity, specificity, and area under the ROC curve (AUC) compared with existing methods. These results demonstrate that the proposed framework provides a distinctive and effective solution for enhanced gastric cancer diagnosis.**

***Index Terms*—Disease classification, optimization, stomach disease, convolutional neural network, image classification, deep learning.**

I. Introduction

Gastric cancer ranks among the leading causes of cancer-related deaths globally. The high mortality rate is largely attributed to diagnosis at advanced stages and complications associated with late detection and treatment. Improving the success rate of gastric cancer treatment critically depends on early diagnosis and accurate assessment of tumour progression, which in turn supports appropriate and timely treatment planning. Conventional clinical workflows primarily rely on the visual assessment of endoscopic and histopathological images by experienced clinicians, which can be subjective, time-consuming, and prone to inter-observer variability.

Recent progress in deep learning, particularly in convolutional neural networks (CNNs), has led to substantial advances in medical image analysis. CNNs can automatically learn high-level spatial and contextual features from medical images, enabling accurate classification of complex patterns associated with cancerous tissue. For gastric cancer image analysis, CNN-based methods have demonstrated superior performance compared with traditional machine learning techniques that depend on handcrafted features and shallow classifiers.

In this context, we propose a CNN-based framework for enhanced gastric cancer classification that not only distinguishes cancerous from non-cancerous tissue but also estimates the percentage of the image area affected by cancer. Standard classification approaches typically provide only binary or multi-class labels, without offering quantitative information about tumour burden. In contrast, the proposed scheme combines categorical classification with percentage-based quantification, thereby providing more informative outputs that can assist clinicians in making safer and more informed diagnostic and treatment decisions.

CNNs constitute a powerful class of machine learning models for automatic, high-level feature extraction and classification in medical image analysis. Their ability to learn discriminative representations directly from raw images allows the development of automated systems for detecting and grading medical conditions, including various types of gastric lesions. This work exploits these capabilities to design an optimized CNN architecture tailored for gastric cancer diagnosis.

II. Literature Review

Several studies have investigated artificial intelligence and deep learning techniques for the detection and classification of gastric cancer. Researchers have not only proposed various models for identifying gastric abnormalities but have also highlighted several challenges that must be addressed to achieve robust and clinically reliable systems [1]. Existing approaches have explored diverse feature extraction and classification strategies to improve detection performance in complex gastric imaging scenarios.



Fig. 1. Stages of gastric cancer.

In [2], the authors employed deep learning methods together with feature optimization techniques to design an effective disease detection system. They proposed a system to detect ulcers and bleeding in wireless capsule endoscopy (WCE) images. The preprocessing pipeline included 3D median filtering, 3D box filtering, and HSV color-space enhancement. Subsequently, geometrical feature extraction was used to generate binary images and masks, which were then exploited for further analysis.

The procedure in [3] included the extraction of shape, color, and texture-sensitive features, which were fused using a serial feature fusion strategy to construct a comprehensive feature set. In the next stage, correlation coefficient analysis and principal component analysis (PCA) were used for feature selection to reduce redundancy and dimensionality while preserving discriminative information [4]. Support vector machine (SVM) classifiers were then trained on the resulting feature set and achieved satisfactory classification accuracy in the detection of gastric abnormalities [5].

In another line of work, handcrafted features were combined with deep learning-based representations for stomach infection classification [6]. The feature extraction stage involved computing discrete cosine transform (DCT) features, color features, and discrete wavelet transform (DWT) features, along with features extracted from the VGG16 network. A genetic algorithm (GA) was applied to this combined feature set to perform optimal feature selection. The resulting deep and classical optimized features were used to train an ensemble classifier, achieving a classification rate of 96.5% [7].

Several researchers have also developed automated deep learning systems that directly utilize deep features for stomach infection detection and early lesion identification [8]. In [9], transfer learning with a pre-trained VGG16 model was adopted, followed by lesion detection and feature extraction from the fully connected layers. Particle swarm optimization (PSO) was then applied to refine the feature set. The selected features were used as input to various classifiers, with the cubic SVM achieving the highest accuracy performance in the experiments [10].

A. Systematic Reviews & Survey Overviews

Systematic reviews and survey studies consistently report a shift in gastric cancer image analysis from traditional image processing and handcrafted feature-based machine learning methods to modern deep learning approaches based on CNNs. Traditional classifiers such as SVM and k-nearest neighbors (k-NN) achieved reasonable performance but often suffered from limited generalization capability and high sensitivity to variations in imaging conditions, acquisition protocols, and lesion appearance. CNN-based methods, by contrast, tend to offer improved robustness and scalability across heterogeneous datasets.

B. CNN-Based Gastric Cancer Classification

CNN-based gastric cancer classification has emerged as an efficient and accurate approach for automated cancer diagnosis, owing to its capacity to learn complex and discriminative features directly from medical images. By combining convolutional, pooling, and fully connected layers within a unified architecture, CNNs can effectively model both local and global image characteristics. In gastric endoscopic and histopathological imaging, such architectures have demonstrated strong performance in distinguishing cancerous from normal regions and in localizing suspicious lesions with high sensitivity and specificity.

C. Image Classification

Image classification is a fundamental task in computer vision that aims to automatically assign predefined labels or categories to images based on their visual content. In medical image analysis, classification plays a central role in disease diagnosis and screening by distinguishing normal from pathological patterns. Modern deep CNN architectures exploit rich texture, shape, and intensity features and can learn hierarchical representations from large-scale datasets. This capability has resulted in significant performance gains over traditional methods in a wide range of medical imaging applications, including gastric cancer detection.

D. Feature Extraction Using Transfer Learning

Transfer learning-based feature extraction has become a widely adopted strategy in medical image analysis, especially when annotated data is limited. Pre-trained deep learning models such as VGG, ResNet, Inception, and DenseNet, originally trained on large-scale natural image datasets, are repurposed to extract meaningful features from medical images. These models can capture both low-level and high-level patterns that are relevant for tasks such as gastric cancer image classification. By leveraging pre-learned knowledge, transfer learning accelerates convergence, reduces overfitting, and improves performance while reducing the need for extensive labeled medical data.

E. Feature Optimization

Feature optimization is a critical step for improving the performance of image classification models by maximizing the relevance and discriminative power of the extracted features. After feature extraction using deep learning or transfer learning architectures, optimization techniques such as

dimensionality reduction, feature selection algorithms, and regularization are applied to remove redundancy and irrelevant information. These strategies reduce computational complexity while preserving or enhancing classification accuracy, thereby enabling more efficient and robust gastric cancer detection systems.

III. Methodology

The proposed method for enhanced gastric cancer image classification is based on an optimized CNN model designed to classify cancerous regions and estimate the percentage of cancerous tissue in input medical images. First, the gastric endoscopic or histopathological images are preprocessed to improve image quality through resizing, normalization, and noise removal. This preprocessing ensures consistent input resolution and intensity distribution across the dataset. Next, feature extraction is performed using a CNN architecture with multiple convolutional layers to automatically learn discriminative spatial features from the images. To further improve model performance, hyperparameter tuning, architectural refinement, and regularization techniques are employed to mitigate overfitting and enhance generalization.

A. Problem Definition

Despite technological advances in medical imaging and diagnostic tools, achieving highly accurate and early detection of gastric cancer remains challenging. This difficulty arises from the heterogeneous appearance of tumours, variations in image quality, and the inherent subjectivity of manual interpretation by clinicians. Many existing automated systems focus solely on binary classification (cancerous vs. non-cancerous), providing limited information about disease severity. Traditional machine learning approaches that rely on handcrafted features often exhibit weak robustness and generalization. Furthermore, numerous deep learning methods do not explicitly quantify the extent of cancer involvement, even though such quantitative information is crucial for treatment planning and prognosis.

B. Data Collection and Preprocessing

For the proposed enhanced gastric cancer classification system, data acquisition involves collecting endoscopic or histopathological images of varying resolutions from medical archives, ensuring a representative set of both cancerous and non-cancerous tissue samples. Preprocessing steps include resizing images to a consistent resolution, normalizing pixel intensities to a common range, and applying noise reduction techniques to reduce artefacts. These steps standardize the input data and improve the reliability of subsequent feature extraction and classification stages.

C. Exploratory Data Analysis

Exploratory data analysis (EDA) is conducted on the curated gastric cancer image dataset to understand its characteristics and identify potential issues before model training. EDA includes assessing the number of images per class, examining class imbalance, and analyzing image quality, size, and intensity distributions. Statistical measures such as mean, standard deviation, and histograms of pixel intensities are computed. EDA also helps to detect irregularities, missing annotations, or imaging artefacts, ensuring that the final dataset is suitable for training an optimized CNN model capable of accurate classification and percentage estimation of cancer involvement.

D. Model Architecture

The architectural framework of the proposed gastric cancer classifier integrates an optimized CNN that performs both classification and percentage-based assessment of cancer. The model comprises multiple convolutional and pooling layers with varying filter sizes to capture diverse texture and spatial features. Batch normalization and dropout layers are incorporated to promote training stability and reduce overfitting. The extracted high-level features are passed through fully connected layers with nonlinear activation functions such as ReLU, followed by a final sigmoid or softmax layer for binary or multi-class classification. Additionally, a regression output head can be integrated to estimate the percentage of cancerous tissue, thereby providing quantitative information alongside categorical predictions. Hyperparameters such as learning rate, number of filters, depth of the network, and regularization coefficients are tuned to achieve high accuracy and clinically meaningful performance.

CNNs are widely recognized as powerful feature extractors for medical imaging tasks. The inferences produced by well-designed CNN architectures have been shown to be highly effective in detecting subtle pathological patterns at low signal levels in various imaging modalities. A typical CNN design includes three key components: convolutional layers (CLs), pooling layers, and fully connected (FC) layers. Convolutional layers compute feature maps by applying learnable filters across local receptive fields, while pooling layers downsample these feature maps to provide translation invariance and reduce computational cost. Fully connected layers then combine the extracted features to produce final predictions.



Fig. 2. Architectural flow of the proposed optimized CNN model.

The convolutional filters operate as sliding windows over the input images, computing dot products between the filter weights and local pixel regions (e.g., blocks of size 3×3 to 8×8). As these filters are convolved across the image, they learn

to detect recurring patterns such as edges, textures, and lesion-specific structures at different spatial locations, enabling robust feature extraction for downstream classification and regression tasks.

E. Evaluation Metrics

The performance of the proposed model is assessed using standard classification metrics. Let TP, TN, FP, and FN denote true positives, true negatives, false positives, and false negatives, respectively.

- **Accuracy:** Accuracy measures the proportion of correctly classified samples among all samples.

$$\text{Accuracy} = \frac{TP + TN}{TP + TN + FP + FN} \tag{1}$$

- **Precision:** Precision quantifies the proportion of correctly identified positive cases among all samples predicted as positive.

$$\text{Precision} = \frac{TP}{TP + FP} \tag{2}$$

- **Recall:** Recall (sensitivity) measures the proportion of actual positive cases that are correctly identified by the model.

$$\text{Recall} = \frac{TP}{TP + FN} \tag{3}$$

- **F1-Score:** The F1-score is the harmonic mean of precision and recall, providing a single metric that balances both.

$$F1 = \frac{2 \times \text{Precision} \times \text{Recall}}{\text{Precision} + \text{Recall}} \tag{4}$$

In addition to these metrics, the area under the ROC curve (AUC-ROC) and the mean absolute error (MAE) for percentage estimation are used to evaluate the model's discrimination ability and quantitative prediction performance, respectively.

F. Deep Feature Fusion Results

The deep feature fusion strategy employed in the proposed gastric cancer classification system yields substantial improvements in both accuracy and robustness. By fusing feature representations from multiple layers of the optimized CNN, the model simultaneously exploits low-level texture descriptors and high-level semantic features. This rich, complementary feature space enhances the ability to distinguish malignant from benign regions, particularly in challenging and heterogeneous image samples. The final results, reported in the subsequent section, demonstrate the benefits of feature fusion in terms of improved accuracy, precision, recall, and F1-score, as well as more reliable percentage estimates for malignant regions. These improvements translate into reduced misclassification risk and better generalization across images with varying quality, contrast, and acquisition settings.

IV. Results and Analysis

The proposed gastric disease classification method was evaluated on a challenging gastric image dataset along with additional difficult benchmark datasets. The experiments analyze overall performance as well as class-wise behavior, using metrics such as accuracy, loss, root mean squared error (RMSE), and MAE for both training and testing sets. The results confirm the robustness of the model across different subsets of the data.

TABLE I
Performance of Enhanced Gastric Cancer Classification

Metric	Value
Accuracy (%)	94.5
Precision (%)	93.7
Recall (%)	94.1
F1-Score (%)	93.9
AUC-ROC	0.97
MAE (%)	3.9

We also compare the proposed enhanced CNN model with a baseline image classification framework based on a hybrid architecture combining EfficientNetB6 and DenseNet169. The comparison considers accuracy and loss values for both training and testing phases, highlighting the performance differences between the two approaches.

TABLE II
Performance Metrics for Baseline Gastric Cancer Image Classification

Metric	Value
Accuracy (%)	92.3
Precision (%)	91.5
Recall (%)	92.0
F1-Score (%)	91.7
AUC-ROC	0.95

A. Prediction Performance

The optimized CNN architecture for gastric cancer classification achieves highly competitive predictive performance. As summarized in Table I, the model attains an accuracy of 94.5%, precision of 93.7%, recall of 94.1%, and F1-score of 93.9%, indicating a balanced ability to correctly identify both cancerous and non-cancerous images while keeping false positives and false negatives low. The AUC-ROC value of 0.97 further confirms strong discrimination capability across different decision thresholds. Beyond categorical classification, the model estimates the percentage of cancer-affected tissue with an MAE of 3.9%, providing predictions that closely approximate the true tumour burden. These results underscore the potential of the proposed model as a clinically useful tool to support gastric cancer diagnosis and treatment planning.

As shown in Table III, the enhanced CNN consistently outperforms the baseline image classification model across all major classification metrics, including accuracy, precision, recall, F1-score, and AUC-ROC. Since the baseline model does not perform percentage estimation, the MAE metric



Fig. 3. Confusion matrix of the optimized CNN model.

TABLE III
COMPARATIVE EVALUATION BETWEEN THE PROPOSED ENHANCED CNN AND BASELINE IMAGE CLASSIFICATION

Metric	Image Classification	Enhanced CNN
Accuracy (%)	92.3	94.5
Precision (%)	91.5	93.7
Recall (%)	92.0	94.1
F1-Score (%)	91.7	93.9
AUC-ROC	0.95	0.97
MAE	–	3.9

applies only to the enhanced CNN. Overall, the evaluation demonstrates that the proposed model offers superior classification quality and more informative quantitative outputs.

V. DISCUSSION

This work presents a CNN-based gastric cancer prediction system that serves as a robust classifier, capable of providing both categorical diagnoses of cancerous tissue and quantitative estimates of the percentage area affected by cancer. By combining advanced image processing techniques with an optimized CNN architecture, the system leverages transfer learning and deep feature fusion to extract informative low-level and high-level features from gastric images. The experimental results, including an accuracy of 94.5%, precision of 93.7%, recall of 94.1%, F1-score of 93.9%, AUC-ROC of 0.97, and MAE of 3.9%, demonstrate the effectiveness of the proposed approach for both classification and percentage-based cancer area estimation.

Comparative analysis against a baseline image classification method further confirms the advantages of the proposed architecture. The enhanced CNN shows improved efficiency and reliability for gastric image analysis, whereas baseline methods may fail to provide sufficiently precise or meaningful outputs for clinical decision making. Moreover, the integration of quantitative cancer estimation contributes additional value by enabling clinicians to better assess tumour burden and monitor disease progression over time. Future research can build upon these promising results by investigating multi-class staging of gastric cancer, exploring 3D image analysis, and conducting extensive clinical validation studies.

VI. CONCLUSION AND FUTURE SCOPE

The results of this study demonstrate the development of an effective CNN-based system for precise diagnosis of gastric cancer and estimation of the percentage of tissue affected by cancer. The proposed model delivers superior performance compared with a baseline image classification framework, achieving improvements in key metrics such as accuracy, precision, recall, F1-score, AUC-ROC, and MAE. These gains translate into a substantial enhancement over existing solutions in terms of both diagnostic reliability and quantitative assessment capability.



Fig. 4. Training and validation convergence behavior of the proposed CNN model.

In addition to supporting more accurate identification and validation of diagnostic outputs, the system enables clinicians to assess disease severity and make better-informed treatment decisions. Future extensions of this work may include developing multi-class classification models for detailed cancer staging, incorporating 3D imaging modalities, and integrating the proposed system into real-time clinical workflows. Such advancements would further enhance the applicability of the model in routine gastric cancer screening and management.

ACKNOWLEDGMENT

The authors gratefully acknowledge Vel Tech Rangarajan Dr. Sagunthala R&D Institute of Science and Technology for their support and research facilities. The authors also thank their peers for constructive feedback that improved the quality of this work and their academic advisors for their guidance in refining the methodology and overall study direction.

REFERENCES

[1] M. Iizuka *et al.*, "Deep CNN model for whole-slide gastric histopathology classification using weakly supervised learning," 2020.

[2] Y. Kanavati *et al.*, "Endoscopic cancer classification using EfficientNet-based transfer learning," 2021.

[3] J. Jang *et al.*, "Automated segmentation of gastric carcinoma pathological subtypes using CNN on whole-slide images," 2021.

[4] Bhardwaj *et al.*, "Advanced CNN models with EfficientNetB6 and DenseNet169 for gastric cancer diagnosis," 2024.

[5] Dhinesh *et al.*, "Hybrid CNN model integrating VGG-19 and gradient boosting for histopathological gastric image analysis," 2023.

[6] Y. Xu, L. Wang, and P. Zhang, "Fine-tuned ResNet architectures for gastric cancer detection from endoscopic images," *Applied Soft Computing*, vol. 111, p. 107685, 2021.

[7] Y. Ren, J. Han, and F. Luo, "Explainable CNN framework for endoscopic gastric lesion detection using Grad-CAM visualization," *Medical Physics*, vol. 50, no. 5, pp. 3221–3235, 2023.

[8] L. Gao, P. Chen, and S. Yuan, "Ensemble CNN-based approach for gastric cancer histopathology classification," *Pattern Recognition Letters*, vol. 159, pp. 1–9, 2022.

[9] X.-Y. Feng, X. Xu, and Y. Jin, "Clinical validation of CNN-based artificial intelligence systems for gastric cancer diagnosis," *World Journal of Gastrointestinal Oncology*, vol. 13, no. 9, 2021.

[10] T. Wang, J. Li, and L. Xu, "Optimized CNN models with genetic algorithms for gastric cancer classification," *Expert Systems with Applications*, vol. 247, p. 123456, 2024.

[11] C. C. Chen, J. Yang, and M. Luo, "Transfer learning-based CNN for gastric cancer endoscopy image classification," *Diagnostics*, vol. 12, no. 11, p. 2698, 2022.

[12] Y. Zhou, F. Li, and X. Qiu, "Deep convolutional neural network for gastric carcinoma classification in digital histopathology," 2020.

[13] M. M. Islam, T. N. Poly, Y. C. J. Li, and H.-C. Yang, "Artificial intelligence in gastric cancer: Identifying gastric cancer using endoscopic images with a convolutional neural network," *Cancers*, vol. 14, no. 21, p. 5253, 2022.

[14] X. Guo, H. Zhao, Z. Shi, Y. Wang, and M. Jin, "Convolutional neural networks for gastric cancer diagnosis," *Journal of Software & Systems*, vol. 10, no. 3, pp. 737–745, 2024.

[15] M. Yurdakul and S. Tasdemir, "CoAtNeXt: An attention-enhanced ConvNeXtV2-transformer hybrid model for gastric tissue classification," 2024.

[16] A. K. Kumar and G. R. Kancharla, "An optimized deep learning method for gastric cancer image classification using histopathological images," *Vascular & Endovascular Review*, 2025.

[17] A. D. S. Aroop, D. S. Juliet, and S. Ebenezer, "Optimising gastric cancer classification with QCNN and fine-tuning," *IJECES*, 2025.

[18] "Optimising MobileNetV2 for early gastric cancer detection with dynamic pelican optimiser," *Heliyon*, 2024.

[19] A. Loddo, A. Usai, and C. Di Ruberto, "Gastric cancer image classification: Comparative analysis and feature fusion," *Journal of Imaging*, 2024.

[20] G. R. Mudavadkar *et al.*, "Gastric cancer detection with ensemble learning on digital pathology (GasHisSDB)," *Diagnostics*, 2024.