

1. Pressure Relief Valve

Application : Pressure Relief Valve (P.R.V.) is a mechanical safety device used for relief of excessive pressure build up and Transformer, Top Changer, Pressure Tanks & Pressure Lines for indoor & outdoor application. Suitable for repeated operation as compared to Conventional Explosion Vent which is for single use.

Working : The release Port is sealed by a Stainless-Steel Diaphragm resting on an “O” Ring. Heavy Duty Spring Set keeps the port closed in normal condition. As soon as the pressure exceeds the pre determined safe limit due to any reason like change in temperature, formation of vapor etc. The diaphragm gets lifted from the seat. This exposes the tank pressure to a greater area. Resulting to sudden increase of force. Thus instantaneously opening of release port and allowing vapor, gas & liquid to flow out of tank. Resulting to fall of pressure. The diaphragm restores its normal position as soon as pressure drops below the set limit and is ready for second jump. Spring retainer prevents the dislocation of spring during repeated operation. The lift of diaphragm also operates the Limit Switch (Double Pole/ Double Throw type) & Visual Indicator (Flag) by help of Rod. Engineered for rugged use & long life each P.R.V. is checked for its operational condition individually. It is important to note that depending upon the tank fluid different “O” Ring material is suggested.

Note : - Our standard product feature is

- 1). PRV with Nitrile Rubber Gasket.
- 2). Limit Switch confirms to weather protection IP-67 and is with $\frac{3}{4}$ " 16 T.P.I. (B.S.C.) PVC Cable Gland.

Model :

1. Pressure Relief Valve with Switches

Model:

DP-1

Page :



Model	Port Size	No. of Holes	Bolt Size / Hole Size	P.C.D
DP-1	1"	4	M08 / 10 mm. Ø	85 mm

Models Available

Where: Ø = Size of Release Port (6", 3", 1")

= No. of Electrical Contacts [(1 for 1 N.O. & 1 N.C.) & (2 for 2 N.O. & 2 N.C.)]

S = With Shroud / Oil Direction Cap

P = Number of Pins

C = Number of Cable Cor

Features	Model
Without Electrical Contact & Visual Indicator	DP-Ø
With Electrical Contact & Visual Indicator	DP-ØEF#
With Shroud/ Oil Collection Cap	DP-ØEF#S
With Plug and Socket Type Limit Switch Connection	DP-ØEF#P
With Shroud /Oil Collection Cap & Plug and Socket Connection	DP-ØEF#SP
With Shroud /Oil Collection Cap & Plug and Socket Connection & Cable	DP-ØEF#SPC

DP-3

Page :



Model	Port Size	No. of Holes	Bolt Size / Hole Size	P.C.D
DP-3	3"	4	M10 / 12 mm. Ø	125 mm

Models Available

Where: Ø = Size of Release Port (6", 3", 1")

= No. of Electrical Contacts [(1 for 1 N.O. & 1 N.C.) & (2 for 2 N.O. & 2 N.C.)]

S = With Shroud / Oil Direction Cap

P = Number of Pins

C = Number of Cable Cor

Features	Model
Without Electrical Contact & Visual Indicator	DP-Ø
With Electrical Contact & Visual Indicator	DP-ØEF#
With Shroud/ Oil Collection Cap	DP-ØEF#S

With Plug and Socket Type Limit Switch Connection	DP-ØEF#P
With Shroud /Oil Collection Cap & Plug and Socket Connection	DP-ØEF#SP
With Shroud /Oil Collection Cap & Plug and Socket Connection & Cable	DP-ØEF#SPC

DP-6

Page:



Model	Port Size	No. of Holes	Bolt Size / Hole Size	P.C.D
DP-6	6"	6	M12 / 14 mm. Ø	235 mm

Models Available

Where: Ø = Size of Release Port (6", 3", 1")

= No. of Electrical Contacts [(1 for 1 N.O. & 1 N.C.) & (2 for 2 N.O. & 2 N.C.)]

S = With Shroud / Oil Direction Cap

P = Number of Pins

C = Number of Cable Cor

Features	Model
Without Electrical Contact & Visual Indicator	DP-Ø
With Electrical Contact & Visual Indicator	DP-ØEF#
With Shroud/ Oil Collection Cap	DP-ØEF#S
With Plug and Socket Type Limit Switch Connection	DP-ØEF#P
With Shroud /Oil Collection Cap & Plug and Socket Connection	DP-ØEF#SP
With Shroud /Oil Collection Cap & Plug and Socket Connection & Cable	DP-ØEF#SPC

2. Threaded Pressure Relief Valve

Application : Pressure Relief Valve (P.R.V.) is a safety device to be used in Transformer, Pressure Tanks & Pressure Lines for indoor & outdoor application. Suitable for repeated operation as compared to Conventional Explosion Vent which is for single use. It is compact, highly reliable and particularly designed to be used on O.L.T.C., Transformers, & similar equipment's / tank with non-corrosive liquid.

Features : Spring Safety Valve completely made of Brass /Aluminium, compact, highly reliable and particularly useful for use in transformer & tanks containing non corrosive liquid even in extreme outdoor condition Reliable Operating Pressure from 20 to 100 KPa. (0.20 to 1.00 kg/cm sq.) Positive Resealing Pressure. • Operating Temperature: 0 to 100° C (of tank liquid). Sealing is with Nitrile Rubber Gasket. Valve Resetting Automatic. Suitable for repeated use. Protective Rain Guard Cap directs the Oil Spillage downwards. Flat Mounting Gasket can be provided if required. Depending upon nature of Tank Fluid we can supply with Viton Gaskets and "O" Ring. PRV at different Cracking Pressure (higher/lower) can be supplied as per your request. Normally we supply in Natural Finish. However, if required by customer we can supply with Ni-Cr plated or suitably painted.

Note :

Each of these models have the following features :

- These can be used as an Oil Filling Cap.

- Mounting position preferably at the tank cover or topside is to be provided with leak proof welded suitably threaded boss having matching threads and tightened by help of Teflon Tape / Sealing Liquid.

Other Details :

These are available in two different sizes

- 1). Small Size PRV
- 2). Medium Size PRV

THREADED SMALL SIZE PRV :

These are available only in brass.

Table 1

Parameter	2	3	4
Thread Nomenclature (Ø)	2	3	4
Size of Mounting Thread			
British (B/N)	1/4"	3/8"	1/2"
Metric	M12	M16	M20
Old Model	TS-04	TS-03	TS-04
Passage Area (Appx.) (mm/sq)	30	70	125
Body (A/F) in mm "B" (B.S.P. Thread)	18	22	30
Body (A/F) in mm "N" (N.P.T. Thread)	16	18	24
Body (A/F) in mm "M" (Metric Thread)	18	24	30
Total Length (±) 10 mm (Suit to Assembly)	40	45	55

Table 2

Model Nomenclature	Model 1/4" BSP	3/8" BSP
Plain	BTØ	BB2
With Stainless Steel Pull Ring	BTØR	BN2R
With Cap (Rain Guard)	BTØC	BB2P
With Cap (Rain Guard) and Pull Ring	BTØCR	BB3SR
With Cap (Rain Guard) Riveted / Screwed	BTØCS	BB2SS
With Visual Indicator (Flag)	BTØF	BB3F

Where :

- T - Type of thread (B - BSP, N – NPT, M - Metric)
- Ø - Thread Nomenclature: For B.S.P. & N.P.T. Thread (2-1/4", 3-3/8", 4-1/2")
For Metric Thread – Thread Size e.g. M12

- **C - Cap (Rain Guard) (P - Plastic, S - Stainless Steel, B - Brass)**
-

Note :

Our all models have option of availability in Natural Finish / Nickel Plated.

Page :

THREADED SMALL SIZE PRV :

These are available only in brass.

Thread Nomenclature (Ø)		2	3	4
Size of Mounting Thread	British (B/N)	1/4 "	3/8"	1/2 "
	(Metric)	M12	M16	M20
Old Model		TS-04	TS-03	TS-04
Passage Area (Appx.) (mm/sq)		30	70	125
Body (A/F) in mm "B" (B.S.P. Thread)		18	22	30
Body (A/F) in mm "N" (N.P.T. Thread)		16	18	24
Body (A/F) in mm "M" (Metric Thread)		18	24	30
Total Length (±) 10 mm (Suit to Assembly)		40	45	55

Model Nomenclature	Model	1/4 " BSP	3/8" BSP
Plain	BTØ	BB2	
With Stainless Steel Pull Ring	BTØR	BN2R	
With Cap (Rain Guard)	BTØC	BB2P	
With Cap (Rain Guard) and Pull Ring	BTØCR		BB3SR
With Cap (Rain Guard) Riveted /Screwed	BTØCS	BB2SS	
With Visual Indicator (Flag)	BTØF		BB3F

Where :

- T - Type of thread (B - BSP, N – NPT, M- Metric)
- Ø- Thread Nomenclature: For B.S.P. & N.P.T. Thread (2-1/4", 3- 3/8", 4-1/2") For Metric Thread – Thread Size e.g. M12
- C- Cap (Rain Guard) (P- Plastic S- Stainless Steel, B- Brass)

Note :

Our all models have option of availability in Natural Finish/ Nickel Plated.



BN2R



BB2



BB2SS



BB2P



BB3SR



BB3F

Isme note hata na hai

THREADED MEDIUM SIZE PRV :

THREADED MEDIUM SIZE PRV :

Table 1

Parameter	4	6	8	10				
Thread Nomenclature (Ø)	4	6	8	10				
Size of Mounting Thread								
British (B/N)	1/2"	3/4"	1"	1 1/4"				
Metric NA	M26	M36	M42					
Old Model	T-05	T-06	G-1	G1.25				
Passage Area (Appx.) (mm/sq)				125	250	400	800	
Body (A/F) in mm "B" (B.S.P. Thread)					30	36	40	46
Body (A/F) in mm "N" (N.P.T. Thread)					24	30	36	40
Body (A/F) in mm "M" (Metric Thread)					30	36	45	56
Total Length (±) 10 mm (Suit to Assembly)						55	55	55 70

Table 2

Model Nomenclature	Model 1/2"	3/4"	1"
Plain #TØ	SB8		
With Stainless Steel Pull Ring	#TØR		
With Cap (Rain Guard)	#TØC		BB8P / AB8P
With Cap (Rain Guard) and Pull Ring	#TØCR		
With Cap (Rain Guard) Riveted / Screwed	#TØCS		SB4SS
With Visual Indicator (Flag)	#TØF		
With Oil Collection Bend	#TØO	BB6O	

Where :

- - Material of the body (A - Aluminium, B - Brass, S - Stainless Steel)

- T - Type of Thread (B - BSP, N – NPT, M - Metric)
- Ø - Thread Nomenclature:
 - For B.S.P. & N.P.T. Thread (Ø 3/4", 8 - 1", 10 - 1.25")
 - For Metric Thread – Thread Size e.g. M26
- C - Cap (Rain Guard) (P - Plastic, S - Stainless Steel)

Page :

THREADED MEDIUM SIZE PRV :

Thread Nomenclature (Ø)		4	6	8	10
Size of Mounting Thread	British (B/N)	1/2 "	3/4 "	1"	1 1/4"
	(Metric)	NA	M26	M36	M42
Old Model		T-05	T-06	G-1	G1.25
Passage Area (Appx.) (mm/sq)		125	250	40	800
Body (A/F) in mm "B" (B.S.P. Thread)		30	36	40	46
Body (A/F) in mm "N" (N.P.T. Thread)		24	30	36	40
Body (A/F) in mm "M" (Metric Thread)		30	36	45	56
Total Length (±) 10 mm (Suit to Assembly)		55	55	55	70

Model Nomenclature	Model	1/2 "	3/4 "	1"
Plain	# TØ			SB8
With Stainless Steel Pull Ring	#TØR			
With Cap (Rain Guard)	#TØC			BB8P / AB8P
With Cap (Rain Guard) and Pull Ring	#TØCR			
With Cap (Rain Guard) Riveted /Screwed	#TØCS	SB4SS		
With Visual Indicator (Flag)	#TØF			
With Oil Collection Bend	#TØO		BB6O	

Where :

- #- Material of the body (A- Aluminium, B-Brass, S-Stainless Steel)
- T - Type of Thread (B - BSP, N – NPT, M- Metric)
- Ø- Thread Nomenclature:
For B.S.P. & N.P.T. Thread (6- 3/4", 8- 1", 10-1.25")
For Metric Thread – Thread Size e.g. M26
- C- Cap (Rain Guard) (P- Plastic S- Stainless Steel).

Note :

Our all models have option of availability in Natural Finish/ Nickel Plated.



SB4SS (T-05)



BB6O



BB8P(G-1B)



AB8P(G-1A)



SB8 (G-1S)

Isme Note hatana hai

3. Flange Pressure Relief Valve

FLANGE PRV :

These PRV are mounted directly on holes provided on Tank

Other Details:

Parameter	1"	1.25"	1.5"	1.75"	2"					
Model "P Ø"	P-25	P-32	P-38	P-40	P-50 / P-2					
Passage Area (Appx.) (mm/sq)	500	800	1000	1500	2000					
Number of Holes	2	2	2	3	4					
Mounting Hole Diameter	8	8	10	10	12					
Total Length (±) 20% (Suit to Assembly)				55	65	80	90	100		

Details Nomenclature Table

Details Nomenclature	Model
Basic Nomenclature	FMP-Ø
With Stainless Steel Pull Ring	FMP-ØR
With Cap (Rain Guard)	FMP-ØC
With Cap and Stainless-Steel Pull Ring	FMP-ØCR

Where :

- F - Finish (N - Natural, C – Cr Plated, P - Painted)
 - M - Material of the body (A - Aluminium, B - Brass, I - Mild Steel / Cast Iron, S - Stainless Steel)
 - Ø - Port Diameter (mm)
 - C - Cap (Rain Guard) (P - Plastic, S - Stainless Steel)
 - R - Stainless Steel Pull Ring
-

Models Shown:

- CP-50 / CNP-2
- PIP-38
- PIP-32

- PIP-25S
 - NAP-25S
 - CUSTOM MADE
 - PAP-25P
-

Note :

(If needed, you can add standard note)

Our all models have option of availability in Natural Finish / Nickel Plated.

FLANGE PRV :

These PRV are mounted directly on holes provided on Tank

Other Details:

Port Diameter Ø	1"	1.25"	1.5"	1.75"	2"
Model "P Ø"	P-25	P-32	P-38	P-40	P-50 / P-2
Passage Area (Appx.) (mm/sq)	500	800	1000	1500	2000
Number of Holes	2	2	2	3	4
Mounting Hole Diameter	8	8	10	10	12
Total Length (±) 20% (Suit to Assembly)	55	65	80	90	100

Details Nomenclature	Model
Basic Nomenclature	FMP-Ø
With Stainless Steel Pull Ring	FMP-ØR
With Cap (Rain Guard)	FMP-ØC
With Cap and Stainless-Steel Pull Ring	FMP-ØCR

Where :

- F - Finish (N- Natural, C –Cr Plated, P-Painted)
- M-Material of the body (A- Aluminium, B-Brass, I-Mild Steel/ Cast Iron, S-Stainless Steel)
- Ø- Port Diameter (mm)
- C- Cap (Rain Guard) (P- Plastic, S-Stainless Steel)
- R-Stainless Steel Pull Ring



CP-50 / CNP-2



PIP-38



PIP-25S



NAP-25S



CUSTOM MADE



PAP-25P



PIP-32

2. Oil Level Indicator

Application : Oil level gauge are designed for general industrial use for level monitoring of tanks and similar vessels.

Working :

- Easy to fit these oil Level Gauge gives a clear visibility from distance due to refractive property.
- Depending upon nature of liquid, seal ensures Leak Proof Assembly.

1.Vertical Oil Level Indicator

Application : Oil level gauge are designed for general industrial use for level monitoring of Hermatically Sealed Transformer and tanks and similar vessels.

Working :

- Easy to fit Oil Level Gauge gives a clear visibility from distance due to refractive property.
- Compatible rubber seal ensures Leak Proof Assembly. Features : • UV Protected Polycarbonate Clear window.
- Nitrophyl Float suitable for use in transformer oil.
- Working Temperature- -40 to 120 °C

Mounting Options

Thread Mounting (Vertical)

Mounting Thread	G-1" (1-BSP)	G-1½" (1.5-BSP)	G-2" (2-BSP)
Brass (B)	BB-80*L	BB-120*L	BB-240*L
Aluminium (A)	AB-80L	N/A	N/A

Flange Mounting (Normal)

Model: P-250*L (Body: Aluminium)

Model: BG-1FCL (Flange Mounting)

Model: BG-1FL

2.Threaded Oil Level Indicator

Model: 502 series - Thread Mounting Oil level indicator

- Available in Brass and Aluminium.
- Float Ball give the clear of Oil level.
- Available in 1" and 1 (1)/(2)" Mounting.

3.Prismatic Oil Level Indicator

Model:Prismatic-

Available in Polycarbonate and Acrylic Material .

- Different size are available according to customer need .

4.Tubular Oil Level Indicator

Application : Tubular oil level gauge are designed for general industrial use for level monitoring of tanks and similar vessels.

Working :

Easy to fit these Tubular Oil Level Gauge gives a clear visibility from distance due to refractive property.

Float provided helps to know the Liquid Level from distant.

Depending upon nature of liquid, rubber seal ensures Leak Proof Assembly.

Model (TOLG***) :

Different Models are:

ATOLG***- This model has the feature of tightening its bolt from back. This makes it Anti Theft.

BTOLG***-This model has the feature of tightening its Bolt from front.

Where : *** is the PCD of the mounting holes in mm.

3. Nitrogen Gas Monitoring System

Application : Used in Transformer or other sealed tank while Storing / Transportation to provide constant Nitrogen (N₂) / Inert Gas / Dry Air pressure so as not to allow atmospheric air & moisture to enter Tank.

Working : Gas regulator is used to automatically maintain a positive pressure of 0.05 to 0.50 kg / cm. sq. or as desired (pre information necessary) inside the connected tank by help of attached High Pressure gas cylinder In case pressure falls below set pressure(or as set) due to leakage or temperature variation, regulator automatically allows required additional gas to flow from the attached High-Pressure gas cylinder This builds up the

required pressure. Double Stage regulation beside minimizes the risk also increases the flow rate thus the efficiency of system. To know the inlet & outlet pressure, gauges are attached. Safety valve at High Pressure (H.P) & Low-Pressure (L.P.) is attached so that if any unwanted pressure builds up in regulator chamber is released. High Pressure cylinder is not a standard part of our item / supply

Model :

1.SDGR-02

PAGE :

MODEL	No. of Cylinders	No. of Stages	No. of Gauges	Features
SDGR-02	1 or 2	2	2	Box Mounting.

2.SDGR-02D

Page:

MODEL	No. of Cylinders	No. of Stages	No. of Gauges	Features
SDGR-02 D	1	2	2	Direct Single Cylinder Mounting

3.DGR-02

PAGE:

MODEL	No. of Cylinders	No. of Stages	No. of Gauges	Features
DGR-02	1 or 2	2	2	Box Mounting.

4.DGR-05

PAGE:

MODEL	No. of Cylinders	No. of Stages	No. of Gauges	Features
DGR-05	1 or 2	2	5	Box Mounting. Individual Cylinder Pressure can be visualized

5.TGR-02

PAGE:

MODE L	No. of Cylinder s	No. of Stages	No. of Gauges	Features
TGR-0 2	1 or 2	3	2	Box Mounting. It gives precise control of even very Low Pressure. Gas Purging at Higher Pressure for Conservator without Air Cell can be done by help of 3 Way Valve

4. PRESSURE RELIEF VALVE WITH LIQUID LEVEL INDICATOR

Application :

XD series of Tubular Oil Level gauge is specialized product for hermetically sealed transformers.

It is combo of:

- Pressure Relief Valve at the Top with effective diameter of 1".
- Oil Level Indicator where Blue indicated that the oil is sufficient and red indicates oil is to be refilled.

Pressure Relief Valve (P.R.V.) is a safety device to be used in Transformer, Pressure Tanks & Pressure Lines for indoor & outdoor application. Suitable for repeated operation as compared to Conventional Explosion Vent which is for single use. It is compact, highly reliable and particularly designed to be used on O.L.T.C., Transformers, & similar equipment's / tank with non-corrosive liquid.

Level Indicator is used to know level of liquid in Transformer / Tank for indoor and outdoor application. This product is very useful for hermetically sealed transformers.

Features :

Reliable Operating Pressure from 20 to 70 kPa. (0.20 to 0.70 kg/cm.sq.)

Spring Safety Valve is compact, highly reliable and particularly useful for use in transformer & tanks containing non corrosive liquid even in extreme outdoor condition.

Compact and Rugged Design.

It is to mounted Vertically.

Positive Resealing Pressure.

Operating Temperature: -40° C to 105° C (of tank liquid).

Normally our sealing is with Nitrile Rubber "O" Ring.

Valve Resetting Automatic.

Suitable for repeated use.

Float compatible with Transformer Oil UV Protected Polycarbonate Clear window Each assembly acts as a conservator also.

Models Available

Based on PRV Mounting there are different varieties:

PRV Mounting	Model
Threaded	ALXD
Flange	ALXF

5. PRESSURE ALARM SYSTEM (Same No Changes in page)

6. Tank Components

Application

Tank Valves are especially designed to permit quick inflation, deflation & gauging of containers with / without various standard equipment such as air chucks, deflators & pressure gauge. They provide minimum protrusion within the containers where space is at premium. Widely used in hermetically sealed transformers.

Working

These valves are fitted with VALVE CORE a tiny precise item whose every point serves a specific purpose.

Key Components:

- **Plug:** Single piece construction permits full flow of gas giving clear & fast inflation/ deflation.
- **Teflon Sleeve:** Super slippery, self-swiveling & non-sticky gasket turns as it tightens, thus maintaining a perfect sealing.
- **Ferrule & Plunger Washer:** Scientifically designed to optimum air blast along with cleaning the plunger washer each time valve operates.
- **Spring:** Corrosion Resistant Stainless Steel / Brass coil spring provide right tension for the best seal.
- **Plunger Pin:** Seating at the top & bottom of plunger pin provides positive location for inflation/deflation pressure gauge.

- **Brass Valve Cap:** Provides maximum sealing force with minimum effort. Thus avoiding entry of any dirt particles to the valve mouth to impair the operating efficiency of valve core.

Valve Core with valve housing is yet an ACE OF STANDARDIZATION

Models Available

1. GFV-1

page:

Model	Thread Size	Material	Available in	Remark/Note
GFV-1	1/8"	Brass	Both NPT and BSP	Longer than usual valves (33mm length). Used for special gases like SF6 applications and switchgears

2. GFV-2

page:

Model	Thread Size	Material	Available in	Remark/Note
GFV-2	1/8"	Brass	Both NPT and BSP	Most commonly used model. Specially designed smaller size valve to be mounted from inside of the tank.

3. GFV-3

Page:

Only image

4. GFV-4

PAGE:

Model	Thread Size	Material	Available in	Remark/Note
GFV-4	1/4"	Brass	Both NPT and BSP	---

5. GFV-5

PAGE:

Model	Thread Size	Material	Available in	Remark/Note
GFV-5	---	Both Brass and Aluminium	Without thread	Economical alternative to GFV-2. To be mounted from inside of the tank.

6.GFV-6

PAGE:

Model	Thread Size	Material	Available in	Remark/Note
GFV-6	---	Both Brass and Aluminium	Without thread	Economical alternative to GFV-1. To be mounted from inside of the tank.

Special Options & Variants

GFV-1B Model: Available with 1/8" B.S.P. Mounting Thread, to be fitted with Rubber "O" or Aluminum Washer.

GFV-2B Model: Available with 1/8" B.S.P. Mounting Thread, to be fitted with Rubber "O" or Aluminum Washer.

Brass Cap Options: All models have option of availability with / without Brass Cap.

Finish Options: All models have option of availability in Natural Finish / Nickel Plated.

7. SOLENOID INTERLOCK DEVICE

(SAME PAGE NO CHANGE)