

AI Assisted Coding

Assignment - 02

Name : B.Sushma

RollNo:2303A54040

Batch: 48

Lab2: Exploring Additional AI Coding Tools beyond Copilot – Gemini (Colab) and Cursor AI

Task1: Statistical Summary for Survey Data

❖ **Scenario:** You are a data analyst intern working with survey responses stored as numerical lists.

- **Prompt used:**

"Write a Python function that takes a list of numbers and returns the mean, minimum, and maximum values."

- **Generated code:**

```
import statistics
def analyze_numbers(numbers):
    """
    Calculate the mean, minimum, and maximum of a list of numbers. Args:
    numbers (list): A list of numerical values.
    Returns:
    tuple: A tuple containing (mean, minimum, maximum). Returns
    (None, None, None) if the list is empty.
    """
    if not numbers:
        return None, None, None
    mean_value = statistics.mean(numbers)
    min_value = min(numbers)
    max_value = max(numbers)
    return mean_value, min_value, max_value
```

Example Usage

```
data = [10, 20, 30, 40, 50]
mean, minimum, maximum = analyze_numbers(data)
print(f"List: {data}")
print(f"Mean: {mean}")
print(f"Minimum: {minimum}")
print(f"Maximum: {maximum}")
```

```

data_empty = []
mean_empty,min_empty,max_empty=analyze_numbers(data_empty)
print(f"\nList: {data_empty}")
print(f"Mean: {mean_empty}")
print(f"Minimum: {min_empty}")
print(f"Maximum:{max_empty}")

```

- **SampleOutput:**

List:[10,20,30,40,50]Mean:30Minimum:10Maximum:50 List: []
Mean: None Minimum: None Maximum: None

- **ShortExplanationofLogic:**

The **mean** represents the average of a set of numbers. It is obtained by adding all the values in the list and dividing the sum by the total number of elements.

The **minimumvalue** is the smallest number present in the list, and the **maximumvalue** is the largest number present in the list. These values are calculated using Python's built-in min() and max() functions.

The function accepts a list of numerical values as input, computes the mean, minimum, and maximum values, and displays them as a statistical summary of the given data.

The screenshot shows a Google Colab notebook with the following code and output:

```

import statistics

def analyze_numbers(numbers):
    """
    Calculates the mean, minimum, and maximum of a list of numbers.

    Args:
        numbers (list): A list of numerical values.

    Returns:
        tuple: A tuple containing (mean, minimum, maximum).
        Returns (None, None, None) if the list is empty.
    """
    if not numbers:
        return None, None, None
    mean_value = statistics.mean(numbers)
    min_value = min(numbers)
    max_value = max(numbers)
    return mean_value, min_value, max_value

```

Example Usage

```

data = [10, 20, 30, 40, 50]
mean, minimum, maximum = analyze_numbers(data)

print(f"List: {data}")
print(f"Mean: {mean}")
print(f"Minimum: {minimum}")
print(f"Maximum: {maximum}")

data_empty = []
mean_empty, min_empty, max_empty = analyze_numbers(data_empty)
print(f"List: {data_empty}")
print(f"Mean: {mean_empty}")
print(f"Minimum: {min_empty}")
print(f"Maximum: {max_empty}")

```

Output:

```

List: [10, 20, 30, 40, 50]
Mean: 30
Minimum: 10
Maximum: 50

List: []
Mean: None
Minimum: None
Maximum: None

```

The Gemini AI chat window provides the following response:

Write a Python function that takes a list of numbers and returns the mean, minimum, and maximum values.

Certainly! Here's a Python function that takes a list of numbers and returns its mean, minimum, and maximum values. I've also included an example of how to use it.

[Explain the analyze_numbers function](#) [Call the analyze_numbers function with sample data](#)

What can I help you build?

Gemini 2.5 Flash

Task2:ArmstrongNumber–AI Comparison

❖ Scenario: You are evaluating AI tools for numeric validation logic.

- **Promptused(Gemini):**

"Write a Python program to check whether a given number is an Armstrong number."

- **Prompt used (Copilot):**

"Write a Python program to check whether a given number is an Armstrong number."

- **Generated code (Gemini):**

```
def is_armstrong_number(number):  
    """  
    Checks if a given number is an Armstrong number.  
    An Armstrong number (also known as a narcissistic number,  
    pluperfect digital invariant, or plus perfect number)  
    is a number that is the sum of its own digits each raised to the  
    power of the number of digits.  
    Args:  
        number (int): The integer to check. Returns:  
        bool: True if the number is an Armstrong number, False otherwise. """  
    if not isinstance(number, int) or number < 0: return  
    False  
    num_str = str(number)  
    n = len(num_str)  
    sum_of_powers = 0  
    for digit_char in num_str:  
        digit = int(digit_char)  
        sum_of_powers += digit**n  
    return sum_of_powers == number
```

- **Generated code (Copilot):**

```
#!/usr/bin/env python3 """Armstrong  
number checker (task2).  
  
Usage:  
python3 task2.py 153  
python3 task2.py # prompts for input """  
import argparse  
import sys  
  
def is_armstrong(n: int) -> bool:  
    if n < 0:  
        return False  
    digits = [int(d) for d in str(n)]  
    p = len(digits)  
    return sum(d**p for d in digits) == n  
  
def main() -> None:  
    parser = argparse.ArgumentParser(description='Check Armstrong numbers')  
    parser.add_argument('number', nargs='?', type=int, help='integer to check')  
    args = parser.parse_args()
```

```

if args.number is None:
    try:
        s = input("Enter a non-negative integer: ").strip()
        num = int(s)
    except (EOFError, ValueError):
        print("Invalid input", file=sys.stderr)
        sys.exit(1)
    else:
        num = args.number

if is_armstrong(num):
    print(f"{num} is an Armstrong number.")
else:
    print(f"{num} is not an Armstrong number.")

if __name__ == '__main__':
    main()

```

- **Sample Input (Gemini):**

#Test with some numbers

print(f"Is 153 an Armstrong number? {is_armstrong_number(153)}") # Expected: True ($1^3 + 5^3 + 3^3 = 1 + 125 + 27 = 153$)

print(f"Is 9474 an Armstrong number? {is_armstrong_number(9474)}") # Expected: True ($9^4 + 4^4 + 7^4 + 4^4 = 6561 + 256 + 2401 + 256 = 9474$)

print(f"Is 9 an Armstrong number? {is_armstrong_number(9)}") # Expected: True ($9^1 = 9$)

print(f"Is 10 an Armstrong number? {is_armstrong_number(10)}") # Expected: False ($1^2 + 0^2 = 1 \neq 10$)

print(f"Is 123 an Armstrong number? {is_armstrong_number(123)}") # Expected: False

- **Sample Input (Copilot):**

Enter a non-negative integer: 343

- **Sample Output (Gemini):**

Is 153 an Armstrong number? True

Is 9474 an Armstrong number? True

Is 9 an Armstrong number? True

Is 10 an Armstrong number? False

Is 123 an Armstrong number? False

- **Sample Output (Copilot):**

343 is not an Armstrong number.

- **Side-by-Side Comparison Table:**

| Feature | Google Gemini | GitHub Copilot |
|---------------------|--------------------------------------|--------------------------------|
| Code structure | Uses a separate function | Written directly in main logic |
| Readability | Very clear and modular | Simple and straightforward |
| Logic clarity | Easy to understand with function | Easy but less modular |
| Beginner friendly | High | Medium |
| Explanation support | Provides explanation along with code | No explanation, only code |
| Best use case | Learning and documentation | Fast coding inside editor |

• Side-by-Side Comparison Table:

Analysis : Google Gemini generated a well-structured and modular solution using a function, making it suitable for learning and reuse. GitHub Copilot produced a concise and direct implementation, which is efficient for quick development within an IDE. Both tools correctly implemented the Armstrong number logic, but Gemini provided better clarity and explanation, while Copilot focused on speed and simplicity.

Conclusion : Both AI tools effectively generated correct Armstrong number checking programs. Google Gemini is more helpful for understanding and learning due to its explanations, while GitHub Copilot is ideal for rapid code generation during development.

The screenshot displays a Google Colab notebook titled 'AI_LAB2.ipynb'. The main code cell contains a Python function `is_armstrong_number` that checks if a given number is an Armstrong number. The function includes detailed comments explaining the logic: it converts the number to a string, iterates through each digit, calculates its power, and sums them up. Below the function, there is an 'Example Usage' section with test cases and their expected results. The Gemini chat interface on the right shows the prompt 'Write a Python program to check whether a number is an Armstrong number.' and the generated code.

```
def is_armstrong_number(number):
    """
    Checks if a given number is an Armstrong number.

    An Armstrong number (also known as a narcissistic number,
    or pluperfect digital invariant, or plus perfect number)
    is a number that is the sum of its own digits each raised
    to the power of the number of digits.

    Args:
        number (int): The integer to check.

    Returns:
        bool: True if the number is an Armstrong number, False otherwise.
    """
    if not isinstance(number, int) or number < 0:
        return False

    num_str = str(number)
    n = len(num_str)
    sum_of_powers = 0

    for digit_char in num_str:
        digit = int(digit_char)
        sum_of_powers += digit ** n

    return sum_of_powers == number
```

Example Usage

```
# Test with some numbers
print(f'Is 153 an Armstrong number? (is_armstrong_number(153))') # Expected: True (1^3 + 5^3 + 3^3 = 1 + 125 + 27 = 153)
print(f'Is 9474 an Armstrong number? (is_armstrong_number(9474))') # Expected: True (9^4 + 4^4 + 7^4 + 4^4 = 6561 + 256 + 2401 + 256 = 9474)
print(f'Is 9 an Armstrong number? (is_armstrong_number(9))') # Expected: True (9^1 = 9)
print(f'Is 10 an Armstrong number? (is_armstrong_number(10))') # Expected: False (1^2 + 0^2 = 1 != 10)
print(f'Is 123 an Armstrong number? (is_armstrong_number(123))') # Expected: False
```

Is 153 an Armstrong number? True
Is 9474 an Armstrong number? True
Is 9 an Armstrong number? True
Is 10 an Armstrong number? False
Is 123 an Armstrong number? False

Gemini

Write a Python program to check whether a number is an Armstrong number.


Okay, here's a Python program that defines a function to check if a number is an Armstrong number, along with some example usage.

Show example usage for is_armstrong_number Explain how the is_armstrong_number function works

Test the analyzer_numbers function with different inputs

What can I help you build?

Gemini 2.5 Flash



Task3:LeapYearValidationUsingCursorAI

❖ Scenario: You are validating a calendar module for a backend system.

- **Prompt 1:**
"Write a Python program to check whether a given year is a leap year."
- **Generated code:**

```
year=int(input("Enter a year:")) #
A year is a leap year if:
#- It is divisible by 4 AND
#- not divisible by 100, UNLESS #- it
is also divisible by 400
if(year%4==0 and year%100!=0) or (year%400==0): print(f"{ year}
is a leap year.")
else:
print(f"{ year} is not a leap year.")
```
- **Prompt 2:**
"Write an optimized Python program with proper conditions and comments to check whether a year is a leap year."
- **Generated code:**

```
year=int(input("Enter a year:"))
```

```
# A year is a leap year if:
```

```
# 1. It is divisible by 400 → leap year
```

```
# 2. Else if it is divisible by 100 → not a leap year # 3.
```

```
Else if it is divisible by 4 → leap year
```

```
# 4. Otherwise → not a leap year
```

```

if year % 400 ==
0:print(f"{year}isaleapyear.")
elif year % 100 == 0:
print(f"{year}isnotaleap year.")
elif year % 4 ==
0:print(f"{year}isaleapyear.")
else:
print(f"{year}isnotaleap year.")

```

- **SampleInput:**


Enter year:2026


- **SampleOutput:**

2026is notaleap year.

- **ShortExplanationofLogic:**

The first version of the code generated by Cursor AI provided basic leap year validation logic. The second prompt resulted in improved code with better readability and clear comments explaining the conditions. The optimized version is easier to understand and more suitable for real-world applications.





Task4:StudentLogic+AIRefactoring(Odd/Even Sum)

❖ Scenario:Company policy requires developerstowrite logic before using AI.

- **Promptused:**
"RefactorthisPythoncodetoimprovereadabilityandefficiency."
- **StudentCode:**

T =(1, 2, 3, 4, 5, 6,7)

even_sum=0

odd_sum=0 for

i in t:

if i% 2 == 0:

even_sum=even_sum+i else:

odd_sum= odd_sum+ i

print("Sumofevennumbers:",even_sum)

print("Sum of odd numbers:", odd_sum)

- **AI Code:**


```
t= (1,2,3,4,5,6,7)
```

```
#Using generatorexpressionswithsumfor clarityand efficiency
```

```
even_sum=sum(i for i in t if i%2==0)odd_sum =  
sum(i for i in t if i % 2 != 0)
```

```
print("Sum of even numbers:", even_sum) print("Sum  
of odd numbers:", odd_sum)
```

- **Sample Output:**

Sum of even numbers: 12

Sum of odd numbers: 16

The screenshot displays a Visual Studio Code editor window with a file named `leap_year.py`. The editor shows the following Python code:

```
1 t = (1, 2, 3, 4, 5, 6, 7)
2
3 # Using generator expressions with sum for clarity and efficiency
4 even_sum = sum(i for i in t if i % 2 == 0)
5 odd_sum = sum(i for i in t if i % 2 != 0)
6
7 print("Sum of even numbers:", even_sum)
8 print("Sum of odd numbers:", odd_sum)
```

On the right side of the editor, a panel titled "Python program for leap year che..." shows a refactored version of the code, highlighting it as "Refactored, more readable and efficient version".

At the bottom, the "Terminal" panel shows the execution of the script. It displays the command `python3 leap_year.py` being run in a terminal window. The output shows that 2026 is not a leap year, 2024 is a leap year, and the sums of even and odd numbers from the tuple (1, 2, 3, 4, 5, 6, 7) are 12 and 16, respectively.