

1.

```
sushmitha@DESKTOP-607RQ7V:~$ nano Week1_1.c
sushmitha@DESKTOP-607RQ7V:~$ gcc Week1_1.c -o Week1_1
sushmitha@DESKTOP-607RQ7V:~$ ./Week1_1
Enter Linux command: uname
Parent PID : 727
Child PID : 728
Linux
Child process completed.
sushmitha@DESKTOP-607RQ7V:~$
```

```
sushmitha@DESKTOP-6O7RQ7V: ~
GNU nano 8.7.1 Week1_1.c
#include <stdio.h>
#include <stdlib.h>
#include <unistd.h>
#include <sys/wait.h>

int main()
{
char cmd[100];
printf("Enter Linex command: ");
scanf("%s", cmd);
pid_t pid = fork();
if(pid == 0)
{
printf("Child PID : %d\n", getpid());
execlp(cmd, cmd, NULL);
perror("Execution Filed");
}
else if(pid > 0)
{
printf("Parent PID : %d\n", getpid());
wait(NULL);
printf("Child process completed.\n");
}
else
{
printf("Fork Failed\n");
}
return 0;
}
```

2. copying the contents from one file to another file

```
sushmitha@DESKTOP-6O7RQ7V:~$ nano input.txt
sushmitha@DESKTOP-6O7RQ7V:~$ nano Week1_2.c
sushmitha@DESKTOP-6O7RQ7V:~$ gcc Week1_2.c -o Week1_2
sushmitha@DESKTOP-6O7RQ7V:~$ ./Week1_2
File copied successfully.
sushmitha@DESKTOP-6O7RQ7V:~$ nano Week1_2.c
```

 sushmitha@DESKTOP-6O7RQ7V: ~

GNU nano 8.7.1

```
#include <stdio.h>
#include <fcntl.h>
#include <unistd.h>

int main()
{
    int src, dest;
    char buffer[1024];
    int bytes;

    src = open("input.txt", O_RDONLY);
    if(src < 0)
    {
        printf("Cannot open source file\n");
        return 1;
    }
    dest = open("output.txt", O_WRONLY | O_CREAT | O_TRUNC, 0644);
    while((bytes = read(src, buffer, sizeof(buffer))) > 0)
    {
        write(dest, buffer, bytes);
    }
    close(src);
    close(dest);

    printf("File copied successfully.\n");
    return 0;
}
```