

## PIPELINES

### 1. Input:

```
sushmitha@LAPTOP-B9O7BO x + v
GNU nano 8.7.1 fifo_write.c
#include <stdio.h>
#include <fcntl.h>
#include <unistd.h>
#include <string.h>

int main(){

int fd;
char message[] = "Hello from Writer";

fd = open("myfifo", O_WRONLY);

write(fd, message, strlen(message) +1);

close(fd);

printf("Messages sent\n");

return 0;

}
```

### Output:

```
sushmitha@LAPTOP-B9O7BO x + v
sushmitha@LAPTOP-B9O7BO6L:~$ nano fifo_write.c
sushmitha@LAPTOP-B9O7BO6L:~$ gcc fifo_write.c -o fifo_write
sushmitha@LAPTOP-B9O7BO6L:~$ ./fifo_write
Messages sent
```

### 2.Input:

```
sushmitha@LAPTOP-B907BO x + v
GNU nano 8.7.1 fifo_read.c
#include <stdio.h>
#include <sys/types.h>
#include <sys/stat.h>

int main(){
if(mkfifo("myfifo",0666)== -1){
perror("mkfifo");
return 1;
}
printf("FIFO Created\n");

return 0;
}
```

Output:

```
sushmitha@LAPTOP-B907B06L:~$ nano fifo_read.c
sushmitha@LAPTOP-B907B06L:~$ gcc fifo_read.c -o fifo_read
sushmitha@LAPTOP-B907B06L:~$ ./fifo_read
FIFO Created
```

3.Input:

```
sushmitha@LAPTOP-B907BO x + v
GNU nano 8.7.1 fifo_create.c
#include <stdio.h>
#include <sys/types.h>
#include <sys/stat.h>

int main(){
if(mkfifo("myfifo",0666)== -1){
perror("mkfifo");
return 1;
}
printf("FIFO Created\n");

return 0;
}
```

Output:

```
sushmitha@LAPTOP-B907B06L:~$ nano fifo_create.c
sushmitha@LAPTOP-B907B06L:~$ gcc fifo_create.c -o fifo_create
sushmitha@LAPTOP-B907B06L:~$ ./fifo_create
mkfifo: File exists
sushmitha@LAPTOP-B907B06L:~$ |
```