

Some Simple Programs

Task 1

Implement the following function:

```
// calculate the number of occurrences of a given value in an
array
public static int calcOccurenceNumber(int arr[], int value) {
    int result=0;
    // insert the code here
    return result;
}
// find the maximal value of an array
public static int findMax(int arr[]) {
    int result=0;
    // insert the code here
    return result;
}
// calculate the number of occurrences of the maximal value
public static int calcMaxOccurenceNumber(int arr[]) {
    int result=0;
    // insert the code here
    return result;
}
```

The functions should be tested like this:

```
public static void main(String[] args) {
    int[] testArray = {12, 12 -234, 2, 777, 12, 777};
    System.out.println("calculated maximal value is: "+
        findMax(testArray)+" should be 777");
    System.out.println("calculated number of occurrences is: "+
        calcOccurenceNumber(testArray, 12)+" should be 3");
    System.out.println("calculated max number of occurrences is: "+
        calcMaxOccurenceNumber(testArray)+" should be 2");
    ....
}
```

Task 2

The English mathematician J. Wallis in 1655 presented the following formula for calculating the number of PI.

$$\prod_{n=1}^{\infty} \frac{(2n)(2n)}{(2n-1)(2n+1)} = \frac{2}{1} \cdot \frac{2}{3} \cdot \frac{4}{3} \cdot \frac{4}{5} \cdot \frac{6}{5} \cdot \frac{6}{7} \cdot \frac{8}{7} \cdot \frac{8}{9} \cdots = \frac{\pi}{2}$$

Implement a function to calculates the number PI, n is a parameter:

```
// use formula according to Wallies
public static double calculatePiAccWallies(int iterNo) {
    double result=1.0;
    // insert your code here
...
}
```

Please do NOT forget that inter arithmetic produces integer results!

Therefore you should convert integer value to double by a cast operator (double) :

```
double result=4/5;
System.out.println(result); // 0
result=(double)4/5;
System.out.println(result); // 0.8
```

Task 3

The Scottish astronomer J. Gregory in 1671 presented the following formula for calculating the number PI.

$$\sum_{n=0}^{\infty} \frac{(-1)^n}{2n+1} = \frac{1}{1} - \frac{1}{3} + \frac{1}{5} - \frac{1}{7} + \frac{1}{9} - \dots = \frac{\pi}{4}$$

Implement a function to calculates the number PI, n is a parameter:

```
// use formula according to Gregory
public static double calculatePiAccGregory(int iterNo) {
    double result=0.0;
    int powerMinusOne=1;
    // insert your code here
...
}
```

Task 4

Test the above defined functions in the following way:

```
double value;
int iterNo=4;
value=calculatePiAccWallies(iterNo);
System.out.println("Wallies for: "+iterNo+"\t"+value);
value=calculatePiAccGregory(iterNo);
System.out.println("Gregory for: "+iterNo+"\t"+value);
iterNo=20;
```

```
value=calculatePiAccWallies(iterNo);  
System.out.println("Wallies for: "+iterNo+"\t"+value);  
value=calculatePiAccGregory(iterNo);  
System.out.println("Gregory for: "+iterNo+"\t"+value);
```

The result should look like:

```
Proper value of PI: 3.141592653589793  
Wallies for: 4  2.9257142857142853  
Gregory for: 4  2.8952380952380956  
Wallies for: 20 3.1015772634382706  
Gregory for: 20 3.09162380666784
```

Andrzej Siemiński