

```
PS C:\Users\SUSI\OneDrive\Desktop\genai_trainpinecone> node query.js
```

```
]
```

Ask me Anything about SQL: what is primary key

Using Pinecone config: { indexName: 'samples', controllerHostUrl: undefined }

Printing top 5 Documents

Rank 1

to the set implementations: the `structuremap` is based on a balanced binary tree and accessing elements takes $O(\log n)$ time, while the `structureunordered_map` uses hashing and accessing elements takes $O(1)$ time on average.

The following code creates a map where the keys are strings and the values are integers:

```
map<string,int> m;
```

```
m["monkey"] = 4;
```

```
m["banana"] = 3;
```

```
m["harpsichord"] = 9;
```

```
cout << m["banana"] << "\n"; // 3
```

If the value of a key is requested but the map does not contain it, the key is automatically added to the map with a default value. For example, in the following code, the key "aybabbu" with value 0 is added to the map.

```
map<string,int> m;
```

```
cout << m["aybabbu"] << "\n"; // 0
```

```
38
```

Rank 2

The function `count` checks if a key exists in a map:

```
if (m.count("aybabbu")) {
```

```
// key exists
```

```
}
```

The following code prints all the keys and values in a map:

```
for (auto x : m) {
```

```
cout << x.first << " " << x.second << "\n";
```

```
}
```

Iterators and ranges

Many functions in the C++ standard library operate with iterators. An iterator is a variable that points to an element in a data structure.

The often used iterators `begin` and `end` define a range that contains all elements in a data structure. The iterator `begin` points to the first element in the data structure, and the iterator `end` points to the position after the last element. The situation looks as follows:

The situation looks as follows:

```
{ 3, 4, 6, 8, 12, 13, 14, 17 }
```

```
↑↑
```

 Get started

 Database

Quickstart

Indexes (1)

Backups

 Assistant

 Inference

 API keys

 Manage

DATABASE USAGE

RUs  2 / 1M

Storage  1.66MB / 2GB

WUs  1.7K / 2M

Search: 10 results (top_k=10)

1

SCORE
1.0002

_id: 00736ab3-7fe2-4a59-a9ef-bf9f2d25a24f
loc.lines.from: 1
loc.lines.to: 21
loc.pageNumber: 48
pdf.info.Author: ""
pdf.info.CreationDate: "D:20180703151359+03'00'"
pdf.info.Creator: "LaTeX with hyperref package"
pdf.info.IsAcroFormPresent: false

[Show 12 more](#)

2

SCORE
0.6958

_id: ac0a6aa4-34d3-4a15-bdad-fc666bbb05f4
loc.lines.from: 1
loc.lines.to: 19
loc.pageNumber: 47
pdf.info.Author: ""
pdf.info.CreationDate: "D:20180703151359+03'00'"
pdf.info.Creator: "LaTeX with hyperref package"
pdf.info.IsAcroFormPresent: false

[Show 12 more](#)

PS C:\Users\SUSI\OneDrive\Desktop\genai_trainpinecone> node query.js

2

2

218

Stored answer in Pinecone record qa-1779359530040

Final Response:

```
[
  {
    rank: 1,
    text: 'to the set implementations: the structuremapis based on a balanced binary tree\n' +
      'and accessing elements takesO(logn) time, while the structureunordered_map\n' +
      'uses hashing and accessing elements takesO(1) time on average.\n' +
      'The following code creates a map where the keys are strings and the values\n' +
      'are integers:\n' +
      'map<string,int> m;\n' +
      'm["monkey"] = 4;\n' +
      'm["banana"] = 3;\n' +
      'm["harpsichord"] = 9;\n' +
      'cout << m["banana"] << "\\n"; // 3\n' +
      'If the value of a key is requested but the map does not contain it, the key\n' +
      'is automatically added to the map with a default value. For example, in the\n' +
      'following code, the key "aybaltu" with value 0 is added to the map.\n' +
      'map<string,int> m;\n' +
      'cout << m["aybaltu"] << "\\n"; // 0\n' +
      '38'
  },
  {
    rank: 2,
    text: 'The functioncountchecks if a key exists in a map:\n' +
      'if (m.count("aybaltu")) {\n' +
      '    // key exists\n' +
      '}\n' +
      'The following code prints all the keys and values in a map:\n' +
      'for (auto x : m) {\n' +
      '    cout << x.first << " " << x.second << "\\n";\n' +
      '}\n' +
      'Iterators and ranges\n' +
      'Many functions in the C++ standard library operate with iterators. Aniterator\n' +
      'is a variable that points to an element in a data structure.\n' +
      'The often used iteratorsbeginandenddefine a range that contains all ele-\n' +
```


PS C:\Users\SUSI\OneDrive\Desktop\genai_trainpinecone> node index.js

Documents loaded.

chunking completed.

Embeddings model loaded.

[

-0.035676900297403336,	0.02067919448018074,	0.004704619292169809,
0.026537032797932625,	-0.05029105022549629,	-0.16263702511787415,
0.07464320957660675,	-0.004593968857079744,	-0.0392242968082428,
0.014838811941444874,	0.07412069290876389,	0.05244540423154831,
0.024248186498880386,	-0.0355895459651947,	-0.01704428158700466,
-0.032389670610427856,	0.01327565312385559,	-0.027636192739009857,
-0.14560452103614807,	-0.029047636315226555,	0.0029109525494277477,
0.05354895070195198,	0.0021155052818357944,	0.023001007735729218,
-0.07671955227851868,	-0.018206903710961342,	0.036103107035160065,
0.04898757487535477,	0.0054113189689815044,	-0.05354077368974686,
0.04813114553689957,	0.019792072474956512,	0.12143835425376892,
-0.029806246981024742,	-0.0022303368896245956,	0.06927875429391861,
-0.024674655869603157,	-0.07868247479200363,	-0.022389570251107216,
0.04622144624590874,	0.04468970000743866,	-0.07921043783426285,
-0.0176420658826828,	-0.026334717869758606,	0.011012181639671326,
0.003921629395335913,	0.012964746914803982,	0.037536706775426865,
0.07678192108869553,	0.005714388098567724,	-0.04046017304062843,
-0.061701755970716476,	-0.010977390222251415,	0.012750825844705105,
0.09151556342840195,	0.01741793192923069,	0.01895410753786564,
-0.023597823455929756,	-0.00165523961186409,	-0.03548949956893921,
-0.03456887602806091,	0.033128928393125534,	-0.011946831829845905,
0.016800440847873688,	0.10341189801692963,	-0.08281534165143967,
-0.02241182141005993,	0.02569510042667389,	-0.05345121771097183,
-0.07810984551906586,	-0.06361131370067596,	-0.010754967108368874,
0.01007383968681097,	0.07209061831235886,	-0.03441225737333298,
0.009379268623888493,	0.01778976432979107,	0.022968705743551254,
0.011541169136762619,	0.0380103774368763,	0.05795690044760704,
-0.07044194638729095,	0.01849963515996933,	0.02845963090658188,
0.014203060418367386,	0.02086000144481659,	0.005321622360497713,
-0.008943027816712856,	-0.050120383501052856,	-0.014696399681270123,
-0.11694052815437317,	-0.02824294939637184,	0.048198800534009933,
0.01857229880988598,	-0.08611014485359192,	-0.016483865678310394,
0.10267853736877441,	-0.03173527866601944,	-0.13756610453128815,
0.22513727843761444,		

... 284 more items

]