

Module 31

Partha Pratin Das

Objectives & Outline

Staff Salary
Processing
C Solution
C++ Solution

Virtual Function Pointer Table

Summary

Module 31: Programming in C++

Virtual Function Table

Partha Pratim Das

Department of Computer Science and Engineering Indian Institute of Technology, Kharagpur ppd@cse.iitkgp.ernet.in

Tanwi Mallick Srijoni Majumdar Himadri B G S Bhuyan



Module Objectives

Module 31

Partha Pratin Das

Objectives & Outline

Staff Salary Processing C Solution C++ Solution

Virtual Function Pointer Tabl

Summar

 Understand Virtual Function Table for dynamic binding (polymorphic dispatch)



Module Outline

Module 31

Partha Pratin Das

Objectives & Outline

Staff Salary Processing C Solution C++ Solution

Virtual Function Pointer Table

Summar

- Staff Salary Processing: RECAP
 - C Solution using Function Pointers
 - C++ Solution using Polymorphic Hierarchy
 - Comparison of C and C++ Solutions
- Virtual Function Table for Polymorphic Dispatch



Staff Salary Processing: Problem Statement: RECAP (Module 29)

Module 31

Partha Pratii Das

Objectives & Outline

Staff Salary Processing C Solution C++ Solution

Virtual Function Pointer Table

- An organization needs to develop a salary processing application for its staff
- At present it has an engineering division only where Engineers and Managers work. Every Engineer reports to some Manager. Every Manager can also work like an Engineer
- The logic for processing salary for Engineers and Managers are different as they have different salary heads
- In future, it may add Directors to the team. Then every Manager will report to some Director. Every Director could also work like a Manager
- The logic for processing salary for Directors will also be distinct
- Further, in future it may open other divisions, like Sales division, and expand the workforce
- Make a suitable extensible design



C Solution: Function Pointers Engineer + Manager: RECAP (Module 29)

Module 31

Partha Pratin Das

Objectives a

Staff Salary Processing C Solution C++ Solutior

Function
Pointer Table

Summar

• How to represent Engineers, Managers, and Directors?

- struct
- How to initialize objects?
 - Initialization functions
- How to have a collection of mixed objects?
 - Array of union
- How to model variations in salary processing algorithms?
 - struct-specific functions
- How to invoke the correct algorithm for a correct employee type?
 - Function switch
 - Function pointers



C Solution: Function Pointers Engineer + Manager + Director

Module 31

Partha Pratir Das

Objectives & Outline

Staff Salary Processing C Solution C++ Solution

Function Pointer Table

Summa

```
#include <stdio.h>
#include <string.h>
typedef enum E_TYPE { Er, Mgr, Dir } E_TYPE;
typedef void (*psFuncPtr)(void *);
typedef struct Engineer { char *name_; } Engineer;
Engineer *InitEngineer(const char *name) { Engineer *e = (Engineer *)malloc(sizeof(Engineer));
    e->name = strdup(name): return e:
void ProcessSalaryEngineer(void *v) { Engineer *e = (Engineer *)v;
    printf("%s: Process Salary for Engineer\n", e->name_);
typedef struct Manager { char *name_; Engineer *reports_[10]; } Manager;
Manager *InitManager(const char *name) { Manager *m = (Manager *)malloc(sizeof(Manager));
   m->name = strdup(name): return m:
void ProcessSalaryManager(void *v) { Manager *m = (Manager *)v;
    printf("%s: Process Salary for Manager\n", m->name );
typedef struct Director { char *name_; Manager *reports_[10]; } Director;
Director *InitDirector(const char *name) { Director *d = (Director *)malloc(sizeof(Director)):
   d->name = strdup(name): return d:
void ProcessSalaryDirector(void *v) { Director *d = (Director *)v;
    printf("%s: Process Salary for Director\n", d->name ):
}
```



C Solution: Function Pointers Engineer + Manager + Director

Module 31

Partha Pratin Das

Objectives & Outline

Staff Salary Processing C Solution C++ Solution

Function Pointer Table

Summary

```
typedef struct Staff {
    E_TYPE type_;
   void *p:
} Staff;
int main() {
    psFuncPtr psArray[] = { ProcessSalaryEngineer.
                            ProcessSalaryManager,
                            ProcessSalaryDirector };
    Staff staff [] = { { Er. InitEngineer("Rohit") }.
                      { Mgr, InitEngineer("Kamala") },
                      { Mgr, InitEngineer("Rajib") },
                      { Er, InitEngineer("Kavita") }.
                      { Er, InitEngineer("Shambhu") },
                      { Dir, InitEngineer("Ranjana") } };
    for (int i = 0: i < sizeof(staff) / sizeof(Staff): ++i)
        psArray[staff[i].type_](staff[i].p);
    return 0:
}
----
Output:
Rohit: Process Salary for Engineer
Kamala: Process Salary for Manager
Rajib: Process Salary for Manager
Kavita: Process Salary for Engineer
Shambhu: Process Salary for Engineer
Ranjana: Process Salary for Director
```



C++ Solution: Polymorphic Hierarchy: RECAP Engineer + Manager + Director: (Module 30)

Module 31

Partha Pratir Das

Objectives & Outline

Staff Salary Processing C Solution C++ Solution

Virtual Function Pointer Table

Summa



- How to represent Engineers, Managers, and Directors?
 - Polymorphic class hierarchy
- How to initialize objects?
 - Constructor / Destructor
- How to have a collection of mixed objects?
 - array of base class pointers
- How to model variations in salary processing algorithms?
 - Member functions
- How to invoke the correct algorithm for a correct employee type?
 - Virtual Functions



C++ Solution: Polymorphic Hierarchy: RECAP Engineer + Manager + Director: (Module 30)

Module 31

Partha Pratin Das

Objectives & Outline

Staff Salary Processing C Solution C++ Solution

Function Pointer Table

Summa

```
#include <iostream>
#include <string>
using namespace std:
class Engineer {
protected:
    string name_;
public:
    Engineer(const string& name) : name_(name) {}
    virtual void ProcessSalarv()
                 { cout << name_ << ": Process Salary for Engineer" << endl; }
};
class Manager : public Engineer {
    Engineer *reports_[10];
public:
    Manager(const string& name) : Engineer(name) {}
   void ProcessSalarv()
         { cout << name_ << ": Process Salary for Manager" << endl; }
1:
class Director : public Manager {
   Manager *reports_[10];
public:
    Director(const string& name) : Manager(name) {}
   void ProcessSalary()
         { cout << name_ << ": Process Salary for Director" << endl; }
1:
```



C++ Solution: Polymorphic Hierarchy: RECAP Engineer + Manager + Director: (Module 30)

Module 31

Partha Pratir Das

Objectives & Outline

Staff Salary Processing C Solution C++ Solution

Virtual Function Pointer Table

Summa

```
int main() {
    Engineer e1("Rohit");
    Engineer e2("Kavita"):
    Engineer e3("Shambhu");
    Manager m1("Kamala");
   Manager m2("Rajib"):
    Director d("Ranjana"):
    Engineer *staff[] = { &e1, &m1, &m2, &e2, &e3, &d };
    for (int i = 0; i < sizeof(staff) / sizeof(Engineer*); ++i) staff[i]->ProcessSalary();
    return 0:
Output:
Rohit: Process Salary for Engineer
Kamala: Process Salary for Manager
Rajib: Process Salary for Manager
Kavita: Process Salary for Engineer
Shambhu: Process Salary for Engineer
```

Ranjana: Process Salary for Director



C and C++ Solutions: A Comparison

Module 31

Partha Pratir Das

Objectives & Outline

Staff Salary Processing C Solution C++ Solution

Virtual Function Pointer Table

Summary

C Solution

- How to represent Engineers, Managers, and Directors?
 - structs
- How to initialize objects?
 - Initialization functions
- How to have a collection of mixed objects?
 - array of union wrappers
- How to model variations in salary processing algorithms?
 - functions for structs
- How to invoke the correct algorithm for a correct employee type?
 - Function switch
 - Function pointers

C++ Solution

- How to represent Engineers, Managers, and Directors?
 - Polymorphic hierarchy
- How to initialize objects?
 - Ctor / Dtor
- How to have a collection of mixed objects?
 - array of base class pointers
- How to model variations in salary processing algorithms?
 - class member functions
- How to invoke the correct algorithm for a correct employee type?
 - Virtual Functions



C and C++ Solutions: A Comparison

C Solution (Function Pointer)

Module 31

C++ Solution

```
#include <stdio.h>
                                                  #include <iostream>
  #include <string.h>
                                                  #include <string>
 typedef enum E_TYPE { Er, Mgr, Dir } E_TYPE;
                                                  using namespace std;
 typedef void (*psFuncPtr)(void *);
 typedef struct { E_TYPE type_; void *p; } Staff;
 typedef struct { char *name_; } Engineer;
                                                  class Engineer { protected: string name_;
 Engineer *InitEngineer(const char *name):
                                                  public: Engineer(const string& name):
  void ProcessSalarvEngineer(void *v):
                                                      virtual void ProcessSalarv(): }:
  typedef struct { char *name_; } Manager;
                                                  class Manager : public Engineer {
 Manager *InitManager(const char *name);
                                                  public: Manager(const string& name);
 void ProcessSalaryManager(void *v);
                                                      void ProcessSalary(); };
 typedef struct { char *name_; } Director;
                                                  class Director : public Manager {
 Director *InitDirector(const char *name):
                                                  public: Director(const string& name);
 void ProcessSalarvDirector(void *v):
                                                      void ProcessSalarv(): }:
 int main() { psFuncPtr psArray[] = {
                                                  int main() {
      ProcessSalaryEngineer,
      ProcessSalaryManager.
      ProcessSalaryDirector }:
      Staff staff[] = {}
                                                      Engineer e1("Rohit");
      { Er. InitEngineer("Rohit") }.
                                                      Manager m1("Kamala"):
      { Mgr, InitEngineer("Kamala") },
                                                      Director d("Ranjana");
      { Dir, InitEngineer("Ranjana") } };
                                                      Engineer *staff[] = { &e1, &m1, &d };
      for (int i = 0; i <
                                                      for(int i = 0; i <
          sizeof(staff)/sizeof(Staff); ++i)
                                                          sizeof(staff)/sizeof(Engineer*); ++i)
         psArrav[staff[i].type ](staff[i].p):
                                                          staff[i]->ProcessSalary():
      return 0:
                                                      return 0:
NPTEL MOOCs Programming in C++
```

C++ Solution (Virtual Function)



Virtual Function Pointer Table

Module 31

Virtual Function Pointer Table

```
Base Class
                                                   Derived Class
```

```
class B {
                                                  class D: public B {
    int i:
                                                       int i:
public:
                                                  public:
   B(int i_): i(i_) {}
                                                       D(int i_, int j_): B(i_), j(j_) {}
                                                           void f(int): // D::f(D*const. int)
        void f(int): // B::f(B*const. int)
virtual void g(int); // B::g(B*const, int)
                                                           void g(int); // D::g(D*const, int)
                                                   }
B b(100):
                                                  D d(200, 500):
B *p = &b;
                                                  B *p = &d;
```

b Object Layout

VFT Object B::g(B*const, int) vft n \rightarrow B::i

| Source Expression b.f(15); | Compiled Expression B::f(&b, 15); |
|----------------------------|-----------------------------------|
| p->f(25); | B::f(p, 25); |

```
b.g(35);
                         B::g(&b, 35);
p->g(45);
                         p->vft[0](p, 45);
```

d Object Layout

| Object | | |
|--------|---------------|---|
| vft | \rightarrow | (|
| B::i | 200 | |
| D::j | 500 | |
| | | |

d.f(15):

```
VFT
D::g(D*const. int)
```

```
Source Expression
                       Compiled Expression
                       D::f(&d. 15):
p->f(25);
                       D::f(p, 25);
```

```
d.g(35);
                       D::g(&d, 35);
p->g(45);
                       p->vft[0](p, 45);
```



Virtual Function Pointer Table

Module 31

Partha Pratir Das

Objectives of Outline

Staff Salary Processing C Solution C++ Solution

Virtual Function Pointer Table

Summar

- Whenever a class defines a virtual function a hidden member variable is added to the class which points to an array of pointers to (virtual) functions called the Virtual Function Table (VFT)
- VFT pointers are used at run-time to invoke the appropriate function implementations, because at compile time it may not yet be known if the base function is to be called or a derived one implemented by a class that inherits from the base class
- VFT is class-specific all instances of the class has the same VFT
- VFT carries the Run-Time Type Information (RTTI) of objects



Virtual Function Pointer Table

Module 31

Partha Pratir Das

Objectives & Outline

Staff Salary Processing C Solution C++ Solution

Virtual Function Pointer Table

Summar

```
class A { public:
    virtual void f(int) { }
    virtual void g(double) { }
    int h(A *) { }
};
class B: public A { public:
    void f(int) { }
    virtual int h(B *) { }
};
class C: public B { public:
    void g(double) { }
    int h(B *) { }
};
A a; B b; C c;
A *pA; B *pB;
```

Source Expression Compiled Expression pA->f(2); pA->vft[0](pA, 2); pA->vft[1](pA, 3.2); pA -> g(3.2);pA->h(&a); A::h(pA, &a); pA->h(&b): A::h(pA, &b): pB->f(2);pB->vft[0](pB, 2); pB->vft[1](pB, 3.2): pB->g(3.2);pB->vft[2](pB, &a); pB->h(&a): pB->h(&b); pB->vft[2](pB, &b);

a Object Layout

| Object | | VFT |
|--------|---|-----------------------|
| vft → | 0 | A::f(A*const, int) |
| | 1 | A::g(A*const, double) |

b Object Layout



c Object Layout





Module Summary

Module 31

Partha Pratir Das

Objectives &

Staff Salary Processing C Solution C++ Solution

Function
Pointer Table

Summary

- Leveraging an innovative solution to the Salary Processing Application in C using function pointers, we compare C and C++ solutions to the problem
- The new C solution is used to explain the mechanism for dynamic binding (polymorphic dispatch) based on virtual function tables



Instructor and TAs

Module 31

Partha Pratii Das

Objectives Outline

Staff Salary Processing C Solution C++ Solutio

Virtual Function Pointer Tabl

Summary

| Name | Mail | Mobile |
|---------------------------------|---------------------------|------------|
| Partha Pratim Das, Instructor | ppd@cse.iitkgp.ernet.in | 9830030880 |
| Tanwi Mallick, <i>TA</i> | tanwimallick@gmail.com | 9674277774 |
| Srijoni Majumdar, <i>TA</i> | majumdarsrijoni@gmail.com | 9674474267 |
| Himadri B G S Bhuyan, <i>TA</i> | himadribhuyan@gmail.com | 9438911655 |