

TASK1:

```
suvishal@Patel: ~/skill_week4 x + -
suvishal@Patel:~$ mkdir skill_week4
cd skill_week4
suvishal@Patel:~/skill_week4$ gcc --version
gcc (Ubuntu 15.2.0-16ubuntu1) 15.2.0
Copyright (C) 2025 Free Software Foundation, Inc.
This is free software; see the source for copying conditions. There is NO
warranty; not even for MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.

suvishal@Patel:~/skill_week4$ nano task1.c
suvishal@Patel:~/skill_week4$ gcc task1.c -o task1
suvishal@Patel:~/skill_week4$ ./task1
myShell> echo Hello
--- Parsed Tokens ---
Token 1: echo
Token 2: Hello
Parent Process PID: 960
Created Child PID: 963
Child Process PID: 963
Hello
Child exited with status: 0
Command execution completed.
myShell> ls
--- Parsed Tokens ---
Token 1: ls
Parent Process PID: 960
Child Process PID: 964
Created Child PID: 964
task1 task1.c
Child exited with status: 0
Command execution completed.
myShell> pwd
--- Parsed Tokens ---
Token 1: pwd
Parent Process PID: 960
Created Child PID: 965
Child Process PID: 965
/home/suvishal/skill_week4
Child exited with status: 0
Command execution completed.
myShell> exit
Shell terminated.
suvishal@Patel:~/skill_week4$ |
```

TASK2:

```
suvisal@Patel:~/skill_week4$ nano task2.c
suvisal@Patel:~/skill_week4$ gcc task2.c -o task2
suvisal@Patel:~/skill_week4$ ./task2
myShell> echo Hello
Parsing Result:
Argument 1: echo
Argument 2: Hello
Child PID: 1028
Hello
Child exited with status: 0
Command execution completed.
myShell> echo 'Hello World'
Parsing Result:
Argument 1: echo
Argument 2: Hello World
Child PID: 1029
Hello World
Child exited with status: 0
Command execution completed.
myShell> exit
Shell terminated.
suvisal@Patel:~/skill_week4$ |
```

TASK3:

```
suvisal@Patel:~/skill_week4$ nano task3.c
suvisal@Patel:~/skill_week4$ gcc task3.c -o task3
suvisal@Patel:~/skill_week4$ ./task3
myShell> echo "Hello World"
--- Parsed Arguments ---
Argument 1: echo
Argument 2: Hello World
Child Process
PID = 1113
Hello World
Child process completed.
myShell> echo "Hello $USER"
--- Parsed Arguments ---
Argument 1: echo
Argument 2: Hello korsa
Child Process
PID = 1116
Hello korsa
Child process completed.
myShell> exit
Shell terminated.
suvisal@Patel:~/skill_week4$ |
```

TASK4:

```
suvishal@Patel:~/skill_week4$ nano task4.c
suvishal@Patel:~/skill_week4$ gcc task4.c -o task4
suvishal@Patel:~/skill_week4$ ./task4
myShell$ echo Hello World
--- Parsed Arguments ---
Argument 1: echo
Argument 2: Hello World
Parent Process PID: 1179
Created Child PID: 1203
Child Process PID: 1203
Hello World
Child exited with status: 0
Command execution completed.
myShell$ echo Hello\@World
--- Parsed Arguments ---
Argument 1: echo
Argument 2: Hello@World
Parent Process PID: 1179
Created Child PID: 1206
Child Process PID: 1206
Hello@World
Child exited with status: 0
Command execution completed.
myShell$ echo \$USER
--- Parsed Arguments ---
Argument 1: echo
Argument 2: $USER
Parent Process PID: 1179
Child Process PID: 1212
Created Child PID: 1212
$USER
Child exited with status: 0
Command execution completed.
myShell$ exit
Shell terminated.
suvishal@Patel:~/skill_week4$ |
```

TASK5: