

Week 1: Basics & Implementation

Topics: - Input/Output, Loops, Conditionals - Arrays, Strings, Basic Math - Simple sorting

Weekly Tips: - Focus on writing clean, readable code. - Always test edge cases (0, 1, negative numbers, large numbers). - Use online judge IDE or local compiler to verify behavior.

Week 2: Ad-hoc & Simulation

Topics: - Simulation - Ad-hoc logic problems - Greedy basics

Weekly Tips: - Think step by step, simulate processes on paper first. - Carefully read problem constraints to optimize loops. - Greedy approach works if problem guarantees local optimality leads to global optimality.

Week 3: Sorting & Searching

Topics: - Sorting algorithms: QuickSort, MergeSort, STL sort - Binary Search & Ternary Search - Two-pointer technique

Weekly Tips: - Always check if STL sort suffices before implementing manually. - Binary search can be applied to sorted arrays or answer space. - Two-pointer technique is useful for finding pairs, sums, or sliding windows.

Week 4: Strings & Pattern Matching

Topics: - String searching: KMP, Rabin-Karp - Palindromes & substrings - Prefix/Suffix techniques

Weekly Tips: - Understand failure function in KMP for linear-time matching. - Use rolling hash for fast substring comparison. - Practice manipulating strings efficiently with STL.

Week 5: Recursion & Backtracking

Topics: - Recursion basics - Backtracking: N-Queens, subsets, combinations - Depth-First Search (DFS) for combinatorial problems

Weekly Tips: - Draw recursion trees to understand problem flow. - Watch stack usage and avoid unnecessary deep recursion. - Memoization can be applied to optimize repetitive recursive calls.

Week 6: Graph Theory Basics

Topics: - Graph representation: adjacency list & matrix - BFS & DFS traversal - Connected components - Shortest paths (Dijkstra, BFS for unweighted)

Weekly Tips: - Always check graph type: directed, undirected, weighted, unweighted. - Use visited array to avoid revisiting nodes. - For unweighted shortest paths, BFS is sufficient.

Week 7: Dynamic Programming (DP)

Topics: - Introduction to DP: memoization & tabulation - Classic problems: Fibonacci, Knapsack, LIS - Grid DP, state compression

Weekly Tips: - Identify overlapping subproblems and optimal substructure. - Start with recursive solution, then memoize or tabulate. - Practice simple to complex DP to build intuition.

Week 8: Advanced Graph Algorithms

Topics: - Minimum Spanning Trees: Prim, Kruskal - Bellman-Ford for negative weights - Floyd-Warshall for all-pairs shortest paths - Strongly Connected Components (Kosaraju, Tarjan)

Weekly Tips: - MST: Focus on edge selection and cycle prevention. - Bellman-Ford: Detect negative cycles. - Floyd-Warshall: Use DP-like approach for all-pairs shortest path. - SCC: Identify components and condensation graph.

Week 9: Greedy & Interval Problems

Topics: - Activity Selection Problem - Interval Scheduling - Interval Covering - Fractional Knapsack

Weekly Tips: - Always sort intervals by finishing time for scheduling problems. - Greedy works when local optimum leads to global optimum. - Pay attention to edge cases where intervals overlap. - Fractional Knapsack can be solved using sorting by value/weight ratio.

Week 10: Advanced Dynamic Programming

Topics: - DP on Trees - Bitmask DP - Sequence DP with constraints (e.g., subsequences, partitions) - Optimization techniques: prefix sums, cumulative DP

Weekly Tips: - DP on trees: use DFS and store DP for subtrees. - Bitmask DP: useful for problems with small n (≤ 20) subsets. - Sequence DP: carefully define states and transitions. - Optimize using cumulative sums, monotonic queues when possible.

Week 11: Network Flow & Matching

Topics: - Max Flow (Ford-Fulkerson, Edmonds-Karp) - Min Cut - Bipartite Matching (Hungarian Algorithm, Hopcroft-Karp) - Flow-based problem solving

Weekly Tips: - Max Flow: Understand residual graph and augmenting paths. - Min Cut: Relates to Max Flow by MFMC theorem. - Bipartite Matching: Use flow or DFS-based approaches. - Practice transforming problems into flow networks.

Week 12: Geometry & Computational Geometry

Topics: - Points, Lines, and Vectors - Distances and Angles - Convex Hull (Graham Scan, Andrew's Algorithm) - Polygon Area and Intersection - Line Sweep and Geometric Algorithms

Weekly Tips: - Use structures/classes for points and vectors for clarity. - Pay attention to precision and rounding errors with floating points. - Start with simple geometry: distances, dot/cross product. - Convex hull is fundamental for many polygon problems. - Line sweep technique is useful for intervals and intersections.

Week 13: String Algorithms & Advanced Pattern Matching

Topics: - Suffix Arrays & LCP arrays - Trie (Prefix Tree) - Z-Algorithm for pattern matching - String Hashing (Rabin-Karp) - Aho-Corasick Algorithm

Weekly Tips: - Suffix arrays allow fast substring search and comparison. - Tries are useful for prefix-based problems and autocomplete. - Z-algorithm computes matching prefixes efficiently. - Rolling hash (Rabin-Karp) allows constant-time substring hashing. - Aho-Corasick handles multiple pattern matching efficiently.

Problem 1: Suffix Array Construction

Link: [CSES Distinct Substrings](#) **Difficulty:** Advanced

C++ Solution with Explanation Comments:

```
#include <bits/stdc++.h>
using namespace std;
int main(){
    string s; cin>>s; s+='$';
    int n=s.size();
    vector<int> p(n), c(n);
    // k=0 sorting single characters
    vector<pair<char,int>> a(n);
    for(int i=0;i<n;i++) a[i]={s[i],i};
```

```

sort(a.begin(),a.end());
for(int i=0;i<n;i++) p[i]=a[i].second;
c[p[0]]=0;
for(int i=1;i<n;i++) c[p[i]] = c[p[i-1]] + (a[i].first!=a[i-1].first);
int k=0;
vector<int> pn(n), cn(n);
while((1<<k)<n){
    for(int i=0;i<n;i++){
        pn[i] = (p[i] - (1<<k) + n)%n;
    }
    vector<int> cnt(n,0);
    for(int x:c) cnt[x]++;
    vector<int> pos(n); pos[0]=0;
    for(int i=1;i<n;i++) pos[i]=pos[i-1]+cnt[i-1];
    for(int x:pn){
        p[pos[c[x]]]=x;
        pos[c[x]]++;
    }
    cn[p[0]]=0;
    for(int i=1;i<n;i++){
        pair<int,int> prev={c[p[i-1]],c[(p[i-1]+(1<<k))%n]};
        pair<int,int> now={c[p[i]],c[(p[i]+(1<<k))%n]};
        cn[p[i]]=cn[p[i-1]] + (now!=prev);
    }
    c=cn; k++;
}
for(int i=1;i<n;i++) cout<<p[i]<<" ";
}

```

Explanation Comments: - Constructs suffix array using doubling algorithm. - $p[i]$ stores starting index of i -th lexicographically smallest suffix. - $c[i]$ stores equivalence class to compare substrings.

End of Week 13 - Focus on efficient substring and pattern matching techniques. - Understand the use cases for each string algorithm. - Practice problems involving substring counts, pattern searches, and multi-pattern matching.