R290 Heat Pump Water Heater(Side Discharge)

HIGHLY Full DC
Inverter Compressor

Enamel Water Tank

Micro-channel
Heat Exchanger

RENESA Chip



Self-developed
Plug&Play Mainboard

User-friendly
Controller

R290 Refrigerant

COP 5.2
A20/15, W15/55

STC: 36

Smart Energy
Management System

Smart APP &
Web IOT Platform

WaterMark

Specification

Product Picture				
Model		**GHWVSH-210AA1**	**GHWVSH-270AA1**	**GHWVSH-320AA1**
Power Supply	V/Ph/Hz	220~240V/50Hz/60Hz		
Rated Heating Capacity	kW	3	3	3
Rated Power Input	kW	0.577	0.577	0.577
COP	/	5.2	5.2	5.2
Maximum Powert Input	kW	3.1	3.1	3.1
Maximum Current Input	A	16	16	16
Water tank Volume	L	210	270	320
Refrigerant	/	R290		
Heat Exchanger	/	Microchannel		
Defrosting method	/	by 4-way valve		
Water Proof Level	/	IPX4		
Max Water Tank Pressure	MPa	0.85		
Outer Casing / Shape	/	METAL		
Expansion Valve	/	Electronic		
Air Flow	m^3/h	1000		
Air Discharge	/	Horizontal		
Air Duct Diameter	/	Non-ducted		
Electric Heater — Rated Power	kW	1.6		
Electric Heater — Rated Current	A	7.1		
Default Water Temperature	°C	60		
MAX Water Temperature	°C	75		
Operating Ambient Temperature	°C	-7-46		
Noise	dB(A)	43		
Water Pipe Diameter	inch	G3/4		
Net Weight	kg	116	130	146
Gross Weight	kg	126	150	166
Unpacked Dimension(L×W×H)	mm	650×650×1650	650×650×1870	650×650×2090
Packed Dimension(L×W×H)	mm	720×720×1785	720×720×2005	720×720×2225
Loading qty(20GP/40HQ)	/	21/45	21/45	21/45
Heating Capacity at Air 20°C/15°C, Water Temperature from 15°C to 55°C				
Note: The data above is for reference only. Please refer to the nameplate on the unit if for more specific data.				