R290 Heat Pump Water Heater(Top Discharge)

GMCC Compressor

Enamel/Steel
Water Tank

Micro-channel
Heat Exchanger

RENESA Chip



Self-developed
Plug&Play Mainboard

User-friendly
Controller

R290 Refrigerant

High Temp.
Output:75°C

CE, ErP Certified

Custom Services

Smart APP &
Web IOT Platform

Energy Class A+

Specification

Product Picture								
HEAT PUMP PARAMETERS(Enamel/Duplex)		GHWSVT-100AA1/ GHWSVB-100AA1	GHWSVT-120AA1/ GHWSVB-120AA1	GHWSVT-150AA1/ GHWSVB-150AB1	GHWSVT-150AB1/ GHWSVB-150AA1	GHWSVT-200AA1/ GHWSVB-200AA1	GHWSVT-250AA1/ GHWSVB-250AA1	GHWSVT-300AA1/ GHWSVB-300AA1
Installation Type	/	Wall-mounted	Wall-mounted	Wall-mounted	Floor standing	Floor standing	Floor standing	Floor standing
Power supply	V/Ph/Hz	220-240~/1/50						
Water tank Volume	L	100	120	150	150	200	250	300
Tapping cycle	/	M		L		XL		
Norminal Heating Capacity	kW	1.1				1.6		
Energy Class		A+						
* Heating Capacity at Air 7°C/6°C,Water 15°C in, 55°C out								
Heating Capacity	kW	0.8	0.82	0.84	0.84	1.302/1.23	1.18/1.30	1.18/1.30
Heating Time	H	5.16	6.13	7.18	7.18	6.62	9.77	9.77
COP	/	2.65	2.75/2.65	2.89/2.82	2.89/2.82	2.97/2.93	3.02/3.10	3.02/3.15
Standby power input(7/6°C)	W	30						
Water Heating Energy Efficiency	/	113.76%	113.72%	118.99%	118.99%	122.47%	127.80%	129.60%
* Heating Capacity at Air 14°C/13°C, Water 15°C in, 55°C out								
Heating Capacity	kW	0.94	0.97	1.00	1.00	1.41	1.43	1.43
COP	/	3.05	3.2	3.34	3.34	3.42	3.53	3.53
* Heating Capacity at Air 20°C/15°C, Water 15°C in, 55°C out								
Heating Capacity	kW	0.95	0.98	1.03	1.03	1.48	1.5	1.5
COP	/	3.24	3.45	3.56	3.56	3.65	3.71	3.75
Refrigerant	/	R290						
Electric Heater	kW	1.6						
Sound power level	dB(A)	55						
Max.Water Outlet Temp. (without using backup heater)	°C	65						
Max. Water Outlet Temp.	°C	75						
Operation Range	°C	-7~45						
Water Outlet Temp. setting range	°C	15-75						
Rated Power	W	400+1600 (e-heater)				900+1600 (e-heater)		
Rated Current	A	2.1 +7.1 (e-heater)				3.9 +7.1 (e-heater)		
Rated water yield*	L/H	23.6				34.4		
Air flow	m^3/h	500				450		
Unit protection Indoor unit (IP xx)	/	IPX1						
TANK								
Max allowed pressure of tank	bar	10						
Inner Tank Material		Enamel/ Duplex 2101 /2205, 304 /316L						
CONNECTIONS AND DIMENSIONS								
Hot water outlet	inch	G 1/2				G 3/4		
Cold water inlet	inch	G 1/2				G 3/4		
Size of water drain	inch	G 1/2				G 3/4		
Condensed water outlet	inch	G 1/2						
Net Dimensions (L×W×H)	mm	Ø510*1240	Ø510*1435/ Ø510*1390	Ø510*1660/ Ø510*1616	Ø510*1690/ Ø510*1616	Ø570*1720/ Ø570*1720	Ø650*1720/ Ø650*1626	Ø650*1926/ Ø650*1826
Packing Dimensions (L×W×H)	mm	570×570×1280	570×570×1595/ 570×570×1550	570×570×1845/ 570×570×1800	570×570×1820/ 570×570×1730	640×640×1890/ 640×640×1850	720×720×1850/ 720×720×1756	720×720×2070/ 720×720×1956
Net Weight	kg	51/45	59/48	69/53	71/53	93/66	105/73	117/80
Gross Weight	kg	67/61	75/68	85/76	87/76	109/81	123/91	137/100
Note: The data above is for reference only. Please refer to the nameplate on the unit if for more specific data.								