R134a PV-Powered Heat Pump Water Heater(Split Type)

HIGHLY Full DC
Inverter Compressor

Enamel Water Tank

Full DC Motor

R134a

R134a Refrigerant

Micro-channel
Heat Exchanger



Finned Heat Exchanger

PV Direct Supply

MPPT Function

COP 4.2

Quick Heating

75°C

MAX 75°C Outlet
Water Temperature

Smart APP &
Web IOT Platform

Specification

Product Picture				
Volume		1.5HP 200L	1.5HP 300L	1.5HP 500L
Model		GHWVSHST-200CA1	GHWVSHST-300CA1	GHWVSHST-500CA1
Rated AC Power input(AC)	V/Ph/Hz	208~240V/50~60Hz		
Solar Pannel Power (DC)	V	90V~380V		
Heating capacity	W	4500	5000	
Hot water yield	L/h	100	110	
Power Input	W	1060	1190	
Rated current	A	5.2	5.6	
Max. power input	W	1500	1600	
Max. current input	A	8.5	9.3	
Starting current	A	4.0		
COP	/	4.25	4.20	
Heating type	/	Fluorine Cycle		
Refrigerant type	/	R134a		
IP Class	/	IPX4		
Electrical Shockproof	/	I		
Maximum Allowable Pressure	MPa	3.2		
Maximum Outlet Water temperature	°C	75°C		
Operating Ambient Temperature	°C	-7~46		
Noise	dB(A)	≤52		
Water Piping Connections	inch	G3/4		
Main Unit Net Weight/Gross Weight	kg	33/40		
Main Unit size (L×W×H)	mm	790×312×565		
Packing size (L×W×H)	mm	925×390×598		
TANK				
Water tank volume	L	200	300	500
Water tank Net Weight/Gross Weight	kg	70/79	90/110	130/148
Water tank size	mm	Φ500×1716	Φ600×1700	Φ700×1750
Packing size (L×W×H)	mm	610×610×1760	700×700×1760	800×800×1800
Remark: working condition, Inlet water temperature 15°C, Outlet water temperature 55°C, Dry bulb temperature 20°C, Wet bulb temperature15°C.				
Note: The data above is for reference only. Please refer to the nameplate on the unit if for more specific data.				