R410A Heat Pump Water Heater

Hi-efficient heat pump specialized compressor

Enamel Water Tank

Full DC Motor

Water cycle, environment-friendly refrigerant R410A

Wilo water pumps



Finned Heat Exchanger

Separating the water from electricity

Easy installation & maintenance

24 Hours — 24 hours stable hot water supply

Quick Heating

55°C — MAX 55°C Outlet Water Temperature

Stable Silent Operation

Specification

Product Picture						
Model			GHWSHS -3.6DA1	GHWSHS -5.5DA1	GHWSHS -10.5DA1	GHWSHS -14DA1
Power Supply		V/Ph/Hz	220~240V~/1/50Hz			
Product Technical data						
Heating Capacity		W	3750	5300	10600	14000
Rated Hot Water Production		L/h	80	114	228	300
Rated Power Input		W	882	1232	2524	3325
Rated Current Input		A	4.05	5.66	11.59	14.60
COP (20/15°C, IN 15°C,OUT55°C)		/	4.25	4.30	4.20	4.21
Electric Heater	Rated Power Input	W	2000		4000	
	Rated Current Input	A	9.08	9.10	18.25	18.15
Max.Power Input		W	1450	1920	4400	4650
Max.Current Input		A	7.22	10.50	24.05	26.85
Refrigerant Type		/	R410A			
Operation Pressure(Low Side)		MPa	0.8			
Operation Pressure(High Side)		MPa	4.2			
Maximum Allowable Pressure		MPa	4.4			
Water Tank Volume		L	200~300		300~500	500L
Rated Working Pressure Of Tank		MPa	0.8			
Electronic Expansion Valve		/	DunAn 1.3C	DunAn 1.65C	DunAn 2.0C	DunAn 2.5C
Electrical Shockproof		/	I			
IP Class		/	IPX4			
Max. water temperature		°C	55.0			
Operating Ambient Temperature		°C	-15~46			
Noise		dB(A)	54		55	
Water Piping Connections		inch	G1/2		G3/4	
Net Weight/Gross Weight		kg	50/55	57/62	65/90	70/95
Unit Dimension (L×D×H)		mm	947×370×565		1078×390×705	
Packed Dimensions (L×D×H)		mm	1002×414×591		1130×436×850	
Heating Capacity at Air 20°C/15°C, Water Temperature from 15°C to 55°C						
Note: The data above is for reference only. Please refer to the nameplate on the unit if for more specific data.						