R32 PV-Powered Inverter Swimming Pool Heat Pump

Mitsubishi / GMCC Full DC Inverter Compressor

Full DC Motor

Metal/ABS Casing

DUNAN EEV

Titanium Tube Heat Exchanger



Finned Heat Exchanger

R32 Refrigerant

PV Direct Supply

MPPT Function

Precise water temperature control

Minimum operating temperature -15°C

Smart APP & Web IOT Platform

Specification

Product Picture										
Capacity		7kW	9kW	12kW	15kW	18kW	25kW	35kW	25kW	35kW
Model		GSPVSHP-7BA1	GSPVSHP-9BA1	GSPVSHP-12BA1	GSPVSHP-15BA1	GSPVSHP-18BA1	GSPVSHP-25BA1	GSPVSHP-35BA1	GSPVTHP-25BA1	GSPVTHP-25BA1
* Heating Capacity at Air 26°C, Humidity 80%, Water 26°C in, 28°C out										
Heating Capacity	kW	1.7~7.6	2.3~9.5	3.0~12	3.8~15	4.8~18	6.8~25.0	8.8~35	6.8~25	8.8~35
Power Input	kW	0.11~1.12	0.15~1.40	0.19~1.91	0.24~2.5	0.30~3.09	0.43~4.12	0.56~5.15	0.43~4.12	0.56~5.15
COP	/	6.8~12.8	6.8~12.8	6.8~13	6.8~12.8	6.8~12.8	6.80~12.80	6.8~12.8	6.8~12.8	6.8~12.8
* Heating Capacity at Air 15°C, Humidity 70%, Water 26°C in, 28°C out										
Heating Capacity	kW	1.4~6.1	1.9~7.6	2.3~9.8	3~12.5	3.8~16.5	5.5~22.0	6.4~25.5	5.5~22	6.4~25.5
Power Input	kW	0.18~1.24	0.25~1.55	0.30~1.96	0.39~2.76	0.5~3.37	0.72~4.7	0.84~5.2	0.72~4.7	0.84~5.2
COP	/	4.9~7.6	4.9~7.6	5~7.6	4.9~7.6	4.9~7.6	4.9~7.6	4.9~7.6	4.9~7.6	4.9~7.6
* Cooling Capacity at Air 35°C, Water 29°C in, 27°C out										
Cooling Capacity	kW	1.0~4.2	1.3~5.3	1.7~7.2	2.1~9.4	2.7~11.6	3.8~14.9	4.9~19.3	3.8~14.9	4.9~19.3
Power Input	kW	0.15~1.11	0.19~1.4	0.25~1.89	0.31~2.47	0.4~3.05	0.77~3.92	0.73~5.08	0.77~3.92	0.99~5.08
EER	/	3.5~6.2	3.4~6.0	3.6~6.5	3.6~6.5	3.6~6.5	3.8~6.7	3.5~6.4	3.8~6.7	3.5~6.4
* General data										
DC Power supply	V	90V~380V							310V~560V	
AC Power supply	V/Ph/Hz	220~240V/1/50							380~415V/3/50	
Max Power Input	kW	1.55	1.78	2.55	3.15	3.75	5.17	7.25	6.43	7.25
Max Current	A	7.3	8.3	11.8	14.5	17.5	24.5	33.5	7.9	12.8
Water Flow Volume	m^3/h	2.5	3.5	4.5	5.5	6.5	9	12	9	12
Refrigerant	/	R32								
Heat Exchanger	/	Titanium								
Air Flow Direction	/	Horizontal								
Kind of defrost	/	by 4-way valve								
compressor	/	Mitsubishi								
Casing Material	/	ABS								
Water Proof Level	/	IPX4								
Working temp. range	°C	-15~43								
Water Pipe connection size	/	DN50								
Noise level 1m	dB(A)	39~49	40~52	42~53	43~55	45~56	47~58	49~59	47~58	49~59
Noise level 10m	dB(A)	20~29	20~32	22~33	23~35	25~36	27~38	29~39	27~38	29~39
Net Weight	kg	42	43	43	46	50	69	80	70	81
Gross Weight	kg	53	54	57	59	64	85	96	86	97
Net Dimensions (L×W×H)	mm	880×340×590		920×380×650			1092×445×742			
Package Dimensions (L×W×H)	mm	930×400×640		990×400×761			1150×460×870			
Note: The data above is for reference only. Please refer to the nameplate on the unit if for more specific data.										