R32 Swimming Pool Heat Pump (Double-side Airflow Outlet)

Mitsubishi / GMCC Full DC Inverter Compressor

Full DC Motor

Metal Casing

DUNAN EEV

Titanium Tube Heat Exchanger



Finned Heat Exchanger

R32 Refrigerant

COP 16

Low Noise

Precise water temperature control

Minimum operating temperature -15°C

Smart APP & Web IOT Platform

Specification

Product Picture												
Capacity		7kW	9kW	12kW	15kW	18kW	21kW	25kW	28kW	21kW	25kW	28kW
Model		GSPVSD-7BA1	GSPVSD-9BA1	GSPVSD-12BA1	GSPVSD-15BA1	GSPVSD-18BA1	GSPVSD-21BA1	GSPVSD-25BA1	GSPVSD-28BA1	GSPVSD-21BA1	GSPVSD-25BA1	GSPVSD-28BA1
Heating Condition#1: (DB/WB) 27°C/24.3°C; Water Inlet/Outlet Temperature: 26°C/28°C.												
Heating Capacity	kW	7.5~1.6	9.5~2.3	11.5~3.0	15.0~3.8	18.0~4.8	20.5~5.6	24.2~6.8	28.6~7.2	21.5~5.6	25~6.8	28.6~7.2
Power Input	kW	1.12~0.11	1.40~0.15	1.91~0.19	2.5~0.24	3.09~0.30	3.34~0.33	4.12~0.43	4.39~0.49	3.34~0.33	4.12~0.43	4.39~0.49
COP	/	16.05~6.85	16.25~7.12	16.05~7.22	16.05~7.25	16.05~7.25	16.15~6.41	16.05~6.55	16.10~6.58	16.15~6.41	16.05~6.55	16.10~6.58
Heating Condition#2: (DB/WB) 15°C/12°C; Water Inlet Temperature: 26°C.												
Heating Capacity	kW	5.5~1.4	7.0~1.9	8.5~2.3	11.3~3.5	14.2~3.8	15.5~4.5	19.2~5.5	21.5~6.1	15.5~4.5	19.2~5.5	21.5~6.1
Power Input	kW	1.24~0.18	1.55~0.25	1.96~0.30	2.76~0.39	3.37~0.5	3.79~0.65	4.65~0.76	4.99~0.95	3.79~0.65	4.65~0.76	4.99~0.95
COP	/	7.62~4.95	7.55~4.75	7.52~4.85	7.45~4.75	7.35~4.75	7.33~4.96	7.28~4.69	7.23~4.95	7.33~4.96	7.28~4.69	7.23~4.95
Advised Pool Size	m^3	15~25	18~40	25~45	30~55	35~65	45~85	50~95	55~100	45~85	50~95	55~100
Max Power Input	kW	1.8	2.5	2.9	3.8	4.5	5.5	6.2	6.9	5.5	6.2	6.9
Max Current	A	9.1	12.6	14.6	19.2	22.7	27.8	31.3	34.8	9.8	11.1	12.3
Power Supply	V/Ph/Hz	220V-240V~/50Hz/60Hz								380V-415V/3N~/50Hz/60Hz		
Refrigerant/charge	/	R32										
Water Flow	m^3/h	2.5	3.5	4.5	5.5	6.5	9.5	10.5	12.5	9.5	10.5	12.5
Water Pressure Drop	kPa	15		18		25	35					
Heating Temperature Range	°C	15~40										
Cooling Temperature Range	°C	8~28										
Operating Ambient Temperature	°C	-15~46										
Noise Level at 1m	dB(A)	36~48	37~49	40~50	40~52	42~54	44~56	44~56	45~58	44~56	44~56	45~58
Noise Level at 10m	dB(A)	18~28	19~30	21~31	22~32	24~33	24~34	24~35	25~36	24~34	24~35	25~36
Water Pipe connection	/	DN50										
Net Weight	kg	55	64	65	70	75	80	83	88	80	83	88
Shipping Weight	kg	66	75	76	81	86	92	95	100	92	95	100
Net Dimension (L×W×H)	mm	1000×452×637			1050×460×750		1350×550×800			1350×550×800		
Packing Dimension (L×W×H)	mm	1096×480×651			1150×495×780		1450×600×823			1450×600×823		

Note: The data above is for reference only. Please refer to the nameplate on the unit if for more specific data.