R32 Swimming Pool Heat Pump (Top Discharge)

Mitsubishi Full DC Inverter Compressor



Self-developed Plug&Play Mainboard

Metal/ABS Casing

DUNAN EEV

Titanium Tube Heat Exchanger



Finned Heat Exchanger

R32 Refrigerant

COP 14

Low Noise

Precise water temperature control

Minimum operating temperature -15°C

Smart APP & Web IOT Platform

Specification

Product Picture											
Capacity		7kW	9kW	12kW	15kW	18kW	25kW	35kW	25kW	35kW	41kW
Model		GSPVSV-7BA1	GSPVSV-9BA1	GSPVSV-12BA1	GSPVSV-15BA1	GSPVSV-18BA1	GSPVSV-25BA1	GSPVSV-35BA1	GSPVTV-25BA1	GSPVTV-35BA1	GSPVTV-41BA1
* Heating Capacity at Air 26°C, Humidity 80%, Water 26°C in, 28°C out											
Heating Capacity	kW	1.7~7.0	2.3~8.8	3.9~11.0	5.8~14.5	6.2~17.9	7.5~24.5	8.8~35	7.5~24.5	8.8~35	10~41
Power Input	kW	0.21~1.06	0.35~1.35	0.45~1.84	0.54~2.43	0.58~3.09	0.69~4.52	0.76~6.00	0.69~4.52	0.76~6.00	1.34~6.52
COP	/	5.5~13.8	5.5~13.4	5.9~14.0	5.6~13.5	5.5~13.2	5.7~13.1	5.4~12.8	5.7~13.1	5.4~12.8	5.6~12.8
* Heating Capacity at Air 15°C, Humidity 70%, Water 26°C in, 28°C out											
Heating Capacity	kW	1.40~5.3	1.9~7.0	2.3~9.4	3.6~12.5	4.2~15.0	5.5~21	6.9~28.6	5.5~21	6.9~28.6	7.9~35
Power Input	kW	0.18~1.2	0.25~1.51	0.40~1.9	0.49~2.67	0.55~3.37	0.72~4.7	0.76~5.6	0.72~4.7	1.06~5.6	1.15~6.7
COP	/	4.8~6.6	4.9~6.8	4.7~6.6	4.6~6.5	4.9~6.6	4.9~6.8	4.9~6.6	4.9~6.8	4.9~6.6	4.8~6.7
* Cooling Capacity at Air 35°C, Water 29°C in, 27°C out											
Cooling Capacity	kW	1.0~4.2	1.3~5.3	1.9~6.8	2.1~9.4	2.7~11.6	3.8~14.9	4.9~19.3	3.8~14.9	4.9~19.3	5.9~23.4
Power Input	kW	0.15~1.11	0.19~1.4	0.25~1.89	0.54~2.47	0.66~3.05	0.77~3.92	0.93~5.08	0.77~3.92	0.99~5.08	1.26~5.88
EER	/	3.5~6.0	3.5~6.1	3.4~6.5	3.6~6.3	3.4~6.2	3.8~6.7	3.4~6.4	3.8~6.7	3.5~6.4	3.1~6.3
* General data											
Power supply	V/Ph/Hz	220~240V/1/50Hz/60Hz							380~415V/3/50Hz/60Hz		
Max Power Input	kW	1.45	1.75	2.75	3.15	3.75	5.17	6.43	4.76	7.20	9.58
Max Current	A	7.10	8.30	11.50	14.50	17.50	23.50	30.00	7.90	12.70	13.50
Water Flow Volume	m^3/h	2.5	3.5	4.5	5.5	6.5	9	12	9	12	18
Refrigerant	/	R32									
Heat Exchanger	/	Titanium									
Air Flow Direction	/	vertical									
Casing Material	/	ABS									
Working temp. range	°C	-15~43									
Noise Level at 1m	dB(A)	39~51	40~52	41~53	42~54	43~56	47~58	46~59	47~58	49~59	49~59
Water Pipe connection	/	DN50									
Net Weight	kg	50	55	65	71	73	95	113	96	114	115
Shipping Weight	kg	61	67	79	85	87	112	130	113	131	132
Net Dimension (L×W×H)	mm	530×530×655		650×650×790			730×730×980				
Packing Dimension (L×W×H)	mm	600×560×820		720×680×950			800×760×1110				
Note: The data above is for reference only. Please refer to the nameplate on the unit if for more specific data.											