R32 Commercial Inverter Swimming Pool Heat Pump

Mitsubishi Full DC Inverter Compressor

Full DC Motor

User-Friendly Controller

DUNAN EEV

Titanium Tube Heat Exchanger

Finned Heat Exchanger

R32 Refrigerant Eco-Friendly

Wide Operating Range

Low Noise

Heating & Cooling Function

Smart Defrosting

WIFI

Specification

Product Picture					
Model		60KW	90KW	130KW	250kW
Power Supply		380-415V/50Hz/60Hz	380-415V/50Hz/60Hz	380-415V/50Hz/60Hz	380-415V/50Hz/60Hz
Heating Capacity at Air 26°C/24°C, Water 26°C in, 28°C out					
Heating Capacity	kW	25~60	30~90	40~130	70~250
Power Input	kW	1.77~8.85	2.67~13.85	3.62~19.85	6.35~38.20
COP	/	6.80~11.30	6.50~11.20	6.55~11.05	6.55~11.05
Heating Capacity at Air 15°C/12°C, Water 26°C in, 28°C out					
Heating Capacity	kW	15~55	25~80	35~105	60~200
Power Input	kW	1.97~11.22	3.35~16.80	5.00~24.65	8.00~41.68
COP	/	4.90~7.60	4.80~7.50	4.80~7.60	4.80~7.50
Cooling Capacity at Air 35°C/24°C, Water 28°C in, 26°C out					
Cooling Capacity	kW	10~36	15~56	20~80	40~155
Power Input	kW	1.72~9.60	2.60~14.95	3.45~21.50	7.15~41.20
EER	/	3.75~5.80	3.75~5.80	3.75~5.80	3.75~5.60
Max Power Input	kW	15.0	20.0	28.0	56
Max Current	A	27.5	35.5	50.5	100.5
Refrigerant	/	R32			
Heat Exchanger	/	Titanium			
Expansion Valve	/	Electronic			
Air Flow Direction		Vertical			
Water Flow Volume	m^3/h	26	38	56	110
Working temperature range	°C	-15~46	-15~46	-15~46	-15~46
Noise	dB(A)	≤60	≤65	≤68	≤76
Net Weight	kg	280	420	750	1290
Water connection	mm	63	63	75	125

Note: The data above is for reference only. Please refer to the nameplate on the unit if for more specific data.