R32 Mini Swimming Pool Heat Pump (Side Discharge)

GMCC Compressor

Wireless Router

Metal Casing

Sanhua 4-way Valve

Titanium Tube
Heat Exchanger



Finned Heat Exchanger

R32 Refrigerant

COP 4.4

Low Noise

Precise water
temperature control

Minimum operating
temperature -7°C

Smart APP

Specification

Product Picture				
Model		GSPSHM-3BA1	GSPSHM-4BA1	GSPSHM-5BA1
* Heating Capacity at Air 26°C, Humidity 80%, Water 26°C in, 28°C out				
Heating Capacity	kW	2.70	3.70	4.60
Power Input	kW	0.61	0.83	1.05
COP	/	4.43	4.45	4.40
* Heating Capacity at Air 15°C, Humidity 70%, Water 26°C in, 28°C out				
Heating Capacity	kW	2.10	2.80	3.50
Power Input	kW	0.57	0.78	0.98
COP	/	3.68	3.60	3.57
*cooling Capacity at Air 35°C, Humidity 70%, Water 12°C in, 7°C out				
cooling Capacity	kW	1.26	1.67	1.98
Power Input	kW	0.64	0.85	1.00
EER	/	1.96	1.95	1.98
* General data				
Power supply	V/Ph/Hz	220V~240V/50Hz		
Rated Power Input	kW	0.70	0.90	1.50
Rated Current	A	3.2	4.8	7.6
Water Flow Volume	m^3/h	1.5	2.0	2.5
Pressure drop of water side	KPa	20.0		
Advised pool size	m^3	2~4	3~6	4~9
Refrigerant	/	R32		
Setting Temperature Range(Heating)	°C	15~40		
Setting Temperature Range(Cooling)	°C	2~28		
Operating Ambient Temperature	°C	-7~43		
Noise level	dB(A)	48	48	49
Water connection	/	DN32		
Net Weight	kg	23	25	27
Gross Weight	kg	28	29	30
Net Dimensions (L×W×H)	mm	420×360×453		
Package Dimensions (L×W×H)	mm	515×475×540		
Note: The data above is for reference only. Please refer to the nameplate on the unit if for more specific data.				