Ice Bath Chiller

Titanium Tube
Heat Exchanger

Prefilter

AC fan motor

UV ozone sterilizer

Silent fan blade

DC Water Pump

R32 Refrigerant

Titanium heat exchanger, corrosion resistance

Low Noise

Built-in ozone generator, prefilter,DC water pump

Layered design for easy maintenance

Smart APP & Web IOT Platform

Specification

Product Picture			
Capacity		2KW	4KW
Model		GWCSH-2BA1	GWCSH-4BA1
* Heating Capacity at Air 26°C, Humidity 80%, Water 26°C in, 28°C out			
Heating Capacity	kW	/	5.25
Power Input	kW	/	1.24
COP	/	/	4.25
* Heating Capacity at Air 15°C, Humidity 70%, Water 26°C in, 28°C out			
Heating Capacity	kW	/	3.98
Power Input	kW	/	1.01
COP	/	/	3.94
*cooling Capacity at Air 35°C, Humidity 70%, Water 12°C in, 7°C out			
cooling Capacity	kW	1.00	2.00
Power Input	kW	0.60	1.00
EER	/	1.70	1.20
* General data			
Power supply	V/Ph/Hz	220V/1/50Hz	
Max Power Input	kW	0.70	2.00
Max Current	A	3.2	8.8
Water Flow Volume	m^3/h	1.5	2.0
Advised pool size	m^3	0~10	5~16
Refrigerant	/	R32	
Setting Temperature Range	°C	3-38	
Operating Ambient Temperature	°C	10~43	-7~43
Noise level	dB(A)	45	50
Water connection	inch	G1	
Net Weight	kg	28	39
Gross Weight	kg	33	42
Net Dimensions (L×W×H)	mm	490×308×658	490×308×658
Package Dimensions (L×W×H)	mm	590×440×775	590×440×775
Note: The data above is for reference only. Please refer to the nameplate on the unit if for more specific data.			