R290 Residential Air to Water Heat Pump

HIGHLY Full DC
Inverter Compressor

RENESA Chip

Danfoss / Weyee
Plate Heat Exchanger

Refrigerant Leak Sensor

Grundfos / Shimge
Circulation Pump

Noise Reduction
Compartment

High&Low Pressure Sensor

OHIZUMI
Temperature Sensor

3S Technology

75°C

MAX 75°C Outlet
Water Temperature

CE, ErP, KEYMARK
Certified

Integrated
Terminal Block

X16

Centralized Control

Smart APP &
Web IOT Platform

Specification

Capacity			6kW	8kW	10kW	10kW	12kW	12kW	16kW	16kW	18kW	18kW	24kW
Model			GSHVSH -6AA1	GSHVSH -8AA1	GSHVSH -10AA1	GSHVTH -10AA1	GSHVSH -12AA1	GSHVTH -12AA1	GSHVSH -16AA1	GSHVTH -16AA1	GSHVSH -18AA1	GSHVTH -18AA1	GSHVTH -24AA1
Power Supply			220~240V~ /50Hz	220~240V~ /50Hz	220~240V~ /50Hz	380~415V /3N~/50Hz	220~240V~ /50Hz	380~415V /3N~/50Hz	220~240V~ /50Hz	380~415V /3N~/50Hz	220~240V~ /50Hz	380~415V /3N~/50Hz	380~415V /3N~/50Hz
Heating Capacity (Max) (A7/6°C,W30/35°C)	Heating Capacity	kW	6.07 (2.63~9.10)	8.11 (3.57~12.29)	10.25 (4.39~13.50)	10.25 (4.39~13.50)	11.98 (4.39~15.45)	11.98 (4.39~15.45)	16.20 (6.17~18.51)	16.20 (6.17~18.51)	17.60 (6.50~22.00)	17.60 (6.50~22.00)	24.05 (9.63~29.13)
	Power Input	kW	1.19 (0.54~2.28)	1.60 (0.74~3.17)	2.07 (0.89~3.55)	2.07 (0.89~3.55)	2.45 (0.89~4.06)	2.45 (0.89~4.06)	3.38 (1.26~4.83)	3.38 (1.26~4.83)	3.62 (1.35~5.88)	3.62 (1.35~5.88)	4.96 (2.00~7.82)
	COP	/	5.10 (4.20~5.40)	5.07 (4.10~5.35)	4.95 (3.90~5.30)	4.95 (3.90~5.30)	4.89 (3.85~5.20)	4.89 (3.85~5.20)	4.79 (3.75~5.00)	4.79 (3.75~5.00)	4.86 (3.82~5.30)	4.86 (3.82~5.30)	4.85 (3.86~5.30)
Heating Capacity (Max) (A7/6°C,W47/55°C)	Heating Capacity	kW	5.99 (2.99~8.19)	8.11 (3.65~10.96)	10.07 (3.85~11.75)	10.07 (3.85~11.75)	11.55 (3.85~13.35)	11.55 (3.85~13.35)	15.89 (5.75~17.20)	15.89 (5.75~17.20)	17.85 (5.45~18.89)	17.85 (5.45~18.89)	23.85 (8.45~25.89)
	Power Input	kW	1.87 (1.03~2.92)	2.65 (1.11~3.87)	3.12 (1.20~4.35)	3.12 (1.20~4.35)	3.71 (1.20~5.03)	3.71 (1.20~5.03)	5.30 (1.81~5.84)	5.30 (1.81~5.84)	5.88 (2.15~6.85)	5.88 (2.15~6.85)	8.01 (2.86~9.12)
	COP	/	3.20 (2.90~3.46)	3.18 (2.83~3.45)	3.23 (2.75~3.57)	3.23 (2.75~3.57)	3.11 (2.65~3.57)	3.11 (2.65~3.57)	3.00 (2.83~3.45)	3.00 (2.83~3.45)	3.03 (2.64~3.57)	3.03 (2.64~3.57)	2.98 (2.84~3.57)
Cooling Capacity (Max) (A35/24°C,W12/7°C)	Cooling Capacity	kW	5.00 (1.38~5.70)	7.10 (1.44~8.11)	8.50 (3.65~9.45)	8.50 (3.65~9.45)	10.00 (3.65~11.04)	10.00 (3.65~11.04)	13.00 (4.03~13.51)	13.00 (4.03~13.51)	15.00 (4.55~17.20)	15.00 (4.55~17.20)	17.00 (6.15~19.50)
	Power Input	kW	1.77 (0.67~2.44)	2.51 (0.90~3.20)	3.01 (1.12~3.51)	3.01 (1.12~3.51)	3.68 (1.12~3.97)	3.68 (1.12~3.97)	4.60 (1.45~5.03)	4.60 (1.45~5.03)	5.52 (1.85~7.31)	5.52 (1.85~7.31)	6.14 (2.50~9.75)
	EER	/	2.82 (2.03~3.20)	2.83 (2.00~3.15)	2.82 (2.00~3.10)	2.82 (2.00~3.10)	2.72 (1.95~3.00)	2.72 (1.95~3.00)	2.83 (1.98~3.05)	2.83 (1.98~3.05)	2.72 (1.96~2.98)	2.72 (1.96~2.98)	2.77 (2.03~3.00)
ERP Level(Outlet water temp. at 35°C/55°C)		/	A+++/A+++						A+++/A++		A+++/A+++		
Rated Power Input		kW	3.6	4.65	5.05	5.05	5.45	5.86	6.95	6.95	7.5	10.52	12.52
Rated Current Input		A	15.0	20.4	23.0	8.5	25.0	10.5	30.5	11.7	35.0	17.3	19.5
Refrigerant Type		/	R290										
Rated water flow		m^3/h	1.00	1.37	1.72	1.72	2.06	2.06	2.75	2.75	3.1	3.1	4.2
Water Pressure Drop		kPa	20	25	20				55				60
Fan quantity		/	1								2		
Fan motor type		/	DC inverter										
Compressor		/	DC inverter										
Circulating pump		/	Inverter type / Built-in										
IP Class		/	IPX4										
Max. outlet water Temp.		°C	75										
Operating temperature range (Heating mode)		°C	-25~45										
Operating temperature range (Cooing mode)		°C	16~45										
Sound pressure at 1m distance		dB(A)	43(39~51)	43(39~51)	44(39~52)	44(39~52)	46(39~52)	46(39~52)	48(39~55)	48(39~55)	49(39~55)	49(39~55)	52(50~60)
Sound pressure at 3m distance		dB(A)	35(32~44)	35(32~44)	37(32~45)	37(32~45)	39(32~45)	39(32~45)	41(32~48)	41(32~48)	47(32~48)	47(32~48)	45(43~53)
Water Piping Connections		inch	G1						G5/4				G3/2
UnPacked Weight		kg	110	125	145	145	145	145	190	190	220	220	220
Packed Weight		kg	115	135	165	165	165	165	220	220	240	240	240
Unpacked Dimensions (L×D×H)		mm	1290×460×955						1490×500×1005		1190×500×1515		
Packed Dimensions (L×D×H)		mm	1320×500×1094						1520×540×1140		1220×540×1640		

Note: The data above is for reference only. Please refer to the nameplate on the unit if for more specific data.