R290 Commercial Air to Water Heat Pump

HITACHI Full DC
Inverter Compressor

RENESA Chip

Full DC Motor

DUNAN EEV



Self-developed
Plug&Play Mainboard

Refrigerant Leak Sensor

R290 Refrigerant

3S Technology

CE, ErP, KEYMARK
Certified

MAX 75°C Outlet
Water Temperature

Centralized Control

Smart APP &
Web IOT Platform

Specification

Product Picture				
Model		GSHVTV-50AA1	GSHVTV-75AA1	GSHVTV-100AA1
Power Supply		380V~415V/3/50Hz		
Nominal Heating (Max) (A7/6°C,W30/35°C)				
Heating Capacity	kW	18.50~50.50	25.00~76.0	35.50~105.00
Power Input	kW	3.95~14.80	5.75~21.71	7.95~30.43
COP1	/	3.5~4.70	3.55~4.65	3.5~4.62
Nominal Heating (Max) (A7/6°C,W47/55°C)				
Heating Capacity	kW	10.85~40.00	19.58~67.27	26.85~93.45
Power Input	kW	3.74~13.79	6.19~26.91	8.52~37.38
COP2	/	3.02~3.52	2.50~3.38	2.55~3.28
Nominal Cooling (Max) (A35/24°C,W12/7°C)				
Cooling Capacity	kW	10.15~28.50	13.5~ 48.5	16.20~ 65.50
Power Input	kW	3.63~12.95	6.91~20.90	7.35~ 33.41
EER	/	2.20~2.70	2.00~2.45	2.00~2.50
Max Power Input	kW	19.3	30.5	40.5
Max Current	A	35.0	54.5	82.0
ERP level(35°C)/(55°C)	/	A+++/A++		
Maximun Allowable Pressure	MPa	3.2		
Refrigerant	/	R290		
ELectrical Shockproof	/	I		
Compressor quantity	/	1	2	
Fan motor quantity	/	1	2	
Fan motor Type	/	DC		
Expansion Valve	/	EEV/sanhua		
Air Flow Direction	/	Vertical		
IP class	/	IPX4		
Water Flow Volume	m^3/h	6.0	9.0	12.5
Water Pressure Drop	kPa	65	75	76
Working temperature range	°C	-25~46		
Noise	dB(A)	55(39-55)	62(54-72)	
Water connection	/	G3/2	Flange DN80	
Net Weight	kg	450	780	900
Dimensions(L×W×H)	mm	1100×1100×2150	2200×1100×2255	
Packing(L×W×H)	mm	1144×1144×2250	2260×1160×2385	
Note: The data above is for reference only. Please refer to the nameplate on the unit if for more specific data.				