# R32 Residential Air to Water Heat Pump

Panasonic EVI Full DC Inverter Compressor

RENESA Chip

Hrale

DUNAN EEV

Shimge Circulation Pump

Noise Reduction Compartment

High&Low Pressure Sensor

OHIZUMI Temperature Sensor

3S Technology

CE, ErP, KEYMARK Certified

Screw-free Design

Integrated Terminal Block

X16

Centralized Control

Smart APP & Web IOT Platform



# Specification

| | | | | | | | | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Product Picture | | | | | | | | | | | | | | | | | |
| Capacity | | | 6kW | 8kW | 10kW | 10kW | 12kW | 12kW | 14kW | 14kW | 16kW | 16kW | 18kW | 18kW | 24kW | 30kW | 34kW |
| Model | | | GSHVSH-6BA1 | GSHVSH-8BA1 | GSHVSH-10BA1 | GSHVTH-10BA1 | GSHVSH-12BA1 | GSHVTH-12BA1 | GSHVSH-14BA1 | GSHVTH-14BA1 | GSHVSH-16BA1 | GSHVTH-16BA1 | GSHVSH-18BA1 | GSHVTH-18BA1 | GSHVTH-24BA1 | GSHVTH-30BA1 | GSHVTH-34BA1 |
| Power Supply | | | 220~240V~/50Hz | 220~240V~/50Hz | 220~240V~/50Hz | 220~240V~/50Hz | 220~240V~/50Hz | 380~415V/3N~/50Hz | 220~240V~/50Hz | 380~415V/3N~/50Hz | 220~240V~/50Hz | 380~415V/3N~/50Hz | 220~240V~/50Hz | 380~415V/3N~/50Hz | 380~415V/3N~/50Hz | 380~415V/3N~/50Hz | 380~415V/3N~/50Hz |
| Nominal Heating (Max) (A7/6°C, W30/35°C) | Heating Capacity | kW | 6.05 (2.80~8.80) | 8.20 (5.10~10.85) | 10.05 (5.10~12.90) | 10.05 (5.10~12.90) | 12.00 (5.90~15.12) | 12.00 (5.90~15.12) | 14.05 (6.10~16.99) | 14.05 (6.10~16.99) | 15.80 (6.37~19.11) | 15.80 (6.37~19.11) | 18.21 (6.90~21.00) | 18.21 (6.90~21.00) | 24.05 (7.90~26.20) | 30.05 (9.17~32.71) | 34.15 (9.17~36.80) |
| | Power Input | kW | 1.29 (0.59~1.95) | 1.74 (0.86~2.42) | 2.16 (0.86~2.88) | 2.16 (0.86~2.88) | 2.45 (1.15~3.61) | 2.45 (1.15~3.61) | 2.99 (1.15~4.15) | 2.99 (1.15~4.15) | 3.43 (1.31~4.93) | 3.43 (1.31~4.93) | 3.65 (1.36~5.28) | 3.65 (1.36~5.28) | 5.29 (1.78~6.45) | 6.60 (2.51~8.07) | 7.59 (2.51~9.09) |
| | COP | / | 4.70 (4.25~5.05) | 4.70 (4.23~5.08) | 4.65 (4.23~5.05) | 4.65 (4.23~5.05) | 4.90 (4.15~5.06) | 4.90 (4.15~5.06) | 4.70 (4.15~5.05) | 4.70 (4.15~5.05) | 4.64 (4.10~5.02) | 4.64 (4.10~5.02) | 4.99 (4.05~5.05) | 4.99 (4.05~5.05) | 4.55 (4.03~5.02) | 4.55 (4.05~5.03) | 4.50 (4.05~5.03) |
| Nominal Heating (Max) (A7/6°C, W47/55°C) | Heating Capacity | kW | 5.88 (2.30~7.62) | 8.05 (3.85~9.41) | 9.50 (3.85~11.20) | 9.50 (3.85~11.20) | 12.00 (4.90~13.15) | 12.00 (4.90~13.15) | 13.98 (4.90~15.10) | 13.98 (4.90~15.10) | 15.70 (4.90~17.6) | 15.70 (4.90~17.6) | 18.10 (6.30~19.90) | 18.10 (6.30~19.90) | 22.99 (6.90~26.10) | 29.86 (9.73~31.82) | 33.50 (9.73~36.80) |
| | Power Input | kW | 1.78 (0.75~2.61) | 2.44 (1.13~3.15) | 2.92 (1.13~3.75) | 2.92 (1.13~3.75) | 3.96 (1.65~4.56) | 3.96 (1.65~4.56) | 4.30 (1.65~5.25) | 4.30 (1.65~5.25) | 4.83 (1.65~5.33) | 4.83 (1.65~5.33) | 5.82 (1.65~6.82) | 5.82 (1.65~6.82) | 8.04 (1.95~8.55) | 10.12 (2.75~10.36) | 11.55 (2.75~12.06) |
| | COP | / | 3.30 (2.92~3.33) | 3.30 (2.99~3.46) | 3.25 (2.99~3.46) | 3.25 (2.99~3.46) | 3.03 (2.87~3.38) | 3.03 (2.87~3.38) | 3.25 (2.87~3.38) | 3.25 (2.87~3.38) | 3.25 (2.87~3.38) | 3.25 (2.87~3.38) | 3.11 (2.91~3.34) | 3.11 (2.91~3.34) | 2.86 (3.05~3.42) | 2.95 (3.05~3.42) | 2.90 (3.05~3.42) |
| Nominal Cooling (Max) (A35/24°C, W12/7°C) | Cooling Capacity | kW | 5.00 (1.80~7.10) | 7.0 (2.60~8.50) | 8.50 (2.60~10.30) | 8.50 (2.60~10.30) | 10.00 (4.50~11.85) | 10.00 (4.50~11.85) | 11.5 (4.50~13.50) | 11.5 (4.50~13.50) | 13.00 (5.05~15.00) | 13.00 (5.05~15.00) | 15.00 (5.50~17.50) | 15.00 (5.50~17.50) | 19.50 (5.20~21.30) | 23.5 (7.33~26.70) | 28.5 (7.33~30.03) |
| | Power Input | kW | 2.0 (0.61~2.43) | 2.69 (0.91~2.93) | 3.40 (0.91~3.65) | 3.40 (0.91~3.65) | 4.00 (1.45~4.30) | 4.00 (1.45~4.30) | 4.42 (1.45~4.85) | 4.42 (1.45~4.85) | 5.20 (1.65~5.33) | 5.20 (1.65~5.33) | 6.00 (1.65~6.25) | 6.00 (1.65~6.25) | 7.80 (1.95~8.20) | 9.40 (2.75~10.27) | 11.40 (2.75~11.56) |
| | EER | / | 2.50 (2.45~3.05) | 2.60 (2.45~3.05) | 2.50 (2.35~3.00) | 2.50 (2.35~3.00) | 2.50 (2.40~2.96) | 2.50 (2.40~2.96) | 2.60 (2.42~2.89) | 2.60 (2.42~2.89) | 2.50 (2.42~2.85) | 2.50 (2.42~2.85) | 2.50 (2.38~2.96) | 2.50 (2.38~2.96) | 2.50 (2.34~2.95) | 2.50 (2.36~2.98) | 2.50 (2.35~2.92) |
| ERP Level (Outlet water temp. at 35°C/55°C) | | / | A+++/A++ | | | | | | | | | | | | | | |
| Rated Input Power | | kW | 2.78 | 3.49 | 3.79 | 3.89 | 5.05 | 5.05 | 6.11 | 6.11 | 7.12 | 7.12 | 7.80 | 7.56 | 11.50 | 11.65 | 13.10 |
| Rated Input Current | | A | 12 | 15 | 17 | 6.5 | 22.2 | 8.5 | 27.50 | 10.50 | 33.00 | 12.50 | 35.00 | 13.00 | 18.50 | 19.76 | 22.00 |
| Refrigerant Type | | / | R32 | | | | | | | | | | | | | | |
| Rated water flow | | $m^3/h$ | 1.1 | 1.38 | 1.72 | 1.72 | 2.06 | 2.06 | 2.41 | 2.41 | 2.75 | 2.75 | 3.10 | 3.10 | 4.12 | 5.85 | 5.85 |
| Pressure drop at rating water flow | | kPa | 29 | | | | 32 | | | | | | | | 35 | 39 | |
| Fan quantity | | / | 1 | | | | | | | | | | 2 | | | | |
| Fan motor type | | / | DC inverter | | | | | | | | | | | | | | |
| Compressor | | / | Panasonic / DC inverter / Rotary / EVI | | | | | | | | | | | | | | |
| Circulating pump | | / | Inverter type / Built-in | | | | | | | | | | | | | | |
| IP Class | | / | IPX4 | | | | | | | | | | | | | | |
| Max outlet water temperature | | °C | 60 | | | | | | | | | | | | | | |
| Operating temperature range (Heating mode) | | °C | -38~43 | | | | | | | | | | | | | | |
| Operating temperature range (Cooing mode) | | °C | 16~48 | | | | | | | | | | | | | | |
| Sound pressure at 1m distance | | dB(A) | 49 | 43(39~52) | 45(39~52) | 45(39~52) | 45(39~53) | 45(39~53) | 46(39~53) | 46(39~53) | 48(39~54) | 48(39~54) | 48(39~54) | 48(39~54) | 52 (40~58) | 52 (42~62) | 52 (42~62) |
| Water piping connections | | inch | G1 | | | | | | G5/4 | | | | | | | G3/2 | |
| UnPacked Weight | | kg | 113 | 120 | 120 | 121 | 128 | 126 | 132 | 131 | 132 | 131 | 175 | 174 | 181 | 212 | 212 |
| Packed Weight | | kg | 125 | 132 | 132 | 133 | 140 | 138 | 144 | 143 | 144 | 143 | 189 | 188 | 195 | 228 | 228 |
| Unpacked Dimensions (L×D×H) | | mm | 1170×462×855 | | | | | | | | | | 1130×452×1443 | | | 1220×452×1657 | |
| Packed Dimensions (L×D×H) | | mm | 1230×540×1010 | | | | | | | | | | 1190×540×1600 | | | 1280×540×1815 | |

Note: The data above is for reference only. Please refer to the nameplate on the unit if for more specific data.