R32 Commercial Air to Water Heat Pump

HITACHI Full DC
Inverter Compressor

RENESA Chip

Full DC Motor

DUNAN EEV



Self-developed
Plug&Play Mainboard

Sanhua 4-way Valve

R32 Refrigerant

3S Technology

CE, ErP, KEYMARK
Certified

EVI Technology

Centralized Control

Smart APP &
Web IOT Platform

Specification

Product Picture				
Capacity		50kW	100kW	210KW
Model		GSHVTV-50BA1	GSHVTV-100BA1	GSHVTV-210BA1
Power Supply		380V~415V/3/50Hz		
Nominal Heating (Max) (A7/6°C,W30/35°C)				
Heating Capacity	kW	46.0(13.9~52.8)	92.0(28.5~107.8)	176.0(49.7~213.0)
Power Input	kW	11.1(3.0~15.2)	22.2(5.9~30.3)	42.33(11.1~60.0)
COP	/	4.14(3.50~4.75)	4.15(3.52~4.80)	4.16(3.55~4.82)
Nominal Heating (Max) (A7/6°C,W47/55°C)				
Heating Capacity	kW	43.3(13.5~49.5)	86.5(27.9~102.3)	172.0(48.6~202.0)
Power Input	kW	16.5(4.3~19.5)	32.8(9.0~40.1)	64.89(17.1~79.2)
COP	/	2.63(2.53~3.12)	2.64(2.53~3.12)	2.65(2.55~3.12)
Nominal Heating (Max) (A-12°C/-14°C, W 50/55°C)				
Heating Capacity	kW	34.0(10.3~35.3)	68.0(21.3~72.1)	136.8(36.3~141.0)
Power Input	kW	19.6(4.9~20.7)	38.8(9.9~42.4)	79.4(18.1~82.0)
COP	/	1.73(1.70~2.20)	1.75(1.70~2.20)	1.72(1.65~2.15)
Nominal Cooling (Max) (A35/24°C,W12/7°C)				
Cooling Capacity	kW	28.0(12.2~30.6)	56(25.2~62.5)	106.0(39.4-135.2)
Power Input	kW	12.1(5.1~17.2)	27.0(10.7~31.1)	46.1(18.7-73.1)
Max Power Input	kW	22.0	43.0	82.0
Max Current	A	43.5	85.0	160.0
Compressor quantity	/	1	2	
Expansion Valve	/	EEV		
Air Flow Direction	/	Vertical		
IP class	/	IPX4		
Water Flow Volume	m^3/h	8.0	16.0	30.0
Water Pressure Drop	kPa	70	73	76
Working temperature range	°C	-35~46		
Noise	dB(A)	≤65	≤68	≤76
Water connection	/	G1-1/2	(Flange)DN 65	(Flange)DN 80
Net Weight	kg	450	780	1250
Dimensions(L×W×H)	mm	1100×1100×2150	2000×1110×2250	2400×1160×2450
Note: The data above is for reference only. Please refer to the nameplate on the unit if for more specific data.				