R410A Commercial Air to Water Heat Pump

COPELAND

Full DC Motor

User-friendly Controller

DUNAN EEV



Casing



Finned Heat Exchanger

R410A Refrigerant Eco-Friendly

Wide Operating Range

Low Noise

Heating & Cooling Function

Smart Defrosting

WIFI

Specification

Product Picture				
Model	5HP-R410A	10HP-R410A	20HP-R410A	30HP-R410A
Power Supply	380~415V/3/50Hz			
Heating Capacity (KW)	19.00	38.50	76.80	110.00
Rated Input Power (KW)	4.50	8.98	17.90	25.80
Rated Current (A)	8.04	16.05	32.00	46.12
COP	4.22	4.29	4.29	4.26
Max Power Input(kW)	7.50	14.80	28.90	34.90
Max Current(A)	12.90	24.85	51.00	60.60
Water Temp. Range (°C)	Default 55, 28~60			
Working temp. range(°C)	-15~43			
Anti-electric chock class	I			
Water proof grade	IPX4			
Water flow volume(L/h)	4000	8000	16000	20000
Water Pressure Drop(kPa)	50	60	65	65
Compressor qty.	1	2	2	2
Fan motor qty.	1	2	2	2
Color	Black, Matte surface			
Air Flow Direction	Vertical			
Safeties	LP & HP Cutout, Current & Voltage, Overheat, Temperature, Pressure Protection			
Defrosting	Auto and By manual			
Noise(dB)	55	58	71	72
Net Weight(kg)	155	259	650	715
Water connection(mm)	Male thread 25	Female thread 32	Female thread 50	Female thread 50

Note: The data above is for reference only. Please refer to the nameplate on the unit if for more specific data.