

Computer Vision-IT416

Dinesh Naik

Department of Information Technology, National Institute of Technology Karnataka, India

April 5, 2022





General RANSAC Algorithm:

1. Randomly choose s samples. Typically s is the minimum samples to fit a model.

For homography:

s = 4 points.

General RANSAC Algorithm:

- 1. Randomly choose s samples. Typically s is the minimum samples to fit a model.
- 2. Fit the model to the randomly chosen samples.

For homography:

s = 4 points.

General RANSAC Algorithm:

- 1. Randomly choose s samples. Typically s is the minimum samples to fit a model.
- 2. Fit the model to the randomly chosen samples.
- 3. Count the number M of data points (inliers) that fit the model within a measure of error ε .

For homography:

s=4 points. ε is acceptable alignment error in pixels.

General RANSAC Algorithm:

- 1. Randomly choose s samples. Typically s is the minimum samples to fit a model.
- 2. Fit the model to the randomly chosen samples.
- 3. Count the number M of data points (inliers) that fit the model within a measure of error ε .
- 4. Repeat Steps 1-3 N times

For homography:

s=4 points. ε is acceptable alignment error in pixels.

General RANSAC Algorithm:

- 1. Randomly choose s samples. Typically s is the minimum samples to fit a model.
- 2. Fit the model to the randomly chosen samples.
- 3. Count the number M of data points (inliers) that fit the model within a measure of error ε .
- 4. Repeat Steps 1-3 N times
- 5. Choose the model that has the largest number M of inliers.

For homography:

s=4 points. ε is acceptable alignment error in pixels.

