

# 1. Two Sum



Given an array of integers `nums` and an integer `target`, return *indices of the two numbers such that they add up to `target`*.

You may assume that each input would have **exactly one solution**, and you may not use the *same* element twice.

You can return the answer in any order.

## Example 1:

**Input:** `nums = [2,7,11,15]`, `target = 9`

**Output:** `[0,1]`

**Explanation:** Because `nums[0] + nums[1] == 9`, we return `[0, 1]`.

## Example 2:

**Input:** `nums = [3,2,4]`, `target = 6`

**Output:** `[1,2]`

## Example 3:

**Input:** `nums = [3,3]`, `target = 6`

**Output:** `[0,1]`

## Constraints:

- $2 \leq \text{nums.length} \leq 10^4$
- $-10^9 \leq \text{nums}[i] \leq 10^9$
- $-10^9 \leq \text{target} \leq 10^9$
- **Only one valid answer exists.**

**Follow-up:** Can you come up with an algorithm that is less than  $O(n^2)$  time complexity?

---

```
class Solution {
    public int[] twoSum(int[] nums, int target) {
        HashMap<Integer,Integer> hm=new HashMap<>();
        int [] arr=new int[2];
        for(int i=0;i<nums.length;i++)
        {
            if(hm.containsKey(target-nums[i]))
            {
                arr[0]=hm.get(target-nums[i]);
                arr[1]=i;
            }
            else
            {
                hm.put(nums[i],i);
            }
        }
        return arr;
    }
}
```

---

## 11. Container With Most Water




You are given an integer array `height` of length `n`. There are `n` vertical lines drawn such that the two endpoints of the  $i^{\text{th}}$  line are  $(i, 0)$  and  $(i, \text{height}[i])$ .

Find two lines that together with the x-axis form a container, such that the container contains the most water.

Return *the maximum amount of water a container can store*.

**Notice** that you may not slant the container.

**Example 1:**



**Input:** height = [1,8,6,2,5,4,8,3,7]

**Output:** 49

**Explanation:** The above vertical lines are represented by array [1,8,6,2,5,4,8,3,7]

#### Example 2:

**Input:** height = [1,1]

**Output:** 1

#### Constraints:

- $n == \text{height.length}$
- $2 \leq n \leq 10^5$
- $0 \leq \text{height}[i] \leq 10^4$

1.  $O(N)$

```

class Solution {
    public int maxArea(int[] height) {
        int right=height.length-1;
        int left=0;
        int maxVolume=Integer.MIN_VALUE;
        while(left<right)
        {
            int width=right-left;
            int heightAtIndex=(height[left]<height[right])?height[left]:height[right];
            if((width*heightAtIndex)>maxVolume)
            {
                maxVolume=width*heightAtIndex;
            }
            else if(height[left]<height[right])
            {
                left++;
            }
            else
            {
                right--;
            }
        }

        return maxVolume;
    }
}

```

2.  $O(N^2)$

```

class Solution {
    public int maxArea(int[] height) {
        int n=height.length;

        int maxVolume=Integer.MIN_VALUE;
        for(int i=0;i<n;i++)
        {
            for(int j=i+1;j<n;j++)
            {
                int minHeight=(height[i]<height[j])?height[i]:height[j];
                int volume=minHeight*(j-i);
                if(volume>maxVolume)
                    maxVolume=volume;
            }
        }
        return maxVolume;
    }
}

```

## 15. 3Sum



Given an integer array `nums`, return all the triplets `[nums[i], nums[j], nums[k]]` such that  $i \neq j$ ,  $i \neq k$ , and  $j \neq k$ , and  $nums[i] + nums[j] + nums[k] == 0$ .

Notice that the solution set must not contain duplicate triplets.

### Example 1:

**Input:** `nums = [-1,0,1,2,-1,-4]`

**Output:** `[[-1,-1,2],[-1,0,1]]`

**Explanation:**

`nums[0] + nums[1] + nums[2] = (-1) + 0 + 1 = 0.`

`nums[1] + nums[2] + nums[4] = 0 + 1 + (-1) = 0.`

`nums[0] + nums[3] + nums[4] = (-1) + 2 + (-1) = 0.`

The distinct triplets are `[-1,0,1]` and `[-1,-1,2]`.

Notice that the order of the output and the order of the triplets does not matter.

### Example 2:

**Input:** `nums = [0,1,1]`

**Output:** `[]`

**Explanation:** The only possible triplet does not sum up to 0.

### Example 3:

**Input:** `nums = [0,0,0]`

**Output:** `[[0,0,0]]`

**Explanation:** The only possible triplet sums up to 0.

### Constraints:

- $3 \leq \text{nums.length} \leq 3000$
- $-10^5 \leq \text{nums}[i] \leq 10^5$

---

1. time:  $O(N^2)$ , space:  $O(N)$

```

public List<List<Integer>> threeSum(int[] nums) {
    Arrays.sort(nums);
    List<List<Integer>> list = new ArrayList<List<Integer>>();
    for(int i = 0; i < nums.length-2; i++) {
        if(i > 0 && (nums[i] == nums[i-1])) continue; // avoid duplicates
        for(int j = i+1, k = nums.length-1; j<k;) {
            if(nums[i] + nums[j] + nums[k] == 0) {
                list.add(Arrays.asList(nums[i],nums[j],nums[k]));
                j++;k--;
                while((j < k) && (nums[j] == nums[j-1]))j++;// avoid duplicates
                while((j < k) && (nums[k] == nums[k+1]))k--;// avoid duplicates
            }else if(nums[i] + nums[j] + nums[k] > 0) k--;
            else j++;
        }
    }
    return list;
}

```

2. time:  $O(N^3)$  , space: $O(N)$

```

class Solution {
    public List<List<Integer>> threeSum(int[] nums) {
        Arrays.sort(nums);
        ArrayList<List<Integer>> al=new ArrayList<>();
        HashSet<List<Integer>> hs=new HashSet<>();
        for(int i=0;i<nums.length;i++)
        {
            for(int j=i+1;j<nums.length;j++)
            {
                for(int k=j+1;k<nums.length;k++)
                {
                    if(nums[i]+nums[j]+nums[k]==0)
                    {
                        hs.add(new ArrayList<>(List.of(nums[i],nums[j],nums[k])));
                    }
                }
            }
        }
        hs.stream().forEach(i->al.add(i));
        return al;
    }
}

```

Given a string `s` containing just the characters `'('`, `)'`, `'{'`, `'}'`, `'['` and `']'`, determine if the input string is valid.

An input string is valid if:

1. Open brackets must be closed by the same type of brackets.
2. Open brackets must be closed in the correct order.
3. Every close bracket has a corresponding open bracket of the same type.

#### Example 1:

**Input:** `s = "()"`

**Output:** `true`

#### Example 2:

**Input:** `s = "()[]{}"`

**Output:** `true`

#### Example 3:

**Input:** `s = "["`

**Output:** `false`

#### Constraints:

- $1 \leq s.length \leq 10^4$
- `s` consists of parentheses only `'()[]{}'`.

```
class Solution {
    public boolean isValid(String s) {
        Stack<Character> stack = new Stack<Character>();
        for (char c : s.toCharArray()) {
            if (c == '(')
                stack.push(')');
            else if (c == '{')
                stack.push('}');
            else if (c == '[')
                stack.push(']');
            else if (stack.isEmpty() || stack.pop() != c)
                return false;
        }
        return stack.isEmpty();
    }
}
```

---

## 49. Group Anagrams



Given an array of strings `strs`, group **the anagrams** together. You can return the answer in **any order**.

An **Anagram** is a word or phrase formed by rearranging the letters of a different word or phrase, typically using all the original letters exactly once.

### Example 1:

**Input:** `strs = ["eat","tea","tan","ate","nat","bat"]`  
**Output:** `[["bat"],["nat","tan"],["ate","eat","tea"]]`

### Example 2:

**Input:** `strs = [""]`  
**Output:** `[[""]]`

### Example 3:

**Input:** `strs = ["a"]`  
**Output:** `[["a"]]`

### Constraints:

- $1 \leq \text{strs.length} \leq 10^4$
- $0 \leq \text{strs}[i].\text{length} \leq 100$
- `strs[i]` consists of lowercase English letters.

```
1. public List<List<String>> groupAnagrams(String[] strs) {  
    if (strs == null || strs.length == 0) return new ArrayList<>();  
    Map<String, List<String>> map = new HashMap<>();  
    for (String s : strs) {  
        char[] ca = s.toCharArray();  
        Arrays.sort(ca);  
        String keyStr = String.valueOf(ca);  
        if (!map.containsKey(keyStr)) map.put(keyStr, new ArrayList<>());  
        map.get(keyStr).add(s);  
    }  
    return new ArrayList<>(map.values());  
}
```



2.

```
import java.util.*;
class Solution {
    public List<List<String>> groupAnagrams(String[] strs) {
        HashMap<String,ArrayList<String>> hm=new HashMap<>();
        for(int i=0;i<strs.length;i++)
        {
            //each string in array
            //key is sorted string
            String sortedStringChar=sortString(strs[i]);
            if(!hm.containsKey(sortedStringChar))
            {
                ArrayList<String> alString=new ArrayList<>();
                alString.add(strs[i]);
                hm.put(sortedStringChar,alString);
            }
            else
            {
                ArrayList<String> al=hm.get(sortedStringChar);
                al.add(strs[i]);
                hm.put(sortedStringChar,al);
            }
        }
        System.out.println(hm);
        Collection<ArrayList<String>> valuesCollection =hm.values();
        ArrayList<List<String>> result=new ArrayList<List<String>>();
        valuesCollection.stream().forEach(i->{result.add(i);});
        return result;
    }
    public static String sortString(String inputString)
    {
        // Converting input string to character array
        char tempArray[] = inputString.toCharArray();

        // Sorting temp array using
        Arrays.sort(tempArray);

        // Returning new sorted string
        return new String(tempArray);
    }
}
```

## 125. Valid Palindrome



A phrase is a **palindrome** if, after converting all uppercase letters into lowercase letters and removing all non-alphanumeric characters, it reads the same forward and backward. Alphanumeric characters include letters and numbers.

Given a string `s`, return `true` if it is a **palindrome**, or `false` otherwise.

**Example 1:**

**Input:** `s = "A man, a plan, a canal: Panama"`

**Output:** `true`

**Explanation:** "amanaplanacanalpanama" is a palindrome.

**Example 2:**

**Input:** `s = "race a car"`

**Output:** `false`

**Explanation:** "raceacar" is not a palindrome.

**Example 3:**

**Input:** `s = " "`

**Output:** `true`

**Explanation:** `s` is an empty string "" after removing non-alphanumeric characters. Since an empty string reads the same forward and backward, it is a palindrome.

**Constraints:**

- $1 \leq s.length \leq 2 * 10^5$
- `s` consists only of printable ASCII characters.

---

1.Array generic operation

```

class Solution {
    public boolean isPalindrome(String s) {
        s=s.toLowerCase().trim();
        s=s.replaceAll(" ", "");
        char[] ch=s.toCharArray();
        ArrayList<Character>arrayList=new ArrayList<>();
        for(char i:ch)
        {
            if((i>='a'&& i<='z')||(i>='0'&&i<='9'))
                arrayList.add(i);
        }
        for(int i=0;i<(arrayList.size()-1);i++)
        {
            if(arrayList.get(i)!=arrayList.get(arrayList.size() - 1 - i))
                return false;
        }
        return true;
    }
}

```

2. 2 pointer Note: Character.isLetterOrDigit(cHead) -> allows alphanumeric

```

public class Solution {
    public boolean isPalindrome(String s) {
        if (s.isEmpty()) {
            return true;
        }
        int head = 0, tail = s.length() - 1;
        char cHead, cTail;
        while(head <= tail) {
            cHead = s.charAt(head);
            cTail = s.charAt(tail);
            if (!Character.isLetterOrDigit(cHead)) {
                head++;
            } else if(!Character.isLetterOrDigit(cTail)) {
                tail--;
            } else {
                if (Character.toLowerCase(cHead) != Character.toLowerCase
(cTail)) {
                    return false;
                }
                head++;
                tail--;
            }
        }
        return true;
    }
}

```

## 128. Longest Consecutive Sequence



Given an unsorted array of integers `nums` , return *the length of the longest consecutive elements sequence*.

You must write an algorithm that runs in  $O(n)$  time.

### Example 1:

**Input:** `nums = [100,4,200,1,3,2]`

**Output:** 4

**Explanation:** The longest consecutive elements sequence is [1, 2, 3, 4]. Therefore its length is 4.

### Example 2:

**Input:** `nums = [0,3,7,2,5,8,4,6,0,1]`

**Output:** 9

### Constraints:

- $0 \leq \text{nums.length} \leq 10^5$
  - $-10^9 \leq \text{nums}[i] \leq 10^9$
-

```

class Solution {
    public int longestConsecutive(int[] nums) {
        // finding the number of digits that are continuous
        Arrays.sort(nums);
        //get the result as maximum continuous numbers
        int result=1;
        //continuous number count for each count
        int conti=1;
        for(int i=0;i<nums.length-1;i++)
        {
            //continuous number
            if(nums[i+1]==nums[i]+1)
            {
                conti++;
                result=conti>result?conti:result;
            }
            //same number
            else if(nums[i+1]==nums[i])
            {
                continue;
            }
            //reset for not continuous
            else
            {
                conti=1;
            }
        }
        //if length of nums is zero then no continuous number
        if(nums.length==0)
            return 0;
        else
            return result;
    }
}

```

## 150. Evaluate Reverse Polish Notation



You are given an array of strings `tokens` that represents an arithmetic expression in a Reverse Polish Notation ([http://en.wikipedia.org/wiki/Reverse\\_Polish\\_notation](http://en.wikipedia.org/wiki/Reverse_Polish_notation)).

Evaluate the expression. Return *an integer that represents the value of the expression*.

**Note** that:

- The valid operators are `'+'`, `'-'`, `'*'`, and `'/'`.
- Each operand may be an integer or another expression.
- The division between two integers always **truncates toward zero**.

- There will not be any division by zero.
- The input represents a valid arithmetic expression in a reverse polish notation.
- The answer and all the intermediate calculations can be represented in a **32-bit** integer.

#### Example 1:

**Input:** tokens = ["2","1","+","3","\*"]

**Output:** 9

**Explanation:**  $((2 + 1) * 3) = 9$

#### Example 2:

**Input:** tokens = ["4","13","5","/","+"]

**Output:** 6

**Explanation:**  $(4 + (13 / 5)) = 6$

#### Example 3:

**Input:** tokens = ["10","6","9","3","+","-11","\*","/", "\*", "17","+","5","+"]

**Output:** 22

**Explanation:**  $((10 * (6 / ((9 + 3) * -11))) + 17) + 5$

$= ((10 * (6 / (12 * -11))) + 17) + 5$

$= ((10 * (6 / -132)) + 17) + 5$

$= ((10 * 0) + 17) + 5$

$= (0 + 17) + 5$

$= 17 + 5$

$= 22$

#### Constraints:

- $1 \leq \text{tokens.length} \leq 10^4$
  - $\text{tokens}[i]$  is either an operator: "+", "-", "\*", or "/", or an integer in the range  $[-200, 200]$ .
-

```

public class Solution {
    public int evalRPN(String[] tokens) {
        int a,b;
        Stack<Integer> S = new Stack<Integer>();
        for (String s : tokens) {
            if(s.equals("+")) {
                S.add(S.pop()+S.pop());
            }
            else if(s.equals("/")) {
                b = S.pop();
                a = S.pop();
                S.add(a / b);
            }
            else if(s.equals("*")) {
                S.add(S.pop() * S.pop());
            }
            else if(s.equals("-")) {
                b = S.pop();
                a = S.pop();
                S.add(a - b);
            }
            else {
                S.add(Integer.parseInt(s));
            }
        }
        return S.pop();
    }
}

```

### Note:

to convert string to integer

```
Integer.parseInt(s)
```

## 155. Min Stack



Design a stack that supports push, pop, top, and retrieving the minimum element in constant time.

Implement the `MinStack` class:

- `MinStack()` initializes the stack object.
- `void push(int val)` pushes the element `val` onto the stack.
- `void pop()` removes the element on the top of the stack.
- `int top()` gets the top element of the stack.
- `int getMin()` retrieves the minimum element in the stack.

You must implement a solution with  $O(1)$  time complexity for each function.

### Example 1:

#### Input

```
["MinStack", "push", "push", "push", "getMin", "pop", "top", "getMin"]  
[[], [-2], [0], [-3], [], [], [], []]
```

#### Output

```
[null, null, null, null, -3, null, 0, -2]
```

#### Explanation

```
MinStack minStack = new MinStack();  
minStack.push(-2);  
minStack.push(0);  
minStack.push(-3);  
minStack.getMin(); // return -3  
minStack.pop();  
minStack.top();    // return 0  
minStack.getMin(); // return -2
```

### Constraints:

- $-2^{31} \leq \text{val} \leq 2^{31} - 1$
  - Methods `pop`, `top` and `getMin` operations will always be called on **non-empty** stacks.
  - At most  $3 \cdot 10^4$  calls will be made to `push`, `pop`, `top`, and `getMin`.
-



```

class MinStack {
    Stack<Integer> st;
    PriorityQueue<Integer> pq;
    public MinStack() {
        st=new Stack<>();
        pq=new PriorityQueue<>();
    }

    public void push(int val) {
        st.push(val);
        pq.add(val);
    }

    public void pop() {
        pq.remove(st.pop());
    }

    public int top() {
        return st.peek();
    }

    public int getMin() {
        return pq.peek();
    }
}

/**
 * Your MinStack object will be instantiated and called as such:
 * MinStack obj = new MinStack();
 * obj.push(val);
 * obj.pop();
 * int param_3 = obj.top();
 * int param_4 = obj.getMin();
 */

```

## 167. Two Sum II - Input Array Is Sorted



Given a **1-indexed** array of integers `numbers` that is already **sorted in non-decreasing order**, find two numbers such that they add up to a specific `target` number. Let these two numbers be `numbers[index1]` and `numbers[index2]` where  $1 \leq \text{index}_1 < \text{index}_2 \leq \text{numbers.length}$ .

Return *the indices of the two numbers*, `index1` and `index2`, **added by one** as an integer array `[index1, index2]` of length 2.

The tests are generated such that there is **exactly one solution**. You **may not** use the same element twice.

Your solution must use only constant extra space.

#### Example 1:

**Input:** numbers = [2,7,11,15], target = 9

**Output:** [1,2]

**Explanation:** The sum of 2 and 7 is 9. Therefore,  $\text{index}_1 = 1$ ,  $\text{index}_2 = 2$ . We return [1, 2].

#### Example 2:

**Input:** numbers = [2,3,4], target = 6

**Output:** [1,3]

**Explanation:** The sum of 2 and 4 is 6. Therefore  $\text{index}_1 = 1$ ,  $\text{index}_2 = 3$ . We return [1, 3].

#### Example 3:

**Input:** numbers = [-1,0], target = -1

**Output:** [1,2]

**Explanation:** The sum of -1 and 0 is -1. Therefore  $\text{index}_1 = 1$ ,  $\text{index}_2 = 2$ . We return [1, 2].

#### Constraints:

- $2 \leq \text{numbers.length} \leq 3 * 10^4$
- $-1000 \leq \text{numbers}[i] \leq 1000$
- numbers is sorted in **non-decreasing order**.
- $-1000 \leq \text{target} \leq 1000$
- The tests are generated such that there is **exactly one solution**.

1.

```
class Solution {
    public int[] twoSum(int[] numbers, int target) {
        int l = 0, r = numbers.length - 1;
        while (numbers[l] + numbers[r] != target) {
            if (numbers[l] + numbers[r] > target) r--;
            else l++;
        }
        return new int[]{l + 1, r + 1};
    }
}
```

2.

```
class Solution {
    public int[] twoSum(int[] numbers, int target) {
        int [] result=new int[2];
        int j=numbers.length-1;
        int i=0;
        while(i<j)
        {
            if(numbers[i]+numbers[j]==target)
            {
                result[0]=i+1;
                result[1]=j+1;
                break;
            }
            else if(numbers[i]+numbers[j]>target)
            {
                j--;
            }
            else
            {
                i++;
            }
        }
        return result;
    }
}
```

## 217. Contains Duplicate



Given an integer array `nums` , return `true` if any value appears **at least twice** in the array, and return `false` if every element is distinct.

### Example 1:

**Input:** `nums = [1,2,3,1]`

**Output:** `true`

### Example 2:

**Input:** `nums = [1,2,3,4]`

**Output:** `false`

### Example 3:

**Input:** `nums = [1,1,1,3,3,4,3,2,4,2]`

**Output:** `true`

**Constraints:**

- $1 \leq \text{nums.length} \leq 10^5$
- $-10^9 \leq \text{nums}[i] \leq 10^9$

```
class Solution {
    public boolean containsDuplicate(int[] nums) {
        HashSet<Integer> flag = new HashSet<Integer>();

        for(int i : nums) {
            if(!flag.add(i)) {
                return true;
            }
        }
        return false;
    }
}
```

## 238. Product of Array Except Self



Given an integer array `nums`, return an array `answer` such that `answer[i]` is equal to the product of all the elements of `nums` except `nums[i]`.

The product of any prefix or suffix of `nums` is **guaranteed** to fit in a **32-bit** integer.

You must write an algorithm that runs in  $O(n)$  time and without using the division operation.

**Example 1:**

**Input:** `nums = [1,2,3,4]`

**Output:** `[24,12,8,6]`

**Example 2:**

**Input:** `nums = [-1,1,0,-3,3]`

**Output:** `[0,0,9,0,0]`

**Constraints:**

- $2 \leq \text{nums.length} \leq 10^5$
- $-30 \leq \text{nums}[i] \leq 30$

- The product of any prefix or suffix of `nums` is **guaranteed** to fit in a **32-bit** integer.

**Follow up:** Can you solve the problem in  $O(1)$  extra space complexity? (The output array **does not** count as extra space for space complexity analysis.)

```
class Solution {
    public int[] productExceptSelf(int[] nums) {
        int n = nums.length;
        int[] res = new int[n];
        // Calculate lefts and store in res.
        int left = 1;
        for (int i = 0; i < n; i++) {
            if (i > 0)
                left = left * nums[i - 1];
            res[i] = left;
        }
        // Calculate rights and the product from the end of the array.
        int right = 1;
        for (int i = n - 1; i >= 0; i--) {
            if (i < n - 1)
                right = right * nums[i + 1];
            res[i] *= right;
        }
        return res;
    }
}
```

## 242. Valid Anagram



Given two strings `s` and `t`, return `true` if `t` is an anagram of `s`, and `false` otherwise.

An **Anagram** is a word or phrase formed by rearranging the letters of a different word or phrase, typically using all the original letters exactly once.

**Example 1:**

**Input:** `s = "anagram", t = "nagaram"`  
**Output:** `true`

**Example 2:**

**Input:** s = "rat", t = "car"

**Output:** false

**Constraints:**

- $1 \leq s.length, t.length \leq 5 * 10^4$
- s and t consist of lowercase English letters.

**Follow up:** What if the inputs contain Unicode characters? How would you adapt your solution to such a case?

```
class Solution {
    public boolean isAnagram(String s, String t) {
        int arr[] = new int[30];
        for (int i = 0; i < s.length(); i++)
        {
            int ch = (int)(s.charAt(i) - 'a');
            arr[ch]++;
        }
        for (int i = 0; i < t.length(); i++)
        {
            int ch = (int)(t.charAt(i) - 'a');
            arr[ch]--;
        }
        // int t=0;
        for (int i = 0; i < 30; i++)
        {
            if (arr[i] != 0)
                return false;
        }
        return true;
    }
}
```

## 347. Top K Frequent Elements



Given an integer array `nums` and an integer `k`, return *the k most frequent elements*. You may return the answer in **any order**.

**Example 1:**

**Input:** nums = [1,1,1,2,2,3], k = 2

**Output:** [1,2]

**Example 2:**

**Input:** nums = [1], k = 1

**Output:** [1]

**Constraints:**

- $1 \leq \text{nums.length} \leq 10^5$
- $-10^4 \leq \text{nums}[i] \leq 10^4$
- k is in the range [1, the number of unique elements in the array].
- It is **guaranteed** that the answer is **unique**.

**Follow up:** Your algorithm's time complexity must be better than  $O(n \log n)$ , where n is the array's size.

```
class Solution {
    public int[] topKFrequent(int[] nums, int k) {
        HashMap<Integer, Integer> map = new HashMap<>();
        for (int n : nums) {
            map.put(n, map.getOrDefault(n,0) + 1);
        }

        PriorityQueue<int[]> pq = new PriorityQueue<>((a,b) -> Integer.compare(a[1], b[1]));
        for (Map.Entry<Integer, Integer> e : map.entrySet()) {
            pq.add(new int[]{e.getKey(), e.getValue()});
            while (pq.size() > k) {
                pq.poll();
            }
        }

        int[] result = new int[k];
        for (int i = 0; i < k; i++) {
            result[i] = pq.poll()[0];
        }

        return result;
    }
}
```

## 739. Daily Temperatures



Given an array of integers `temperatures` represents the daily temperatures, return *an array* `answer` such that `answer[i]` is the number of days you have to wait after the  $i^{\text{th}}$  day to get a warmer temperature. If there is no future day for which this is possible, keep `answer[i] == 0` instead.

### Example 1:

**Input:** `temperatures = [73,74,75,71,69,72,76,73]`

**Output:** `[1,1,4,2,1,1,0,0]`

### Example 2:

**Input:** `temperatures = [30,40,50,60]`

**Output:** `[1,1,1,0]`

### Example 3:

**Input:** `temperatures = [30,60,90]`

**Output:** `[1,1,0]`

### Constraints:

- $1 \leq \text{temperatures.length} \leq 10^5$
- $30 \leq \text{temperatures}[i] \leq 100$

#### 1. Stacks

```
public int[] dailyTemperatures(int[] temperatures) {
    Stack<Integer> stack = new Stack<>();
    int[] ret = new int[temperatures.length];
    for(int i = 0; i < temperatures.length; i++) {
        while(!stack.isEmpty() && temperatures[i] > temperatures[stack.peek()]) {
            int idx = stack.pop();
            ret[idx] = i - idx;
        }
        stack.push(i);
    }
    return ret;
}
```

#### 2. Array



```
public int[] dailyTemperatures(int[] temperatures) {
    int[] stack = new int[temperatures.length];
    int top = -1;
    int[] ret = new int[temperatures.length];
    for(int i = 0; i < temperatures.length; i++) {
        while(top > -1 && temperatures[i] > temperatures[stack[top]]) {
            int idx = stack[top--];
            ret[idx] = i - idx;
        }
        stack[++top] = i;
    }
    return ret;
}
```

---