Three stress tests of UltraBreak

Axis 1: Image or text?

Inference only on an existing attack image



UltraBreak image



Typographic baseline
(plain text, no optimization)

Each image is run with the jailbreak prompt and with a neutral question

Compare

Drop in ASR when the jailbreak text is removed
UltraBreak vs. the typographic baseline

Axis 2: Newer models?

Inference only on recent open-weight VLMs

Matched pairs that differ in one property

Thinking vs. instruct

Qwen3-VL-8B-Instruct | Qwen3-VL-8B-Thinking

Preference-aligned vs. not

InternVL3.5-8B-Instruct | InternVL3.5-8B-MPO

Proposed pairs, to be confirmed

Compare

ASR difference within each pair
(thinking minus instruct, aligned minus unaligned)

Axis 3: Stable across runs?

Needs GPU time to re-optimize the image



seed 0 | seed 1 | seed 2

Re-optimize the image with several random seeds (and AdvBench if time allows)

Compare

Mean and standard deviation of ASR
across seeds

Every axis	ASR on held-out prompts, judged by a keyword check and an LLM judge, compared with a no-attack baseline, reported with confidence intervals.
Benign track	The image targets a harmless string. A response that begins with it means the model was steered; one that only contains it means the model read it.