Java Programming I

Introduction to Eclipse

Contents

- Features
- Creating a simple application
- Debugging applications
- Getting help information

Features

- Eclipse is an integrated development environment (IDE) used in computer programming, and is the most widely used Java IDE.
- It contains a base workspace and an extensible plug-in system for customizing the environment.
- Eclipse is written mostly in Java and its primary use is for developing Java applications.
- It may also be used to develop applications in other programming languages via plug-ins.

Eclipse platform



- The term Workbench refers to the desktop development environment. The Workbench aims to achieve seamless tool integration and controlled openness by providing a common paradigm for the creation, management, and navigation of workspace resources.

Eclipse platform

- Each Workbench window contains one or more perspectives.
- Perspectives contain views and editors and control what appears in certain menus and tool bars.
- More than one Workbench window can exist on the desktop at any given time.

Welcome window



Hello World App



Hello World App



Hello World App



Hello World App



Hello World App



Hello World App



Hello World App



Hello World App



Hello World App



Hello World App



Hello World App



Hello World App



Hello World App



Hello World App



Hello World App



Hello World App



Summary

- Start Eclipse.
- Create a new Java Project:
  - File->New->Java Project.
  - Enter a project name into the Project name field, for example, "Hello World Project".
  - Click "Finish"

Summary

- Create a new Java class:
  - File->New->Class
  - Enter "HelloWorld" into the Name field.
  - Click the checkbox indicating that you would like Eclipse to create a "public static void main(String[] args)" method.
  - Click "Finish".
  - A Java editor for HelloWorld.java will open. In the main method enter the following line:

    System.out.println("Hello World!");
  - Save using ctrl-s. This automatically compiles HelloWorld.java.

Summary

- Right Click on the HelloWorld name class.
- Select "Run as“ -> “Java Application”
- You will be prompted to create a Launch configuration. Select "Java Application“.
  - The console will open and display "Hello World!".

Debugging


workspace - Java - TestObjects/src/TestObjects2.java - Eclipse
File Edit Source Refactor Navigate Search Project Run Window Help
Quick Access
Package Explorer
HelloWorld
TestObjects
src
(default package)
TestObjects2.java
JRE System Library [JavaSE-1.8]
TestObjects2.java
30 }
31 public float getLength() {
32 return length;
33 }
34 public float getHeight() {
35 return height;
36 }
37 public float getWidth() {
38 return width;
39 }
40 public float perimeter() {
41 return 2* 2*(length + height) + 4* width;
42 }
43 }
44 public class TestObjects2 {
45
46 public static void main(String[] args) {
47 // TODO Auto-generated method stub
48 Rectangle r1 = new Rectangle(2.0f,3.0f);
49 Box b1 = new Box(2.0f,3.0f,4.0f);
Toggle Breakpoint Ctrl+Shift+B
Toggle Breakpoint Enablement
Go to Annotation Ctrl+1
Add Bookmark...
Add Task...
Show Quick Diff Ctrl+Shift+Q
Show Line Numbers
Folding
Preferences...
Breakpoint Properties...
Task List
Find
All
Activate...
Outline
Rectangle
length : float
height : float
Rectangle(float, float)
getLength() : float
getHeight() : float
perimeter() : float
Box
length : float
height : float
width : float
Box(float, float, float)
getLength() : float
No consoles to display at this time.
Writable
Smart Insert
29 : 9
Search Windows
ENG
8:39 PM
5/21/2017

Debugging


workspace - Java - TestObjects/src/TestObjects2.java - Eclipse
File Edit Source Refactor Navigate Search Project Run Window Help
Quick Access
1 TestObjects2
1 Java Application Alt+Shift+D, J
Debug As
Debug Configurations...
Organize Favorites...
TestObjects
src
(default package)
TestObjects2.java
JRE System Library [JavaSE-1.8]
}
public float getLength() {
return length;
}
public float getHeight() {
return height;
}
public float getWidth() {
return width;
}
public float perimeter() {
return 2* 2*(length + height) + 4* width;
}
}
public class TestObjects2 {
public static void main(String[] args) {
// TODO Auto-generated method stub
Rectangle r1 = new Rectangle(2.0f,3.0f);
Box b1 = new Box(2.0f,3.0f,4.0f);
System.out.println("Rectange: length=" + r1.getLength() +
" height=" + r1.getHeight() +
" perimeter=" + r1.perimeter());
System.out.println("Box: length=" + b1.getLength() +
" height=" + b1.getHeight() +
" width=" + b1.getWidth() +
" perimeter=" + b1.perimeter());
}
}
Task List
Find
All
Activate...
Outline
Rectangle
length : float
height : float
Rectangle(float, float)
getLength() : float
getHeight() : float
perimeter() : float
Box
length : float
height : float
width : float
Box(float, float, float)
getLength() : float
Problems
Javadoc
Declaration
Console
No consoles to display at this time.
TestObjects2.java - TestObjects/src
Search Windows
ENG
8:42 PM
5/21/2017

Debugging


Confirm Perspective Switch
This kind of launch is configured to open the Debug perspective when it suspends.
This Debug perspective is designed to support application debugging. It incorporates views for displaying the debug stack, variables and breakpoint management.
Do you want to open this perspective now?
Remember my decision
Yes
No

Debugging


workspace - Debug - TestObjects/src/TestObjects2.java - Eclipse
File Edit Source Refactor Navigate Search Project Run Window Help
Quick Access
Debug
TestObjects2 [Java Application]
TestObjects2 at localhost:63697
Thread [main] (Suspended (breakpoint at line 49 in TestObjects2))
TestObjects2.main(String[]) line: 49
C:\Program Files\Java\jre1.8.0_131\bin\javaw.exe (May 21, 2017, 8:06:38 PM)
Variables
Breakpoints
Name
Value
args
String[0] (id=16)
r1
Rectangle (id=17)
TestObjects2.java
45
46 public static void main(String[] args) {
47 // TODO Auto-generated method stub
48 Rectangle r1 = new Rectangle(2.0f,3.0f);
49 Box b1 = new Box(2.0f,3.0f,4.0f);
50 System.out.println("Rectange: length=" + r1.getLength() +
51 " height=" + r1.getHeight() +
52 " perimeter=" + r1.perimeter());
53 System.out.println("Box: length=" + b1.getLength() +
54 " height=" + b1.getHeight() +
55 " width=" + b1.getWidth() +
56 " perimeter=" + b1.perimeter());
57 }
58
59 }
60
Outline
getLength() : float
getHeight() : float
perimeter() : float
Box
length : float
height : float
width : float
Box(float, float, float)
getLength() : float
getHeight() : float
getWidth() : float
perimeter() : float
TestObjects2
main(String[]) : void
Console
Tasks
TestObjects2 [Java Application] C:\Program Files\Java\jre1.8.0_131\bin\javaw.exe (May 21, 2017, 8:06:38 PM)
Writable
Smart Insert
49 : 1

Debugging


workspace - Debug - TestObjects/src/TestObjects2.java - Eclipse
File Edit Source Refactor Navigate Search Project Run Window Help
Resume F8
Suspend
Terminate Ctrl+F2
Disconnect
Step Into F5
Step Into Selection Ctrl+F5
Step Over F6
Step Return F7
Run to Line Ctrl+R
Use Step Filters Shift+F5
Run Ctrl+F11
Debug F11
Run History
Run As
Run Configurations...
Debug History
Debug As
Debug Configurations...
Toggle Breakpoint Ctrl+Shift+B
Toggle Line Breakpoint
Toggle Method Breakpoint
Toggle Watchpoint
Skip All Breakpoints Ctrl+Alt+B
Remove All Breakpoints
Add Java Exception Breakpoint...
Add Class Load Breakpoint...
All References...
All Instances... Ctrl+Shift+N
Instance Count...
Watch
Inspect Ctrl+Shift+I
Display Ctrl+Shift+D
Execute Ctrl+U
Force Return Alt+Shift+F
External Tools
Variables
Breakpoints
Name
Value
args
String[0] (id=16)
r1
Rectangle (id=17)
Outline
getLength() : float
getHeight() : float
perimeter() : float
Box
length : float
height : float
width : float
Box(float, float, float)
getLength() : float
getHeight() : float
getWidth() : float
perimeter() : float
TestObjects2
main(String[]) : void
Writable
Smart Insert
49 : 1
Search Windows
ENG
8:20 PM
5/21/2017

Comments on the previous slide

- Debug: shows the live stack trace of methods. We are currently only in the main method of out program. If other programs were currently running, we would see them here. It also has some stepping buttons that we will cover shortly.
- Variables: shows the values of all the variables that have been declared.
- Breakpoints: this view shows the location of all our breakpoints in the code (we can have many different breakpoints).
- TestObject2.java: we can view where are in our code at the time of the breakpoint

Comments on the previous slide

- To create a *breakpoint*, right-click along the left side of the Java editor on the line of code you wish to break on, (Also, double-clicking on the left side of the editor will create a breakpoint.)
- Step into command: to step into the next method call at the currently executing line of code.
- Step over command: to step over the next method call (without entering it) at the currently executing line of code. Even though the method is never stepped into, the method will be executed normally.
  - To step into / step over a method you must have execution suspended and be stepping through code.

https://www.eclipse.org/users/



https://www.eclipse.org/neon/



Getting help information

- Query in Google:
  - how to debug java program in eclipse



https://blog.codecamp.jp/eclipse

Summary

- Eclipse is a powerful IDE.
- It is a main instrument to create and debug Java application.
- It protects users from many types of errors at the development process.
- It provides users with simple and powerful tools to debug applications.
- It has intuitively understood GUI.