



Vidyavardhini's College of Engineering and Technology
Department of Artificial Intelligence & Data Science

Experiment No.9
Implementation of Graph traversal techniques - Depth First Search, Breadth First Search
Name: suzen machado
Roll No: 23
Date of Performance:03/10/23
Date of Submission: 10/10/23
Marks:
Sign:

Experiment No. 9: Depth First Search and Breath First Search

Aim : Implementation of DFS and BFS traversal of graph.


Objective:

1. Understand the Graph data structure and its basic operations.
2. Understand the method of representing a graph.
3. Understand the method of constructing the Graph ADT and defining its operations

Theory:

A graph is a collection of nodes or vertices, connected in pairs by lines referred to as edges. A graph can be directed or undirected.

One method of traversing through nodes is depth first search. Here we traverse from the starting node and proceed from top to bottom. At a moment we reach a dead end from where the further movement is not possible and we backtrack and then proceed according to left right order. A stack is used to keep track of a visited node which helps in backtracking.



	0	1	2	3	4
0	0	1	0	0	1
1	1	0	1	1	1
2	0	1	0	1	0
3	0	1	1	0	1
4	1	1	0	1	0

DFS Traversal –0 1 2 3 4

Algorithm

Algorithm: DFS_LL(V)

Input: V is a starting vertex


Output : A list VISIT giving order of visited vertices during traversal.

Description: linked structure of graph with gptra as pointer

1. if gptra = NULL then print “Graph is empty” exit
2. u=v
3. OPEN.PUSH(u)
4. while OPEN.TOP !=NULL do
 - u=OPEN.POP()
 - if search(VISIT,u) = FALSE then
 - INSERT_END(VISIT,u)
 - Ptr = gptra(u)
 - While ptr.LINK != NULL do
 - Vptr = ptr.LINK
 - OPEN.PUSH(vptr.LABEL)
 - End while
- End if
- End while
5. Return VISIT
6. Stop



BFS Traversal



	0	1	2	3	4
0	0	1	0	0	1
1	1	0	1	1	1
2	0	1	0	1	0
3	0	1	1	0	1
4	1	1	0	1	0

BFS Traversal – 0 1 4 2 3 Algorithm

Algorithm: DFS() i=0

count=1 visited[i]=1

print("Visited vertex i")

repeat this till queue is empty or all nodes visited

repeat this for all nodes from first till last

if($g[i][j] \neq 0$ & $visited[j] \neq 1$)

{ push(j) } i=pop()

print("Visited vertex i")

visited[i]=1 count++

Algorithm: BFS() i=0

count=1

visited[i]=1

print("Visited vertex i")

repeat this till queue is empty or all nodes visited

repeat this for all nodes from first till last

if($g[i][j] \neq 0$ & $visited[j] \neq 1$)



```
{
enqueue(j)
}

i=dequeue()
print("Visited vertex
i") visited[i]=1 count++
```

Code:

Dfs

```
#include <stdio.h> #define MAX 5 void
depth_first_search(int adj[][MAX],int visited[],int start)
{
    int stack[MAX];
    int top = - 1, i; printf("%c-
",start + 65); visited[start] = 1;
    stack[++top] = start;
    while(top!= -1)
    {
        start = stack[top];
        for(i = 0; i < MAX; i++)
        {
            if(adj[start][i] && visited[i] == 0)
            {
```



Vidyavardhini's College of Engineering and Technology

Department of Artificial Intelligence & Data Science

```
stack[++top] = i;

printf("%c-", i + 65);

visited[i] = 1; break;

}

}

        if(i == MAX)

top--;

}

}

int main()

{

    int adj[MAX][MAX];

    int visited[MAX] = {0}, i, j;

    printf("\n Enter the adjacency matrix: ");

    for(i = 0; i < MAX; i++)        for(j =

0; j < MAX; j++) scanf("%d", &adj[i][j]);

    printf("DFS Traversal: ");

    depth_first_search(adj,visited,0);

    printf("\n");

    return 0;

}
```



Bfs

```
#include <stdio.h> #define MAX 10 void  
breadth_first_search(int adj[][MAX],int visited[],int start)  
{  
    int queue[MAX],rear=-1,front=-1, i;  
    queue[++rear] = start; visited[start] = 1;  
    while(rear != front)  
    {  
        start = queue[++front];  
        if(start == 4)  
            printf("5\t"); else  
            printf("%c \t",start + 65);  
        for(i = 0; i < MAX; i++)  
        {  
            if(adj[start][i] == 1 && visited[i] == 0)  
            {  
                queue[++rear] = i; visited[i]  
= 1;  
            }  
        }  
    }  
}  
int main()
```



Vidyavardhini's College of Engineering and Technology

Department of Artificial Intelligence & Data Science

```
{  
    int visited[MAX] = {0};  
  
    int adj[MAX][MAX], i, j;  
  
    printf("\n Enter the adjacency matrix: ");  
  
    for(i = 0; i < MAX; i++)        for(j =  
0; j < MAX; j++)  
  
        scanf("%d", &adj[i][j]);  
  
    breadth_first_search(adj,visited,0);  
  
    return 0;  
}
```

Output:

dfs

The screenshot shows a C++ IDE with a menu bar (File, Edit, Search, Run, Compile, Debug, Project, Options, Window, Help) and a toolbar. The main window displays the following text:

```
Enter the adjacency matrix: 0 1 1 0 0  
1 0 0 1 0  
1 0 0 1 1  
0 1 1 0 1  
0 0 1 1 0  
DFS Traversal: A-B-D-C-E-
```

Bfs



Vidyavardhini's College of Engineering and Technology

Department of Artificial Intelligence & Data Science

```
Output 2=111
Enter the adjacency matrix: 0 1 0 1 0 0 0 0 0 0
1 0 1 0 1 0 0 0 0 0
0 1 0 0 0 1 0 0 0 0
1 0 0 0 0 0 1 0 0 0
0 1 0 0 0 0 0 1 0 0
0 0 1 0 0 0 0 0 1 0
0 0 0 1 0 0 0 0 0 1
0 0 0 0 1 0 0 0 0 0
0 0 0 0 1 0 0 0 0 0
0 0 0 0 0 1 0 0 0 0
0 0 0 0 0 1 0 0 0 0
A      B      D      C      5      G      F      H      J      I
```

Conclusion:

1) Write the graph representation used by your program and explain why you choose that.

- The program uses an adjacency matrix to represent the graph. An adjacency matrix is a 2D array where each cell $adj[i][j]$ represents an edge between vertex i and vertex j . The value in the cell indicates the presence (usually 1) or absence (usually 0) of an edge. This representation was chosen because it provides a simple and straightforward way to implement both depth-first search (DFS) and breadth-first search (BFS) algorithms. It allows for easy traversal and checking of connections between nodes. However, it may not be the most memory-efficient representation for sparse graphs.

2) Write the applications of BFS and DFS other than finding connected nodes and explain how it is attained?

- Applications of BFS and DFS:

- Shortest Path Finding: Both BFS and DFS can be used to find the shortest path between two nodes in a graph. BFS typically finds the shortest path in an unweighted graph, while DFS can find paths in weighted graphs using backtracking.
- Web Crawling: Search engines use BFS to crawl and index web pages efficiently. Starting from a seed webpage, they explore links level by level.
- Solving Puzzles: DFS is commonly used to solve puzzles like mazes, Sudoku, and the NQueens problem. It explores possible solutions by trying various paths.
- Network Broadcasting: BFS is used for broadcasting messages or information in computer networks. It ensures that messages reach all connected nodes without unnecessary duplication.
- Topological Sorting: DFS can be used to find the topological ordering of vertices in a directed acyclic graph, which is essential in scheduling and task management.



Vidyavardhini's College of Engineering and Technology

Department of Artificial Intelligence & Data Science

- Spanning Trees: Both algorithms are used to find minimum spanning trees in graphs, which have applications in network design and clustering.
- Social Networking: BFS can help find the degree of separation between two individuals in a social network, such as the "Six Degrees of Kevin Bacon" game.
- Garbage Collection: DFS is used in garbage collection algorithms to reclaim memory from objects that are no longer reachable in programming languages like Java.

These algorithms can be adapted and applied in various domains to solve a wide range of problems beyond simply finding connected nodes in a graph.