

Genealogies of Sequential Monte Carlo Algorithms

Suzie Brown

with Jere Koskela, Adam Johansen and Paul Jenkins

Department of Statistics, University of Warwick


WARWICK
THE UNIVERSITY OF WARWICK

OxWaSP

Sequential Monte Carlo

SMC¹ is an effective Monte Carlo method for models with strong correlation between parameters. For example, inferring a sequence of underlying parameters from an autocorrelated time series.

We approximate posterior distributions by samples of “particles”. The algorithm starts with N equally-weighted particles and repeats the steps:



1. **Propagate:** update particle positions for the next parameter
2. **Weight:** weight particles according to agreement with the observation
3. **Resample:** duplicate high-weight particles and kill off low-weight particles to obtain a new sample of N particles.

The figure shows a particle approximation for a tractable model. The exact posterior mode and 95% HPD set are obtained with the Kalman filter.




Figure: Exact posterior (purple) and weighted SMC particles before resampling (black) for a linear Gaussian HMM.

Ancestral Degeneracy

For some applications, we want to approximate the *joint* distribution over all parameters. We have N samples from this distribution: the “trajectories” of each of the N particles.

Due to resampling these trajectories overlap, coalescing backwards in time. At some point all the trajectories coalesce, and we approximate that parameter's distribution with just one sample!





Figure: Trajectories from a sample of $N=6$ particles. At most points there are just one or two distinct samples.

This phenomenon is known as *ancestral degeneracy*², since the joint structure of the trajectories can be viewed as a *genealogy* of particles. It is one of the main issues in SMC, so we would like to analyse it.

The Kingman Coalescent

Kingman's N -coalescent is the coalescent process on a population of size N in which each pair of lineages merges with unit rate.

The Kingman coalescent³ arises as an extension of the N -coalescent in the $N \rightarrow \infty$ limit. It is the limiting genealogy for a large class of population models.



A realisation of the 50-coalescent.

Source: Wikimedia Commons

SMC Genealogies

The genealogy depends on the number of offspring of each particle upon resampling at each time t , denoted $(\nu_t^{(1)}, \dots, \nu_t^{(N)})$. A key quantity in the asymptotic analysis is the coalescence rate

$$c_N(t) := \frac{1}{(N)_2} \sum_{i=1}^N \mathbb{E} \left[(\nu_t^{(i)})_2 \right].$$

To obtain convergence to the Kingman coalescent, we rescale time by the inverse coalescence rate to achieve the required unit rate.

It has been shown that, under such a rescaling and some standard assumptions, genealogies induced by multinomial resampling converge (in the sense of finite-dimensional distributions) to the Kingman coalescent⁴. Simulations show the same structure even for finite N .

We have since extended this result to cover conditional SMC⁵ with multinomial resampling. In this algorithm, a certain “immortal trajectory” is conditioned to survive all the resampling steps. This still admits the Kingman coalescent as its limiting genealogy, but simulations show different behaviour for $N < \infty$.

CSMC treeheight, $N=8192$




Figure: Average height of subtrees with n randomly chosen nodes, for different choices of immortal trajectory.

It appears that the process undergoes a phase transition when the immortal trajectory is particularly “unlikely” and n approaches N .

1. Gordon, N. J., Salmond, D. J., & Smith, A. F. (1993). Novel approach to nonlinear/non-Gaussian Bayesian state estimation. *IEE:F* 140(3), 107-113. IET Digital Library.
2. Doucet, A., & Johansen, A. M. (2011). A tutorial on particle filtering and smoothing: Fifteen years later. *Handbook of nonlinear filtering*, 656-704. OUP.
3. Kingman, J.F.C. (1982). The coalescent. *Stochastic processes and their applications*, 13(3), 235-248.
4. Koskela, J. et al. (2018). Asymptotic genealogies of interacting particle systems with an application to sequential Monte Carlo. arXiv:1804.01811.
5. Andrieu, C., Doucet, A., & Holenstein, R. (2010). Particle Markov chain Monte Carlo methods. *RSS:B*, 72(3), 269-342.