index.html

Online Quiz Application - page structure (HTML)

```html
<!DOCTYPE html>
<html lang="en">
<head>
<meta charset="UTF-8">
<meta name="viewport" content="width=device-width, initial-scale=1">
<title>Online Quiz Application</title>
<link rel="stylesheet" href="style.css">
</head>
<body>
<main class="card" id="app">

  <!-- Screen 1: Category selection -->
  <section id="screen-home">
    <h1>Online Quiz</h1>
    <p class="sub">Choose a category to begin. Each quiz is timed.</p>
    <div id="categories" class="grid"></div>
  </section>

  <!-- Screen 2: Quiz -->
  <section id="screen-quiz" class="hidden">
    <div class="topbar">
      <span id="cat-name"></span>
      <span id="timer" class="timer">00:00</span>
    </div>
    <div class="progress"><div id="bar"></div></div>
    <p class="count" id="q-count"></p>
    <h2 id="q-text"></h2>
    <div id="options"></div>
    <div class="nav">
      <button id="btn-prev" class="btn ghost">Previous</button>
      <button id="btn-next" class="btn">Next</button>
    </div>
  </section>

  <!-- Screen 3: Result -->
  <section id="screen-result" class="hidden">
    <h1>Quiz Result</h1>
    <div class="score-box">
      <div class="big" id="score-text"></div>
      <div id="percent-text"></div>
      <div id="best-text" class="best"></div>
    </div>
    <h3>Performance Summary</h3>
    <table id="summary"></table>
    <h3>Answer Review</h3>
    <div id="review"></div>
    <div class="nav">
      <button id="btn-restart" class="btn">Restart Quiz</button>
      <button id="btn-home" class="btn ghost">Another Category</button>
    </div>
  </section>

</main>
<script src="script.js"></script>
</body>
</html>
```