

```
In [1]: import pandas as pd
from openpyxl.workbook import Workbook

#reading excel file
df = pd.read_excel('C:/Users/svasudev/OneDrive - IGMFinancial/Documents/Predictive Analyti
engine='openpyxl', sheet_name=0, header=0, index_col=False, keep_default_na=
```

```
In [2]: #Top 5 rows of the Excel file
df.head()
```

Out[2]:

	Date	Ottawa	Toronto West/Ouest	Toronto East/Est	Windsor	London	Peterborough	St. Catharine's	Sudbury	Sault Saint Marie	Thunder Bay	N
0	1990-01-03	55.9	49.1	48.7	45.2	50.1	0.0	0.0	56.4	54.8	56.6	
1	1990-01-10	55.9	47.7	46.8	49.7	47.6	0.0	0.0	56.4	54.9	56.8	
2	1990-01-17	55.9	53.2	53.2	49.6	53.7	0.0	0.0	55.8	54.9	56.8	
3	1990-01-24	55.9	53.2	53.5	49.0	52.1	0.0	0.0	55.7	54.9	56.8	
4	1990-01-31	55.9	51.9	52.6	48.6	49.1	0.0	0.0	55.6	54.8	56.8	

```
In [3]: #Datatype and Null Information about the columns in the Excel file
df.info()
```

```
<class 'pandas.core.frame.DataFrame'>
RangeIndex: 9962 entries, 0 to 9961
Data columns (total 20 columns):
#   Column                                     Non-Null Count  Dtype
---  -
0   Date                                     9962 non-null   datetime64[ns]
1   Ottawa                                 9962 non-null   float64
2   Toronto West/Ouest                     9962 non-null   float64
3   Toronto East/Est                       9962 non-null   float64
4   Windsor                                9962 non-null   float64
5   London                                 9962 non-null   float64
6   Peterborough                           9962 non-null   float64
7   St. Catharine's                        9962 non-null   float64
8   Sudbury                                9962 non-null   float64
9   Sault Saint Marie                      9962 non-null   float64
10  Thunder Bay                             9962 non-null   float64
11  North Bay                               9962 non-null   float64
12  Timmins                                 9962 non-null   float64
13  Kenora                                  9962 non-null   float64
14  Parry Sound                             9962 non-null   float64
15  Ontario Average/Moyenne provinciale    9962 non-null   float64
16  Southern Average/Moyenne du sud de l'Ontario  9962 non-null   float64
17  Northern Average/Moyenne du nord de l'Ontario 9962 non-null   float64
```

```
18 Fuel Type          9962 non-null    object
19 Type de carburant   9962 non-null    object
dtypes: datetime64[ns](1), float64(17), object(2)
memory usage: 1.5+ MB
```

```
In [4]: #Creating a new dataframe
df2 = pd.DataFrame()
```

```
In [5]: #Choosing rows from the original dataframe with Fuel Type "Premium Gasoline" and pasting it
df2 = df.loc[df['Fuel Type']=='Premium Gasoline']
```

```
In [6]: #Datatype and Null Information about the columns in the new dataframe
df2.info()
```

```
<class 'pandas.core.frame.DataFrame'>
Int64Index: 1675 entries, 6612 to 8286
Data columns (total 20 columns):
#   Column                                     Non-Null Count  Dtype
---  -
0   Date                                     1675 non-null   datetime64[ns]
1   Ottawa                                 1675 non-null   float64
2   Toronto West/Ouest                     1675 non-null   float64
3   Toronto East/Est                       1675 non-null   float64
4   Windsor                                 1675 non-null   float64
5   London                                 1675 non-null   float64
6   Peterborough                           1675 non-null   float64
7   St. Catharine's                        1675 non-null   float64
8   Sudbury                                1675 non-null   float64
9   Sault Saint Marie                      1675 non-null   float64
10  Thunder Bay                            1675 non-null   float64
11  North Bay                              1675 non-null   float64
12  Timmins                                1675 non-null   float64
13  Kenora                                 1675 non-null   float64
14  Parry Sound                            1675 non-null   float64
15  Ontario Average/Moyenne provinciale    1675 non-null   float64
16  Southern Average/Moyenne du sud de l'Ontario 1675 non-null   float64
17  Northern Average/Moyenne du nord de l'Ontario 1675 non-null   float64
18  Fuel Type                               1675 non-null   object
19  Type de carburant                       1675 non-null   object
dtypes: datetime64[ns](1), float64(17), object(2)
memory usage: 274.8+ KB
```

```
In [7]: df2.head()
```

```
Out[7]:
```

	Date	Ottawa	Toronto West/Ouest	Toronto East/Est	Windsor	London	Peterborough	St. Catharine's	Sudbury	Sault Saint Marie	Thunder Bay
6612	1990-01-03	59.5	52.9	52.7	49.2	54.0	0.0	0.0	60.2	58.6	60.4
6613	1990-01-10	59.6	51.6	50.9	53.7	51.5	0.0	0.0	60.2	58.7	60.5
6614	1990-01-17	59.7	57.4	57.4	53.6	57.6	0.0	0.0	59.6	58.6	60.6
6615	1990-01-24	59.8	57.1	57.5	53.1	56.0	0.0	0.0	59.5	58.6	60.5

	Date	Ottawa	Toronto West/Ouest	Toronto East/Est	Windsor	London	Peterborough	St. Catharine's	Sudbury	Sault Saint Marie	Thunder Bay
6616	1990-01-31	59.8	55.9	56.6	52.6	53.1	0.0	0.0	59.5	58.6	60.6

```
In [8]: #Creating a new dataframe
df3 = pd.DataFrame()
```

```
In [9]: #Analyzing 'Premium Gasoline' price for Toronto West/Ouest Region only and pasting it into df3
df3.insert(0, "Date", df2['Date'], True)
df3.insert(1, "Toronto West/Ouest", df2['Toronto West/Ouest'], True)
```

```
In [10]: df3.head()
```

```
Out[10]:
```

	Date	Toronto West/Ouest
6612	1990-01-03	52.9
6613	1990-01-10	51.6
6614	1990-01-17	57.4
6615	1990-01-24	57.1
6616	1990-01-31	55.9

```
In [11]: #Date column only had weekly values. Sometimes the week started on Wednesday and sometimes on Thursday.
#this inconsistency, converting the date column into daily values and assigning the previous value to the daily values.
df3.set_index('Date', inplace=True)
df3 = df3.resample('D').ffill().reset_index()
```

```
In [12]: #Last 10 values from the dataset
df3.tail(10)
```

```
Out[12]:
```

	Date	Toronto West/Ouest
11707	2022-01-22	171.7
11708	2022-01-23	171.7
11709	2022-01-24	173.8
11710	2022-01-25	173.8
11711	2022-01-26	173.8
11712	2022-01-27	173.8
11713	2022-01-28	173.8
11714	2022-01-29	173.8
11715	2022-01-30	173.8
11716	2022-01-31	179.1

```
In [13]: #Checking for null values
df3.isnull().values.any()
```

```
Out[13]: False
```

```
In [14]: #Splitting the "Date" column into year, month and week to explore trends
df3['Year']=df3['Date'].dt.year
df3['Month']=df3['Date'].dt.month
df3['Week']=df3['Date'].dt.isocalendar().week
```

```
In [15]: df3.head(10)
```

```
Out[15]:
```

	Date	Toronto West/Ouest	Year	Month	Week
0	1990-01-03	52.9	1990	1	1
1	1990-01-04	52.9	1990	1	1
2	1990-01-05	52.9	1990	1	1
3	1990-01-06	52.9	1990	1	1
4	1990-01-07	52.9	1990	1	1
5	1990-01-08	52.9	1990	1	2
6	1990-01-09	52.9	1990	1	2
7	1990-01-10	51.6	1990	1	2
8	1990-01-11	51.6	1990	1	2
9	1990-01-12	51.6	1990	1	2

```
In [16]: #Splitting the dataset in Train and Test
#Train from Year 1990 to Year 2019
#Test from Year 2020

train = df3[(df3['Date'] > '1990-01-01') & (df3['Date'] <= '2019-12-31')]
test = df3[df3['Date'] >= '2020-01-01']
```


Yearly Price Visualization on Train and Test Dataset

```
In [17]: import matplotlib.pyplot as plt
from matplotlib.pyplot import figure

yearly_train_Price = train.groupby(['Year'])['Toronto West/Ouest'].mean()
yearly_test_Price = test.groupby(['Year'])['Toronto West/Ouest'].mean()

figure(figsize=(15, 4), dpi=80)
plt.plot(yearly_train_Price, label='Train',c='blue')
plt.plot(yearly_test_Price, label='Test',c='orange')
plt.legend(loc='best')
plt.suptitle('Premium Gasoline Prices for Toronto West/Ouest', fontsize=20)
plt.xlabel('Year')
plt.ylabel('Price (cents per litre)')
plt.show()
```

Premium Gasoline Prices for Toronto West/Ouest



DataPrep for Time Series

```
In [18]: train.index = pd.DatetimeIndex(train['Date'])
#Changing the frequency of the index to Daily
train.index = train.asfreq('d').index

test.index = pd.DatetimeIndex(test['Date'])
#Changing the frequency of the index to Daily
test.index = test.asfreq('d').index
```

Train and Time Series Dataset

```
In [19]: train_time_series = pd.DataFrame()
train_time_series.index = train.index
train_time_series.insert(0,"Toronto West/Ouest Gas Price Train",train['Toronto West/Ouest'])

test_time_series = pd.DataFrame()
test_time_series.index = test.index
test_time_series.insert(0,"Toronto West/Ouest Gas Price Test",test['Toronto West/Ouest'],1)

print(train_time_series.tail())
print(test_time_series.tail())
```

```
Toronto West/Ouest Gas Price Train
Date
2019-12-27      140.0
2019-12-28      140.0
2019-12-29      140.0
2019-12-30      141.4
2019-12-31      141.4

Toronto West/Ouest Gas Price Test
Date
2022-01-27      173.8
2022-01-28      173.8
2022-01-29      173.8
2022-01-30      173.8
2022-01-31      179.1
```

ARIMA Model

To predict time series with ARIMA, we need to set the values of three parameters (p,d,q):

p: The order of the auto-regressive (AR) model (i.e., the number of lag observations)

d: The degree of differencing.

q: The order of the moving average (MA) model.

Checking if data is stationary - We can see that it is not based on the P-value - Augmented Dickey Fuller Test

In [20]:

```
from statsmodels.tsa.stattools import adfuller
results = adfuller(train_time_series['Toronto West/Ouest Gas Price Train'])
print('ADF Statistic: ', results[0])
print('p-value: ', results[1])
print('Critical Values', results[4])
```

```
ADF Statistic: -1.6893782195924107
p-value: 0.43659327958563665
Critical Values {'1%': -3.4309487036285113, '5%': -2.8618045938569296, '10%': -2.5669108381800188}
```

Taking First difference - P value is < 0.05 . We can stop at the First Difference; $d = 1$

In [21]:


```
train_time_series_stationary1 = train_time_series.diff().dropna()
results1 = adfuller(train_time_series_stationary1['Toronto West/Ouest Gas Price Train'])
print('ADF Statistic: ', results1[0])
print('p-value: ', results1[1])
print('Critical Values', results1[4])
```

```
ADF Statistic: -17.831642858594112
p-value: 3.1316063696252024e-30
Critical Values {'1%': -3.4309487036285113, '5%': -2.8618045938569296, '10%': -2.5669108381800188}
```

The Order of Autoregressive Term p ; $p = 0$

In [22]:


```
plt.rcParams.update({'figure.figsize': (12, 3), 'figure.dpi': 120})
from statsmodels.graphics.tsaplots import plot_pacf
plot_pacf(train_time_series_stationary1, lags=10, title="Partial Autocorrelation 1st Order Differencing")
plt.xlabel('Lag')
plt.ylabel('PACF')
plt.show()
```



The order of the Moving Average term q ; $q = 0$

In [23]:

```
plt.rcParams.update({'figure.figsize':(12,3), 'figure.dpi':120})
from statsmodels.graphics.tsaplots import plot_acf
plot_acf(train_time_series_stationary1, lags=20, title="Autocorrelation 1st Order Differencing")
plt.xlabel('Lag')
plt.ylabel('ACF')
plt.show()
```



Check the above p,d,q parameters with Auto Arima - Best Model ARIMA (0,1,0)

In [24]:

```
import pmdarima as pm
from pmdarima.model_selection import train_test_split
import numpy as np

modell = pm.auto_arima(train_time_series, trace=True, error_action='ignore', suppress_warnings=True)
modell.fit(train_time_series)

forecast1 = modell.predict(n_periods=len(test_time_series))
forecast1 = pd.DataFrame(forecast1, index = test_time_series.index, columns=['Prediction'])
```

Performing stepwise search to minimize aic

```
ARIMA(2,1,2) (0,0,0) [0] intercept : AIC=33257.281, Time=1.48 sec
ARIMA(0,1,0) (0,0,0) [0] intercept : AIC=33249.281, Time=0.25 sec
ARIMA(1,1,0) (0,0,0) [0] intercept : AIC=33251.281, Time=0.67 sec
ARIMA(0,1,1) (0,0,0) [0] intercept : AIC=33251.281, Time=0.82 sec
ARIMA(0,1,0) (0,0,0) [0]           : AIC=33247.868, Time=0.13 sec
ARIMA(1,1,1) (0,0,0) [0] intercept : AIC=33253.281, Time=1.09 sec
```

Best model: ARIMA(0,1,0) (0,0,0) [0]

Total fit time: 4.488 seconds

Model Summary

In [25]:

```
import statsmodels.api as sm
model = sm.tsa.arima.ARIMA(train_time_series, order=(0,1,0))
model_result = model.fit()
print(model_result.summary())
```

SARIMAX Results

```
=====
=====
Dep. Variable:      Toronto West/Ouest Gas Price Train    No. Observations:      1
0955
Model:              ARIMA(0, 1, 0)    Log Likelihood      -1662
2.934
Date:              Sun, 06 Mar 2022    AIC      3324
```

```
7.868
Time: 17:15:16 BIC 3325
5.169
Sample: 01-03-1990 HQIC 3325
0.328
```

- 12-31-2019

Covariance Type: opg

```
=====
              coef      std err          z      P>|z|      [0.025      0.975]
-----
sigma2          1.2180          0.002      524.838      0.000          1.213          1.223
=====
Ljung-Box (L1) (Q):                0.00      Jarque-Bera (JB):          4437271.29
Prob(Q):                1.00      Prob(JB):                0.00
Heteroskedasticity (H):            1.67      Skew:                1.24
Prob(H) (two-sided):            0.00      Kurtosis:            101.57
=====
```

Warnings:

[1] Covariance matrix calculated using the outer product of gradients (complex-step).

Model Prediction

```
In [26]: import warnings
warnings.filterwarnings('ignore')
ARIMA_Predict = model_result.predict(start='1/1/2020', end='1/31/2022')
ARIMA_Predict_df = pd.DataFrame(ARIMA_Predict)
```


```
In [27]: ARIMA_Predict_df.tail()
```

```
Out[27]:
```

	predicted_mean
2022-01-27	141.4
2022-01-28	141.4
2022-01-29	141.4
2022-01-30	141.4
2022-01-31	141.4

```
In [28]: figure(figsize=(15, 4), dpi=80)
plt.plot(ARIMA_Predict_df, label='Predicted Prices',c='blue')
plt.plot(test_time_series, label='Original Prices',c='orange')
plt.legend(loc='best')
plt.suptitle('ARIMA Model Premium Gasoline Prices Forecast Toronto West/Ouest', fontsize=20)
plt.xlabel('Year')
plt.ylabel('Price (cents per litre)')
plt.show()
```


ARIMA Model Premium Gasoline Prices Forecast Toronto West/Ouest



Evaluation of the Model

Mean Absolute Error (MAE) ARIMA

```
In [29]: from sklearn.metrics import mean_absolute_error
maeARIMA=mean_absolute_error(test_time_series['Toronto West/Ouest Gas Price Test'],ARIMA_P
print('Mean Absolute Error ARIMA = {}'.format(round(maeARIMA, 2)))
```

Mean Absolute Error ARIMA = 17.67

Mean squared error (MSE) ARIMA

```
In [30]: from sklearn.metrics import mean_squared_error
mseARIMA=mean_squared_error(test_time_series['Toronto West/Ouest Gas Price Test'],ARIMA_P
print('The Mean Squared Error ARIMA = {}'.format(round(mseARIMA, 2)))
```

The Mean Squared Error ARIMA = 404.84

Root mean squared error (RMSE) ARIMA

```
In [31]: from numpy import sqrt
rmseARIMA = sqrt(mseARIMA)
print('The Root Mean Squared Error ARIMA = {}'.format(round(rmseARIMA, 2)))
```


The Root Mean Squared Error ARIMA = 20.12

Prophet Model

```
In [32]: from fbprophet import Prophet
d={'ds':train['Date'],'y':train['Toronto West/Ouest']}
df_pred=pd.DataFrame(data=d)
model_prophet = Prophet(daily_seasonality=False)
model_prophet_result = model_prophet.fit(df_pred)
```

```
In [33]: future = model_prophet.make_future_dataframe(periods=765)
forecast = model_prophet.predict(future)
forecast = forecast[(forecast['ds'] >= '2020-01-01') & (forecast['ds'] <= '2022-01-31')]
```

```
In [34]: fig, ax = plt.subplots()
ax.plot(forecast['ds'], forecast['yhat'], label='Predicted Prices')
ax.plot(test['Date'], test['Toronto West/Ouest'], label='Original Prices')
plt.ylim([0,200])
legend = ax.legend(loc='upper center', shadow=True)
plt.title('Prophet Model Premium Gasoline Prices Forecast Toronto West/Ouest')
plt.xlabel('Month')
plt.ylabel('Price')
plt.show()
```



Mean Absolute Error (MAE) Prophet

```
In [35]: maeProphet=mean_absolute_error(test['Toronto West/Ouest'],forecast['yhat'])
print('Mean Absolute Error Prophet = {}'.format(round(maeProphet, 2)))
```

Mean Absolute Error Prophet = 17.52

Mean squared error (MSE) Prophet

```
In [36]: mseProphet = mean_squared_error(test['Toronto West/Ouest'],forecast['yhat'])
print('The Mean Squared Error Prophet = {}'.format(round(mseProphet, 2)))
```

The Mean Squared Error Prophet = 423.9

Root mean squared error (RMSE) Prophet

```
In [37]: rmseProphet = sqrt(mseProphet)
print('The Root Mean Squared Error Prophet = {}'.format(round(rmseProphet, 2)))
```

The Root Mean Squared Error Prophet = 20.59