Name: Saai Vardhan D
Registration number : 192525205

CSA 0421 - OPERATING SYSTEM

Experiment 1:

Create a new process by invoking the appropriate system call. Get the process identifier of the
currently running process and its respective parent using system calls and display the same
using a C program.

Executable C program :

```c
#include <stdio.h>
#include <stdlib.h>
int main()
{
   FILE *fptr1, *fptr2;
   char filename[100], c;
   printf("Enter the filename to open for reading \n");
   scanf("%s", filename);
   fptr1 = fopen(filename, "r");
   if (fptr1 == NULL)
   {
       printf("Cannot open file %s \n", filename);
       exit(0);
   }
   printf("Enter the filename to open for writing \n");
   scanf("%s", filename);
   fptr2 = fopen(filename, "w");
   if(fptr2 == NULL)
   {
       printf("Cannot open file %s \n", filename);
       exit(0);
   }
   c = fgetc(fptr1);
   while (c != EOF)
   {
       fputc(c, fptr2);
       c = fgetc(fptr1);
   }
   printf("\nContents copied to %s", filename);
   fclose(fptr1);
   fclose(fptr2);
```

```
    return 0;
}
```

Output Screenshot:



Experiment 2:

Identify the system calls to copy the content of one file to another and illustrate the same using
a C program.

Executable C code :

```c
#include <stdio.h>
#include <stdlib.h>
int main()
{
   FILE *fptr1, *fptr2;
   char filename[100], c;
   printf("Enter the filename to open for reading \n");
   scanf("%s", filename);
   fptr1 = fopen(filename, "r");
   if (fptr1 == NULL)
   {
       printf("Cannot open file %s \n", filename);
       exit(0);
   }
   printf("Enter the filename to open for writing \n");
   scanf("%s", filename);
   fptr2 = fopen(filename, "w");
   if(fptr2 == NULL)
```

```c
    {
        printf("Cannot open file %s \n", filename);
        exit(0);
    }
    c = fgetc(fptr1);
    while (c != EOF)
    {
        fputc(c, fptr2);
        c = fgetc(fptr1);
    }
    printf("\nContents copied to %s", filename);
    fclose(fptr1);
    fclose(fptr2);
    return 0;
}
```

Output screenshot:



Experiment 3 :
Design a CPU scheduling program with C using First Come First Served technique with the
following considerations.
a. All processes are activated at time 0.
b. Assume that no process waits on I/O devices.

Executable C code:

```c
#include <stdio.h>

int main() {
    int n, i, bt[10], wt[10], tat[10];
    float avgwt = 0, avgtat = 0;
```

```c
    printf("Enter number of processes: ");
    scanf("%d", &n);

    printf("Enter burst time of each process:\n");
    for (i = 0; i < n; i++) {
        printf("P%d: ", i + 1);
        scanf("%d", &bt[i]);
    }

    wt[0] = 0;
    for (i = 1; i < n; i++) {
        wt[i] = wt[i - 1] + bt[i - 1];
    }

    printf("\nProcess\tBT\tWT\tTAT\n");
    for (i = 0; i < n; i++) {
        tat[i] = wt[i] + bt[i];
        avgwt += wt[i];
        avgtat += tat[i];
        printf("P%d\t%d\t%d\t%d\n", i + 1, bt[i], wt[i], tat[i]);
    }

    printf("\nAverage Waiting Time = %.2f\n", avgwt / n);
    printf("Average Turnaround Time = %.2f\n", avgtat / n);
    return 0;
}
```

Output screenshot:



Experiment 4:

Construct a scheduling program with C that selects the waiting process with the smallest
execution time to execute next.

Executable C code:

```c
#include <stdio.h>

int main() {
   int n, i, j, temp, p[10], bt[10], wt[10], tat[10];
   float avgwt = 0, avgtat = 0;

   printf("Enter number of processes: ");
   scanf("%d", &n);

   printf("Enter burst time of each process:\n");
   for (i = 0; i < n; i++) {
       printf("P%d: ", i + 1);
       scanf("%d", &bt[i]);
       p[i] = i + 1;
   }

   // sort by burst time
   for (i = 0; i < n - 1; i++) {
       for (j = i + 1; j < n; j++) {
           if (bt[i] > bt[j]) {
               temp = bt[i]; bt[i] = bt[j]; bt[j] = temp;
               temp = p[i]; p[i] = p[j]; p[j] = temp;
           }
       }
   }


   wt[0] = 0;
   for (i = 1; i < n; i++) {
       wt[i] = wt[i - 1] + bt[i - 1];
   }

   printf("\nProcess\tBT\tWT\tTAT\n");
   for (i = 0; i < n; i++) {
       tat[i] = wt[i] + bt[i];
       avgwt += wt[i];
       avgtat += tat[i];
       printf("P%d\t%d\t%d\t%d\n", p[i], bt[i], wt[i], tat[i]);
   }

   printf("\nAverage Waiting Time = %.2f\n", avgwt / n);
   printf("Average Turnaround Time = %.2f\n", avgtat / n);
   return 0;
```

```
}
```

Output Screenshot :



Experiment 5:

Construct a scheduling program with C that selects the waiting process with the highest priority to execute next.

Executable C code :

```c
#include <stdio.h>

int main() {
    int n, i, j, temp, p[10], bt[10], pr[10], wt[10], tat[10];
    float avgwt = 0, avgtat = 0;

    printf("Enter number of processes: ");
    scanf("%d", &n);

    printf("Enter burst time and priority of each process:\n");
    for (i = 0; i < n; i++) {
        printf("P%d: ", i + 1);
        scanf("%d %d", &bt[i], &pr[i]);
        p[i] = i + 1;
    }


    // sort by priority (lower number = higher priority)
    for (i = 0; i < n - 1; i++) {
        for (j = i + 1; j < n; j++) {
            if (pr[i] > pr[j]) {
                temp = pr[i]; pr[i] = pr[j]; pr[j] = temp;
                temp = bt[i]; bt[i] = bt[j]; bt[j] = temp;
                temp = p[i]; p[i] = p[j]; p[j] = temp;
            }
        }
    }

    wt[0] = 0;
    for (i = 1; i < n; i++) {
        wt[i] = wt[i - 1] + bt[i - 1];
    }

    printf("\nProcess\tPriority\tBT\tWT\tTAT\n");
    for (i = 0; i < n; i++) {
        tat[i] = wt[i] + bt[i];
        avgwt += wt[i];
        avgtat += tat[i];
        printf("P%d\t%d\t\t%d\t%d\t%d\n", p[i], pr[i], bt[i], wt[i], tat[i]);
    }

    printf("\nAverage Waiting Time = %.2f\n", avgwt / n);
    printf("Average Turnaround Time = %.2f\n", avgtat / n);
    return 0;
}
```

Output screenshot:



Github repo link : https://github.com/Nithish250707/Csa0421