




ANDROID STATIC ANALYSIS REPORT

app_icon



 **Happ (3.21.1)**

File Name:

Happ.apk

Package Name:

su.happ.proxyutility


Scan Date:

May 30, 2026, 12:03 p.m.

App Security Score:

52/100 (MEDIUM RISK)

Grade:



Trackers Detection:

1/432

 FINDINGS SEVERITY

 HIGH	 MEDIUM	 INFO	 SECURE	 HOTSPOT
3	19	2	3	1

FILE INFORMATION

File Name: Happ.apk

Size: 56.28MB

MD5: 20078740d0312196fdea42fb881c8740

SHA1: b7a3132533f81efbf2cadcc237ab1104e0d55f3e

SHA256: 94a61e96a6d6d6bd5cffe2771b46e190cc660d97d9117337f180d3096d9c71ba

APP INFORMATION

App Name: Happ

Package Name: su.happ.proxyutility

Main Activity: su.happ.proxyutility.feature.main.MainActivity

Target SDK: 36

Min SDK: 21

Max SDK:

Android Version Name: 3.21.1

Android Version Code: 1513

APP COMPONENTS

Activities: 31

Services: 17

Receivers: 14

Providers: 5

Exported Activities: 0

Exported Services: 2

Exported Receivers: 5

Exported Providers: 0

CERTIFICATE INFORMATION

Binary is signed

v1 signature: True

v2 signature: True

v3 signature: False

v4 signature: False

X.509 Subject: O=FlyFrog LLC, L=WILMINGTON, ST=Delaware, C=US

Signature Algorithm: rsassa_pkcs1v15

Valid From: 2024-05-21 16:36:30+00:00

Valid To: 2049-05-15 16:36:30+00:00

Issuer: O=FlyFrog LLC, L=WILMINGTON, ST=Delaware, C=US

Serial Number: 0x1

Hash Algorithm: sha256

md5: 7d7dd228a5a04c64c57ccbc117f97e3f
sha1: 83e533d544adb50a774f4735e3ac8c57538b2432
sha256: 397e98abed03c5f263ffaf4e8a1043b2a59f538b99e75cf152fa05a7e8007d8d
sha512: 860279173753605d9b42603278308be99bcbe31a0bed28baefd9f9c491a6b1862025ac6a1d211e14dd35e7c83032d93ba3d9c6d84e32361768ebf4d9891cead4
PublicKey Algorithm: rsa
Bit Size: 2048
Fingerprint: 2d0e91b08dd6c73b44a067597201cf40124bfc47dd704742f69d22992ac7f1d5
Found 1 unique certificates

≡ APPLICATION PERMISSIONS

PERMISSION	STATUS	INFO	DESCRIPTION
android.permission.REQUEST_INSTALL_PACKAGES	dangerous	Allows an application to request installing packages.	Malicious applications can use this to try and trick users into installing additional malicious packages.
android.permission.QUERY_ALL_PACKAGES	normal	enables querying any normal app on the device.	Allows query of any normal app on the device, regardless of manifest declarations.
android.permission.ACCESS_NETWORK_STATE	normal	view network status	Allows an application to view the status of all networks.
android.permission.CHANGE_NETWORK_STATE	normal	change network connectivity	Allows applications to change network connectivity state.
android.permission.INTERNET	normal	full Internet access	Allows an application to create network sockets.
android.permission.CAMERA	dangerous	take pictures and videos	Allows application to take pictures and videos with the camera. This allows the application to collect images that the camera is seeing at any time.
android.permission.FOREGROUND_SERVICE	normal	enables regular apps to use Service.startForeground.	Allows a regular application to use Service.startForeground.
android.permission.FOREGROUND_SERVICE_SPECIAL_USE	normal	enables special-use foreground services.	Allows a regular application to use Service.startForeground with the type "specialUse".
android.permission.POST_NOTIFICATIONS	dangerous	allows an app to post notifications.	Allows an app to post notifications
android.permission.REQUEST_IGNORE_BATTERY_OPTIMIZATIONS	normal	permission for using Settings.ACTION_REQUEST_IGNORE_BATTERY_OPTIMIZATIONS.	Permission an application must hold in order to use Settings.ACTION_REQUEST_IGNORE_BATTERY_OPTIMIZATIONS.
android.permission.RECEIVE_BOOT_COMPLETED	normal	automatically start at boot	Allows an application to start itself as soon as the system has finished booting. This can make it take longer to start the phone and allow the application to slow down the overall phone by always running.
android.permission.QUICKBOOT_POWERON	unknown	Unknown permission	Unknown permission from android reference

PERMISSION	STATUS	INFO	DESCRIPTION
android.permission.WAKE_LOCK	normal	prevent phone from sleeping	Allows an application to prevent the phone from going to sleep.
com.google.android.c2dm.permission.RECEIVE	normal	recieve push notifications	Allows an application to receive push notifications from cloud.
su.happ.proxyutility.DYNAMIC_RECEIVER_NOT_EXPORTED_PERMISSION	unknown	Unknown permission	Unknown permission from android reference

APKID ANALYSIS

FILE	DETAILS	
classes.dex	FINDINGS	DETAILS
	Anti-VM Code	Build.FINGERPRINT check Build.MODEL check Build.MANUFACTURER check Build.PRODUCT check Build.HARDWARE check Build.BOARD check Build.TAGS check SIM operator check possible ro.secure check possible VM check
	Anti Debug Code	Debug.isDebuggerConnected() check
	Compiler	r8
classes2.dex	FINDINGS	DETAILS
	Compiler	r8

FILE	DETAILS	
lib/arm64-v8a/libgojni.so	FINDINGS	DETAILS
	anti_hook	syscalls
lib/arm64-v8a/libtoolChecker.so	FINDINGS	DETAILS
	anti_root	RootBeer
lib/armeabi-v7a/libtoolChecker.so	FINDINGS	DETAILS
	anti_root	RootBeer

BROWSABLE ACTIVITIES

ACTIVITY	INTENT
su.happ.proxyutility.feature.main.MainActivity	Schemes: happ://, content://, Hosts: *, Mime Types: */*, application/json, Path Patterns: .*\\.json, .*json, .*happ, .*\\.happ,

NETWORK SECURITY

NO	SCOPE	SEVERITY	DESCRIPTION
----	-------	----------	-------------

CERTIFICATE ANALYSIS

HIGH: 0 | WARNING: 1 | INFO: 1

TITLE	SEVERITY	DESCRIPTION
Signed Application	info	Application is signed with a code signing certificate
Application vulnerable to Janus Vulnerability	warning	Application is signed with v1 signature scheme, making it vulnerable to Janus vulnerability on Android 5.0-8.0, if signed only with v1 signature scheme. Applications running on Android 5.0-7.0 signed with v1, and v2/v3 scheme is also vulnerable.

Q MANIFEST ANALYSIS

HIGH: 2 | WARNING: 8 | INFO: 0 | SUPPRESSED: 0

NO	ISSUE	SEVERITY	DESCRIPTION
1	App can be installed on a vulnerable unpatched Android version 5.0-5.0.2, [minSdk=21]	high	This application can be installed on an older version of android that has multiple unfixed vulnerabilities. These devices won't receive reasonable security updates from Google. Support an Android version => 10, API 29 to receive reasonable security updates.
2	Clear text traffic is Enabled For App[android:usesCleartextTraffic=true]	high	The app intends to use cleartext network traffic, such as cleartext HTTP, FTP stacks, DownloadManager, and MediaPlayer. The default value for apps that target API level 27 or lower is "true". Apps that target API level 28 or higher default to "false". The key reason for avoiding cleartext traffic is the lack of confidentiality, authenticity, and protections against tampering; a network attacker can eavesdrop on transmitted data and also modify it without being detected.
3	Application Data can be Backed up [android:allowBackup=true]	warning	This flag allows anyone to backup your application data via adb. It allows users who have enabled USB debugging to copy application data off of the device.
4	Service (androidx.work.impl.background.systemjob.SystemJobService) is Protected by a permission, but the protection level of the permission should be checked. Permission: android.permission.BIND_JOB_SERVICE [android:exported=true]	warning	A Service is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. It is protected by a permission which is not defined in the analysed application. As a result, the protection level of the permission should be checked where it is defined. If it is set to normal or dangerous, a malicious application can request and obtain the permission and interact with the component. If it is set to signature, only applications signed with the same certificate can obtain the permission.
5	Broadcast Receiver (su.happ.proxyutility.receiver.WidgetProvider) is not Protected. [android:exported=true]	warning	A Broadcast Receiver is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
6	Broadcast Receiver (su.happ.proxyutility.receiver.BootUpReceiver) is Protected by a permission, but the protection level of the permission should be checked. Permission: android.permission.RECEIVE_BOOT_COMPLETED [android:exported=true]	warning	A Broadcast Receiver is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. It is protected by a permission which is not defined in the analysed application. As a result, the protection level of the permission should be checked where it is defined. If it is set to normal or dangerous, a malicious application can request and obtain the permission and interact with the component. If it is set to signature, only applications signed with the same certificate can obtain the permission.

NO	ISSUE	SEVERITY	DESCRIPTION
7	Service (su.happ.proxyutility.service.QSTileService) is Protected by a permission, but the protection level of the permission should be checked. Permission: android.permission.BIND_QUICK_SETTINGS_TILE [android:exported=true]	warning	A Service is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. It is protected by a permission which is not defined in the analysed application. As a result, the protection level of the permission should be checked where it is defined. If it is set to normal or dangerous, a malicious application can request and obtain the permission and interact with the component. If it is set to signature, only applications signed with the same certificate can obtain the permission.
8	Broadcast Receiver (com.google.firebase.iid.FirebaseInstanceIdReceiver) is Protected by a permission, but the protection level of the permission should be checked. Permission: com.google.android.c2dm.permission.SEND [android:exported=true]	warning	A Broadcast Receiver is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. It is protected by a permission which is not defined in the analysed application. As a result, the protection level of the permission should be checked where it is defined. If it is set to normal or dangerous, a malicious application can request and obtain the permission and interact with the component. If it is set to signature, only applications signed with the same certificate can obtain the permission.
9	Broadcast Receiver (androidx.work.impl.diagnostics.DiagnosticsReceiver) is Protected by a permission, but the protection level of the permission should be checked. Permission: android.permission.DUMP [android:exported=true]	warning	A Broadcast Receiver is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. It is protected by a permission which is not defined in the analysed application. As a result, the protection level of the permission should be checked where it is defined. If it is set to normal or dangerous, a malicious application can request and obtain the permission and interact with the component. If it is set to signature, only applications signed with the same certificate can obtain the permission.
10	Broadcast Receiver (androidx.profileinstaller.ProfileInstallReceiver) is Protected by a permission, but the protection level of the permission should be checked. Permission: android.permission.DUMP [android:exported=true]	warning	A Broadcast Receiver is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. It is protected by a permission which is not defined in the analysed application. As a result, the protection level of the permission should be checked where it is defined. If it is set to normal or dangerous, a malicious application can request and obtain the permission and interact with the component. If it is set to signature, only applications signed with the same certificate can obtain the permission.

</> CODE ANALYSIS

HIGH: 1 | WARNING: 8 | INFO: 2 | SECURE: 2 | SUPPRESSED: 0

NO	ISSUE	SEVERITY	STANDARDS	FILES
1	Files may contain hardcoded sensitive information like usernames, passwords, keys etc.	warning	CWE-312: Cleartext Storage of Sensitive Information OWASP Top 10: M9: Reverse Engineering OWASP MASVS: MSTG-STORAGE-14	defpackage/a03.java defpackage/po2.java defpackage/qj4.java defpackage/qv0.java defpackage/t63.java org/conscrypt/OpenSSLKeyFactory.java org/conscrypt/OpenSSLRSAKeyFactory.java su/happ/proxyutility/dto/AuthData.java su/happ/proxyutility/dto/MetaParams.java su/happ/proxyutility/dto/XRayConfig.java

NO	ISSUE	SEVERITY	STANDARDS	FILES
2	IP Address disclosure	warning	CWE: CWE-200: Information Exposure OWASP MASVS: MSTG-CODE-2	defpackage/a31.java defpackage/c54.java defpackage/cd3.java defpackage/k73.java defpackage/ki4.java defpackage/qc5.java defpackage/qg.java defpackage/ty3.java org/conscript/TrustManagerImpl.java su/happ/proxyutility/dto/RouteSettings.java su/happ/proxyutility/dto/XRayConfig.java su/happ/proxyutility/dto/enums/GeoUserAgent .java su/happ/proxyutility/feature/main/MainActivity .java su/happ/proxyutility/service/XRayProxyOnlySer vice.java su/happ/proxyutility/service/XRayVpnService.ja va su/happ/proxyutility/ui/ServerActivity.java

NO	ISSUE	SEVERITY	STANDARDS	FILES
3	The App logs information. Sensitive information should never be logged.	info	CWE: CWE-532: Insertion of Sensitive Information into Log File OWASP MASVS: MSTG-STORAGE-3	defpackage/b91.java defpackage/ba0.java defpackage/bh2.java defpackage/bh5.java defpackage/cg5.java defpackage/dg5.java defpackage/eh5.java defpackage/fa5.java defpackage/gk.java defpackage/gz0.java defpackage/hf5.java defpackage/hg5.java defpackage/id1.java defpackage/jf0.java defpackage/kx.java defpackage/l5.java defpackage/lb5.java defpackage/ld1.java defpackage/lg1.java defpackage/n45.java defpackage/n70.java defpackage/q80.java defpackage/q94.java defpackage/qb1.java defpackage/qd1.java defpackage/rg1.java defpackage/rv3.java defpackage/s75.java defpackage/sa5.java defpackage/sg5.java defpackage/tx2.java defpackage/vv2.java defpackage/wa2.java defpackage/wn4.java defpackage/xm3.java defpackage/yv4.java defpackage/z75.java defpackage/zc5.java defpackage/zg5.java defpackage/zi1.java defpackage/zq.java defpackage/zv3.java io/sentry/android/core/q.java io/sentry/i2.java io/sentry/internal/debugmeta/c.java org/conscrypt/ct/CTVerifier.java

NO	ISSUE	SEVERITY	STANDARDS	FILES
4	App uses SQLite Database and execute raw SQL query. Untrusted user input in raw SQL queries can cause SQL Injection. Also sensitive information should be encrypted and written to the database.	warning	CWE: CWE-89: Improper Neutralization of Special Elements used in an SQL Command ('SQL Injection') OWASP Top 10: M7: Client Code Quality	defpackage/kx.java defpackage/l5.java defpackage/mq2.java defpackage/n05.java defpackage/nh3.java defpackage/ob1.java defpackage/p04.java defpackage/qi0.java defpackage/xm2.java defpackage/yd.java defpackage/z91.java
5	The App uses an insecure Random Number Generator.	warning	CWE: CWE-330: Use of Insufficiently Random Values OWASP Top 10: M5: Insufficient Cryptography OWASP MASVS: MSTG-CRYPTO-6	defpackage/a8.java defpackage/r1.java defpackage/s01.java defpackage/t01.java defpackage/w53.java j\$/util/concurrent/ThreadLocalRandom.java
6	App can read/write to External Storage. Any App can read data written to External Storage.	warning	CWE: CWE-276: Incorrect Default Permissions OWASP Top 10: M2: Insecure Data Storage OWASP MASVS: MSTG-STORAGE-2	defpackage/h25.java defpackage/k05.java io/sentry/android/core/i0.java
7	This App copies data to clipboard. Sensitive data should not be copied to clipboard as other applications can access it.	info	OWASP MASVS: MSTG-STORAGE-10	defpackage/h25.java
8	SHA-1 is a weak hash known to have hash collisions.	warning	CWE: CWE-327: Use of a Broken or Risky Cryptographic Algorithm OWASP Top 10: M5: Insufficient Cryptography OWASP MASVS: MSTG-CRYPTO-4	defpackage/b31.java defpackage/ci1.java defpackage/jq2.java io/sentry/p5.java
9	App creates temp file. Sensitive information should never be written into a temp file.	warning	CWE: CWE-276: Incorrect Default Permissions OWASP Top 10: M2: Insecure Data Storage OWASP MASVS: MSTG-STORAGE-2	com/github/luben/zstd/util/Native.java defpackage/hj0.java
10	This App may request root (Super User) privileges.	warning	CWE: CWE-250: Execution with Unnecessary Privileges OWASP MASVS: MSTG-RESILIENCE-1	defpackage/ro1.java io/sentry/android/core/internal/util/l.java
11	This App uses SSL certificate pinning to detect or prevent MITM attacks in secure communication channel.	secure	OWASP MASVS: MSTG-NETWORK-4	org/conscrypt/Conscrypt.java org/conscrypt/DefaultSSLContextImpl.java org/conscrypt/SSLParametersImpl.java
12	This App may have root detection capabilities.	secure	OWASP MASVS: MSTG-RESILIENCE-1	defpackage/xm3.java io/sentry/android/core/internal/util/l.java

NO	ISSUE	SEVERITY	STANDARDS	FILES
13	Insecure Implementation of SSL. Trusting all the certificates or accepting self signed certificates is a critical Security Hole. This application is vulnerable to MITM attacks	high	CWE: CWE-295: Improper Certificate Validation OWASP Top 10: M3: Insecure Communication OWASP MASVS: MSTG-NETWORK-3	org/conscript/Conscript.java

SHARED LIBRARY BINARY ANALYSIS

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
1	armeabi-v7a/libsentry.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['_vsnprintf_chk', '_read_chk', '_memmove_chk', '_strncpy_chk', '_strlen_chk', '_memcpy_chk']	True info Symbols are stripped.
2	armeabi-v7a/libgojni.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
3	armeabi-v7a/libmmkv.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['_vsnprintf_chk', '__strchr_chk', '__strcat_chk', '__memcpy_chk', '__read_chk', '__strncpy_chk']	True info Symbols are stripped.
4	armeabi-v7a/libconscrypt_jni.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
5	armeabi-v7a/libsentry-android.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk']	True info Symbols are stripped.
6	armeabi-v7a/libzstd-jni-1.5.7-8.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Partial RELRO warning This shared object has partial RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In partial RELRO, the non-PLT part of the GOT section is read only but .got.plt is still writeable. Use the option -z,relro,-z,now to enable full RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
7	armeabi-v7a/libsurface_util_jni.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.
8	armeabi-v7a/libcore.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk', '__vsnprintf_chk', '__strcpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
9	armeabi-v7a/libtun2socks.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['_vsnprintf_chk', '__read_chk', '__strcpy_chk', '__FD_SET_chk', '__umask_chk', '__memcpy_chk', '__vsprintf_chk', '__strlen_chk']	True info Symbols are stripped.
10	armeabi-v7a/libtoolChecker.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
11	armeabi-v7a/libimage_processing_util_jni.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk']	True info Symbols are stripped.
12	armeabi-v7a/liberror-code.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__read_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
13	armeabi-v7a/libdatastore_shared_counter.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.
14	arm64-v8a/libsentry.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['_vsnprintf_chk', '_read_chk', '_memmove_chk', '_strncpy_chk', '_strlen_chk', '_memcpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
15	arm64-v8a/libgojni.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.
16	arm64-v8a/libmmkv.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['_vsnprintf_chk', '_strchr_chk', '_strcat_chk', '_memcpy_chk', '_read_chk', '_strncpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
17	arm64-v8a/libconscript_jni.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memmove_chk', '__strchr_chk', '__memset_chk', '__memcpy_chk', '__vsnprintf_chk', '__read_chk', '__strlen_chk']	True info Symbols are stripped.
18	arm64-v8a/libentry-android.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsnprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
19	arm64-v8a/libzstd-jni-1.5.7-8.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.
20	arm64-v8a/libsurface_util_jni.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
21	arm64-v8a/libcore.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk', '__vsnprintf_chk', '__strcpy_chk']	True info Symbols are stripped.
22	arm64-v8a/libtun2socks.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strcpy_chk', '__read_chk', '__FD_SET_chk', '__umask_chk', '__memcpy_chk', '__vsprintf_chk', '__vsnprintf_chk', '__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
23	arm64-v8a/libtoolChecker.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.
24	arm64-v8a/libimage_processing_util_jni.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
25	arm64-v8a/liberror-code.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__read_chk']	True info Symbols are stripped.
26	arm64-v8a/libdatastore_shared_counter.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
27	armeabi-v7a/libsentry.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['_vsprintf_chk', '_read_chk', '_memmove_chk', '_strncpy_chk', '_strlen_chk', '_memcpy_chk']	True info Symbols are stripped.
28	armeabi-v7a/libgojni.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
29	armeabi-v7a/libmmkv.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['_vsnprintf_chk', '__strchr_chk', '__strcat_chk', '__memcpy_chk', '__read_chk', '__strncpy_chk']	True info Symbols are stripped.
30	armeabi-v7a/libconscrypt_jni.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
31	armeabi-v7a/lib Sentry-android.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk']	True info Symbols are stripped.
32	armeabi-v7a/libzstd-jni-1.5.7-8.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Partial RELRO warning This shared object has partial RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In partial RELRO, the non-PLT part of the GOT section is read only but .got.plt is still writeable. Use the option -z,relro,-z,now to enable full RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
33	armeabi-v7a/libsurface_util_jni.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.
34	armeabi-v7a/libcore.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['_memcpy_chk', '_vsnprintf_chk', '_strcpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
35	armeabi-v7a/libtun2socks.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['_vsnprintf_chk', '__read_chk', '__strcpy_chk', '__FD_SET_chk', '__umask_chk', '__memcpy_chk', '__vsprintf_chk', '__strlen_chk']	True info Symbols are stripped.
36	armeabi-v7a/libtoolChecker.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
37	armeabi-v7a/libimage_processing_util_jni.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['_memcpy_chk']	True info Symbols are stripped.
38	armeabi-v7a/liberror-code.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['_read_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
39	armeabi-v7a/libdatastore_shared_counter.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.
40	arm64-v8a/libsentry.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['_vsnprintf_chk', '_read_chk', '_memmove_chk', '_strncpy_chk', '_strlen_chk', '_memcpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
41	arm64-v8a/libgojni.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.
42	arm64-v8a/libmmkv.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['_vsnprintf_chk', '__strchr_chk', '__strcat_chk', '__memcpy_chk', '__read_chk', '__strncpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
43	arm64-v8a/libconscript_jni.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memmove_chk', '__strchr_chk', '__memset_chk', '__memcpy_chk', '__vsnprintf_chk', '__read_chk', '__strlen_chk']	True info Symbols are stripped.
44	arm64-v8a/libentry-android.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsnprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
45	arm64-v8a/libzstd-jni-1.5.7-8.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.
46	arm64-v8a/libsurface_util_jni.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
47	arm64-v8a/libcore.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk', '__vsnprintf_chk', '__strcpy_chk']	True info Symbols are stripped.
48	arm64-v8a/libtun2socks.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strcpy_chk', '__read_chk', '__FD_SET_chk', '__umask_chk', '__memcpy_chk', '__vsprintf_chk', '__vsnprintf_chk', '__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
49	arm64-v8a/libtoolChecker.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.
50	arm64-v8a/libimage_processing_util_jni.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
51	arm64-v8a/liberror-code.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__read_chk']	True info Symbols are stripped.
52	arm64-v8a/libdatastore_shared_counter.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NIAP ANALYSIS v1.3

NO	IDENTIFIER	REQUIREMENT	FEATURE	DESCRIPTION
----	------------	-------------	---------	-------------

BEHAVIOUR ANALYSIS

RULE ID	BEHAVIOUR	LABEL	FILES
00013	Read file and put it into a stream	file	defpackage/c01.java defpackage/c73.java defpackage/ch2.java defpackage/d84.java defpackage/g93.java defpackage/gf2.java defpackage/gz0.java defpackage/h93.java defpackage/hj0.java defpackage/i02.java defpackage/im4.java defpackage/ir0.java defpackage/k4.java defpackage/lg1.java defpackage/lu4.java defpackage/mu2.java defpackage/pv4.java defpackage/qv4.java defpackage/r11.java defpackage/rc0.java defpackage/rx1.java defpackage/s11.java defpackage/s30.java defpackage/ze2.java defpackage/zm0.java io/sentry/a3.java io/sentry/android/core/SentryPerformanceProvider.java io/sentry/android/replay/k.java io/sentry/b0.java io/sentry/cache/a.java io/sentry/cache/c.java io/sentry/config/a.java io/sentry/internal/debugmeta/c.java io/sentry/y2.java org/conscrypt/DefaultSSLContextImpl.java org/conscrypt/FileClientSessionCache.java org/conscrypt/KeyManagerFactoryImpl.java su/happ/proxyutility/feature/logs/LogsViewSettingsActivity.java
00147	Get the time of current location	collection location	defpackage/ub.java
00075	Get location of the device	collection location	defpackage/ub.java
00115	Get last known location of the device	collection location	defpackage/ub.java
00079	Hide the current app's icon	evasion	defpackage/f13.java

RULE ID	BEHAVIOUR	LABEL	FILES
00063	Implicit intent(view a web page, make a phone call, etc.)	control	defpackage/a60.java defpackage/fm.java defpackage/h25.java defpackage/id1.java defpackage/k05.java defpackage/nh.java defpackage/x40.java su/happ/proxyutility/service/SubscriptionUpdater\$updateTask.java
00051	Implicit intent(view a web page, make a phone call, etc.) via setData	control	defpackage/a60.java defpackage/fm.java defpackage/id1.java defpackage/k05.java defpackage/nh.java defpackage/x40.java su/happ/proxyutility/service/SubscriptionUpdater\$updateTask.java
00162	Create InetAddress object and connecting to it	socket	defpackage/h.java defpackage/qg.java defpackage/ya4.java org/conscrypt/AbstractConscryptSocket.java
00163	Create new Socket and connecting to it	socket	defpackage/h.java defpackage/qg.java defpackage/ya4.java org/conscrypt/AbstractConscryptSocket.java org/conscrypt/KitKatPlatformOpenSSLSocketImplAdapter.java org/conscrypt/PreKitKatPlatformOpenSSLSocketImplAdapter.java
00036	Get resource file from res/raw directory	reflection	defpackage/a60.java defpackage/id1.java defpackage/nh.java defpackage/sj4.java

RULE ID	BEHAVIOUR	LABEL	FILES
00022	Open a file from given absolute path of the file	file	com/github/luben/zstd/util/Native.java defpackage/bh2.java defpackage/gd0.java defpackage/h15.java defpackage/h25.java defpackage/kc0.java defpackage/tw.java defpackage/wl4.java defpackage/x11.java io/sentry/a3.java io/sentry/android/core/i0.java io/sentry/android/core/l.java io/sentry/android/core/v.java io/sentry/android/core/w0.java io/sentry/android/replay/capture/i.java io/sentry/android/replay/j.java io/sentry/android/replay/k.java io/sentry/b0.java io/sentry/cache/a.java io/sentry/cache/c.java io/sentry/p5.java io/sentry/y2.java su/happ/proxyutility/service/XRayVpnService.java
00191	Get messages in the SMS inbox	sms	defpackage/sj4.java
00089	Connect to a URL and receive input stream from the server	command network	defpackage/b31.java defpackage/gk.java io/sentry/transport/e.java
00109	Connect to a URL and get the response code	network command	defpackage/b31.java defpackage/gk.java io/sentry/transport/e.java
00012	Read data and put it into a buffer stream	file	defpackage/gz0.java io/sentry/b0.java io/sentry/cache/c.java io/sentry/config/a.java io/sentry/internal/debugmeta/c.java io/sentry/y2.java org/conscrypt/DefaultSSLContextImpl.java
00125	Check if the given file path exist	file	su/happ/proxyutility/ui/BaseActivity.java

RULE ID	BEHAVIOUR	LABEL	FILES
00091	Retrieve data from broadcast	collection	defpackage/h4.java defpackage/sa5.java defpackage/w40.java su/happ/proxyutility/feature/main/MainActivity.java
00096	Connect to a URL and set request method	command network	defpackage/gk.java io/sentry/transport/e.java
00030	Connect to the remote server through the given URL	network	io/sentry/transport/e.java
00035	Query the list of the installed packages	reflection	defpackage/n80.java
00112	Get the date of the calendar event	collection calendar	defpackage/eh4.java defpackage/ud4.java defpackage/yd4.java io/sentry/config/a.java
00014	Read file into a stream and put it into a JSON object	file	defpackage/hj0.java
00009	Put data in cursor to JSON object	file	defpackage/hj0.java defpackage/kx.java
00004	Get filename and put it to JSON object	file collection	defpackage/hj0.java

FIREBASE DATABASES ANALYSIS

TITLE	SEVERITY	DESCRIPTION
Firebase Remote Config disabled	secure	Firebase Remote Config is disabled for https://firebase-remoteconfig.googleapis.com/v1/projects/560766616282/namespaces/firebase:fetch?key=AlzaSyCF9f4Sue5wd5Btjo1cHb3frt2QyhA6T0o. This is indicated by the response: {'state': 'NO_TEMPLATE'}

ABUSED PERMISSIONS

TYPE	MATCHES	PERMISSIONS
Malware Permissions	6/25	android.permission.REQUEST_INSTALL_PACKAGES, android.permission.ACCESS_NETWORK_STATE, android.permission.INTERNET, android.permission.CAMERA, android.permission.RECEIVE_BOOT_COMPLETED, android.permission.WAKE_LOCK

TYPE	MATCHES	PERMISSIONS
Other Common Permissions	4/44	android.permission.CHANGE_NETWORK_STATE, android.permission.FOREGROUND_SERVICE, android.permission.REQUEST_IGNORE_BATTERY_OPTIMIZATIONS, com.google.android.c2dm.permission.RECEIVE

Malware Permissions:

Top permissions that are widely abused by known malware.

Other Common Permissions:

Permissions that are commonly abused by known malware.

! OFAC SANCTIONED COUNTRIES

This app may communicate with the following OFAC sanctioned list of countries.

DOMAIN	COUNTRY/REGION
--------	----------------

🔍 DOMAIN MALWARE CHECK

DOMAIN	STATUS	GEOLOCATION
schemas.android.com	ok	No Geolocation information available.
pastebin.com	ok	IP: 8.6.112.0 Country: United States of America Region: Texas City: Dallas Latitude: 32.783058 Longitude: -96.806671 View: Google Map
check.happ.su	ok	IP: 116.202.234.207 Country: Germany Region: Sachsen City: Falkenstein Latitude: 50.477879 Longitude: 12.371290 View: Google Map

DOMAIN	STATUS	GEOLOCATION
ntp2-sync.com	ok	IP: 172.67.157.229 Country: United States of America Region: California City: San Francisco Latitude: 37.775700 Longitude: -122.395203 View: Google Map
firebaseinstallations.googleapis.com	ok	IP: 142.250.150.95 Country: United States of America Region: California City: Mountain View Latitude: 37.405991 Longitude: -122.078514 View: Google Map
dns.google	ok	IP: 8.8.4.4 Country: United States of America Region: California City: Mountain View Latitude: 37.405991 Longitude: -122.078514 View: Google Map
www.w3.org	ok	IP: 8.47.69.0 Country: United States of America Region: California City: San Francisco Latitude: 37.775700 Longitude: -122.395203 View: Google Map
android.googlesource.com	ok	IP: 173.194.221.82 Country: United States of America Region: California City: Mountain View Latitude: 37.405991 Longitude: -122.078514 View: Google Map

DOMAIN	STATUS	GEOLOCATION
firebase.google.com	ok	IP: 192.178.25.78 Country: United States of America Region: California City: Mountain View Latitude: 37.405991 Longitude: -122.078514 View: Google Map
tv.happ.su	ok	IP: 83.69.242.120 Country: Russian Federation Region: Moskva City: Moscow Latitude: 55.752220 Longitude: 37.615559 View: Google Map
www.google.com	ok	IP: 142.251.151.119 Country: United States of America Region: California City: Mountain View Latitude: 37.405991 Longitude: -122.078514 View: Google Map
ai-4docs.com	ok	IP: 45.8.249.229 Country: United States of America Region: Virginia City: Ashburn Latitude: 39.043720 Longitude: -77.487488 View: Google Map
google.com	ok	IP: 64.233.161.101 Country: United States of America Region: California City: Mountain View Latitude: 37.405991 Longitude: -122.078514 View: Google Map

DOMAIN	STATUS	GEOLOCATION
time-ntp.com	ok	IP: 216.239.34.21 Country: United States of America Region: California City: Mountain View Latitude: 37.405991 Longitude: -122.078514 View: Google Map
xmlpull.org	ok	IP: 185.199.110.153 Country: United States of America Region: Pennsylvania City: California Latitude: 40.065632 Longitude: -79.891708 View: Google Map
www.happ.su	ok	IP: 8.47.69.0 Country: United States of America Region: California City: San Francisco Latitude: 37.775700 Longitude: -122.395203 View: Google Map
xml.org	ok	IP: 172.67.205.113 Country: United States of America Region: California City: San Francisco Latitude: 37.775700 Longitude: -122.395203 View: Google Map
10.0.2.2	ok	IP: 10.0.2.2 Country: - Region: - City: - Latitude: 0.000000 Longitude: 0.000000 View: Google Map

DOMAIN	STATUS	GEOLOCATION
yandex.ru	ok	IP: 77.88.55.88 Country: Russian Federation Region: Moskva City: Moscow Latitude: 55.752220 Longitude: 37.615559 View: Google Map
happ.su	ok	IP: 104.21.40.149 Country: United States of America Region: California City: San Francisco Latitude: 37.775700 Longitude: -122.395203 View: Google Map
o312638.ingest.us.sentry.io	ok	IP: 34.160.81.0 Country: United States of America Region: Texas City: Houston Latitude: 29.941401 Longitude: -95.344498 View: Google Map
cloudflare-dns.com	ok	IP: 104.16.248.249 Country: United States of America Region: California City: San Francisco Latitude: 37.775700 Longitude: -122.395203 View: Google Map
youtrack.jetbrains.com	ok	IP: 63.35.30.167 Country: Ireland Region: Dublin City: Dublin Latitude: 53.343990 Longitude: -6.267190 View: Google Map

DOMAIN	STATUS	GEOLOCATION
developer.android.com	ok	IP: 64.233.161.102 Country: United States of America Region: California City: Mountain View Latitude: 37.405991 Longitude: -122.078514 View: Google Map
cloud-api.yandex.net	ok	IP: 213.180.204.127 Country: Russian Federation Region: Moskva City: Moscow Latitude: 55.752220 Longitude: 37.615559 View: Google Map
kotl.in	ok	IP: 34.78.67.165 Country: Belgium Region: Brussels Hoofdstedelijk Gewest City: Brussels Latitude: 50.850449 Longitude: 4.348780 View: Google Map
docs.sentry.io	ok	IP: 76.76.21.93 Country: United States of America Region: California City: Walnut Latitude: 34.015400 Longitude: -117.858223 View: Google Map
cdn.jsdelivr.net	ok	IP: 104.17.207.5 Country: United States of America Region: California City: San Francisco Latitude: 37.775700 Longitude: -122.395203 View: Google Map

DOMAIN	STATUS	GEOLOCATION
raw.githubusercontent.com	ok	IP: 185.199.110.133 Country: United States of America Region: Pennsylvania City: California Latitude: 40.065632 Longitude: -79.891708 View: Google Map
www.gstatic.com	ok	IP: 173.194.221.94 Country: United States of America Region: California City: Mountain View Latitude: 37.405991 Longitude: -122.078514 View: Google Map
ns.adobe.com	ok	No Geolocation information available.
github.com	ok	IP: 140.82.121.4 Country: United States of America Region: California City: San Francisco Latitude: 37.775700 Longitude: -122.395203 View: Google Map
issuetracker.google.com	ok	IP: 173.194.221.101 Country: United States of America Region: California City: Mountain View Latitude: 37.405991 Longitude: -122.078514 View: Google Map

EMAILS

EMAIL	FILE
u0013android@android.com u0013android@android.com0	defpackage/mg5.java
support@happ.su	defpackage/u.java

EMAIL	FILE
380d72dd79917ed695c7@o312638.ingest	defpackage/ty3.java
your.email@example.org	io/sentry/p4.java
jason@zx2c4.comreceive	lib/armeabi-v7a/libgojni.so
ambrop7@gmail.com	lib/armeabi-v7a/libtun2socks.so
jason@zx2c4.comreceive	lib/arm64-v8a/libgojni.so
appro@openssl.org	lib/arm64-v8a/libconscrypt_jni.so
ambrop7@gmail.com	lib/arm64-v8a/libtun2socks.so
jason@zx2c4.comreceive	apktool_out/lib/armeabi-v7a/libgojni.so
ambrop7@gmail.com	apktool_out/lib/armeabi-v7a/libtun2socks.so
jason@zx2c4.comreceive	apktool_out/lib/arm64-v8a/libgojni.so
appro@openssl.org	apktool_out/lib/arm64-v8a/libconscrypt_jni.so
ambrop7@gmail.com	apktool_out/lib/arm64-v8a/libtun2socks.so

TRACKERS

TRACKER	CATEGORIES	URL
Sentry	Crash reporting	https://reports.exodus-privacy.eu.org/trackers/447

HARDCODED SECRETS

POSSIBLE SECRETS
"server_lab_secret_key" : "SecretKey"

POSSIBLE SECRETS
"per_app_proxy_bypass" : "Bypass"
"inbound_authorization_user" : "□□"
"inbound_authorization_password" : "Пароль"
"google_crash_reporting_api_key" : "AlzaSyCF9f4Sue5wd5Btjo1cHb3frt2QyhA6T0o"
"inbound_authorization_password" : "Password"
"inbound_authorization_mode" : "□□□□"
"server_secret_key" : "SecretKey"
"server_obfs_password" : "□□□□"
"inbound_authorization_title" : "Inbounds"
"per_app_proxy_bypass" : "□□"
"server_pre_shared_key" : "PreSharedKey□□□□"
"excluded_routes_menu_add_private" : "□□□□"
"inbound_authorization_user" : "کاربر"
"per_app_proxy_bypass" : "Обход"
"server_lab_public_key" : "PublicKey"
"server_public_key" : "PublicKey"
"send_to_tv_failure_api" : "□□□□□□□□□□□□□□□□[%d]□□□□□□□□"
"inbound_authorization_user" : "Пользователь"
"inbound_authorization_socks_title" : "Socks"
"inbound_authorization_http_title" : "Http"
"inbound_authorization_password" : "□□"

POSSIBLE SECRETS
"server_lab_preshared_key" : "PreSharedKey"
"send_to_tv_failure_api_no_inet" : ""
"inbound_authorization_user" : "User"
"google_api_key" : "AlzaSyCF9f4Sue5wd5Btjo1cHb3frt2QyhA6T0o"
1cbd3130fa23b59692c061c594c16cc0
bd376388b5f723fb4c22dfe6cd4375a05a07476444d5819985007e34
51953eb9618e1c9a1f929a21a0b68540eea2da725b99b315f3b8b489918ef109e156193951ec7e937b1652c0bd3bb1bf073573df883d2c34f1ef451fd46b503f00
258EAFa5-E914-47DA-95CA-C5AB0DC85B11
3617de4a96262c6f5d9e98bf9292dc29f841dbd289a147ce9da3113b5f0b8c00a60b1ce1d7e819d7a431d7c90ea0e5f
6b17d1f2e12c4247f8bce6e563a440f277037d812deb33a0f4a13945d898c296
438188ae27605b83f6ba5c5aee91993ce6bf7031c489999c97150b95417a9856
b3312fa7e23ee7e4988e056be3f82d19181d9c6efe8141120314088f5013875ac656398d8a2ed19d2a85c8edd3ec2aef
dc4747c4eb1f380d72dd79917ed695c7
a-95ed6082-b8e9-46e8-a73f-ff56f00f5d9d
b70e0cbd6bb4bf7f321390b94a03c1d356c21122343280d6115c1d21
c6858e06b70404e9cd9e3ecb662395b4429c648139053fb521f828af606b4d3dbaa14b5e77efe75928fe1dc127a2ffa8de3348b3c1856a429bf97e7e31c2e5bd66
11839296a789a3bc0045c8a5fb42c7d1bd998f54449579b446817afbd17273e662c97ee72995ef42640c550b9013fad0761353c7086a272c24088be94769fd16650
5ac635d8aa3a93e7b3ebbd55769886bc651d06b0cc53b0f63bce3c3e27d2604b
id=1skw19VP2GQsj2Av8nYHKhHoQR3qcpMJW
aa87ca22be8b05378eb1c71ef320ad746e1d3b628ba79b9859f741e082542a385502f25dbf55296c3a545e3872760ab7
b4050a850c04b3abf54132565044b0b7d7bfd8ba270b39432355ffb4

POSSIBLE SECRETS
86254750241babac4b8d52996a675549
AqHnQy35aOM/ZtgUip+BrTHHLnSYBNwQAX0y2g==
4fe342e2fe1a7f9b8ee7eb4a7c0f9e162bce33576b315ececbb6406837bf51f5

SCAN LOGS

Timestamp	Event	Error
2026-05-30 12:03:38	Generating Hashes	OK
2026-05-30 12:03:38	Extracting APK	OK
2026-05-30 12:03:38	Unzipping	OK
2026-05-30 12:03:41	Parsing APK with androguard	OK
2026-05-30 12:03:41	Extracting APK features using aapt/aapt2	OK
2026-05-30 12:03:42	Getting Hardcoded Certificates/Keystores	OK
2026-05-30 12:03:48	Parsing AndroidManifest.xml	OK
2026-05-30 12:03:48	Extracting Manifest Data	OK
2026-05-30 12:03:48	Manifest Analysis Started	OK

2026-05-30 12:03:48	Performing Static Analysis on: Happ (su.happ.proxyutility)	OK
2026-05-30 12:03:53	Checking for Malware Permissions	OK
2026-05-30 12:03:53	Fetching icon path	OK
2026-05-30 12:03:53	Library Binary Analysis Started	OK
2026-05-30 12:03:53	Analyzing lib/armeabi-v7a/libentry.so	OK
2026-05-30 12:03:53	Analyzing lib/armeabi-v7a/libgojni.so	OK
2026-05-30 12:03:53	Analyzing lib/armeabi-v7a/libmmkv.so	OK
2026-05-30 12:03:53	Analyzing lib/armeabi-v7a/libconscript_jni.so	OK
2026-05-30 12:03:53	Analyzing lib/armeabi-v7a/libentry-android.so	OK
2026-05-30 12:03:53	Analyzing lib/armeabi-v7a/libzstd-jni-1.5.7-8.so	OK
2026-05-30 12:03:53	Analyzing lib/armeabi-v7a/libsurface_util_jni.so	OK
2026-05-30 12:03:53	Analyzing lib/armeabi-v7a/libcore.so	OK
2026-05-30 12:03:53	Analyzing lib/armeabi-v7a/libtun2socks.so	OK
2026-05-30 12:03:53	Analyzing lib/armeabi-v7a/libtoolChecker.so	OK

2026-05-30 12:03:53	Analyzing lib/armeabi-v7a/libimage_processing_util_jni.so	OK
2026-05-30 12:03:53	Analyzing lib/armeabi-v7a/liberror-code.so	OK
2026-05-30 12:03:53	Analyzing lib/armeabi-v7a/libdatastore_shared_counter.so	OK
2026-05-30 12:03:53	Analyzing lib/arm64-v8a/libentry.so	OK
2026-05-30 12:03:53	Analyzing lib/arm64-v8a/libgojni.so	OK
2026-05-30 12:03:53	Analyzing lib/arm64-v8a/libmmkv.so	OK
2026-05-30 12:03:53	Analyzing lib/arm64-v8a/libconscript_jni.so	OK
2026-05-30 12:03:54	Analyzing lib/arm64-v8a/libentry-android.so	OK
2026-05-30 12:03:54	Analyzing lib/arm64-v8a/libzstd-jni-1.5.7-8.so	OK
2026-05-30 12:03:54	Analyzing lib/arm64-v8a/libsurface_util_jni.so	OK
2026-05-30 12:03:54	Analyzing lib/arm64-v8a/libcore.so	OK
2026-05-30 12:03:54	Analyzing lib/arm64-v8a/libtun2socks.so	OK
2026-05-30 12:03:54	Analyzing lib/arm64-v8a/libtoolChecker.so	OK
2026-05-30 12:03:54	Analyzing lib/arm64-v8a/libimage_processing_util_jni.so	OK

2026-05-30 12:03:54	Analyzing lib/arm64-v8a/liberror-code.so	OK
2026-05-30 12:03:54	Analyzing lib/arm64-v8a/libdatastore_shared_counter.so	OK
2026-05-30 12:03:54	Analyzing apktool_out/lib/armeabi-v7a/lib Sentry.so	OK
2026-05-30 12:03:54	Analyzing apktool_out/lib/armeabi-v7a/libgojni.so	OK
2026-05-30 12:03:54	Analyzing apktool_out/lib/armeabi-v7a/libmmkv.so	OK
2026-05-30 12:03:54	Analyzing apktool_out/lib/armeabi-v7a/libconscrypt_jni.so	OK
2026-05-30 12:03:54	Analyzing apktool_out/lib/armeabi-v7a/lib Sentry-android.so	OK
2026-05-30 12:03:54	Analyzing apktool_out/lib/armeabi-v7a/libzstd-jni-1.5.7-8.so	OK
2026-05-30 12:03:54	Analyzing apktool_out/lib/armeabi-v7a/libsurface_util_jni.so	OK
2026-05-30 12:03:54	Analyzing apktool_out/lib/armeabi-v7a/libcore.so	OK
2026-05-30 12:03:54	Analyzing apktool_out/lib/armeabi-v7a/libtun2socks.so	OK
2026-05-30 12:03:54	Analyzing apktool_out/lib/armeabi-v7a/libtoolChecker.so	OK
2026-05-30 12:03:54	Analyzing apktool_out/lib/armeabi-v7a/libimage_processing_util_jni.so	OK
2026-05-30 12:03:54	Analyzing apktool_out/lib/armeabi-v7a/liberror-code.so	OK

2026-05-30 12:03:54	Analyzing apktool_out/lib/armeabi-v7a/libdatastore_shared_counter.so	OK
2026-05-30 12:03:54	Analyzing apktool_out/lib/arm64-v8a/libentry.so	OK
2026-05-30 12:03:54	Analyzing apktool_out/lib/arm64-v8a/libgojni.so	OK
2026-05-30 12:03:54	Analyzing apktool_out/lib/arm64-v8a/libmmkv.so	OK
2026-05-30 12:03:54	Analyzing apktool_out/lib/arm64-v8a/libconscript_jni.so	OK
2026-05-30 12:03:54	Analyzing apktool_out/lib/arm64-v8a/libentry-android.so	OK
2026-05-30 12:03:54	Analyzing apktool_out/lib/arm64-v8a/libzstd-jni-1.5.7-8.so	OK
2026-05-30 12:03:54	Analyzing apktool_out/lib/arm64-v8a/libsurface_util_jni.so	OK
2026-05-30 12:03:54	Analyzing apktool_out/lib/arm64-v8a/libcore.so	OK
2026-05-30 12:03:54	Analyzing apktool_out/lib/arm64-v8a/libtun2socks.so	OK
2026-05-30 12:03:54	Analyzing apktool_out/lib/arm64-v8a/libtoolChecker.so	OK
2026-05-30 12:03:54	Analyzing apktool_out/lib/arm64-v8a/libimage_processing_util_jni.so	OK
2026-05-30 12:03:54	Analyzing apktool_out/lib/arm64-v8a/liberror-code.so	OK
2026-05-30 12:03:54	Analyzing apktool_out/lib/arm64-v8a/libdatastore_shared_counter.so	OK

2026-05-30 12:03:54	Reading Code Signing Certificate	OK
2026-05-30 12:03:55	Running APKiD 3.0.0	OK
2026-05-30 12:03:57	Detecting Trackers	OK
2026-05-30 12:03:58	Decompiling APK to Java with JADX	OK
2026-05-30 12:04:17	Converting DEX to Smali	OK
2026-05-30 12:04:17	Code Analysis Started on - java_source	OK
2026-05-30 12:04:23	Android SBOM Analysis Completed	OK
2026-05-30 12:04:26	Android SAST Completed	OK
2026-05-30 12:04:26	Android API Analysis Started	OK
2026-05-30 12:04:28	Android API Analysis Completed	OK
2026-05-30 12:04:28	Android Permission Mapping Started	OK
2026-05-30 12:04:30	Android Permission Mapping Completed	OK
2026-05-30 12:04:30	Android Behaviour Analysis Started	OK
2026-05-30 12:04:32	Android Behaviour Analysis Completed	OK

2026-05-30 12:04:32	Extracting Emails and URLs from Source Code	OK
2026-05-30 12:04:37	Email and URL Extraction Completed	OK
2026-05-30 12:04:37	Extracting String data from APK	OK
2026-05-30 12:04:37	Extracting String data from SO	OK
2026-05-30 12:04:37	Extracting String data from Code	OK
2026-05-30 12:04:37	Extracting String values and entropies from Code	OK
2026-05-30 12:04:39	Performing Malware check on extracted domains	OK
2026-05-30 12:04:41	Saving to Database	OK

Report Generated by - MobSF v4.5.0

Mobile Security Framework (MobSF) is an automated, all-in-one mobile application (Android/iOS/Windows) pen-testing, malware analysis and security assessment framework capable of performing static and dynamic analysis.

© 2026 Mobile Security Framework - MobSF | [Ajin Abraham](#) | [OpenSecurity](#).